

MasterRoc[®] RBA 384

Highly reactive, thixotropic polyurea silicate anchoring resin for rock bolt and cable bolt installation

Description

MasterRoc RBA 384 is a fast reacting, two-component polyurea silicate anchoring resin specifically designed for rock bolt and cable bolt installations. Its unique thixotropic feature makes the overhead applications possible without additional sealing. Its extended setting time feature allows the installation in areas with higher ambient temperature, and in areas where longer open times are required.

Applications

- Resin-into-bolt rock bolting at all angles
- Bolt-into-resin rock bolting at all angles
- For the use with steel and glass fiber bolts

Features

- Thixotropic
- Long distance pumping capability
- Extended setting time
- High structural strength
- Excellent adhesion to damp and low friction substrates
- Does not absorb water or expand in volume when comes in contact with water
- Penetrates cracks wider than 5 mil (0.14 mm)

Benefits

- Secure and precise injection
- Flexibility in applications
- Reliable rock bolting

Physical Characteristics

Technical Data

Physical properties:

	Color	Viscosity, mPa.s	Density, lb/ft ³ (g/cm ³)
Part A	Colorless	490	86.8 (1.39)
Part B	Dark Brown	150	73.7 (1.18)

Note: Viscosity tested at 73 °F (23 °C); Density tested at 68 °F (20 °C)

Mixing Ratio: 1:1 by volume

Reaction characteristics:

Testing Temperature	73 °F (23 °C)
Thixotropic Time	Immediately
Setting Time	280 s ± 30 s
Foam Expansion Factor	1
Compressive Strength	> 5000 psi (35 MPa)
Penetration Capacity	≥ 5 mil (0.14 mm)

Guidelines for Use

Dosage and Application Procedure: The Part A and Part B of MasterRoc RBA 384 resin are delivered ready to use. They should be injected in the ratio of 1:1 by volume, using a two-component injection pump equipped with a static in-line mixer nozzle, as shown in the following picture.



Example of a two-component injection pump.

The curing time is dependent on the temperature of the product and of the ground. Store both parts of MasterRoc RBA 384 resin at a temperature above 50 °F (10 °C) prior to application.

To achieve a favorable mixing result during injection, the addition of a static in-line mixer in conjunction with the mixing head is strongly recommended. The length of the static in-line mixer should be approximately 12 in. (300 mm).

Equipment: For short breaks in the injection process, pump MasterRoc RBA 384 resin Part A through the nozzle including the static in-line mixer.

After the injection process, pump an appropriate cleaning and maintenance agent (such as MasterRoc MP 230 CLN product) or oil that does not contain any water, through the pump and injection hoses until MasterRoc RBA 384 resin is completely flushed out. Store the pump and hoses with the cleaning agent inside and seal all openings.

Storage and Handling

If stored in dry conditions, in unopened and tightly closed original containers, and within a temperature range of 40 °F to 95 °F (5 °C to 35 °C), the components of MasterRoc RBA 384 resin have a shelf life of 24 months.

Safety: The use of gloves, eye protection, and safety clothes are recommended. Any physical contact (e.g. skin or eyes) with the product should be avoided. If contact with skin occurs, wash thoroughly using soap and water. In case of eye contact, rinse thoroughly with water and seek immediate medical advice.

Uncured products should not be allowed to enter local drainage systems. Spillage must be collected using absorbent materials such as sawdust or sand, and be disposed of in accordance with local regulations.

For further information, refer to the Safety Data Sheet or contact your local Master Builders Solutions representative.

Packaging

The Part A and Part B of MasterRoc RBA 384 resin are available in pails, drums, and totes.

Related Documents

Safety Data Sheet: MasterRoc RBA 384 resin Part A, MasterRoc RBA 384 resin Part B

Additional Information

For additional information on MasterRoc RBA 384 resin, contact your local sales representative.

Master Builders Solutions creates technologies for the construction industry inspiring people to build better. We are active in ~40 countries and operate 35 production sites with over 1,600 employees. We develop, produce, and market high-quality chemical admixtures, as well as adjacent core technologies, to master the challenges of today and support a decarbonized future. Our people are pivotal and pair leading technologies and a strong brand heritage to surpass our customers' expectations and drive continuous value creation

Limited Warranty Notice

Master Builders Solutions Admixtures US, LLC ("Master Builders Solutions") warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. MASTER BUILDERS SOLUTIONS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders Solutions. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS SOLUTIONS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders Solutions' present knowledge and experience. However, Master Builders Solutions assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders Solutions reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.