

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MasterGlenium 7500

Version	Revision Date:	SDS Number:	Date of last issue: 08/15/2023
1.2	07/28/2023	000000260511	Date of first issue: 01/09/2023

SECTION 1. IDENTIFICATION

Product name : MasterGlenium 7500

Product code : 000000000050701363 000000000050701363

Manufacturer or supplier's details

Company name of supplier : Master Builders-Admixtures US,LLC

Address : 23700 CHAGRIN BLVD
Beachwood OH 44122

Emergency telephone number : ChemTel: +1-813-248-0585

National Emergency Telephone Number : USA: +1-800-255-3924 ChemTel contract no. MIS9240420

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals admixture

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Skin irritation : Category 2

Eye irritation : Category 2A

Short-term (acute) aquatic hazard : Category 2

Long-term (chronic) aquatic hazard : Category 3

Other hazards

None known.

GHS label elements

Hazard pictograms :



SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MasterGlenium 7500

Version 1.2 Revision Date: 07/28/2023 SDS Number: 000000260511 Date of last issue: 08/15/2023
Date of first issue: 01/09/2023

Signal word	: Warning
Hazard statements	: H315 Causes skin irritation. H319 Causes serious eye irritation. H401 Toxic to aquatic life. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	: Prevention: P264 Wash skin thoroughly after handling. P273 Avoid release to the environment. P280 Wear protective gloves/ eye protection/ face protection. Response: P302 + P352 IF ON SKIN: Wash with plenty of water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P332 + P313 If skin irritation occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 + P364 Take off contaminated clothing and wash it before reuse. Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture :
Mixture
Chemical nature :

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
acetic acid	64-19-7*	$\geq 3 - \leq 7$	TSC
Alkoxylated fatty alkylamines	-	$\geq 0.5 - \leq 1.5$	TSC
(Z)-2,2'-(Octadec-9-enylimino)bisethanol triisobutyl phosphate	13127-82-7*	$\geq 0.5 - \leq 1.5$	TSC
	126-71-6*	$\geq 0.1 - \leq 1$	TSC
acrylic acid	79-10-7*	$\geq 0.1 - \leq 1$	TSC

* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MasterGlenium 7500

Version	Revision Date:	SDS Number:	Date of last issue: 08/15/2023
1.2	07/28/2023	000000260511	Date of first issue: 01/09/2023

SECTION 4. FIRST AID MEASURES

- | | | |
|---|---|--|
| General advice | : | First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing. |
| If inhaled | : | Keep patient calm, remove to fresh air. If symptoms persist, seek medical advice. |
| In case of skin contact | : | After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention. |
| In case of eye contact | : | Contact lenses should be removed. Hold eyelids open and flush with copious amounts of clean, fresh water or a special eyewash solution and seek medical advice. |
| If swallowed | : | Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor. |
| Most important symptoms and effects, both acute and delayed | : | Causes skin irritation. Causes serious eye irritation. Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. |
| Notes to physician | : | Treat symptomatically. |

SECTION 5. FIREFIGHTING MEASURES

- | | | |
|--------------------------------|---|---|
| Suitable extinguishing media | : | Foam
Water spray
Dry powder
Carbon dioxide (CO2) |
| Unsuitable extinguishing media | : | water jet |
| Hazardous combustion products | : | fumes/smoke
harmful vapours
Carbon oxides
nitrogen oxides
carbon black |
| Further information | : | The degree of risk is governed by the burning substance and the fire conditions.
If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MasterGlenium 7500

Version	Revision Date:	SDS Number:	Date of last issue: 08/15/2023
1.2	07/28/2023	000000260511	Date of first issue: 01/09/2023

Contaminated extinguishing water must be disposed of in accordance with official regulations.

Special protective equipment : Wear a self-contained breathing apparatus.
for firefighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
Wear eye/face protection.
Use personal protective clothing.
Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : The product is neither self-ignitable, nor an explosion hazard, nor does it promote fires.

Advice on safe handling : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.

Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Protect from direct sunlight.

Materials to avoid : No materials to be especially mentioned.

Recommended storage temperature : 34 - 106 °F / 1 - 41 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetic acid	64-19-7	TWA	10 ppm	ACGIH
		STEL	15 ppm	ACGIH
		TWA	10 ppm	NIOSH REL

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MasterGlenium 7500

Version 1.2 Revision Date: 07/28/2023 SDS Number: 000000260511 Date of last issue: 08/15/2023
Date of first issue: 01/09/2023

			25 mg/m3	
		ST	15 ppm 37 mg/m3	NIOSH REL
		TWA	10 ppm 25 mg/m3	OSHA Z-1
		TWA	10 ppm 25 mg/m3	OSHA P0
acrylic acid	79-10-7	TWA	2 ppm	ACGIH
		TWA	2 ppm 6 mg/m3	NIOSH REL
		TWA	10 ppm 30 mg/m3	OSHA P0

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits may be exceeded.
Use NIOSH approved respiratory protection.

Hand protection

Remarks : Chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.
The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case. Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN 374): butyl rubber (butyl) - 0.7 mm coating thickness nitrile rubber (NBR) - 0.4 mm coating thickness chloroprene rubber (CR) - 0.5 mm coating thickness Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Body protection must be chosen based on level of activity and exposure.

Protective measures : Do not inhale dust/fumes/aerosols.
Avoid contact with the skin, eyes and clothing.
Avoid exposure.
Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.
Hands and/or face should be washed before breaks and at

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MasterGlenium 7500

Version	Revision Date:	SDS Number:	Date of last issue: 08/15/2023
1.2	07/28/2023	000000260511	Date of first issue: 01/09/2023

the end of the shift.
At the end of the shift the skin should be cleaned and skin-care agents applied.
Gloves must be inspected regularly and prior to each use.
Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: brown
Odour	: slight odour, faint
Odour Threshold	: not determined
pH	: approx. 4.60 (72 °F / 22 °C)
Melting point/freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: A flash point determination is unnecessary due to the high water content.
Evaporation rate	: No data available
Flammability (liquids)	: The product is not flammable.
Self-ignition	: not auto-flammable
Upper explosion limit / Upper flammability limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: 1.049 g/cm ³ (68 °F / 20 °C)
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-	: not applicable for mixtures

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MasterGlenium 7500

Version	Revision Date:	SDS Number:	Date of last issue: 08/15/2023
1.2	07/28/2023	000000260511	Date of first issue: 01/09/2023

octanol/water

Auto-ignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Sublimation point : No data available

Molecular weight : Not applicable

Metal corrosion rate : Not corrosive to metals

Particle characteristics

Particle Size Distribution : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability : The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions : The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids
Strong bases
Strong oxidizing agents
Strong reducing agents

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MasterGlenium 7500

Version	Revision Date:	SDS Number:	Date of last issue: 08/15/2023
1.2	07/28/2023	000000260511	Date of first issue: 01/09/2023

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:

(Z)-2,2'-(Octadec-9-enylimino)bisethanol:

Acute oral toxicity : LD50 (Rat, male and female): 1,260 mg/kg
Method: OECD Test Guideline 401

Skin corrosion/irritation

Causes skin irritation.

Product:

Assessment : Irritating to skin.
Remarks : Expert judgement

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Assessment : Irritating to eyes.
Remarks : Expert judgement

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MasterGlenium 7500

Version	Revision Date:	SDS Number:	Date of last issue: 08/15/2023
1.2	07/28/2023	000000260511	Date of first issue: 01/09/2023

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

Further information

Product:

Remarks : The product has not been tested. The statement has been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Components:

(Z)-2,2'-(Octadec-9-enylimino)bisethanol:

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

acrylic acid:

M-Factor (Acute aquatic toxicity) : 1

Persistence and degradability

Product:

Biodegradability : Remarks: Taking into consideration the properties of several components, the product is estimated not to be readily biodegradable according to OECD classification.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MasterGlenium 7500

Version	Revision Date:	SDS Number:	Date of last issue: 08/15/2023
1.2	07/28/2023	000000260511	Date of first issue: 01/09/2023

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available.
Discharge into the environment must be avoided.

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : There is a high probability that the product is not acutely harmful to aquatic organisms.
The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regulations.
Do not discharge into drains/surface waters/groundwater.
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MasterGlenium 7500

Version	Revision Date:	SDS Number:	Date of last issue: 08/15/2023
1.2	07/28/2023	000000260511	Date of first issue: 01/09/2023

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

acetic acid	64-19-7
acrylic acid	79-10-7

New Jersey Right To Know

acetic acid	64-19-7
-------------	---------

California Prop. 65

Carcinogenic.

WARNING: This product can expose you to chemicals including acetaldehyde, propylene oxide, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

WARNING:

California List of Hazardous Substances

acetic acid	64-19-7
-------------	---------

The components of this product are reported in the following inventories:

TSCA : Product contains substance(s) not listed on TSCA inventory.

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

MasterGlenium 7500


Version
1.2

Revision Date:
07/28/2023

SDS Number:
000000260511

Date of last issue: 08/15/2023
Date of first issue: 01/09/2023

NFPA 704:



HMIS® IV:

HEALTH	/	2
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "/" represents a chronic hazard, while the "-" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA P0	: USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	: 8-hour time weighted average
OSHA Z-1 / TWA	: 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MasterGlenium 7500

Version	Revision Date:	SDS Number:	Date of last issue: 08/15/2023
1.2	07/28/2023	000000260511	Date of first issue: 01/09/2023

Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 07/28/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN