MasterFinish HV 28 gld



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/28/2023

 2.0
 08/15/2023
 000000260661
 Date of first issue: 01/24/2023

SECTION 1. IDENTIFICATION

Product name : MasterFinish HV 28 gld

Product code : 00000000055514096 00000000055514096

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Master Builders Solutions Canada Inc.

Address : 1800 CLARK BLVD

Brampton ON L6T 4M7

Emergency telephone : ChemTel: +1-813-248-0585;

National Emergency Tele-

phone Number

USA: +1-800-255-3924 ChemTel contract no. MIS9240420

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 2

Skin corrosion/irritation : Category 2

Carcinogenicity : Category 1A

Reproductive toxicity : Category 2

Specific target organ toxicity

- single exposure

Category 3

Specific target organ toxicity

- repeated exposure

Category 2 (Central nervous system)

Aspiration hazard : Category 1

Short-term (acute) aquatic

atic : Category 2

hazard

Long-term (chronic) aquatic

Category 3

hazard

MasterFinish HV 28 gld



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/28/2023

 2.0
 08/15/2023
 000000260661
 Date of first issue: 01/24/2023

GHS label elements

Hazard pictograms







Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H350 May cause cancer.

H373 May cause damage to organs (Central nervous system)

through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

H401 Toxic to aquatic life.

Precautionary Statements

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P243 Take action to prevent static discharges.

P273 Avoid release to the environment.

P202 Do not handle until all safety precautions have been read

and understood.

P260 Do not breathe dusts or mists.

P240 Ground and bond container and receiving equipment.

P242 Use only non-sparking tools.

P264 Wash face, hands and any exposed skin thoroughly after

handling.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equip-

ment.

Response:

P308 + P311 IF exposed or concerned: Call a POISON

CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately

all contaminated clothing. Rinse skin with water/ shower. P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/ doctor.

P304 + P340 IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

P302 + P352 IF ON SKIN: Wash with plenty of water.

P332 + P313 If skin irritation occurs: Get medical advice/ atten-

P331 Do NOT induce vomiting.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

P370 + P378 In case of fire: Use water spray, alcohol-resistant

foam, dry chemical or carbon dioxide to extinguish.

MasterFinish HV 28 gld



Version 2.0

Revision Date: 08/15/2023

SDS Number: 000000260661

Date of last issue: 07/28/2023 Date of first issue: 01/24/2023

Storage:

P233 Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous

waste collection point.

Other hazards

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No data available.

Components

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.

If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).

Immediately remove contaminated clothing.

Move out of dangerous area.

Show this material safety data sheet to the doctor in attend-

ance.

Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : Keep patient calm, remove to fresh air, seek medical atten-

tion.

Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : Immediately wash thoroughly with soap and water, seek med-

ical attention.

If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Wash affected eyes for at least 15 minutes under running

water with eyelids held open, consult an eye specialist.

Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

MasterFinish HV 28 gld



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/28/2023

 2.0
 08/15/2023
 000000260661
 Date of first issue: 01/24/2023

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention.

Keep respiratory tract clear. Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause drowsiness or dizziness.

May cause cancer.

Suspected of damaging the unborn child.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Foam
Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

: Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapors accumulating to form explosive concentra-

tions. Vapors can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.

MasterFinish HV 28 gld



Version **Revision Date:** SDS Number: Date of last issue: 07/28/2023 000000260661 Date of first issue: 01/24/2023 2.0 08/15/2023

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against : Product is not explosive. fire and explosion

Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapors).

Use only explosion-proof equipment.

Keep away from open flames, hot surfaces and sources of

ignition.

Avoid formation of aerosol. Advice on safe handling

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage No smoking.

Keep container tightly closed in a dry and well-ventilated

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Keep only in the original container in a cool, dry, wellventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Materials to avoid Observe TRGS 509/510 storage rules.

Recommended storage tem: :

perature

0°C

Further information on stor-

age stability

Minimum storage temperature:





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/28/2023

 2.0
 08/15/2023
 000000260661
 Date of first issue: 01/24/2023

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
Components	CAS-NO.	Value type (Form of	ters / Permissible	Dasis
	400.00.0	exposure)	concentration	CAADOEL
toluene	108-88-3	TWA	50 ppm	CA AB OEL
			188 mg/m3	04.00.051
		TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm	CA QC OEL
		TWA	20 ppm	ACGIH
Silicon dioxide	7631-86-9	TWA (Res-	0.025 mg/m3	CA AB OEL
		pirable par-	(Silica)	
		ticulates)		
Mica-group minerals	12001-26-2	TWA (Res-	3 mg/m3	CA AB OEL
		pirable)		
		TWA (Res-	3 mg/m3	CA BC OEL
		pirable)		
		TWAEV	3 mg/m3	CA QC OEL
		(respirable	g	
		dust)		
		TWA (Res-	0.1 mg/m3	ACGIH
		pirable par-	0.1 1119/1110	7.00
		ticulate mat-		
		ter)		
Titanium dioxide	13463-67-7	TWA	10 mg/m3	CA AB OEL
	13403-01-1	TWA (Total	10 mg/m3	CA BC OEL
			TO HIG/HIS	CA BC OEL
		dust)	2 m m/m 2	CA DC OFI
		TWA (respir-	3 mg/m3	CA BC OEL
		able dust		
		fraction)	40	04.00.051
		TWAEV (to-	10 mg/m3	CA QC OEL
		tal dust)		
		TWA (Res-	0.2 mg/m3	ACGIH
		pirable par-	(Titanium dioxide)	
		ticulate mat-		
		ter)		
		TWA (Res-	2.5 mg/m3	ACGIH
		pirable par-	(Titanium dioxide)	
		ticulate mat-		
		ter)		
Quartz (SiO2)	14808-60-7	TWA (Res-	0.025 mg/m3	CA AB OEL
		pirable par-		
		ticulates)		
		TWA (Res-	0.1 mg/m3	CA ON OEL
		1	_	
		pirable frac-		
		tion)		
			0.1 mg/m3	CA QC OEL
		tion) TWAEV	0.1 mg/m3	CA QC OEL
		tion)	0.1 mg/m3	CA QC OEL

MasterFinish HV 28 gld



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/28/2023

 2.0
 08/15/2023
 000000260661
 Date of first issue: 01/24/2023

pirable)	(Silica)	
TWA (Respirable par-	0.025 mg/m3 (Silica)	ACGIH
ticulate mat-		
ter)		

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the occupa-

tional exposure limits they must use appropriate certified

respirators.

Use NIOSH approved respiratory protection.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : various colours

Odor : sweetish, solvent

Odor Threshold : No data available

pH : Not applicable

Melting point : No applicable information available.

MasterFinish HV 28 gld



Version Revision Date: SDS Number: Date of last issue: 07/28/2023 2.0 08/15/2023 000000260661 Date of first issue: 01/24/2023

Freezing point No applicable information available.

Boiling point : 110 °C

Flash point : 4 °C

Evaporation rate : No applicable information available.

Flammability (solid, gas) : Highly flammable.

Method: derived from flash point

Upper explosion limit / Upper

flammability limit

6.7 %(V)

Lower explosion limit / Lower

flammability limit

2.5 %(V)

Vapor pressure : No data available

Relative vapor density : Heavier than air.

Relative density : No applicable information available.

Density : approx. 1.0 g/cm3 (20 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No applicable information available.

Partition coefficient: n-

octanol/water

Not applicable

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No applicable information available.

Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive

Not explosive

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.

Sublimation temperature : No applicable information available.

Molecular weight : No data available

MasterFinish HV 28 gld



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/28/2023

 2.0
 08/15/2023
 000000260661
 Date of first issue: 01/24/2023

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : Vapors may cause irritation to the eyes, respiratory system

and the skin.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

MasterFinish HV 28 gld



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/28/2023

 2.0
 08/15/2023
 000000260661
 Date of first issue: 01/24/2023

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Suspected of damaging the unborn child.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : The product has not been tested. The statement has been

derived from the properties of the individual components.

Remarks : Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause

narcotic effects.

Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

MasterFinish HV 28 gld



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/28/2023

 2.0
 08/15/2023
 000000260661
 Date of first issue: 01/24/2023

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life.

Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

SECTION 15. REGULATORY INFORMATION

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA ON OEL : Ontario Table of Occupational Exposure Limits made under

the Occupational Health and Safety Act.

CA QC OEL : Québec. Regulation respecting occupational health and safe-

ty, Schedule 1, Part 1: Permissible exposure values for air-





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/28/2023

 2.0
 08/15/2023
 000000260661
 Date of first issue: 01/24/2023

borne contaminants

ACGIH / TWA : 8-hour, time-weighted average
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average
CA ON OEL / TWA : Time-Weighted Average Limit (TWA)

CA ON OEL / TWA : Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV : Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods: vPvB - Very Persistent and Very Bioaccumulative: WHMIS - Workplace Hazardous Materials Information System

Revision Date : 08/15/2023 Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN