

03 30 00	Cast-in-Place Concrete
03 40 00	Precast Concrete
03 70 00	Mass Concrete

MasterGlenium[®] 7925

High-Range Water-Reducing Admixture

Description

MasterGlenium 7925 ready-to-use high-range water-reducing admixture is based on the next generation of polycarboxylate technology. This technology incorporates state-of-the-art molecular engineering to provide fast wet-out of powder materials.

MasterGlenium 7925 admixture is effective in improving the day-to-day production efficiency of a concrete plant by rapidly dispersing powder materials in concrete mixtures, thereby minimizing mixing time. It is formulated to meet ASTM C 494 requirements for Type A, water-reducing, and Type F, high-range water-reducing, admixtures.

Applications

Recommended for use in:

- Concrete requiring high-early compressive strength development
- Concrete mixtures with low w/cm and/or high powder contents
- Production of self-consolidating concrete (SCC) mixtures
- Green Sense[®] Concrete

Features

- Dosage flexibility
- Rapid cement dispersion
- Superior early and ultimate strengths

Benefits

- Optimized mixture costs
- Shorter mixing time in central mixers
- Increased productivity
- Greater batch-to-batch consistency

Guidelines for Use

Dosage: MasterGlenium 7925 admixture has a recommended dosage range of 2-15 fl oz/cwt (130-975 mL/100 kg) of cementitious materials. For most applications, dosages in the range of 2-8 fl oz/cwt (130-520 mL/100 kg) will provide excellent performance. For very high performance and SCC mixtures, up to 15 fl oz/cwt (975 mL/100 kg) of cementitious materials can be utilized. Because of variations in concrete materials, job site conditions and/or applications, dosages outside of this range may be required. In such cases, contact your local sales representative.

Mixing: MasterGlenium 7925 admixture can be added with the initial batch water or as a delayed addition. However, optimum water reduction is generally obtained with a delayed addition.

Product Notes

Corrosivity – Non-Chloride, Non-Corrosive: MasterGlenium 7925 admixture will neither initiate nor promote corrosion of reinforcing steel embedded in concrete, prestressing steel or of galvanized steel floor and roof systems. Neither calcium chloride nor other chloride-based ingredients are used in the manufacture of MasterGlenium 7925 admixture.

Compatibility: MasterGlenium 7925 admixture is compatible with most admixtures used in the production of quality concrete, including normal, mid- and high-range water reducers, accelerators, retarders, extended-set control admixtures, air entrainers, corrosion inhibitors, and shrinkage reducers.

Do not use MasterGlenium 7925 admixture with admixtures containing beta-naphthalene sulfonate. Erratic behaviors in slump, workability retention and pumpability may be experienced.

Storage and Handling

Storage Temperature: MasterGlenium 7925 admixture must be stored at temperatures above 40 °F (5 °C). If MasterGlenium 7925 admixture freezes, thaw and reconstitute by mechanical agitation. **Do not use pressurized air for agitation.**

Shelf Life: MasterGlenium 7925 admixture has a minimum shelf life of 6 months. Depending on storage conditions, the shelf life may be greater than stated. Recirculation is required to enhance the shelf life potential of MasterGlenium 7925 admixture. Please contact your local sales representative regarding suitability for use and dosage recommendations if the shelf life of MasterGlenium 7925 admixture has been exceeded.

Packaging

MasterGlenium 7925 admixture is supplied in 55 gal (208 L) drums, 275 gal (1040 L) totes and by bulk delivery.

Related Documents

Safety Data Sheets: MasterGlenium 7925 admixture

Additional Information

For additional information on MasterGlenium 7925 admixture or on its use in developing concrete mixtures with special performance characteristics, contact your Master Builders Solutions representative.

Master Builders Solutions creates technologies for the construction industry inspiring people to build better. We are active in ~40 countries and operate 35 production sites with over 1,600 employees. We develop, produce, and market high-quality chemical admixtures, as well as adjacent core technologies, to master the challenges of today and support a decarbonized future. Our people are pivotal and pair leading technologies and a strong brand heritage to surpass our customers' expectations and drive continuous value creation.

Limited Warranty Notice

Master Builders Solutions Admixtures US, LLC ("Master Builders Solutions") warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. MASTER BUILDERS SOLUTIONS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders Solutions. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS SOLUTIONS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders Solutions' present knowledge and experience. However, Master Builders Solutions assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders Solutions reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

