



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/15/2023

 3.1
 08/24/2023
 000000256201
 Date of first issue: 01/03/2023

SECTION 1. IDENTIFICATION

Product name : MasterRoc MP 367 Foam PART B

Product code : 00000000050323892 000000000050323892

Manufacturer or supplier's details

Company name of supplier : Master Builders-Admixtures US,LLC

Address : 23700 Chagrin Blvd

Beachwood OH 44122

Emergency telephone : ChemTel: +1-813-248-0585

National Emergency Tele-

phone Number

USA: +1-800-255-3924 ChemTel contract no. MIS9240420

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity (Inhalation -

vapour)

Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Specific target organ toxicity

- single exposure

Category 3

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 2

GHS label elements

MasterRoc MP 367 Foam PART B



Version **Revision Date:** SDS Number: Date of last issue: 08/15/2023 08/24/2023 000000256201 Date of first issue: 01/03/2023 3.1

Hazard pictograms





Signal Word Danger

Hazard Statements H319 Causes serious eye irritation.

> H315 Causes skin irritation. H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing diffi-

culties if inhaled.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or re-

peated exposure if inhaled.

Precautionary Statements

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P271 Use only outdoors or in a well-ventilated area.

P260 Do not breathe dusts or mists.

P261 Avoid breathing mist.

P284 In case of inadequate ventilation wear respiratory protection.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P264 Wash face, hands and any exposed skin thoroughly after

handling.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P314 Get medical advice/ attention if you feel unwell.

P302 + P352 IF ON SKIN: Wash with plenty of water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P332 + P313 If skin irritation occurs: Get medical advice/ atten-

P362 + P364 Take off contaminated clothing and wash it before reuse.

P337 + P313 If eye irritation persists: Get medical advice/ atten-

P312 Call a POISON CENTER or doctor/physician if you feel

unwell.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:





Version Revision Date: SDS Number: Date of last issue: 08/15/2023 3.1 08/24/2023 000000256201 Date of first issue: 01/03/2023

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

Contains isocyanates. Inhalation of isocyanate mists or vapors may cause respiratory irritation, breathlessness, chest discomfort and reduced pulmonary function. Overexposure well above the PEL may result in bronchitis, bronchial spasms and pulmonary edema. Animal tests indicate that skin contact may play a role in causing respiratory sensitization.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Blend based on:

isocyanate

Components

Chemical name	CAS-No.	Concentration (% w/w)
Isocyanic acid, polymethylenepoly-	9016-87-9	>= 30 - < 50
phenylene ester (P-MDI)		
Diphenylmethane-4,4'-diisocyanate	101-68-8	>= 30 - < 50
(MDI)		
tris(2-chloro-1-methylethyl)phosphate	13674-84-5	>= 5 - < 10
triethyl phosphate	78-40-0	>= 1 - < 5
diphenylmethane-2,4'-diisocyanate	5873-54-1	>= 1 - < 5
Isocyanic acid, polymethylenepoly-	57636-09-6	>= 0.1 - < 1
phenylene ester, polymer with alpha-		
hydro-omega-hydroxypoly(oxy-1,2-		
ethanediyl)		

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.

Immediately remove contaminated clothing.

If inhaled : Keep patient calm, remove to fresh air.

If symptoms persist, seek medical advice.

In case of skin contact : After contact with skin, wash immediately with plenty of water

and soap.

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact : Contact lenses should be removed. Hold eyelids open and

flush with copious amounts of clean, fresh water or a special

eyewash solution and seek medical advice.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention.

Do not induce vomiting unless told to by a poison control cen-

ter or doctor.

MasterRoc MP 367 Foam PART B



Version **Revision Date:** SDS Number: Date of last issue: 08/15/2023 08/24/2023 000000256201 Date of first issue: 01/03/2023 3.1

Most important symptoms and effects, both acute and

delayed

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

Harmful if inhaled.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated

exposure if inhaled.

Notes to physician Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media Foam

> Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

water jet

Hazardous combustion prod: :

ucts

fumes/smoke harmful vapours Carbon oxides nitrogen oxides carbon black

Further information The degree of risk is governed by the burning substance and

the fire conditions.

If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not

allow to reach sewage or effluent systems.

Contaminated extinguishing water must be disposed of in

accordance with official regulations.

Special protective equipment: Wear a self-contained breathing apparatus.

for fire-fighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emergency procedures

Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

Wear eve/face protection.

Use personal protective clothing.

Handle in accordance with good building materials hygiene

and safety practice.

Environmental precautions Contain contaminated water/firefighting water.

Do not discharge into drains/surface waters/groundwater.

Methods and materials for

containment and cleaning up

Pick up with suitable appliance and dispose of.

Dispose of absorbed material in accordance with regulations.





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/15/2023

 3.1
 08/24/2023
 000000256201
 Date of first issue: 01/03/2023

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Keep only in the original container in a cool, dry, well-

ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Recommended storage tem-

perature

32 - 95 °F / 0 - 35 °C

Further information on stor-

age stability

PROTECT FROM FREEZING.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Isocyanic acid, polymeth- ylenepolyphenylene ester (P- MDI)	9016-87-9	С	0.02 ppm 0.2 mg/m3	OSHA Z-1
		С	0.02 ppm 0.2 mg/m3	OSHA P0
		TWA	0.005 ppm 0.05 mg/m3	NIOSH REL
		С	0.02 ppm 0.2 mg/m3	NIOSH REL





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/15/2023

 3.1
 08/24/2023
 000000256201
 Date of first issue: 01/03/2023

Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	TWA	0.005 ppm	ACGIH
		С	0.02 ppm 0.2 mg/m3	OSHA Z-1
		С	0.02 ppm 0.2 mg/m3	OSHA P0
		TWA	0.005 ppm 0.05 mg/m3	NIOSH REL
		С	0.02 ppm 0.2 mg/m3	NIOSH REL
triethyl phosphate	78-40-0	TWA	7.45 mg/m3	US WEEL
diphenylmethane-2,4'- diisocyanate	5873-54-1	С	0.02 ppm 0.2 mg/m3	OSHA Z-1
		С	0.02 ppm 0.2 mg/m3	OSHA P0
		TWA	0.005 ppm 0.05 mg/m3	NIOSH REL
		С	0.02 ppm 0.2 mg/m3	NIOSH REL

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : When atmospheric levels may exceed the occupational ex-

posure limit (PEL or TLV) NIOSH-certified air-purifying respirators equipped with an organic vapor sorbent and particulate filter can be used as long as appropriate precautions and

change out schedules are in place.

Hand protection

Remarks : Chemical resistant protective gloves. Manufacturer's direc-

tions for use should be observed because of great diversity of

types.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Body protection must be chosen based on level of activity

and exposure.

Protective measures : Do not inhale dust/fumes/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure.

Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.

Hands and/or face should be washed before breaks and at

the end of the shift.

At the end of the shift the skin should be cleaned and skin-

care agents applied.

Gloves must be inspected regularly and prior to each use.

Replace if necessary (e.g. pinhole leaks).





Version Revision Date: SDS Number: Date of last issue: 08/15/2023 3.1 08/24/2023 000000256201 Date of first issue: 01/03/2023

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : dark brown

Odor : aromatic

Odor Threshold : not determined

pH : substance/mixture reacts with water

Melting point : No data available

boiling temperature : 626 °F / 330 °C

(1,013 hPa)

Flash point : $> 392 \, ^{\circ}\text{F} \, / > 200 \, ^{\circ}\text{C}$

Method: Flashpoint test using closed cup, determination of

flashpoint.

Evaporation rate : not determined

Flammability (liquids) : Not classified as a flammability hazard

Method: derived from flash point

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : < 0.01 hPa (77 °F / 25 °C)

Relative vapor density : 8.5 (68 °F / 20 °C)

Relative density : 1.4 (68 °F / 20 °C)

Density : approx. 1.25 g/cm3 (68 °F / 20 °C)

Bulk density : Not applicable

Solubility(ies)

Water solubility : hydrolyzes

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

not applicable for mixtures





Version Revision Date: SDS Number: Date of last issue: 08/15/2023 3.1 08/24/2023 000000256201 Date of first issue: 01/03/2023

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : 170 mPa.s

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.

Sublimation point : No data available

Molecular weight : Not applicable

Metal corrosion rate : No corrosive effect on metal.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as pre-

scribed/indicated.

Chemical stability : The product is stable if stored and handled as pre-

scribed/indicated.

Possibility of hazardous reac-

tions

The product is stable if stored and handled as pre-

scribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if inhaled.

Product:

Acute inhalation toxicity : ATE: 2.0 mg/l

Remarks: Determined for mist

MasterRoc MP 367 Foam PART B



Version Revision Date: SDS Number: Date of last issue: 08/15/2023 3.1 08/24/2023 000000256201 Date of first issue: 01/03/2023

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from the properties of the individual

components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Persistence and degradability

Product:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge





Version Revision Date: SDS Number: Date of last issue: 08/15/2023 3.1 08/24/2023 000000256201 Date of first issue: 01/03/2023

Result: Under test conditions no biodegradation observed.

Biodegradation: < 10 % Exposure time: 28 d

Method: MITI Test (II), inherent.

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater. Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/15/2023

 3.1
 08/24/2023
 000000256201
 Date of first issue: 01/03/2023

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Diphenylmethane-4,4'-	101-68-8	5000	15640
diisocyanate (MDI)			

SARA 313

The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

9016-87-9

Isocyanic acid,

polymethylenepolyphenylene ester (P-MDI)

Diphenylme- 101-68-8

thane-4,4'diisocyanate (MDI)

US State Regulations

Pennsylvania Right To Know

Isocyanic acid, polymethylenepolyphenylene ester (P-MDI) 9016-87-9 Diphenylmethane-4,4'-diisocyanate (MDI) 101-68-8

New Jersey Right To Know

Isocyanic acid, polymethylenepolyphenylene ester (P-MDI) 9016-87-9 Diphenylmethane-4,4'-diisocyanate (MDI) 101-68-8 diphenylmethane-2,4'-diisocyanate 5873-54-1

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Further information


MasterRoc MP 367 Foam PART B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/15/2023


 3.1
 08/24/2023
 000000256201
 Date of first issue: 01/03/2023

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / C : Ceiling value not be exceeded at any time.

OSHA P0 / C : Ceiling limit
OSHA Z-1 / C : Ceiling
US WEEL / TWA : 8-hr TWA

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance: ELx - Loading rate associated with x% response; EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Admin-





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/15/2023

 3.1
 08/24/2023
 000000256201
 Date of first issue: 01/03/2023

istration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 08/24/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN