

SAFETY DATA SHEET



MasterFinish HV 48 pnk

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
2.0	08/15/2023	000000260657	Date of first issue: 01/18/2023

SECTION 1. IDENTIFICATION

Product name : MasterFinish HV 48 pnk

Product code : 000000000055513990 000000000055513990

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Master Builders Solutions Canada Inc.

Address : 1800 CLARK BLVD
Brampton ON L6T 4M7

Emergency telephone : ChemTel: +1-813-248-0585;

National Emergency Tele-
phone Number : USA: +1-800-255-3924 ChemTel contract no. MIS9240420

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 2

Skin corrosion/irritation : Category 2

Carcinogenicity : Category 1A

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 3
- single exposure

Specific target organ toxicity : Category 2 (Central nervous system)
- repeated exposure

Aspiration hazard : Category 1

Short-term (acute) aquatic hazard : Category 2

Long-term (chronic) aquatic hazard : Category 3

SAFETY DATA SHEET

MasterFinish HV 48 pnk

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
2.0	08/15/2023	000000260657	Date of first issue: 01/18/2023

GHS label elements

Hazard pictograms

:



Signal Word

:

Danger

Hazard Statements

:

H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.
H350 May cause cancer.
H373 May cause damage to organs (Central nervous system) through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.
H401 Toxic to aquatic life.

Precautionary Statements

:

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 Use only outdoors or in a well-ventilated area.
P243 Take action to prevent static discharges.
P273 Avoid release to the environment.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dusts or mists.
P241 Use explosion-proof electrical, ventilating and lighting equipment.
P240 Ground and bond container and receiving equipment.
P242 Use only non-sparking tools.
P264 Wash face, hands and any exposed skin thoroughly after handling.

Response:

P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.
P362 + P364 Take off contaminated clothing and wash it before reuse.

MasterFinish HV 48 pnk

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
2.0	08/15/2023	000000260657	Date of first issue: 01/18/2023

Storage:

P233 Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
toluene	Methylbenzene	108-88-3	>= 50 - < 75
Mica-group minerals	Mica	12001-26-2	>= 5 - < 10
Titanium dioxide	C.I. Pigment White 6	13463-67-7	>= 0.5 - < 1.5
Iron oxide	Ferric oxide	1309-37-1	>= 0.5 - < 1.5
Quartz (SiO ₂)	crystalline silica	14808-60-7	>= 0.3 - < 1

SECTION 4. FIRST AID MEASURES

General advice	: First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.
If inhaled	: If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.
In case of skin contact	: After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.
In case of eye contact	: Remove contact lenses, if present. Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
If swallowed	: Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Do NOT induce vomiting.
Most important symptoms and effects, both acute and delayed	: Causes skin irritation. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness.

MasterFinish HV 48 pnk

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
2.0	08/15/2023	000000260657	Date of first issue: 01/18/2023

Suspected of damaging the unborn child.
May cause cancer.
May cause damage to organs through prolonged or repeated exposure.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam
Water spray
Dry powder
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : water jet
- Specific hazards during fire fighting : See SDS section 10 - Stability and reactivity.
- Hazardous combustion products : harmful vapours
nitrogen oxides
fumes/smoke
carbon black
carbon oxides
- Further information : The degree of risk is governed by the burning substance and the fire conditions.
If exposed to fire, keep containers cool by spraying with water.
Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.
Contaminated extinguishing water must be disposed of in accordance with official regulations.
- Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Contain contaminated water/firefighting water.
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

MasterFinish HV 48 pnk

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
2.0	08/15/2023	000000260657	Date of first issue: 01/18/2023

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.
Use only explosion-proof equipment.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).
- Advice on safe handling : Avoid aerosol formation.
Avoid inhalation of mists/vapours.
Avoid skin contact.
Avoid contact with eyes.
- Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Protect from direct sunlight.
- Recommended storage temperature : > 0 °C
- Further information on storage stability : PROTECT FROM FREEZING.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
toluene	108-88-3	TWA	50 ppm 188 mg/m ³	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm	CA QC OEL
		TWA	20 ppm	ACGIH
Iron oxide	1309-37-1	TWA (Respirable)	5 mg/m ³	CA AB OEL
		TWA (Respirable)	5 mg/m ³	CA AB OEL
		TWA (Fumes)	5 mg/m ³ (Iron)	CA BC OEL
		TWA (Fumes)	5 mg/m ³ (Iron)	CA BC OEL

SAFETY DATA SHEET



MasterFinish HV 48 pnk

Version 2.0 Revision Date: 08/15/2023 SDS Number: 000000260657 Date of last issue: 07/28/2023
Date of first issue: 01/18/2023

		TWA (Dust)	5 mg/m3 (Iron)	CA BC OEL
		TWA (Dust)	5 mg/m3 (Iron)	CA BC OEL
		STEL (Fumes)	10 mg/m3 (Iron)	CA BC OEL
		STEL (Fumes)	10 mg/m3 (Iron)	CA BC OEL
		TWAEV (fume and dust)	5 mg/m3 (Iron)	CA QC OEL
		TWAEV (fume and dust)	5 mg/m3 (Iron)	CA QC OEL
		TWA (Respirable particulate matter)	5 mg/m3	ACGIH
		TWA (Respirable particulate matter)	5 mg/m3	ACGIH
Mica-group minerals	12001-26-2	TWA (Respirable)	3 mg/m3	CA AB OEL
		TWA (Respirable)	3 mg/m3	CA BC OEL
		TWAEV (respirable dust)	3 mg/m3	CA QC OEL
		TWA (Respirable particulate matter)	0.1 mg/m3	ACGIH
Titanium dioxide	13463-67-7	TWA	10 mg/m3	CA AB OEL
		TWA (Total dust)	10 mg/m3	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m3	CA BC OEL
		TWAEV (total dust)	10 mg/m3	CA QC OEL
		TWA (Respirable particulate matter)	0.2 mg/m3 (Titanium dioxide)	ACGIH
		TWA (Respirable particulate matter)	2.5 mg/m3 (Titanium dioxide)	ACGIH

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the occupa-

SAFETY DATA SHEET

MasterFinish HV 48 pnk

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
2.0	08/15/2023	000000260657	Date of first issue: 01/18/2023

tional exposure limits they must use appropriate certified respirators.
Use NIOSH approved respiratory protection.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Tightly fitting safety goggles (chemical goggles).

Skin and body protection : Body protection must be chosen based on level of activity and exposure.

Protective measures : Do not inhale gases/vapours/aerosols.
Avoid contact with the skin, eyes and clothing.
Avoid exposure - obtain special instructions before use.
Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.
Hands and/or face should be washed before breaks and at the end of the shift.
At the end of the shift the skin should be cleaned and skin-care agents applied.
Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.
Gloves must be inspected regularly and prior to each use.
Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : various colours

Odor : sweetish, solvent

Odor Threshold : No data available

pH : Not applicable

Melting point : No applicable information available.

Freezing point : No applicable information available.

Boiling point : 110 °C

SAFETY DATA SHEET



MasterFinish HV 48 pnk

Version 2.0	Revision Date: 08/15/2023	SDS Number: 000000260657	Date of last issue: 07/28/2023 Date of first issue: 01/18/2023
----------------	------------------------------	-----------------------------	---

Flash point	:	4 °C
Evaporation rate	:	No applicable information available.
Flammability (liquids)	:	Highly flammable liquid and vapor. Method: derived from flash point
Upper explosion limit / Upper flammability limit	:	6.7 %(V)
Lower explosion limit / Lower flammability limit	:	2.5 %(V)
Vapor pressure	:	No data available
Relative vapor density	:	Heavier than air.
Relative density	:	No applicable information available.
Density	:	0.96 - 1.15 g/cm3 (20 °C)
Bulk density	:	Not applicable
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No applicable information available.
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, dynamic	:	No applicable information available.
Viscosity, kinematic	:	No applicable information available.
Explosive properties	:	Not explosive
Oxidizing properties	:	Based on its structural properties the product is not classified as oxidizing.
Sublimation temperature	:	No applicable information available.
Molecular weight	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

SAFETY DATA SHEET



MasterFinish HV 48 pnk

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
2.0	08/15/2023	000000260657	Date of first issue: 01/18/2023

Reactivity	:	No hazardous reactions if stored and handled as prescribed/indicated.
Chemical stability	:	The product is stable if stored and handled as prescribed/indicated.
Possibility of hazardous reactions	:	Vapors may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Strong acids Strong bases Strong oxidizing agents Strong reducing agents
Hazardous decomposition products	:	No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer.

IARC	Group 1: Carcinogenic to humans Quartz (SiO ₂) (Silica dust, crystalline)	14808-60-7
	Group 2B: Possibly carcinogenic to humans Titanium dioxide	13463-67-7

Reproductive toxicity

Suspected of damaging the unborn child.

STOT-single exposure

May cause drowsiness or dizziness.

SAFETY DATA SHEET



MasterFinish HV 48 pnk

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
2.0	08/15/2023	000000260657	Date of first issue: 01/18/2023

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

Remarks : The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not discharge product into the environment without control.
The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regulations.
Do not contaminate ponds, waterways or ditches with chemi-

SAFETY DATA SHEET



MasterFinish HV 48 pnk

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
2.0	08/15/2023	000000260657	Date of first issue: 01/18/2023

cal or used container.
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(TOLUENE)
Class : 3
Packing group : II
Labels : 3

IATA-DGR

UN/ID No. : UN 1993
Proper shipping name : Flammable liquid, n.o.s.
(TOLUENE)
Class : 3
Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(TOLUENE)
Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(TOLUENE)
Class : 3
Packing group : II
Labels : 3
ERG Code : 128

SAFETY DATA SHEET



MasterFinish HV 48 pnk

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
2.0	08/15/2023	000000260657	Date of first issue: 01/18/2023

Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants

ACGIH / TWA : 8-hour, time-weighted average

CA AB OEL / TWA : 8-hour Occupational exposure limit

CA BC OEL / TWA : 8-hour time weighted average

CA BC OEL / STEL : short-term exposure limit

CA QC OEL / TWAEV : Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Sub-

SAFETY DATA SHEET



MasterFinish HV 48 pnk

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
2.0	08/15/2023	000000260657	Date of first issue: 01/18/2023

stances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 08/15/2023
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN