MasterFinish RL 220



Version Revision Date: SDS Number: Date of last issue: 07/28/2023 2.0 08/15/2023 000000260374 Date of first issue: 01/09/2023

SECTION 1. IDENTIFICATION

Product name : MasterFinish RL 220

Product code : 00000000055516322 00000000055516322

Manufacturer or supplier's details

Company name of supplier : Master Builders-Admixtures US,LLC

Address : 23700 Chagrin Blvd

Beachwood OH 44122

Emergency telephone : ChemTel: +1-813-248-0585

National Emergency Tele-

phone Number

USA: +1-800-255-3924 ChemTel contract no. MIS9240420

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Aspiration hazard : Category 1

Flammable liquids : Category 3

Skin corrosion/irritation : Category 2

Serious eye damage/eye

irritation

Category 2A

Germ cell mutagenicity : Category 1B

Carcinogenicity : Category 1B

Specific target organ toxicity

- repeated exposure

Category 1 (Central nervous system)

Short-term (acute) aquatic

hazard

Category 3

Long-term (chronic) aquatic

hazard

Category 3

GHS label elements

MasterFinish RL 220



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/28/2023

 2.0
 08/15/2023
 000000260374
 Date of first issue: 01/09/2023

Hazard pictograms :







Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H304 May be fatal if swallowed and enters airways.

H350 May cause cancer.

H340 May cause genetic defects.

H372 Causes damage to organs (Central nervous system)

through prolonged or repeated exposure.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements :

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking. P260 Do not breathe dusts or mists.

P202 Do not handle until all safety precautions have been read

and understood.

P273 Avoid release to the environment.

P243 Take action to prevent static discharges.

P241 Use explosion-proof electrical/ ventilating/ lighting/ .? /

equipment.

P270 Do not eat, drink or smoke when using this product.

P264 Wash face, hands and any exposed skin thoroughly after

handling.

P233 Keep container tightly closed.

P242 Use only non-sparking tools.

P240 Ground and bond container and receiving equipment.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/ attention if you feel unwell. P308 + P311 IF exposed or concerned: Call a POISON

CENTER/ doctor.

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P332 + P313 If skin irritation occurs: Get medical advice/ atten-

tion.

P331 Do NOT induce vomiting.

P337 + P313 If eye irritation persists: Get medical advice/ atten-

tion.

P362 + P364 Take off contaminated clothing and wash it before

MasterFinish RL 220



Version Revision Date: SDS Number: Date of last issue: 07/28/2023 2.0 08/15/2023 000000260374 Date of first issue: 01/09/2023

reuse.

P370 + P378 In case of fire: Use water spray, alcohol-resistant

foam, dry chemical or carbon dioxide to extinguish.

Storage:

P405 Store locked up.

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/container to appropriate hazardous

waste collection point.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Aromatic hydrocarbons

Components

Chemical name	CAS-No.	Concentration (% w/w)
Stoddard solvent	8052-41-3	>= 50 - < 100
2-butoxyethanol	111-76-2	>= 7 - < 10
Distillates (petroleum), solvent-	64742-65-0	>= 5 - < 10
dewaxed heavy paraffinic		
1,2,4-trimethylbenzene	95-63-6	>= 1 - < 5
Trimethylbenzene	25551-13-7	>= 0.3 - < 5
Distillates (petroleum), solvent-	64742-56-9	>= 1 - < 5
dewaxed light paraffinic		
naphthalene	91-20-3	>= 0.3 - < 1
cumene	98-82-8	>= 0 - < 1
ethylbenzene	100-41-4	>= 0 - < 1

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.

Immediately remove contaminated clothing.

If inhaled : If difficulties occur after vapour/aerosol has been inhaled,

remove to fresh air and seek medical attention.

In case of skin contact : After contact with skin, wash immediately with plenty of water

and soap.

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact : Remove contact lenses, if present.

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention. Do NOT induce vomiting.

MasterFinish RL 220



Version **Revision Date:** SDS Number: Date of last issue: 07/28/2023 08/15/2023 000000260374 Date of first issue: 01/09/2023 2.0

Most important symptoms and effects, both acute and

delayed

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation. May cause genetic defects.

May cause cancer.

Causes damage to organs through prolonged or repeated

exposure.

Notes to physician Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media Foam

> Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

water jet

Specific hazards during fire

fighting

See SDS section 10 - Stability and reactivity.

Hazardous combustion prod-

ucts

harmful vapours nitrogen oxides fumes/smoke carbon black carbon oxides

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

for fire-fighters

Special protective equipment : Wear a self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer-

gency procedures

Do not breathe vapour/aerosol/spray mists.

Wear eye/face protection.

If exposed to high vapour concentration, leave area immedi-

ately.

Use personal protective clothing.

Handle in accordance with good building materials hygiene

and safety practice.

Contain contaminated water/firefighting water. **Environmental precautions**

Do not discharge into drains/surface waters/groundwater.

MasterFinish RL 220



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/28/2023

 2.0
 08/15/2023
 000000260374
 Date of first issue: 01/09/2023

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Keep away from open flames, hot surfaces and sources of

ignition.

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapors).

Advice on safe handling : Avoid aerosol formation.

Avoid inhalation of mists/vapours.

Avoid skin contact.

Avoid contact with eyes.

Conditions for safe storage : No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Avoid all sources of ignition: heat, sparks, open flame.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
naphthalene	91-20-3	TWA	10 ppm	ACGIH
		TWA	10 ppm 50 mg/m3	NIOSH REL
		ST	15 ppm 75 mg/m3	NIOSH REL
		TWA	10 ppm 50 mg/m3	OSHA Z-1
		TWA	10 ppm 50 mg/m3	OSHA P0
		STEL	15 ppm 75 mg/m3	OSHA P0
1,2,4-trimethylbenzene	95-63-6	TWA	25 ppm 125 mg/m3	NIOSH REL
		TWA	25 ppm 125 mg/m3	OSHA P0
		TWA	10 ppm	ACGIH

MasterFinish RL 220



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/28/2023

 2.0
 08/15/2023
 000000260374
 Date of first issue: 01/09/2023

2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm	NIOSH REL
			24 mg/m3	
		TWA	50 ppm	OSHA Z-1
			240 mg/m3	
		TWA	25 ppm	OSHA P0
			120 mg/m3	
Stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		С	1,800 mg/m3	NIOSH REL
		TWA	500 ppm	OSHA Z-1
			2,900 mg/m3	
		TWA	100 ppm	OSHA P0
			525 mg/m3	
Trimethylbenzene	25551-13-7	TWA value	25 ppm	ACGIHTLV
		TWA value	25 ppm	29 CFR
			125 mg/m3	1910.1000
				(Table Z-1-A)
		REL value	25 ppm	NIOSH
			125 mg/m3	
		TWA	25 ppm	ACGIH
		TWA	25 ppm	OSHA P0
			125 mg/m3	
Distillates (petroleum), solvent-	64742-65-0	TWA (Inhal-	5 mg/m3	ACGIH
dewaxed heavy paraffinic		able particu-		
		late matter)		
Distillates (petroleum), solvent-	64742-56-9	TWA value	5 mg/m3	ACGIHTLV
dewaxed light paraffinic		(Inhalable		
		fraction)		
		TWA (Inhal-	5 mg/m3	ACGIH
		able particu-		
		late matter)		

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the occupa-

tional exposure limits they must use appropriate certified

respirators.

Use NIOSH approved respiratory protection.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's

directions for use should be observed because of great di-

versity of types.

Eye protection : Tightly fitting safety goggles (chemical goggles).

Skin and body protection : Body protection must be chosen based on level of activity

and exposure.

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

MasterFinish RL 220



Version Revision Date: SDS Number: Date of last issue: 07/28/2023 2.0 08/15/2023 000000260374 Date of first issue: 01/09/2023

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.

Hands and/or face should be washed before breaks and at

the end of the shift.

At the end of the shift the skin should be cleaned and skin-

care agents applied.

Remove contaminated clothing immediately and clean before

re-use or dispose it if necessary.

Gloves must be inspected regularly and prior to each use.

Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : clear

Odor : aromatic

Odor Threshold : No data available

pH : No data available

Melting point : No applicable information available.

Boiling point : 322 °F / 161 °C

Flash point : 103 °F / 39 °C

Evaporation rate : not determined

Flammability (liquids) : Combustible liquid.

Upper explosion limit / Upper

flammability limit

6.0 %(V)

Lower explosion limit / Lower

flammability limit

1.0 %(V)

Vapor pressure : No data available

Relative vapor density : 4.5

Relative density : No applicable information available.

MasterFinish RL 220



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/28/2023

 2.0
 08/15/2023
 000000260374
 Date of first issue: 01/09/2023

Density : approx. 1 g/cm3

Solubility(ies)

Water solubility : slightly soluble

Solubility in other solvents : No applicable information available.

Partition coefficient: n-

octanol/water

No applicable information available.

Autoignition temperature : 450 °F / 232 °C

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : not determined

Viscosity, kinematic : not determined

Explosive properties : Not explosive

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.

Sublimation point : No applicable information available.

Molecular weight : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as pre-

scribed/indicated.

Chemical stability : The product is stable if stored and handled as pre-

scribed/indicated.

Possibility of hazardous reac-

tions

The product is stable if stored and handled as pre-

scribed/indicated.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

Traces of the substances/groups of substances are released

as decomposition products of the dry substance.

carbon oxides nitrogen oxides Hydrocarbons

MasterFinish RL 220



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/28/2023

 2.0
 08/15/2023
 000000260374
 Date of first issue: 01/09/2023

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

May cause genetic defects.

Carcinogenicity

May cause cancer.

may cause car	ncer.	
IARC	Group 1: Carcinogenic to humans benzene	71-43-2
	Group 2B: Possibly carcinogenic to humans ethylbenzene	100-41-4
	Group 2B: Possibly carcinogenic to humans cumene	98-82-8
	Group 2B: Possibly carcinogenic to humans naphthalene	91-20-3
OSHA	OSHA specifically regulated carcinogen benzene	71-43-2
NTP	Reasonably anticipated to be a human carcinogen cumene	98-82-8
	Reasonably anticipated to be a human carcinogen naphthalene	91-20-3

Reproductive toxicity

Not classified based on available information.

Known to be human carcinogen

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

71-43-2

Aspiration toxicity

May be fatal if swallowed and enters airways.

MasterFinish RL 220



Version Revision Date: SDS Number: Date of last issue: 07/28/2023 2.0 08/15/2023 000000260374 Date of first issue: 01/09/2023

Product:

May also damage the lung at swallowing (aspiration hazard).

Further information

Product:

Remarks : Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from the properties of the individual

components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regula-

tions.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

MasterFinish RL 220



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/28/2023

 2.0
 08/15/2023
 000000260374
 Date of first issue: 01/09/2023

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1993

Proper shipping name : FLAMMABLE LIQUID, N.O.S.

Class : 3 Packing group : III Labels : 3

IATA-DGR

UN/ID No. : UN 1993

Proper shipping name : Flammable liquid, n.o.s.

(STODDARD SOLVENT)

Class : 3 Packing group : III

Labels : Flammable Liquids

Packing instruction (cargo : 366

aircraft)

Packing instruction (passen- : 355

ger aircraft)

IMDG-Code

UN number : UN 1993

Proper shipping name : FLAMMABLE LIQUID, N.O.S.

(STODDARD SOLVENT)

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1993

Proper shipping name : Flammable liquids, n.o.s.

(STODDARD SOLVENT)

Class : 3 Packing group : III

Labels : FLAMMABLE LIQUID

ERG Code : 128 Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
xylene	1330-20-7	100	1674
benzene	71-43-2	10	2511





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/28/2023

 2.0
 08/15/2023
 000000260374
 Date of first issue: 01/09/2023

naphthalene	91-20-3	100	25113
ethylbenzene	100-41-4	1000	41855
toluene	108-88-3	1000	41855

SARA 313

The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

1,2,4- 95-63-6

trimethylbenzene

2-butoxyethanol 111-76-2

The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

naphthalene 91-20-3

ethylbenzene 100-41-4

US State Regulations

Pennsylvania Right To Know

1,2,4-trimethylbenzene	95-63-6
2-butoxyethanol	111-76-2
Stoddard solvent	8052-41-3
Trimethylbenzene	25551-13-7
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9

New Jersey Right To Know

1,2,4-trimethylbenzene	95-63-6
2-butoxyethanol	111-76-2
Stoddard solvent	8052-41-3
Trimethylbenzene	25551-13-7
naphthalene	91-20-3
ethylbenzene	100-41-4

California Prop. 65

WARNING: This product can expose you to chemicals including cumene, which is/are known to the State of California to cause cancer, and

toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Further information


MasterFinish RL 220



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/28/2023


 2.0
 08/15/2023
 000000260374
 Date of first issue: 01/09/2023

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA PO : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

1-A) / TWA value

ACGIH / TWA : 8-hour, time-weighted average
ACGIHTLV / TWA value : Time Weighted Average (TWA):
NIOSH / REL value : Recommended exposure limit (REL):

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

NIOSH REL / C : Ceiling value not be exceeded at any time.

OSHA P0 / TWA : 8-hour time weighted average OSHA P0 / STEL : Short-term exposure limit OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Har-

MasterFinish RL 220



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/28/2023

 2.0
 08/15/2023
 000000260374
 Date of first issue: 01/09/2023

monized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk: IC50 - Half maximal inhibitory concentration: ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 08/15/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN