

SAFETY DATA SHEET



MasterFinish OC 38 LIL

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
3.0	08/15/2023	000000260009	Date of first issue: 01/05/2023

SECTION 1. IDENTIFICATION

Product name : MasterFinish OC 38 LIL

Product code : 000000000051014397 000000000051014397

Manufacturer or supplier's details

Company name of supplier : Master Builders-Admixtures US,LLC

Address : 23700 Chagrin Blvd
Beachwood OH 44122

Emergency telephone : ChemTel: +1-813-248-0585

National Emergency Tele-
phone Number : USA: +1-800-255-3924 ChemTel contract no. MIS9240420

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity : Category 2

Flammable liquids : Category 2

Skin corrosion/irritation : Category 2

Serious eye damage/eye
irritation : Category 2A

Specific target organ toxicity : Category 3
- single exposure

Specific target organ toxicity : Category 2
- repeated exposure

Short-term (acute) aquatic
hazard : Category 1

GHS label elements

SAFETY DATA SHEET

MasterFinish OC 38 LIL

Version	Revision Date:	SDS Number:	Date of last issue:
3.0	08/15/2023	000000260009	07/28/2023
			Date of first issue: 01/05/2023

Hazard pictograms

:



Signal Word

:

Danger

Hazard Statements

:

H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.
H315 Causes skin irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.

Precautionary Statements

:

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P243 Take action to prevent static discharges.
P260 Do not breathe dusts or mists.
P242 Use only non-sparking tools.
P240 Ground and bond container and receiving equipment.
P264 Wash face, hands and any exposed skin thoroughly after handling.
P241 Use explosion-proof electrical, ventilating and lighting equipment.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P314 Get medical advice/ attention if you feel unwell.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P391 Collect spillage.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
P233 Keep container tightly closed.

SAFETY DATA SHEET

MasterFinish OC 38 LIL

Version 3.0 Revision Date: 08/15/2023 SDS Number: 000000260009 Date of last issue: 07/28/2023
Date of first issue: 01/05/2023

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No data available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
propan-2-ol	67-63-0	$\geq 25 - < 50$
Amines, N-tallow alkyltrimethylenedi-, oleates	61791-53-5	$\geq 3 - < 5$
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	$\geq 1 - \leq 3$

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.
If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).
Immediately remove contaminated clothing.
Move out of dangerous area.
Show this material safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : Keep patient calm, remove to fresh air, seek medical attention.
Immediately administer a corticosteroid from a controlled/metered dose inhaler.

Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.

In case of skin contact : Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.

In case of eye contact : Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

Immediately flush eye(s) with plenty of water.

SAFETY DATA SHEET



MasterFinish OC 38 LIL

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
3.0	08/15/2023	000000260009	Date of first issue: 01/05/2023

- Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.
- Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Foam
Dry powder
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapors accumulating to form explosive concentra-

SAFETY DATA SHEET



MasterFinish OC 38 LIL

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
3.0	08/15/2023	000000260009	Date of first issue: 01/05/2023

tions. Vapors can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Product is not explosive.

Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).
Use only explosion-proof equipment.
Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Protect from direct sunlight.

Materials to avoid : Observe TRGS 509/510 storage rules.

Recommended storage temperature : 32 °F / 0 °C

SAFETY DATA SHEET

MasterFinish OC 38 LIL

Version 3.0 Revision Date: 08/15/2023 SDS Number: 000000260009 Date of last issue: 07/28/2023
 Date of first issue: 01/05/2023

Further information on storage stability : Minimum storage temperature:

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m ³	NIOSH REL
		ST	500 ppm 1,225 mg/m ³	NIOSH REL
		TWA	400 ppm 980 mg/m ³	OSHA Z-1
		TWA	400 ppm 980 mg/m ³	OSHA P0
		STEL	500 ppm 1,225 mg/m ³	OSHA P0
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (Total dust)	10 mg/m ³	OSHA P0
		TWA (Respirable particulate matter)	0.2 mg/m ³ (Titanium dioxide)	ACGIH
		TWA (Respirable particulate matter)	2.5 mg/m ³ (Titanium dioxide)	ACGIH
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.
 Use NIOSH approved respiratory protection.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
 Tightly fitting safety goggles
 Wear face-shield and protective suit for abnormal processing problems.

SAFETY DATA SHEET



MasterFinish OC 38 LIL

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
3.0	08/15/2023	000000260009	Date of first issue: 01/05/2023

Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Protective measures	: Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: pigmented
Odor	: characteristic
Odor Threshold	: No data available
pH	: slightly alkaline
Melting point	: No applicable information available.
Boiling point	: 183 °F / 84 °C
Flash point	: 54 °F / 12 °C Method: Flash-Point by Pensky-Martens Closed Cup Tester.
Flammability (solid, gas)	: Highly flammable. Method: derived from flash point
Upper explosion limit / Upper flammability limit	: 12.0 %(V)
Lower explosion limit / Lower flammability limit	: 2.0 %(V)
Vapor pressure	: No data available
Relative vapor density	: No data available.
Relative density	: approx. 1.0

SAFETY DATA SHEET



MasterFinish OC 38 LIL

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
3.0	08/15/2023	000000260009	Date of first issue: 01/05/2023

Density	:	1.0 g/cm ³ (68 °F / 20 °C)
Bulk density	:	Not applicable
Solubility(ies)	:	
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	No data available.
Autoignition temperature	:	750 °F / 399 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity	:	
Viscosity, dynamic	:	No data available.
Explosive properties	:	Not explosive Not explosive
Oxidizing properties	:	Based on its structural properties the product is not classified as oxidizing.
Molecular weight	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapors may form explosive mixture with air.
Conditions to avoid	:	See SDS section 7 - Handling and storage. Avoid all sources of ignition: heat, sparks, open flame. Heat, flames and sparks.
Incompatible materials	:	Peroxides Oxidizing agents Reducing agents
Hazardous decomposition products	:	carbon oxides nitrogen oxides Hydrocarbons

MasterFinish OC 38 LIL

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
3.0	08/15/2023	000000260009	Date of first issue: 01/05/2023

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Product:

Acute oral toxicity	:	ATE: > 5,000 mg/kg
Acute inhalation toxicity	:	ATE: > 20.0000 mg/l Remarks: Determined for vapor
		ATE: > 5.0000 mg/l Remarks: Determined for mist
Acute dermal toxicity	:	ATE: > 5,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks	:	May cause skin irritation in susceptible persons.
---------	---	---

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks	:	May cause irreversible eye damage.
---------	---	------------------------------------

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

SAFETY DATA SHEET



MasterFinish OC 38 LIL

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
3.0	08/15/2023	000000260009	Date of first issue: 01/05/2023

Components:

Amines, N-tallow alkyltrimethylenedi-, oleates:

Not applicable

Further information

Product:

Remarks	:	The product has not been tested. The statement has been derived from the properties of the individual components.
Remarks	:	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity	:	Very toxic to aquatic life.
Chronic aquatic toxicity	:	This product has no known ecotoxicological effects.

Persistence and degradability

No data available

Bioaccumulative potential

Components:

Amines, N-tallow alkyltrimethylenedi-, oleates:

Partition coefficient: n-octanol/water	:	Remarks: Not applicable
--	---	-------------------------

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information	:	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life.
-----------------------------------	---	--

SAFETY DATA SHEET



MasterFinish OC 38 LIL

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
3.0	08/15/2023	000000260009	Date of first issue: 01/05/2023

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- | | | |
|------------------------|---|---|
| Waste from residues | : | Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with national, state and local regulations.
Do not discharge into drains/surface waters/groundwater. |
| Contaminated packaging | : | Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product. |

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

- | | | |
|----------------------|---|------------------|
| UN number | : | UN 1139 |
| Proper shipping name | : | COATING SOLUTION |
| Class | : | 3 |
| Packing group | : | II |
| Labels | : | 3 |

IATA-DGR

- | | | |
|--|---|-------------------|
| UN/ID No. | : | UN 1139 |
| Proper shipping name | : | Coating solution |
| Class | : | 3 |
| Packing group | : | II |
| Labels | : | Flammable Liquids |
| Packing instruction (cargo aircraft) | : | 364 |
| Packing instruction (passenger aircraft) | : | 353 |

IMDG-Code

- | | | |
|----------------------|---|---|
| UN number | : | UN 1139 |
| Proper shipping name | : | COATING SOLUTION
(2-PROPANOL, FATTY AMINE OLEAT) |
| Class | : | 3 |
| Packing group | : | II |
| Labels | : | 3 |
| EmS Code | : | F-E, <u>S-E</u> |
| Marine pollutant | : | yes |

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

- | | | |
|----------------------|---|------------------|
| UN/ID/NA number | : | UN 1139 |
| Proper shipping name | : | Coating solution |

SAFETY DATA SHEET



MasterFinish OC 38 LIL

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
3.0	08/15/2023	000000260009	Date of first issue: 01/05/2023

Class	:	3
Packing group	:	II
Labels	:	FLAMMABLE LIQUID
ERG Code	:	127
Marine pollutant	:	no

SECTION 15. REGULATORY INFORMATION

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

propan-2-ol	67-63-0
-------------	---------

US State Regulations

Pennsylvania Right To Know

propan-2-ol	67-63-0
Titanium dioxide	13463-67-7
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0

New Jersey Right To Know

propan-2-ol	67-63-0
Titanium dioxide	13463-67-7

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer, and toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All substances listed as active on the TSCA inventory

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

MasterFinish OC 38 LIL


Version
3.0

Revision Date:
08/15/2023

SDS Number:
000000260009

Date of last issue: 07/28/2023
Date of first issue: 01/05/2023

NFPA 704:



HMIS® IV:

HEALTH		M
FLAMMABILITY		H
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA P0	: USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	: 8-hour time weighted average
OSHA P0 / STEL	: Short-term exposure limit
OSHA Z-1 / TWA	: 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International

SAFETY DATA SHEET



MasterFinish OC 38 LIL

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
3.0	08/15/2023	000000260009	Date of first issue: 01/05/2023

Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 08/15/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN