

3	03 30 00	Cast-in-Place Concrete
	03 40 00	Precast Concrete
	03 70 00	Mass Concrete
	03 37 13	Shotcrete
31	31 74 16	Precast Concrete Tunnel Lining

# MasterFiber® 515

## Type I Steel Fiber

### Description

MasterFiber 515 product is a low carbon, cold-drawn wire fiber manufactured in compliance with ASTM A820/A820M “Standard Specification for Steel Fibers for Fiber-Reinforced Concrete”. MasterFiber 515 product can be used in producing Type I Steel Fiber-Reinforced Concrete meeting the requirements of ASTM C1116/C1116M “Standard Specification for Fiber-Reinforced Concrete”.

### Applications

Recommended for use in:

- Industrial flooring
- Commercial flooring
- Residential foundations
- Basement walls
- Pavements
- Compression layers
- Precast tunnel segments
- Final tunnel lining
- Mass concrete
- Overlays
- Footings/Foundations
- Precast elements
- Shotcrete

### Features

- Uniform distribution throughout the concrete matrix
- Loose fibers specially designed to avoid balling problems

### Benefits

- Provides effective crack control
- Provides uniform shrinkage and temperature reinforcement
- Can be used as the primary reinforcement, depending on the application
- Provides excellent control of settlement cracking
- Reduces construction time and overall labor and material costs
- Increases flexural toughness, impact and shatter resistance
- Can help reduce concrete thickness required
- Can be used for shear resistance in accordance with ACI CODE-318-19 Building Code Requirements for Structural Concrete
- Provides higher energy absorption and increases concrete ductility
- Facilitates sustainable construction

### Performance Characteristics

#### Typical Physical Properties

Specific Gravity	7.85
Melting Point	2000 °F (1093 °C)
Length	2.3 in. (60 mm)
Aspect Ratio	67
Tensile Strength	160 – 203 ksi (1100 – 1400 MPa)



## Guidelines for Use

**Dosage:** For most applications, the typical recommended dosage will be in the range of 15 to 80 lb/yd<sup>3</sup> (9 to 48 kg/m<sup>3</sup>). However, depending on the specific application, dosages outside of the typical range and as high as 200 lb/yd<sup>3</sup> (120 kg/m<sup>3</sup>) may be required. Please contact your local sales representative, if dosages outside the recommended range are required.

**Mixing:** Never add fibers as the first component in the mixer or during the addition of cementitious materials. Fiber bags should be opened, and the fibers introduced together with sand and coarse aggregates.

## Suggested Specification Language

Steel fiber shall meet the requirements of ASTM A820/C820M, Type I steel fiber and designed for use in making fiber-reinforced concrete complying with ASTM C1116/C1116M. Product shall be MasterFiber 515 by Master Builders Solutions.

## Storage and Handling

**Storage Temperature:** MasterFiber 515 product should be stored in a clean, dry area. Avoid storing near wet and high humidity areas. Use caution when stacking to avoid unstable conditions.

## Packaging

MasterFiber 515 product is packaged in 44 lb (20 kg) bags.

## Additional Information

For additional information on the MasterFiber 515 product, contact your local sales representative.

*Master Builders Solutions creates technologies for the construction industry inspiring people to build better. We are active in ~40 countries and operate 35 production sites with over 1,600 employees. We develop, produce, and market high-quality chemical admixtures, as well as adjacent core technologies, to master the challenges of today and support a decarbonized future. Our people are pivotal and pair leading technologies and a strong brand heritage to surpass our customers' expectations and drive continuous value creation.*

## Limited Warranty Notice

Master Builders Solutions Admixtures US, LLC ("Master Builders Solutions") warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. MASTER BUILDERS SOLUTIONS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders Solutions. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS SOLUTIONS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders Solutions' present knowledge and experience. However, Master Builders Solutions assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders Solutions reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.