

MasterRoc[®] SWA 705

Strong Thickener for Soil Conditioning in Tunnel Boring Machines (TBM)

Description

MasterRoc SWA 705 is a liquid polymer, specifically formulated for use in ground and slurry conditioning. MasterRoc SWA 705 polymer works as a binding agent, to increase soil plasticity and cohesion, which helps to improve the balance of pressure in the working chamber, resulting in better ground stability and soil extraction.

MasterRoc SWA 705 polymer can be used to enhance the performance of MasterRoc SLF foams and MasterRoc ACP soil conditioning products in saturated soils. MasterRoc SWA 705 polymer is also suitable for use for an adequate sealing of the excavation face during hyperbaric interventions in combination with the injection of bentonite or filler slurries.

Applications

Recommended for use in:

- Earth pressure Balance (EPB) and Slurry TBMs
- Bentonite slurry modification in case of high soil porosity or saline water conditions
- Improving the yield and filter cake properties of bentonite and filler slurries
- Lubricant for pipe jacking

Features

- Reduced soil permeability
- Ready to use - no mixing equipment required

Benefits

- Provides an even and controlled support pressure and increased face stability by creation of plastic deformation properties in the soil
- Lowers the inner friction and abrasiveness of the soil
- Increases cohesion of coarse sands and gravels
- Improves the yield and filter cake properties of bentonite slurries

Performance Characteristics

Technical Data

Form	Liquid
Color	Light yellow
Density* lb/ft ³ (g/cm ³)	74.3 - 76.8 (1.19 - 1.23)
pH*	8.9 – 9.1
Dynamic Viscosity*	3,000 - 6,000 mPa.s
Solubility in water	Miscible

*@ 68 °F (20 °C)

Application procedure

MasterRoc SWA 705 polymer can be added by a separate dosing pump into the foaming system. Injection point must be right after the foam generators.

MasterRoc SWA 705 polymer can also be used independently, in which case it is injected directly to the working chamber or the screw conveyor. The quantity of MasterRoc SWA 705 polymer needed depends on the soil conditions. For the combination with other soil conditioning agents, please contact your local Master Builders Solutions representative.



Guidelines for Use

Trials should be conducted to determine the optimum dosage of MasterRoc SWA 705 polymer. The dosage depends on the application field and the amount of water content in slurry or excavated ground. Please consult your local Master Builders Solutions representative for guidance.

Storage and Handling

Storage Temperature: MasterRoc SWA 705 polymer must be stored at temperatures above 44 °F (7 °C) to avoid dispensing difficulties due to thickening. Do not allow MasterRoc SWA 705 polymer to freeze, since it cannot be reconstituted after thawing.

Shelf Life: MasterRoc SWA 705 polymer has a minimum shelf life of 12 months. Depending on storage conditions, the shelf life may be greater than stated. Please contact your local Master Builders Solutions representative regarding suitability for use and dosage recommendations if the shelf life of MasterRoc SWA 705 polymer has been exceeded.

Handling: Contact with water in hoses, pumps, tanks or receiving vessels must be avoided to prevent gelling when transferring MasterRoc SWA 705 polymer to other containers.

Dispensing: Consult your local Master Builders Solutions representative for the proper dispensing equipment for MasterRoc SWA 705 polymer. If dispensing directly from the 55 gal (208 L) drum, it is recommended that the larger 2 in. (50 mm) opening be used.

Packaging

MasterRoc SWA 705 polymer is supplied in 55 gal (208 L) drums and 275 gal (1040 L) IBCs.

Safety precautions

MasterRoc SWA 705 polymer contains no hazardous substances. However, standard precautions for handling chemical products should be observed. Avoid eye and skin contact and wear rubber gloves. For further information, refer to the Safety Data Sheet.

Related Documents

Safety Data Sheets: MasterRoc SWA 705 polymer

Additional Information

For additional information on MasterRoc SWA 705 polymer, contact your local sales representative.

Master Builders Solutions creates technologies for the construction industry inspiring people to build better. We are active in ~40 countries and operate 35 production sites with over 1,600 employees. We develop, produce, and market high-quality chemical admixtures, as well as adjacent core technologies, to master the challenges of today and support a decarbonized future. Our people are pivotal and pair leading technologies and a strong brand heritage to surpass our customers' expectations and drive continuous value creation.

Limited Warranty Notice

Master Builders Solutions Admixtures US, LLC ("Master Builders Solutions") warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. MASTER BUILDERS SOLUTIONS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders Solutions. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS SOLUTIONS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders Solutions' present knowledge and experience. However, Master Builders Solutions assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders Solutions reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.