

# MasterProtect 810CP

A form and pour flowable mortar, for low resistivity environments

## Material Description

**MasterProtect 810CP** is a cementitious flowable mortar that is specifically formulated for passive and hybrid anodes used in cathodic protection of reinforced concrete structures and embedding discrete anodes used in impressed current cathodic protection installations. **MasterProtect 810CP** is especially developed for optimum life expectancy of these CP installations. **MasterProtect 810CP** is a blend of hydraulic cements, selected silica, modifying agents and special additives for pH buffering. When mixed with potable water, **MasterProtect 810CP** forms a flowable mortar with flow characteristics suited for steel congested form and pour applications.

## Areas of Application

Encapsulating passive and hybrid anode systems and embedding discrete anodes used in impressed current cathodic protection installations.

## Characteristics and Benefits

- Improved acid resistance compared to normal mortars against the chemicals created at the anode surface – long life of the anode encasement.
- Low resistivity – enhances current flow through anode.
- Expands during setting - guarantees good filling of the hole and embedding of the anode.
- Long open time – Allows for placing in complex form and pour situations.

## Properties

Supply form	Powder
Grain size (max)	1.5mm
Water added per bag (20kg)	3.5-3.7 litres
Colour	Grey
Density (mixed)	2.14kg/L

Compressive Strength (@4.2 litres/20kg bag)	
- 1 day	25 MPa
- 7 days	55 MPa
- 28 days	65 MPa
Flexural strength 7 days	4 MPa
Electrical Resistivity (Wenner 4 probe method)	
- 7 days	~10000 Ω.cm
- 28 days	~31000 Ω.cm
- 56 days	~36000 Ω.cm
- 90 days	~39000 Ω.cm

## Application

### Substrate Preparation

Loose particles in the holes should be removed. Slightly dampen the substrate if possible and remove free standing water.

### Mixing

Pot life ± 60 minutes

Final set ± 240 minutes

Approximately 3.6 litres of water per 20kg powder is necessary in order to obtain a free flowing consistency. The water dose can change depending on the ambient temperature but should be kept between the limits of 3.5-3.7 litres clean water per 20 kg powder.

**MasterProtect 810CP** may be mixed mechanically with a birdcage mixer on a drill or for larger pours a suitable grout pump. Gradually blend the powder into clean water. Mix until lump free consistency is obtained. Do not overmix.

### Application

Do not apply MasterProtect 810CP to frozen substrates or if ambient temperature is below 5°C or expected to fall below 5°C within 4 hours.

All holes can simply be filled with the material. To assist complete filling of those holes, it can be necessary to move the anodes up and down, in order to release any entrapped air.

# MasterProtect 810CP

A form and pour flowable mortar, for low resistivity environments

## Estimating Data

A 20kg bag of **MasterProtect 810CP** mixed with 3.6 litres of water yields 11 litres.

L	Thickness in mm /m <sup>2</sup>	m <sup>3</sup>	Bags /m <sup>3</sup>	m <sup>2</sup> /mm thickness
11	11.mm	(0.011)	91	11.0 m <sup>2</sup>

## Curing

**MasterProtect 810CP** is self-curing. In hot, dry or windy environments it can be necessary to cover the material with some wet cloths after the initial set.

## Cleaning

**MasterProtect 810CP** is a cementitious product. Tools should be cleaned with water before the material hardens.

## Packaging

**MasterProtect 810CP** is available in 20kg moisture resistant paper bags.

## Storage & Shelf Life

**MasterProtect 810CP** is can be stored in tightly sealed original bags for 12 months if kept dry and at moderate temperature.

## Precautions

For the full health and safety hazard information and how to safely handle and use this product, make sure that you obtain a copy of the Safety Data Sheet (SDS) from our office or website.

## Disclaimer

MasterProtect-810CP-ANZ-V7-0723

### STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this MB Solutions Australia Pty Ltd publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use and for ensuring that the application and use of the product is in accordance with the manufacturer's guidelines and recommendations.

### NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by MB Solutions Australia Pty Ltd either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not MB Solutions Australia Pty Ltd, are responsible for carrying out procedures appropriate to a specific application.

### MB Solutions Australia Pty Ltd

ABN 69 634 934 419  
Unit 102, 2 Burbank Place  
Norwest NSW 2153

Freecall: 1300 227 300

[www.master-builders-solutions.com/en-au](http://www.master-builders-solutions.com/en-au)

### MB Solutions New Zealand Ltd

45C William Pickering Drive  
Albany, Auckland  
New Zealand

Phone: +64 9 414 7233

### Emergency Advice:

1300 954 583 within Australia (24hr)  
0800 001 607 within New Zealand

