

03 30 00	<b>Cast-in-Place Concrete</b>
03 40 00	<b>Precast Concrete</b>
03 70 00	<b>Mass Concrete</b>

# MasterPozzolith<sup>®</sup> 700

## Water-Reducing Admixture

### Description

MasterPozzolith 700 ready-to-use, liquid admixture is used for making more uniform and predictable quality concrete. It is formulated to meet ASTM C 494/C 494M requirements for Type A, water-reducing, Type B, retarding, and Type D, water-reducing and retarding, admixtures.

### Applications

Recommended for use in:

- Ready-mixed concrete
- Precast concrete
- Shotcrete
- Lightweight concrete
- Pumped concrete
- 4x4™ Concrete
- Pervious concrete
- Self-consolidating concrete (SCC)

### Features

- Reduced water content for a given workability
- Controlled setting characteristics – normal or retarded

### Benefits

- Improved workability
- Reduced segregation
- Improved finishing characteristics for flatwork and cast surfaces
- Increased compressive and flexural strength

### Guidelines for Use

**Dosage:** MasterPozzolith 700 admixture is recommended for use at a dosage of 3-5 fl oz/cwt (195-325 mL/100 kg) of cementitious materials for Type A applications and up to 7 fl oz/cwt (460 mL/100 kg) for Type B and D requirements. Because of variations in job conditions and concrete materials, dosages other than the recommended amounts may be required. In such cases, contact your local sales representative.

### Product Notes

**Corrosivity:** MasterPozzolith 700 admixture will neither initiate nor promote corrosion of reinforcing steel in concrete. MasterPozzolith 700 admixture does not contain intentionally-added calcium chloride or other chloride-based ingredients.

**Compatibility:** MasterPozzolith 700 admixture may be used in combination with any Master Builders Solutions admixture. When used in conjunction with other admixtures, each admixture must be dispensed separately into the mixture.



## Storage and Handling

**Storage Temperature:** MasterPozzolith 700 admixture must be stored at temperatures above 35 °F (2 °C). If MasterPozzolith 700 admixture freezes, it can be reconstituted by mild mechanical agitation.

**Do not use pressurized air for agitation.**

**Shelf Life:** MasterPozzolith 700 admixture has a minimum shelf life of 6 months. Depending on storage conditions, the shelf life may be greater than stated. Please contact your local sales representative regarding suitability for use and dosage recommendations if the shelf life of MasterPozzolith 700 admixture has been exceeded.

## Packaging

MasterPozzolith 700 admixture is supplied in 55 gal (208 L) drums, 275 gal (1040 L) totes and by bulk delivery.

## Related Documents

Safety Data Sheets: MasterPozzolith 700 admixture

## Additional Information

For additional information on MasterPozzolith 700 admixture or its use in developing a concrete mixture with special performance characteristics, contact your local sales representative.

*Master Builders Solutions creates technologies for the construction industry inspiring people to build better. We are active in ~40 countries and operate 35 production sites with over 1,600 employees. We develop, produce, and market high-quality chemical admixtures, as well as adjacent core technologies, to master the challenges of today and support a decarbonized future. Our people are pivotal and pair leading technologies and a strong brand heritage to surpass our customers' expectations and drive continuous value creation.*

## Limited Warranty Notice

Master Builders Solutions Admixtures US, LLC ("Master Builders Solutions") warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. MASTER BUILDERS SOLUTIONS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders Solutions. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS SOLUTIONS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders Solutions' present knowledge and experience. However, Master Builders Solutions assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders Solutions reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

