

MasterCast 735

High range water reducing admixture for Manufactured Concrete Products, specially engineered for hollow-core slabs and mixes needing high water reduction.

Material Description

MasterCast 735 is an innovative multi-purpose plasticizer specially developed for earth-dry concretes. The product is particularly suitable for the production of concrete block paving. MasterCast 735 reduces the cycle time whilst the appearance is maintained or even improved. MasterCast 735 is a key component to our FIT 4 VALUE concept.

FIT 4 VALUE considers the four elements essential for MCP Manufactures:

- FIT for Economics
- FIT for Performance
- FIT for Aesthetics
- FIT for Durability

Here, FIT means meeting every requirement for economics, performance, aesthetics and durability.

Areas of Application

MasterCast 735 is suitable for Manufacturing Concrete Products, especially:

- Block paving mixes needing high water reduction.
- Blocks.
- Hollow-core slabs.

Characteristics and Benefits

MasterCast 735 offers the following benefits for the MCP industry to:

- Optimised mix design.
- Enhanced productivity due to shorter cycle time.
- Lower curing energy &/or time
- Increased pigment effectiveness

Application Procedure

MasterCast 735 is a liquid ready-to-use admixture to be added to the concrete during the mixing process. The best results are obtained when the admixture is added after all the other

components are already in the mixer and after the addition of at least 80% of the total water.

The water content is adjusted to obtain the desired consistence or workability.

Dosage

The normally recommended dosage rate for MasterCast 735 is 0.2 to 1.0 litres per 100 kg of cement.

The dosage rates given above are for typical usages, they are not meant as absolute limits, as other dosages may be utilised in special cases according to specific job conditions. If required consult our Technical Services Department for advice. Trial mixes should be carried out to ensure optimum dosage and effect.

Compatibility

MasterCast 735 can be used with all types of EN 197 Cements. For use with other special cements, contact our Technical Services Department.

MasterCast 735 should not be pre-mixed with other admixtures. If other admixtures are to be used in concrete containing MasterCast 735 they must be dispensed separately.

When complimentary admixtures are required it is important that trials are performed, prior to any supply, to determine the respective dosages of any complimentary admixture, and the suitability, in the fresh and hardened state, of the resultant concrete. In these circumstances we recommend that you consult our Technical Services Department for further advice.

MasterCast 735 is compatible and recommended for use with:

- MasterFinish MPT 299, cleaning and protection agent.
- MasterFinish form release agents, to enhance appearance.

Packaging

MasterCast 735 is supplied in 1000-litre IBC's and 15-litre containers.



MasterCast 735

High range water reducing admixture for Manufactured Concrete Products, specially engineered for hollow-core slabs and mixes needing high water reduction.

Contact Details

Master Builders Solutions UK Ltd
Swinton Hall Road,
Swinton,
Manchester,
M27 4EU
Tel: +44 (0) 161 727 6300
www.master-builders-solutions.com/en-gb

| Product Data | |
|------------------------------|--|
| Appearance: | Yellow liquid |
| Specific gravity @ 20°C: | 1.12 ± 0.03 g/cm ³ |
| pH-value: | 7.5 ± 1 |
| Alkali content (%): | ≤ 2.50 by mass |
| Chloride content (%): | ≤ 0.10 by mass |
| Logistics | |
| Shelf life: | 12 months if stored according to manufacturer's instructions in unopened container. |
| Storage conditions: | Store in original sealed containers and at temperatures between 5°C and 30°C. Store under cover, out of direct sunlight and protect from extremes of temperature. Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. |
| Handling and transportation: | Refer to MasterCast 735 Safety Data Sheet |
| Disposal: | Refer to MasterCast 735 Safety Data Sheet |

MasterCast 735

High range water reducing admixture for Manufactured Concrete Products, specially engineered for hollow-core slabs and mixes needing high water reduction.

Disclaimer

MasterCast 735, Master Builders Solutions UK Ltd, Version 6

Health and Safety

*For full information on Health and Safety matters regarding this product the relevant Health and Safety Data Sheet should be consulted.

The following general comments apply to all products.

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs, (which may also be tainted with vapour until the product is fully cured and dried). Treat splashes to eyes and skin immediately. If accidentally ingested, seek medical attention. Keep away from children and animals. Reseal containers after use.

Spillage

Chemical products can cause damage; clean spillage immediately.

DISCLAIMER

"Master Builders Solutions UK Ltd" (the Company) endeavours to ensure that advice and information given in Product Data Sheets, Method Statements and Material Safety Data Sheets (all known as Product Literature) is accurate and correct. However, the Company has no control over the selection of its products for particular applications. It is important that any prospective customer, user or specifier, satisfies him/her-self that the product is suitable for the specific application. In this process, due regard should be taken of the nature and composition of the background/base and the ambient conditions both at the time of laying/applying/installing the material and when the completed work is to be brought into use.

Accordingly, no liability will be accepted by the Company for the selection, by others, of a product, which is inappropriate to a particular application.

Products are sold subject to the Company's standard conditions of sale and all customers, users and specifiers, should ensure that they examine the Company's latest Product Literature.