

MasterCast 28 I

Compaction aid for manufactured concrete products

Material Description

MasterCast 28 I is an innovative admixture specially developed for earth-dry concretes. The product is particularly suitable for the production of concrete bricks & blocks. MasterCast 28 I reduces the cycle time whilst the appearance is maintained or even improved. MasterCast 28 I is a key component our FIT 4 VALUE concept.

FIT 4 VALUE considers the four elements essential for MCP Manufactures:

- FIT for Economics
- FIT for Performance
- FIT for Aesthetics
- FIT for Durability

Here, FIT means meeting every requirement for economics, performance, aesthetics and durability.

Areas of Application

MasterCast 28 I is suitable for Manufacturing Concrete Products, especially:

- Block paving mixes.
- Concrete bricks.

Characteristics and Benefits

MasterCast 28 I offers the following benefits for the MCP industry to:

- Optimised mix design.
- Improved aesthetics
- Enhanced productivity due to shorter cycle time.

Application Procedure

MasterCast 28 I is a liquid ready-to-use admixture to be added to the concrete during the mixing process. The best results are obtained when the admixture is added after all the other components are already in the mixer and after the addition of at least 80% of the total water.

The water content is adjusted to obtain the desired consistency or workability.

Dosage

The normally recommended dosage rate for MasterCast 28 I is 0.2 to 1.0 litres per 100 kg of cement.

The dosage rates given above are for typical usages, they are not meant as absolute limits, as other dosages may be utilised in special cases according to specific job conditions. If required consult our Technical Services Department for advice. Trial mixes should be carried out to ensure optimum dosage and effect.

Compatibility

MasterCast 28 I can be used with most types of EN 197 Cements. For use with Pulverised Fuel Ash, or any other special cements, contact our Technical Services Department.

MasterCast 28 I should not be pre-mixed with other admixtures. If other admixtures are to be used in concrete containing MasterCast 28 I they must be dispensed separately.

MasterCast 28 I is compatible with other MBCC admixtures such as accelerators and water repellents.

When such complimentary admixtures are required it is important that laboratory trials are performed, prior to any supply, to determine the respective dosages of any complimentary admixture, and the suitability, in the fresh and hardened state, of the resultant mortar or concrete. In these circumstances we recommend that you consult our Technical Services Department for further advice.

Packaging

MasterCast 28 I is supplied in 1000-litre IBC's and 15-litre containers.

MasterCast 28 I

Compaction aid for manufactured concrete products

Contact Details

Master Builders Solutions UK Ltd
Swinton Hall Road,
Swinton,
Manchester,
M27 4EU
Tel: +44 (0) 161 727 6300
www.master-builders-solutions.com/en-gb

Product Data - General	
Appearance:	Colourless Liquid
Specific gravity @ 20°C:	1.00 ± 0.02 g/cm ³
pH-value:	7.5 ± 1
Solids content:	18.0 ± 1.5%
Corrosion behaviour:	Contains only components according to BS EN 934-1:2008, Annex A.1
Dangerous substances:	No Performance Determined
Durability:	No Performance Determined
Logistics	
Shelf life:	12 months if stored according to manufacturer's instructions in unopened container.
Storage conditions:	Store in original sealed containers and at temperatures between 5°C and 30°C. Store under cover, out of direct sunlight and protect from extremes of temperature. Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging.
Handling and transportation:	Refer to MasterCast 28 I Safety Data Sheet
Disposal:	Refer to MasterCast 28 I Safety Data Sheet

MasterCast 28 I

Compaction aid for manufactured concrete products

Disclaimer

MasterCast 28 I, Master Builders Solutions UK Ltd, Version 2

Health and Safety

*For full information on Health and Safety matters regarding this product the relevant Health and Safety Data Sheet should be consulted.

The following general comments apply to all products.

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs, (which may also be tainted with vapour until the product is fully cured and dried). Treat splashes to eyes and skin immediately. If accidentally ingested, seek medical attention. Keep away from children and animals. Reseal containers after use.

Spillage

Chemical products can cause damage; clean spillage immediately.

DISCLAIMER

"Master Builders Solutions UK Ltd" (the Company) endeavours to ensure that advice and information given in Product Data Sheets, Method Statements and Material Safety Data Sheets (all known as Product Literature) is accurate and correct. However, the Company has no control over the selection of its products for particular applications. It is important that any prospective customer, user or specifier, satisfies him/her-self that the product is suitable for the specific application. In this process, due regard should be taken of the nature and composition of the background/base and the ambient conditions both at the time of laying/applying/installing the material and when the completed work is to be brought into use.

Accordingly, no liability will be accepted by the Company for the selection, by others, of a product, which is inappropriate to a particular application.

Products are sold subject to the Company's standard conditions of sale and all customers, users and specifiers, should ensure that they examine the Company's latest Product Literature.