

MasterSure 1008

New generation super slump retaining aid for extended slump retention

Material Description

MasterSure 1008 is an innovative new generation polycarboxylate ether based slump retaining aid with super retention technology. Additionally, it can help the ready-mixed / precast concrete industries, where more than normal slump retention and durability are required, particularly in hot climates. **MasterSure 1008** is a specifically tailored, stand-alone product, the constituents of its active ingredient exhibiting unique adsorption characteristics to cement. **MasterSure 1008** can be used in conjunction with Master Builders Solutions polycarboxylate ether and modified lignosulphonate based admixtures only to aid in super slump retention of a concrete mix. The excellent dispersion effect makes MasterSure 1008 the ideal aid for the ready-mixed concrete / precast concrete industry, without affecting concrete setting times. The ability to work over a range of water binder ratios including low w/b ratios and still obtain extended slump retention allows for the manufacture of high quality concrete.

MasterSure 1008 is free of added chloride and complies with ASTM C 494/ C 494M-08, Type G, BS EN 934 – 2:2001, AS 1478.1 - 2000 Type SN and is also compatible with all cements meeting recognized international standards.

Areas of Application

- Super slump retaining concrete with equal or less water content than conventional admixtures
- Faster mixing aids logistics during large pours
- Highly flowable concrete
- Highly durable concrete
- Ready-mixed concrete
- Precast concrete
- Mass concrete
- Long distance transport
- Pumped concrete
- Hot weather concretin

Characteristics & Benefits

- High workability - ease of placing and compaction. No segregation.
- Superior slump retention - no re-tempering. Ease of delivery to point of placement
- Low shrinkage and creep - improve dimensional stability. Reduced risk of cracks.
- Good cohesion - ease of pumping.
- Good workability - excellent surface appearance. Self-compacting concrete.
- Superior slump retention, including mid-range slumps.
- High elastic modulus- superior load bearing capacity

Quantity to Use

Dosage of **MasterSure 1008** depends on the mix design, ambient conditions and degree of water reduction and workability required. **MasterSure 1008** is dispensed at a rate of 150 ml to 350ml per 100 kg of cementitious material. Other dosages may also be used depending on the specific working conditions. Trial mixes should be made with job materials to determine the optimum dosage required for a specified job requirement. Dosage of **MasterSure 1008** can be adjusted according to demand of dosing requirement to affect the right degree of workability.

As highlighted, **MasterSure 1008** can be used in combination with other Master Builders Solutions admixtures to achieve longer slump retention or other specific working requirements. The dosage employed in such cases may be different from the above recommendation. Trial mixes should be made with job materials to determine the optimum dosage required for a specified job requirement.

Dispensing

MasterSure 1008 is a ready-to-use admixture to be added to the concrete mix as a separate component along with a polycarboxylate ether or modified lignosulphonate based admixture.



MasterSure 1008

New generation super slump retaining aid for extended slump retention

Optimal mixing is obtained if **MasterSure 1008** is poured into the concrete mix right after the addition of the first 50 -70% of the mixing water. Avoid adding the admixture to the dry aggregates. A separate dispenser and feed line must be used.

Compatibility

MasterSure 1008 is not compatible with MasterRheobuild admixtures or other admixtures containing naphthalene formaldehyde condensates.

MasterSure 1008 can be used with other Master Builders Solutions admixtures to achieve cost effective customised performance. However, those admixtures should be dispensed separately and added separately to ensure complete distribution throughout the mix. **MasterSure 1008** should not be used in conjunction with other admixtures unless specific test information is available.

Packaging

MasterSure 1008 is supplied in 20 litre pails, 1000 litre pallecons and bulk delivery.

Storage & Shelf Life

Containers should be stored tightly sealed in a dry place. Keep away from heat. Store protected against freezing. Keep only in the original container.

MasterSure 1008 has a shelf life of 12 months.

MasterSure 1008 should be recirculated before use.

Precautions

For the full health and safety hazard information and how to safely handle and use this product, make sure that you obtain a copy of the Safety Data Sheet (SDS) from our office or website.

Disclaimer

MasterSure-1008 -ANZ-V9-0326

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this MB Solutions Australia Pty Ltd publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use and for ensuring that the application and use of the product is in accordance with the manufacturer's guidelines and recommendations.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by MB Solutions Australia Pty Ltd either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not MB Solutions Australia Pty Ltd, are responsible for carrying out procedures appropriate to a specific application.

MB Solutions Australia Pty Ltd

ABN 69 634 934 419
11 Stanton Road
Seven Hills NSW 2147

Freecall: 1300 227 300

www.master-builders-solutions.com/en-au

MB Solutions New Zealand Ltd

45C William Pickering Drive
Albany, Auckland
New Zealand

Phone: +64 9 414 7233

Emergency Advice:

1300 954 583 within Australia (24hr)
0800 001 607 within New Zealand