




## M180L™ TRIPLE STACK SERIES

SURFACE MOUNT



The M180L™ Triple Stack provides the functionality of an intense warning light and a useful worklight to illuminate the scene. It utilizes three rows of LED lights to produce a bright, off-angle, 180° spread. The efficient design allows flexibility for multiple mounting options. Features include 29 flash patterns for single-color models, 69 flash patterns for dual-color models, steady burn and an IP67 rating.



VOLTS   AMPS	12-24V   1.7A	12-24V   1.7A	
DIMS	3.4" H x 5.1" L	3.4" H x 5.1" L x 1.4" D $\mid$ 86mm H x 130mm L x 36mm D	
MOUNTING HOLE SPACING	4.74"   121mm	4.74"   121mm	
FLASH PATTERNS	29 Single, 69 Du	29 Single, 69 Dual	
CERTS	CLASS I: (SAE J! RoHS	CLASS I: (SAE J595, SAE J845), CA T13, ECE REG 65, R10, IP67, RoHS	
DETAILS	<ul> <li>Combines the functionality of a warning light and the utility of a scene light in one</li> <li>Produces a bright, off-angle 180-degree warning light that can be used as an alley light</li> <li>Intersection light, and takedown light, Steady burn for scene light functionality</li> <li>Sync-capable with XTP, MegaThin™, Chase™, MR6, MICROPAK, CD5051, HB12PAK and CD9215</li> </ul>		
REPLACE	"_" with $B = Blue$ , $R = Red$		
MODEL	TYPE	ILLUMINATION COLORS	
M180L	Single	B, R,	
M180LMC	Dual	RB	

M180L-R