



AT Command Reference Guide

EM75xx, EM/MC74x1

Important Notice

Information relating to this product and the application or design described herein is believed to be reliable, however such information is provided as a guide only and Semtech assumes no liability for any errors in this document, or for the application or design described herein.

Semtech reserves the right to make changes to the product or this document at any time without notice. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. Semtech warrants performance of its products to the specifications applicable at the time of sale, and all sales are made in accordance with Semtech's standard terms and conditions of sale.

SEMTECH PRODUCTS ARE NOT DESIGNED, INTENDED, AUTHORIZED OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT APPLICATIONS, DEVICES OR SYSTEMS, OR IN NUCLEAR APPLICATIONS IN WHICH THE FAILURE COULD BE REASONABLY EXPECTED TO RESULT IN PERSONAL INJURY, LOSS OF LIFE OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. INCLUSION OF SEMTECH PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE UNDERTAKEN SOLELY AT THE CUSTOMER'S OWN RISK. Should a customer purchase or use Semtech products for any such unauthorized application, the customer shall indemnify and hold Semtech and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs damages and attorney fees which could arise.

The Semtech name and logo are registered trademarks of the Semtech Corporation. All other trademarks and trade names mentioned may be marks and names of Semtech or their respective companies. Semtech reserves the right to make changes to, or discontinue any products described in this document without further notice. Semtech makes no warranty, representation or guarantee, express or implied, regarding the suitability of its products for any particular purpose. All rights reserved.

Wireless Communications

Due to the nature of wireless communications, transmission and reception of data can never be guaranteed. Data may be delayed, corrupted (i.e., have errors) or be totally lost. The Semtech product should not be used in situations where failure to transmit or receive data could result in damage of any kind to the user or any other party, including but not limited to personal injury, death, or loss of property. Semtech accepts no responsibility for damages of any kind resulting from delays or errors in data transmitted or received using the Semtech product, or for failure of the Semtech product to transmit or receive such data.

Safety

Do not operate the Semtech product in areas where blasting is in progress, where explosive atmospheres may be present, near medical equipment, near life support equipment, or near any equipment which may be susceptible to any form of radio interference. In such areas, the Semtech product should be powered off.

Qualcomm Licenses

Semtech’s cellular modules are sold subject to certain notices and restrictions regarding patent licenses from Qualcomm Incorporated. These notices and restrictions are available at www.sierrawireless.com/qualcomm-notices.

Sierra Wireless

Semtech Corporation acquired Sierra Wireless in January 2023. The Sierra Wireless brand is gradually being phased out. During the phase-out period, references to both “Semtech” and “Sierra Wireless” may appear in product documentation.

Contact Information

Sales information and technical support, including warranty and returns	Web: sierrawireless.com/company/contact-us/ Global toll-free number: 1-877-687-7795 6:00 am to 5:00 pm PST
Corporate and product information	Web: sierrawireless.com

Revision History

Revision number	Release date	Changes
1	February 2018	Created document

Revision number	Release date	Changes
2	January 2019	<p>Updated Modem Status Commands chapter</p> <ul style="list-style-type: none"> Updated !DATALOOPBACK (password required), !IMPREF (<carrier_sub-config>), !PCINFO (response format), !PCTEMP (response format), !PCTEMPLIMITS (default parameter values), !PCVOLLIMITS (<hw> replaced <lw>, defaults changed), !USBCOMP (<config type>,<config type desc>) Updated !CUSTOM customizations— removed AUTONETWORKMODE, CMCLIENT, GMMCAUSE7REMAP, IMSIREFRESH, ISVOICEN, LTEREJDELAY, NOROAM, RRCREL7CAPDIS, STKUIIN, WIN7MBOPTIONS Added !LTECA, !TMSTATUS, !USBSPEED <p>Updated Diagnostic Commands chapter</p> <ul style="list-style-type: none"> Updated !RXDEN (usage note), Added !LTERXCONTROL <p>Updated Test Commands chapter</p> <ul style="list-style-type: none"> Updated !DAFTMACT (description), !DALGRXAGC (usage requirements), !DALGTXAGC (usage requirements), Added !DAGFTMRXAGC, !DALTXCONTROL, !DARCONFIG, !DARCONFIGDROP, !DAWTXCONTROL Removed unimplemented commands, !DAWINFO, <p>Updated GPS Commands chapter</p> <ul style="list-style-type: none"> Updated !GPSNMEASENTENCE (new sentence types) <p>Updated AirVantage Commands chapter</p> <ul style="list-style-type: none"> Updated +WDSC <timer_n> parameter details <p>Updated Supported GSM/WCDMA AT Commands chapter</p> <ul style="list-style-type: none"> Added +CCHC, +CCHO, +CGLA, +CPINR
3	July 2020	<p>Updated Modem Status Commands chapter</p> <ul style="list-style-type: none"> Updated !ANTSEL, !BAND, !BOOTHOLD, !GSTATUS, !PCTEMP, !PCTEMPLIMITS, !PCVOLT, !PCVOLLIMITS, !USBCOMP <p>Updated Test Commands chapter</p> <ul style="list-style-type: none"> Updated !DARCONFIG <p>Updated SAR Backoff and Thermal Control Commands chapter</p> <ul style="list-style-type: none"> Updated !SARBACKOFF <p>Updated Band Definitions chapter</p> <ul style="list-style-type: none"> Updated 3GPP Bands table
4	November 2020	<p>Updated Modem Status Commands chapter</p> <ul style="list-style-type: none"> Updated !CUSTOM customizations— added TXONINDICATION <p>Updated Test Commands chapter</p> <ul style="list-style-type: none"> Updated !DALTXCONTROL <p>Updated SAR Backoff and Thermal Control Commands chapter</p> <ul style="list-style-type: none"> Updated !MAXPWR <p>Added SMS Wake Commands chapter</p> <ul style="list-style-type: none"> Added !SMSWAKE, !SMSWAKEWIDTH
5	September 2025	<p>Updated Password Commands</p> <ul style="list-style-type: none"> !ENTERCND !SETCND <p>Updated to Semtech manual template</p>

Revision number	Release date	Changes
6	September 2025	Updated Password Commands <ul style="list-style-type: none">· !ENTERCND· !SETCND
7	January 2026	Updated Modem Status, Customization, and Reset Commands <ul style="list-style-type: none">· !CUSTOM
8	January 2026	Updated Modem Status, Customization, and Reset Commands <ul style="list-style-type: none">· Removed !NVENCRYPTIMEI

Contents

Important Notice	2
Wireless Communications.....	2
Safety.....	2
Qualcomm Licenses	3
Sierra Wireless	3
Contact Information	3
Revision History	3
1: About This Guide	9
1.1 Introduction	9
1.2 Command Access	9
1.3 Command Timing	9
1.3.1 Interval Timing.....	9
1.3.2 Escape Sequence Guard Time.....	9
1.4 Result Codes.....	9
1.5 References	10
1.6 Terminology and Acronyms.....	10
1.7 Current Firmware Versions	10
1.7.1 Version.....	10
1.7.2 Upgrading	10
1.8 Document Structure.....	10
1.9 Conventions	14
2: AT Password Commands	16
2.1 Introduction	16
2.2 Command Summary	16
2.3 Command Reference.....	17
3: Modem Status, Customization, and Reset Commands	19
3.1 Introduction	19
3.2 Command Summary	19

3.3 Command Reference	21
4: Diagnostic Commands	54
4.1 Introduction	54
4.2 Command Summary	54
4.3 Command Reference	55
5: Test Commands	60
5.1 Introduction	60
5.2 Command Summary	60
5.3 Command Reference	61
6: Memory Management Commands	72
6.1 Introduction	72
6.2 Command Summary	72
6.3 Command Reference	73
7: GNSS Commands	76
7.1 Introduction	76
7.2 Command Summary	76
7.3 Command Reference	77
7.3.1 Error Codes	94
8: SIM Commands	97
8.1 Introduction	97
8.2 Command Summary	97
8.3 Command Reference	97
9: OMA-DM Commands	98
9.1 Introduction	98
9.2 Command Summary	98
9.3 Command Reference	99

10: SAR Backoff and Thermal Control Commands	102
10.1 Introduction	102
10.2 Command Summary	102
10.3 Command Reference.....	103
11: AirVantage Commands	107
11.1 Introduction	107
11.2 Command Summary	107
11.3 Command Reference.....	108
12: SMS Wake Commands	119
12.1 Introduction	119
12.2 Command Summary	119
12.3 Command Reference.....	120
13: Supported GSM/WCDMA AT Commands	122
14: Band Definitions	130
15: ASCII Table	132

1: About This Guide

1.1 Introduction

This document describes supported standard and proprietary AT commands available for Semtech AirPrime® products, and provides details where commands vary from the standards. These commands are intended for use by OEMs, and are supplemental to the standard AT commands for GSM devices defined by the 3GPP (3rd Generation Partnership Project) in *TS 27.007 AT command set for User Equipment (UE)* and *TS 27.005 Use of Data Terminal Equipment—Data Circuit terminating Equipment (DTE-DCE) interface for Short Message Service (SMS) and Cell Broadcast Service (BSE)*.

Note: When designing applications that use these AT commands, use Skylight™ or other Semtech applications as functionality templates to ensure proper use of command groups. For questions or concerns relating to command implementation, please contact your Semtech account representative.

1.2 Command Access

Most commands in this reference are password-protected. To use these commands, you must enter the correct password using `AT!ENTERCND` on page 17. Once the password is entered, all commands are available and remain available until the modem is reset or powered off and on.

OEM shall configure the password to be unique to each device.

1.3 Command Timing

1.3.1 Interval Timing

Some commands require time to process before additional commands are entered. For example, the modem returns OK when it receives `AT!DAFTMACT`. If `AT!DARCONFIG` is received too soon after this, the modem returns an error.

When building automated test scripts, ensure that sufficient delays are embedded, where necessary, to avoid these errors.

1.3.2 Escape Sequence Guard Time

The AT escape sequence “+++” requires a guard time of 1.0 seconds before and after it is used.

1.4 Result Codes

Result codes are not shown in the command tables unless special conditions apply. Generally the result code OK is returned when the command has been executed. ERROR may be returned if parameters are out of range, and is returned if the command is not recognized or is not permitted in the current state or condition of the modem.

1.5 References

This guide covers the command sets used by OEMs, designers and testers of Semtech AirPrime products, plus general operational use commands.

You may also want to consult the other documents available on our website at source.sierrawireless.com.

1.6 Terminology and Acronyms

This document makes wide use of acronyms that are in common use in data communications and cellular technology.

1.7 Current Firmware Versions

1.7.1 Version

To determine your firmware revision, enter the identification command **AT+GMR**.

1.7.2 Upgrading

If your modem firmware is an earlier version, you can acquire updated firmware by contacting your account manager.

1.8 Document Structure

This document describes the proprietary commands listed in the tables below — each table corresponds to a specific chapter.

[AT Password Commands](#) — Commands used to enable access to password-protected AT commands and to set the AT command password.

Table 1-1: AT password commands

Command	Description	Page
!ENTERCND	Enable access to password-protected commands	17
!SETCND	Set AT command password	18

[Modem Status, Customization, and Reset Commands](#) — Commands used to determine modem status, adjust customization settings, and reset the modem.

Table 1-2: Modem status commands

Command	Description	Page
!ANTSEL	Set/query external antenna select configuration	21
!BAND	Select/return frequency band set	23
!BOOTHOLD	Reset modem and wait in bootloader for firmware download	25

Table 1-2: Modem status commands (Continued)

Command	Description	Page
!CUSTOM	Set/return customization settings	26
!DATALOOPBACK	Enable/disable and configure loopback mode	30
!GCFEN	Enable/disable GCF test mode	31
!GETBAND	Return the current active band	31
!GSTATUS	Return operational status	32
!HWID	Display hardware version	33
!IMPREF	Query/set Image Management preferences	34
!LTECA	Enable/disable LTE Carrier Aggregation or Display supported LTE CA pairs	36
!LTEINFO	Display LTE network information	38
!NVPLMN	Provision/display PLMN list for Network Personalization locking	40
!PCINFO	Return power control status information	41
!PCOFFEN	Set/return Power Off Enable state	42
!PCTEMP	Return current temperature information	42
!PCTEMPLIMITS	Set/report temperature state limit values	43
!PCVOLT	Return current power supply voltage information	44
!PCVOLTLIMITS	Set/report power supply voltage state limit values	45
!PRIID	Set/report module PRI part number and revision	46
!RESET	Reset modem	46
!SCACT	Activate/deactivate data connection	47
!TMSTATUS	Report Thermal Mitigation Status	48
!USBCOMP	Set/report USB interface configuration	49
!USBINFO	Return information from active USB descriptor	50
!USBPID	Set/report product ID in USB descriptor	51
!USBSPEED	Set/report USB speed	52
&V	Return operating mode AT configuration parameters	53

Diagnostic Commands—Commands used to select frequency bands and diagnose problems.

Table 1-3: Diagnostic commands

Command	Description	Page
!BCFWUPDATESTATUS	Report status of most recent firmware update attempt	55
!ERR	Display diagnostic information	56
!GCCLR	Clear crash dump data	56

Table 1-3: Diagnostic commands (Continued)

Command	Description	Page
!GCDUMP	Display crash dump data	57
!LTERXCONTROL	Enable/disable LTE receive (Rx) diversity during Carrier Aggregation	58
!RXDEN	Enable/disable WCDMA/LTE/TD-SCDMA receive (Rx) diversity	59

Test Commands— Commands required to place the modem in particular modes of operation, test host connectivity, and to configure the transmitters and receivers for test measurements.

Table 1-4: Test commands

Command	Description	Page
!DACGPSTON	Return GPS CtoN and frequency measurement	61
!DACGPSMASKON	Set CGPS IQ log mask	61
!DACGPSSTANDALONE	Enter/exit StandAlone (SA) RF mode	62
!DACGPSTESTMODE	Start/stop CGPS diagnostic task	62
!DAFTMACT	Put modem into Factory Test Mode	63
!DAFTMDEACT	Put modem into online mode from Factory Test Mode	63
!DAGFTMRXAGC	Get FTM Rx AGC (Primary or Diversity)	64
!DALGRXAGC	Return Rx AGC value (LTE only)	65
!DALGTXAGC	Return Tx AGC value and transmitter parameters (LTE only)	66
!DALTXCONTROL	Configure LTE Tx parameters (LTE only)	68
!DAOFFLINE	Place modem offline	69
!DARCONFIG	Set Band and Channel	70
!DARCONFIGDROP	Drop Radio Configurations	71
!DAWTXCONTROL	Configure WCDMA Tx Power (WCDMA only)	71

Memory Management Commands— Commands that control the data stored in non-volatile memory of the modem.

Table 1-5: Memory management commands

Command	Description	Page
!NVBACKUP	Back up device configuration	73
!RMARESET	Back up device configuration	75

[GNSS Commands](#) — Supported on GNSS-enabled modems only.

Table 1-6: GNSS commands

Command	Description	Page
!GPSAUTOSTART	Configure GPS auto-start features	77
!GPSCLRASSIST	Clear specific GPS assistance data	79
!GPSOLDSTART	Clear all GNSS assistance data	80
!GPSEND	End an active session	80
!GPSFIX	Initiate GPS position fix	81
!GPSLBSAPN	Set GPS LBS APNs	82
!GPSLOC	Return last known location of the modem	84
!GPSMOMETHOD	Set/report GPS MO method	85
!GPSNMEACONFIG	Enable and set NMEA data output rate	86
!GPSNMEASENTENCE	Set/report NMEA sentence type	87
!GPSPORTID	Set/report port ID to use over TCP/IP	88
!GPSSATINFO	Request satellite information	89
!GPSSTATUS	Request current status of a position fix session	90
!GPSSUPLURL	Set/report SUPL server URL	91
!GPSSUPLVER	Set/report SUPL server version	92
!GPSTRACK	Initiate local tracking (multiple fix) session	93
+WANT	Enable/disable GNSS antenna power	94

[SIM Commands](#) — Commands used to communicate with an installed (U)SIM.

Table 1-7: SIM commands

Command	Description	Page
+UIMS	Select active SIM interface	97

[OMA-DM Commands](#) — Commands used to configure DM (Device Management) accounts, sessions, and host–device–server interactions.

Table 1-8: OMA-DM commands

Command	Description	Page
!HOSTDEVINFO	Configure host device details	99
!IMSTESTMODE	Enable/disable IMS test mode	100
!OSINFO	Configure host device operating system information	101

SAR Backoff and Thermal Control Commands — Commands used to configure SAR options, and thermal mitigation algorithm parameters and limits.

Table 1-9: SAR Backoff and Thermal Control commands

Command	Description	Page
!MAXPWR	Set/report maximum Tx power	103
!SARBACKOFF	Set/report offset from maximum Tx power	104
!SARINTGPIOMODE	Set/report default pull mode for SAR interrupt GPIOs	105
!SARSTATE	Set/report SAR backoff state	105
!SARSTATEDFLT	Set/report default SAR backoff state	106

AirVantage Commands — Commands used to interact with AirVantage.

Table 1-10: AirVantage commands

Command	Description	Page
+WDSC	Configure AirVantage Management Services	108
+WDSE	Display most recent AirVantage Management Services error	110
+WDSG	Display AirVantage Management Services status information	111
+WDSI	Activate/deactivate AirVantage Management Services unsolicited notifications	112
+WDSI (notification)	AirVantage Management Services events — Unsolicited notification	113
+WDSR	Reply to AirVantage server request	116
+WDSS	Configure/connect AirVantage Management Services session	117

SMS Wake Commands — Commands used for the SMS host wake-up feature.

Table 1-11: AirVantage commands

Command	Description	Page
!SMSWAKE	Enable/disable SMS host wake-up feature	120
!SMSWAKEWIDTH	Set/read SMS Wake signal width	121

1.9 Conventions

The following format conventions are used in this reference:

Character codes or keystrokes that are described with words or standard abbreviations are shown within angle brackets using a different font, such as <CR> for Carriage Return and <space> for a blank space character.

Numeric values are decimal unless prefixed as noted below.

Hexadecimal values are shown with a prefix of 0x, i.e. in the form 0x3D.

Binary values are shown with a prefix of 0b, i.e. in the form 0b0011101.

Command and register syntax is noted using an alternate font: **!CHAN=<c>[,b]**. The leading “AT” characters are not shown but must be included before all commands except as noted in the reference tables.

Characters that are required are shown in uppercase; parameters are noted in lowercase. Required parameters are enclosed in angle brackets (<n>) while optional parameters are enclosed within square brackets ([x]). The brackets are not to be included in the command string.

Commands are presented in table format. Each chapter covers the commands related to that subject and presents a summary table to help you locate a needed command. Commands are in ASCII alphabetical order in the body of each chapter.

Any default settings are noted in the command tables. Note that these are the factory default settings and *not* the default parameter value assumed if no parameter is specified.

Result Code This is a numeric or text code that is returned after all commands (except resets)—text codes are returned if verbose responses are enabled. Only one result code is returned for a command line regardless of the number of individual commands contained on the line.

Response This term indicates a response from the modem that is issued prior to a result code. Reading registers or issuing commands that report information will provide a response followed by a result code unless the command generates an error.

Responses and result codes from the modem, or host system software prompts, are shown in this font:

```
CONNECT 14400
```

2: AT Password Commands

2.1 Introduction

Many AT commands described in this document are password-protected. This chapter describes how to enter or change the password used to gain access to the protected commands.

2.2 Command Summary

[Table 2-1](#) on page 16 lists the commands described in this chapter.

Table 2-1: AT password commands

Command	Description	Page
!ENTERCND	Enable access to password-protected commands	17
!SETCND	Set AT command password	18

2.3 Command Reference

Table 2-2: AT command password details

Command	Description
!ENTERCND	<p>Enable access to password-protected commands</p> <p>To gain access to password-protected AT commands (unlock the commands), enter the password correctly using this command.</p> <p>After unlocking the protected command, the password can be changed using !SETCND.</p> <p>Once the password has been entered correctly, the password-protected AT commands are available until the modem is reset or powered off and on.</p> <hr/> <p>Warning: <i>!ENTERCND does not accept blank passwords. If the password has been cleared (using !SETCND), you will not be able to use password-protected commands, and will have to contact Sierra Wireless for help to reset the password.</i></p> <hr/> <p>Password required: Yes—Query format only.</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!ENTERCND=<"key"> Response: OK Purpose: Unlock password-protected commands. ▪ Query: AT!ENTERCND? Response: OK Purpose: Returns OK if unlocked and Error if locked. <p>Parameters:</p> <ul style="list-style-type: none"> • Password must be entered with quotation marks. (For example, AT!ENTERCND="ExamplePW".) • Password length: 8 – 15 characters (0–9, A–Z, upper or lower case) • Characters may be entered in ASCII format, or in Hex format. (For example: "myPass34" or "ABCDEF01234".)

Table 2-2: AT command password details (Continued)

Command	Description
!SETCND	<p>Set AT command password</p> <p>Change the password used for the !ENTERCND command and save it into persistent memory. OEM shall configure the password to be unique for each device.</p> <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!SETCND=<"key"> Response: OK Purpose: Sets <"Key"> as the new password for accessing protected commands. <p>Parameters:</p> <p><"key"> (New password)</p> <ul style="list-style-type: none"> • Password must be entered with quotation marks (for example, AT!SETCND="NewPW123"). • Password length: 8–15 characters (0–9, A–Z, upper or lower case) • Characters may be entered in ASCII format, or in Hex format. (For example: "myPass32" or "ABCDEF01234".) <hr style="border: 1px solid red;"/> <p>Warning: Do NOT enter a null password (that is, the <"key"> cannot be "") — you will NOT be able to use password-protected commands, and will have to contact Sierra Wireless for help to reset the password.</p> <hr style="border: 1px solid red;"/>

3: Modem Status, Customization, and Reset Commands

3.1 Introduction

This chapter describes commands used to reset the modem, adjust customization settings, retrieve the hardware version, and monitor the temperature, voltage, and modem status.

3.2 Command Summary

Table 3-1 lists the commands described in this chapter.

Table 3-1: Modem status commands

Command	Description	Page
!ANTSEL	Set/query external antenna select configuration	21
!BAND	Select/return frequency band set	23
!BOOTHOLD	Reset modem and wait in bootloader for firmware download	25
!CUSTOM	Set/return customization settings	26
!DATALOOPBACK	Enable/disable and configure loopback mode	30
!GCFEN	Enable/disable GCF test mode	31
!GETBAND	Return the current active band	31
!GSTATUS	Return operational status	32
!HWID	Display hardware version	33
!IMPREF	Query/set Image Management preferences	34
!LTECA	Enable/disable LTE Carrier Aggregation or Display supported LTE CA pairs	36
!LTEINFO	Display LTE network information	38
!NVPLMN	Provision/display PLMN list for Network Personalization locking	40
!PCINFO	Return power control status information	41
!PCOFFEN	Set/return Power Off Enable state	42
!PCTEMP	Return current temperature information	42
!PCTEMPLIMITS	Set/report temperature state limit values	43
!PCVOLT	Return current power supply voltage information	44
!PCVOLTLIMITS	Set/report power supply voltage state limit values	45
!PRIID	Set/report module PRI part number and revision	46
!RESET	Reset modem	46

Table 3-1: Modem status commands (Continued)

Command	Description	Page
!SCACT	Activate/deactivate data connection	47
!TMSTATUS	Report Thermal Mitigation Status	48
!USBCOMP	Set/report USB interface configuration	49
!USBINFO	Return information from active USB descriptor	50
!USBPID	Set/report product ID in USB descriptor	51
!USBSPEED	Set/report USB speed	52
&V	Return operating mode AT configuration parameters	53

3.3 Command Reference

Table 3-2: Modem status, customization, and reset commands

Command	Description
!ANTSEL	<p>Set/query external antenna select configuration</p> <p>Configure the modem to use available GPIOs to select which antenna to use for each specified frequency band. (Any of the available GPIOs that are not needed for a specific band should be configured as not required.)</p> <p>When the modem switches to a frequency band that has been configured using this command, the GPIOs are driven as specified and the host uses them to tune the external antenna appropriately. (This applies whether this is a primary band, or as the secondary component carrier as part of LTE CA (Carrier Aggregation)). If the modem switches to a band that has not been configured, the host uses the default antenna.</p> <hr/> <p><i>Note: Frequency bands are RAT-independent. For example, Band 5 corresponds to any 850-band technology (CDMA, WCDMA, LTE, GSM).</i></p> <hr/> <p>When designing the system, and configuring the device:</p> <ul style="list-style-type: none"> Perform system level testing to ensure that the antenna switching feature does not introduce any handover issues. The tunable antenna should be designed to ensure that it can retune in < 5 μs (recommended) and < 10 μs (maximum). Make sure there are no conflicts between primary (PCell) and secondary (SCell) cells for all supported LTE CA combinations, since a conflict can detune the PCell during LTE CA, resulting in reduced performance. (A conflict occurs when the primary band is configured to drive a GPIO one way (high or low), and the secondary is configured to drive the same GPIO the other way (low or high). <p>Password required: Yes Reset required to apply changes: Yes Persistent across power cycles: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> Execution: AT!ANTSEL=<band>, <gpio1>, <gpio2>, <gpio3>[, <gpio4>] Response: OK Purpose: Configure the GPIOs for the specified <band>. Query: AT!ANTSEL? Response: BAND <band a>: <gpio1>, <gpio2>, <gpio3>[, <gpio4>] BAND <band b>: <gpio1>, <gpio2>, <gpio3>[, <gpio4>] ... Conflicts: (Note: Heading appears only if there are conflicts.) <band q>+<band r>: <gpio1>, <gpio2>, <gpio3>[, <gpio4>] (Note: GPIOs in conflict appear as 'C') ... OK <p>(Continued on next page)</p>

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
!ANTSEL (continued)	<p>Set/query external antenna select configuration (continued)</p> <p>Examples: BAND 2: 1, 0, 1, 1 BAND 5: 1, 1, 2, 2</p> <p>Conflict: B2 + B5: 1, C, 1, 1 (<gpio2> has a conflict ('C')) B5 + B2: 1, C, 1, 1</p> <p>OK</p> <p>Purpose: Display the current external antenna select configuration.</p> <ul style="list-style-type: none"> ▪ Query List: !ANTSEL=? <p>Purpose: Display valid parameter values and command format.</p> <p>Parameters:</p> <p><band> (RF band)</p> <ul style="list-style-type: none"> • low- or high-frequency 3GPP band number, as appropriate. (See Table 14-2 on page 130 for a full list of low-, mid-, and high-frequency bands.) • Valid range: 1–71. Band support is product specific— see the device’s Product Specification or Product Technical Specification document for details. <p><gpio1>, <gpio2>, <gpio3>, <gpio4> (GPIO configurations.)</p> <ul style="list-style-type: none"> • 0— Logic low • 1— Logic high • 2— Not used for antenna selection (Default value for <gpio4> if not specified.) • Note: <gpio4> availability is device-specific— see the appropriate Product Technical Specification for details.) • gpio1–4 correspond to ANT_CTRL0–3 respectively, on EM modules • gpio1–3 correspond to ANT_CTRL0–2 respectively, on MC modules

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
<p>!BAND</p> <hr/> <p><i>Note: The 'Basic' command and response versions are used if you haven't entered the required password. (See Command Access on page 9.)</i></p> <hr/>	<p>Select/return frequency band set</p> <p>Configure the modem to operate on a set of frequency bands, look up available sets, create new sets, or return the current selection.</p> <p>Password required: Yes—Execution (Extended) format</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution (Basic): <ul style="list-style-type: none"> AT!BAND=<Index> Response: OK Purpose: Select an existing set of bands. ▪ Execution (Extended): <ul style="list-style-type: none"> AT!BAND=<Index>, "<Name>", <GWmask>[, <Lmask>[, <Lmask2>[, <Tdsmask>[, <Lmask3>,<Lmask4>]]]] Response: OK Purpose: Create a new set of bands. <p>Query: AT!BAND?</p> <p>Response: Index, Name, GW Band Mask L Band Mask 1 TDS Band Mask L Band Mask 2 L Band Mask 3 L Band Mask 4 <CR><LF> <Index>, <Name> <GWmask> <Lmask1> <Tdsmask> <Lmask2> <Lmask3> <Lmask4> OK</p> <p style="padding-left: 40px;"><i>or</i> (If the current band mask doesn't match a band set) Unknown band mask. Use AT!BAND to set band. <Index> OK</p> <p>Purpose: Report the current band selection. (<GWmask>, <Lmask>, and <Tdsmask> will appear only in Extended responses, and only if applicable.)</p> <ul style="list-style-type: none"> ▪ Query List: AT!BAND=? Purpose: Returns the command format and valid parameter values. <p>Parameters:</p> <p><Index> (Index of a band set. Use the Query List command to display all supported sets)</p> <ul style="list-style-type: none"> • Valid range: 0–13 (Hexadecimal. There are 20 possible values.) <p><Name> (Name of the band set)</p> <ul style="list-style-type: none"> • ASCII string—Up to 30 characters <p>(Continued on next page)</p>

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
!BAND (continued)	<p>Select/return frequency band set (continued)</p> <p><GWmask> (GSM/WCDMA bands included in the set)</p> <ul style="list-style-type: none"> • Format: 64-bit bitmask • Example values (Available bands are device-dependent. Use the extended query command to display the list of bands available for your device.): <ul style="list-style-type: none"> ▪ 0000000000000001—BC0-A 0000000000000002—BC0-B ... 0000000080000000—BC15 0002000000000000—W900 1000000000000000—B19 (850) <p><Lmask1> (LTE bands included in the set)</p> <ul style="list-style-type: none"> • Format: 64-bit bitmask • Example values (Available bands are device-dependent. Use the extended query command to display the list of bands available for your device.): <ul style="list-style-type: none"> ▪ 0000000000000001—Band 1 0000000000000002—Band 2 ... 0000200000000000—Band 46 0000800000000000—Band 48 • Note—The full list of bands in the set is spread across <Lmask1>–<Lmask4>. <p><Lmask2> (LTE bands included in the set)</p> <ul style="list-style-type: none"> • Format: 64-bit bitmask • Example values (Available bands are device-dependent. Use the extended query command to display the list of bands available for your device.): <ul style="list-style-type: none"> ▪ 0000000000000002—Band 66 0000000000000040—Band 71 • Note—The full list of bands in the set is spread across <Lmask1>–<Lmask4>. <p><Lmask3> (Reserved for future use)</p> <ul style="list-style-type: none"> • Format: 64-bit bitmask • Required value: 0000000000000000 • Note—The full list of bands in the set is spread across <Lmask1>–<Lmask4>. <p>(Continued on next page)</p>

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
!BAND (continued)	<p>Select/return frequency band set (continued)</p> <p><Lmask4> (LTE bands included in the set)</p> <ul style="list-style-type: none"> • Format: 64-bit bitmask • Example values (Available bands are device-dependent. Use the extended query command to display the list of bands available for your device.): <ul style="list-style-type: none"> ▪ 0800000000000000—B252 ▪ 4000000000000000—B255 • Note— The full list of bands in the set is spread across <Lmask1>–<Lmask4>. <p><Tdsmask> (TD-SCDMA bands included in the set)</p> <ul style="list-style-type: none"> • Format: 64-bit bitmask • Example values (Available bands are device-dependent. Use the extended query command to display the list of bands available for your device.): <ul style="list-style-type: none"> ▪ 0000000000000001—TDS B34 0000000000000002—TDS B35 0000000000000004—TDS B36 0000000000000008—TDS B38 0000000000000010—TDS B40 0000000000000020—TDS B39
!BOOTHOLD	<p>Reset modem and wait in bootloader for firmware download</p> <p>Prepare for a firmware download by resetting the modem and waiting in 'boot and hold' mode.</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!BOOTHOLD Response: OK Purpose: Force the modem to reset and then wait in boot and hold mode for a firmware download.

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
<p>!CUSTOM</p> <hr/> <p><i>Note: Some customizations may not be available for certain chipsets, firmware revisions, or devices.</i></p> <hr/>	<p>Set/return customization settings</p> <p>Set or return several customization values.</p> <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: ATICUSTOM=<customization>, <value> Response: OK Purpose: Assign <value> to a specific <customization> setting. ▪ Query: ATICUSTOM? Response: (list of enabled <customization>s) OK Purpose: Display customizations that are currently enabled. ▪ Query list: ATICUSTOM=? Purpose: Return a list of valid <customization> values. <p>Parameters:</p> <p><value> (Value being assigned to a specific <customization> setting)</p> <ul style="list-style-type: none"> • Descriptions are included in each of the customizations described below. • Numeric value. Valid range depends on the <customization> type. <p><customization> (String identifying customization setting. The default value for all customizations is 0.)</p> <hr/> <p><i>Note: Use quotation marks around the customization string. For example, ATICUSTOM="CSDOFF";0.</i></p> <hr/> <ul style="list-style-type: none"> • "CFUNPERSISTEN" — Enable/disable persistence (across power cycles) of AT+CFUN setting. <value>: <ul style="list-style-type: none"> ▪ 0—Disable (+CFUN setting does not persist across power cycle) ▪ 1 — Enable (+CFUN setting persists across power cycle) • "CSVOICEREJECT" (Pending future upgrade)—Enable/disable ability to ignore incoming voice call pages from the network. <value>: <ul style="list-style-type: none"> ▪ 0 — Process pages as per device capabilities (default) ▪ 1 — Ignore paging (type 1 and 2) messages ▪ 2 — Reject call setup (voice and circuit-switched VT), returning cause code 88 (Incompatible destination) ▪ 3 — Process voice pages as per device capabilities, and reject call setup (circuit-switched VT), returning cause code 88 (Incompatible destination) ▪ 4 — Reject voice pages, returning cause code 65 (Bearer service not implemented), and reject call setup (circuit-switched VT), returning cause code 88 (Incompatible destination) <p>(Continued on next page)</p>

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
!CUSTOM (continued)	<p>Set—query customization settings (continued)</p> <ul style="list-style-type: none"> • “FASTENUMEN” — Enable/disable fast enumeration for warm/cold boot. <value>: <ul style="list-style-type: none"> ▪ 0 — Disable fast enumeration (Default) ▪ 1 — Enable fast enumeration for cold boot and disable for warm boot ▪ 2 — Enable fast enumeration for warm boot and disable for cold boot ▪ 3 — Enable fast enumeration for warm and cold boot • “GPIOSARENABLE” — Indicate whether SAR backoff is controlled by GPIOs or by AT commands. <value>: <ul style="list-style-type: none"> ▪ 0 — Controlled by AT commands (default) ▪ 1 — Controlled by GPIOs • “GPSENABLE” — Enable/disable the GPS feature. <value>: <ul style="list-style-type: none"> ▪ 0 — GPS disabled ▪ 1 — MO & MT enabled regardless of GPS_DISABLE setting ▪ 2 — MO enabled regardless of GPS_DISABLE setting ▪ 3 — MT enabled regardless of GPS_DISABLE setting ▪ 4 — MO & MT enabled but are gated by GPS_DISABLE setting ▪ 5 — MO enabled but is gated by GPS_DISABLE setting ▪ 6 — MT enabled but is gated by GPS_DISABLE setting ▪ <value> + 80 — Disable GLONASS (For example, 84 = MO & MT narrow-band GPS enabled, but gated by GPS_DISABLE setting.) • “GPSLPM” — Enable/disable GPS in Low Power Mode. <value>: <ul style="list-style-type: none"> ▪ 0 — Enable—GPS engine remains enabled when modem enters LPM (Default) ▪ 1 — Disable—GPS engine is disabled when modem enters LPM • “GPSREFLOC” — Enable/disable reference GPS location reporting. <value>: <ul style="list-style-type: none"> ▪ 0 — Enable (Default) ▪ 1 — Disable • “GPSSEL” — Select GPS antenna (useful only for devices with both a GPS and a shared GPS/Rx diversity antenna). <value>: <ul style="list-style-type: none"> ▪ 0 — Use dedicated GPS antenna (Default) ▪ 1 — Use shared GPS/Rx diversity antenna • “IPV6ENABLE” — Enable/disable IPV6 support. <value>: <ul style="list-style-type: none"> ▪ 0 — Disable IPV6 ▪ 1 — Enable IPV6 (Default) <p>(Continued on next page)</p>

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
<p>!CUSTOM (continued)</p>	<p>Set/query customization settings (continued)</p> <ul style="list-style-type: none"> • "NETWORKNAMEFMT" (Pending future upgrade)— Set MBIM provider name format for vanui (roaming). <value>: <ul style="list-style-type: none"> ▪ 0 — Display one of: SPN, LongName, or ShortName, by order of priority (Default QCT behavior) ▪ 1 — Display one of: LongName or ShortName ▪ 2 — Display [SPN] - [LongName/ShortName] (Note: May be truncated.) ▪ 3 — Display [LongName/ShortName] - [SPN] (Note: May be truncated.) • "PCSCDISABLE" (Pending future upgrade)— Determine functionality of PCSC, GSM Algorithm and Authenticate commands, and +CIMI command. <value>: <ul style="list-style-type: none"> ▪ 0–7 (Default value = 0—all functions enabled) <ul style="list-style-type: none"> ▪ Bit 0: PCSC (0—Enable, 1—Disable) ▪ Bit 1: GSM Algorithm and Authenticate commands (0—Enable, 1—Disable) ▪ Bit 2: AT+CIMI outputs IMSI (0—Enable, 1—Disable) • "QMIDETACHEN" (Pending future upgrade)— Enable/disable QMI NAS detach. <value>: <ul style="list-style-type: none"> ▪ 0 — Disable. QMI detach request returns NO_EFFECT response, and no action is taken. ▪ 1 — Enable. QMI detach request is acted on, and appropriate response is returned based on the detach result. • "SIMHOTSWAPDIS" — Configure SIM hotswap feature <value>: <ul style="list-style-type: none"> ▪ 0 — Enable UIM1 and UIM2 (default) ▪ 1 — Disable UIM1, enable UIM2 ▪ 2 — Enable UIM1, disable UIM2 ▪ 3 — Disable UIM1 and UIM2 • "SIMLPM" — Indicate default SIM power state during Low Power Mode. <value>: <ul style="list-style-type: none"> ▪ 0 — QCT default behavior (same as <value>=2) (Default) Note—The default behavior could change in future revisions. Use <value>=2 if you need to guarantee the described behavior. ▪ 1 — SIM remains powered in LPM ▪ 2—Power down SIM with AT+CFUN=0; Power up SIM with AT+CFUN=1 • "SINGLEAPNSWITCH" (Pending future upgrade)— Indicate device behavior when changing APN name, username, or password. <value>: <ul style="list-style-type: none"> ▪ 0 — Do nothing ▪ 1 — Device detaches and re-attaches after changing APN information ▪ 2 — Power-cycle the UE <p>(Continued on next page)</p>

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
!CUSTOM (continued)	<p data-bbox="496 310 1127 344">Set/query customization settings (continued)</p> <ul style="list-style-type: none"> <li data-bbox="545 375 1354 428">• “TXONINDICATION” — (EM/MC74x1 only) Enable/disable TX_ON indication. <value>: <ul style="list-style-type: none"> <li data-bbox="570 436 834 464">▪ 0 — Disable (Default) <li data-bbox="570 470 1398 554">▪ 1 — Enable. A TX_ON indication will be received when pin 61 (TX_ON) changes state to indicate Tx activity state begins (signal goes high) or ends (signal goes low). (Note—Pin 61 can be used as ANT_CTRL1 or TX_ON.) <li data-bbox="545 562 1127 615">• “UIM2ENABLE” — Enable/disable UIM2 slot support. <value>: <ul style="list-style-type: none"> <li data-bbox="570 623 737 651">▪ 0 — Disable <li data-bbox="570 657 829 684">▪ 1 — Enable (Default) <li data-bbox="570 690 935 718">▪ 2 — Enable eSIM on UIM2 slot <hr/> <p data-bbox="545 753 922 781"><i>Note: eSIM is not supported in EM74x1</i></p> <hr/> <ul style="list-style-type: none"> <li data-bbox="545 827 1362 879">• “USBSERIALENABLE” — Use IMEI as serial number in USB descriptor (USB D). <value>: <ul style="list-style-type: none"> <li data-bbox="570 888 867 915">▪ 0 — Same as 1 (Default) <li data-bbox="570 921 992 949">▪ 1 — Use IMEI as USB serial number <li data-bbox="570 955 1078 982">▪ 2 — Set serial number as NULL in the USB D <li data-bbox="570 989 1292 1016">▪ 3 — Use hard-coded default (0123456789ABCDEF) in the USB D <li data-bbox="545 1024 1378 1098">• “WAKEHOSTEN” (Pending future upgrade) — Enable/disable host wake-up via SMS or incoming data packet. <value>: <ul style="list-style-type: none"> <li data-bbox="570 1106 1362 1159">▪ 0 — Disable—Host will not wake when SMS or incoming data packet is received. (Default) <li data-bbox="570 1165 1089 1192">▪ 1 — Wake host when simple SMS is received. <li data-bbox="570 1199 1187 1226">▪ 2 — Wake host when incoming data packet is received. <li data-bbox="570 1232 1354 1260">▪ 3 — Wake host when simple SMS or incoming data packet is received.

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
!DATALOOPBACK	<p>Enable/disable and configure loopback mode</p> <p>Enable or disable loopback mode and the loopback multiplier, or display the current settings.</p> <p>Password required: Yes Reset required to apply changes: Yes Persistent across power cycles: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Query: ATIDATALOOPBACK? Response: !DATALOOPBACK: Data Loopback Mode; <loopback_mode> Replication Count: <loopback_multiplier> OK Purpose: Display the loopback mode state, and loopback multiplier. ▪ Execution: ATIDATALOOPBACK=<loopback_mode>, <loopback_multiplier> Response: OK Purpose: Enable/disable loopback mode, and set the loopback multiplier. ▪ Query list: ATIDATALOOPBACK=? Purpose: Returns a list of valid parameter values. <p>Parameters:</p> <p><loopback_mode> (Loopback mode state)</p> <ul style="list-style-type: none"> • 0 — Disable data loopback mode • 1 — Enable data loopback mode <p><loopback_multiplier> (Number of downlink bytes sent for each uplink byte (replication count))</p> <ul style="list-style-type: none"> • Decimal value • Maximum=6

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
!GCFEN	<p>Enable/disable GCF test mode</p> <p>Place the modem in GCF testing mode or normal operating mode.</p> <p>Password required: Yes—Execution format only</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!GCFEN=<enableFlag> Response: OK Purpose: Place the modem in GCF testing mode or normal operating mode. ▪ Query: AT!GCFEN? Response: !GCFEN: <enableFlag> OK Purpose: Display the modem’s current mode. ▪ Query List: AT!GCFEN=? Purpose: Return a list of supported <enableFlag> values. <p>Parameters:</p> <p><enableFlag> (Enable/disable GCF testing)</p> <ul style="list-style-type: none"> • 0 — Disable GCF test mode (Default) — This value is used for normal operations. • 1 — Enable GCF test mode.
!GETBAND	<p>Return the current active band</p> <p>Return the active band currently being used by the modem.</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Query: AT!GETBAND? Response: !GETBAND: <active band description> OK or Unknown OK or No Service OK Purpose: Return a description of the current active band, or return an error message. <hr/> <p><i>Note: Due to stack implementation requirements, !GETBAND reports W800 for both W800 and W850.</i></p>

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
!GSTATUS	<p>Return operational status</p> <p>Return specific details about the current operational status of the modem. The response details vary depending on the current RAT. Contact Sierra Wireless for further details if required.</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> Query: ATIGSTATUS? Response (Example shown is for LTE; fields will vary depending on RAT) <pre> !GSTATUS: Current Time: <ctime> Temperature: <temp> Reset Counter: <rcounter> Mode: <mode> System mode: <smode> PS state: <PSstate> LTE band: <lband> LTE bw: <lbw> LTE Rx chan: <lrchan> LTE Tx chan: <ltchan> LTE SCC1 state: <scstate> [LTE SCC1 band:<lband> LTE SCC1 bw: <lbw> LTE SCC1 chan:<lrchan>] LTE SCC2 state: <scstate> [LTE SCC2 band:<lband> LTE SCC2 bw: <lbw> LTE SCC2 chan:<lrchan>] LTE SCC3 state: <scstate> [LTE SCC3 band:<lband> LTE SCC3 bw: <lbw> LTE SCC3 chan:<lrchan>] LTE SCC4 state: <scstate> [LTE SCC4 band:<lband> LTE SCC4 bw: <lbw> LTE SCC4 chan:<lrchan>] EMM state: <emmstate> <emmsubstate> RRC state: <emmconn> IMS Reg State: <imsstate> [IMS mode: <ims mode>] PCC RxM RSSI: <rss> PCC RxM RSRP:<rsrp> PCC RxD RSSI: <rss> PCC RxD RSRP:<rsrp> [SCC1 RxM RSSI: <rss> SCC1 RxM RSRP:<rsrp> SCC1 RxD RSSI: <rss> SCC1 RxD RSRP:<rsrp> SCC2 RxM RSSI: <rss> SCC2 RxM RSRP:<rsrp> SCC2 RxD RSSI: <rss> SCC2 RxD RSRP:<rsrp> SCC3 RxM RSSI: <rss> SCC3 RxM RSRP:<rsrp> SCC3 RxD RSSI: <rss> SCC3 RxD RSRP:<rsrp> SCC4 RxM RSSI: <rss> SCC4 RxM RSRP:<rsrp> SCC4 RxD RSSI: <rss> SCC4 RxD RSRP:<rsrp>] Tx Power: <txpwr> TAC: <tac> RSRQ (dB): <rsrq> Cell ID: <Cell ID> SINR (dB): <sinr> OK </pre>

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
!HWID	<p>Display hardware version</p> <p>Display the device's hardware version number.</p> <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Query: AT!HWID? Response: Revision: <MajorVer>.<MinorVer> OK Purpose: Display hardware version number. ▪ Query List: AT!HWID=? Purpose: Return the query command format. <p>Parameters:</p> <p><MajorVer> (Major versioning number)</p> <ul style="list-style-type: none"> • 0–9 <p><MinorVer> (Minor versioning number)</p> <ul style="list-style-type: none"> • 0–9

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
<p>!IMPREF</p>	<p>Query/set Image Management preferences</p> <p>Indicate which firmware image (firmware plus carrier configuration) should be selected from those available on the device, or enable SIM-based image switching. Use the query format to list the configuration pairs that are currently downloaded and preferred.</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!IMPREF=<preference> Response: OK Purpose: Indicate which image should be used (the preferred image), or enable SIM-based image switching. ▪ Query: AT!IMPREF? Response:! !IMPREF: preferred fw version: <firmware-ver> preferred carrier name: <carrier-name> preferred config name: <carrier-config> preferred subpri index: <carrier-sub-config> current fw version: <firmware-ver> current carrier name: <carrier-name> current config name: <carrier-config> current subpri index: <carrier-sub-config> <p style="margin-left: 40px;">[<mismatch information>] OK</p> <p style="margin-left: 40px;"><i>or</i></p> <p style="margin-left: 40px;">!IMPREF <invalid image> OK</p> <p>Purpose: Query (show) the preferred and current images (firmware plus carrier configuration pairs), or if an image setting does not exist, a message will be displayed, as shown.</p> <p>Parameters:</p> <p><preference> (The preferred carrier, or a flag to enable SIM-based image switching)</p> <ul style="list-style-type: none"> ▪ Valid values: <ul style="list-style-type: none"> ▪ <carrier-name>—Module will search for a matching carrier PRI and the firmware required for that PRI. If found, the new image preference is set. ▪ “AUTO-SIM”—Enable SIM-based switching. (To disable SIM-based switching, select a <carrier-name> instead.) <p><carrier-name> (Unique code identifying the carrier that the firmware was designed for)</p> <ul style="list-style-type: none"> ▪ ASCII string <p><firmware-ver> (Unique firmware version number assigned by Sierra Wireless)</p> <ul style="list-style-type: none"> ▪ ASCII string <p><carrier-config> (Unique code identifying the carrier and configuration details)</p> <ul style="list-style-type: none"> ▪ ASCII string <p><carrier-sub-config> (Sub-configuration for carrier PRI for custom ICCID/IMSI ranges)</p> <ul style="list-style-type: none"> ▪ ASCII string <p>(Continued on next page)</p>

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
!IMPREF	<p>Query/set Image Management preferences (continued)</p> <p><mismatch information> (Message indicating a field mismatch between the current and preferred image settings)</p> <ul style="list-style-type: none"> • ASCII string (quotation marks do not appear): <ul style="list-style-type: none"> ▪ “fw version mismatch” ▪ “carrier name mismatch” ▪ “config name mismatch” <p><invalid image> (Message indicating an image does not exist)</p> <ul style="list-style-type: none"> • ASCII string (quotation marks do not appear): <ul style="list-style-type: none"> ▪ “preferred image setting does not exist” ▪ “current image setting does not exist” <p>Example(s):</p> <ul style="list-style-type: none"> ▪ AT!IMPREF="ABC" (<i>where "ABC" is a carrier name</i>) ▪ AT!IMPREF="AUTO-SIM" (<i>to enable SIM-based switching</i>)

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
!LTECA	<p>Enable/disable LTE Carrier Aggregation or Display supported LTE CA pairs</p> <p>Enable or disable LTE Carrier Aggregation (CA), or (when enabled) display the list of LTE CA pairs supported by the hardware, the permitted combinations due to module band support, and depending on module provisioning, a "prune_ca" list of the actual set of allowed CA combinations (a subset of the combinations that the module supports).</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!LTECA=<flag> Response: OK Purpose: Enable or disable LTE CA. ▪ Query: AT!LTECA? Response: Hardware: <Bd><class>[_<Bd><class>[_<Bd><class>]]:<Bu><class>[,<Bu><class>[,<Bu><class>]] ... Permitted Bands: <Bd><class>[_<Bd><class>[_<Bd><class>]]:<Bu><class>[,<Bu><class>[,<Bu><class>]] ... (If Prune_ca_combos does not exist) Prune_ca_combos: Empty (If Prune_ca_combos exists) Prune_ca_combos: <Bd><class>[-<Bd><class>[-<Bd><class>]]-<bcs> OK Purpose: Return LTE network measurements. ▪ Query List: AT!LTECA=? Purpose: Return the execution command format and valid parameter values. <p>Parameters:</p> <p><flag> (Enable/disable LTE CA)</p> <ul style="list-style-type: none"> • 0 — Disable CA • 1 — Enable CA <p><Bd> (LTE downlink band)</p> <ul style="list-style-type: none"> • Band numbers vary depending on device type, SKU, and PRI configuration. To view the device's supported bands, see !BAND. <p><Bu> (LTE uplink band)</p> <ul style="list-style-type: none"> • Band numbers vary depending on device type, SKU, and PRI configuration. To view the device's supported bands, see !BAND. <p><class> (Aggregated transmission bandwidth configuration)</p> <ul style="list-style-type: none"> • Valid values: 'A'-'I' <p>(Continued on next page)</p>

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
<p>!LTECA (continued)</p>	<p>Enable/disable LTE Carrier Aggregation or Display supported LTE CA pairs (continued)</p> <p><bc> (Bandwidth Combination Set)</p> <ul style="list-style-type: none"> • Integer value, ≥0. See 3GPP specification for details. <p>Example(s):</p> <ul style="list-style-type: none"> ▪ Example where Prune_ca_combos does not exist: <pre>AT!LTECA? Hardware: 12A_30A_66A:12A,30A,66A 13A_66A_66A:13A,66A1 3A_66B:13A,66A ... Permitted Bands: 12A_30A_66A:12A,30A,66A 13A_66A_66A:13A,66A1 3A_66B:13A,66A ... Prune_ca_combos: Empty OK</pre> ▪ Example where Prune_ca_combos exists: <pre>AT!LTECA? Hardware: 12A_30A_66A:12A,30A,66A 13A_66A_66A:13A,66A1 3A_66B:13A,66A ... Permitted Bands: 12A_30A_66A:12A,30A,66A 13A_66A_66A:13A,66A1 3A_66B:13A,66A ... Prune_ca_combos: 1A-8A-0 1A-8A-1 1A-8A-2 2C-0 2A-2A-0 ... OK</pre>

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
!LTEINFO	<p>Display LTE network information</p> <p>Display LTE network information.</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Query: AT!LTEINFO? Response: !LTEINFO: Serving: ...<list of applicable parameters> IntraFreq: ...<list of applicable parameters> InterFreq: ...<list of applicable parameters> GSM: ...<list of applicable parameters> WCDMA: ...<list of applicable parameters> CDMA 1x: ...<list of applicable parameters> CDMA HRPD: ...<list of applicable parameters> <p>Purpose: Return LTE network measurements.</p> <p>Parameters:</p> <p><earfcn> (E-UTRA absolute radio frequency channel number of the serving cell)</p> <ul style="list-style-type: none"> • 16-bit decimal <p><mcc> (MCC code)</p> <ul style="list-style-type: none"> • 16-bit decimal <p><mnc> (MNC code)</p> <ul style="list-style-type: none"> • 16-bit decimal <p><tac> (Tracking area code)</p> <ul style="list-style-type: none"> • 16-bit decimal <p><cid> (LTE Serving cell id)</p> <ul style="list-style-type: none"> • 16-bit hexadecimal <p><bd> (Serving cell operating band)</p> <ul style="list-style-type: none"> • 8-bit decimal <p><d> (Transmission bandwidth configuration of serving cell on the downlink)</p> <ul style="list-style-type: none"> • 8-bit decimal <p><u> (Transmission bandwidth configuration of serving cell on the uplink)</p> <ul style="list-style-type: none"> • 8-bit decimal <p><snr> (Average RSSNR of the serving cell over last measurement period in decibels)</p> <ul style="list-style-type: none"> • 8-bit decimal <p><pci> (Physical cell ID)</p> <ul style="list-style-type: none"> • 16-bit decimal <p><rsrq> (Current Reference Signal Receive Quality as measured by L1)</p> <ul style="list-style-type: none"> • 16-bit decimal <p><rsrp> (Current Reference Signal Receive Power in dBm x10 as measured by L1)</p> <ul style="list-style-type: none"> • 16-bit decimal <p><rssi> (Current Received Signal Strength Indication as measured by L1)</p> <ul style="list-style-type: none"> • 16-bit decimal <p>(Continued on next page)</p>

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
!LTEINFO (continued)	<p>Display LTE network information (continued)</p> <p><rxlv> (Cell selection Rx level (Srxlev) value)</p> <ul style="list-style-type: none"> • 16-bit decimal <p><thresholdlow> (Cell Srxlev low threshold)</p> <ul style="list-style-type: none"> • 8-bit decimal <p><thresholdhi> (Cell Srxlev high threshold)</p> <ul style="list-style-type: none"> • 8-bit decimal <p><priority> (Cell reselection priority)</p> <ul style="list-style-type: none"> • 8-bit decimal <p><threshl> (Reselection threshold for low priority layers)</p> <ul style="list-style-type: none"> • 8-bit decimal <p><threshh> (Reselection threshold for high priority layers)</p> <ul style="list-style-type: none"> • 8-bit decimal <p><prio> (Priority of this frequency group)</p> <ul style="list-style-type: none"> • 8-bit decimal <p><ncc> (Bitmask identifying whether neighbor with a particular Network Color Code is to be reported)</p> <ul style="list-style-type: none"> • 8-bit decimal <p><arfcn> (GSM frequency being reported)</p> <ul style="list-style-type: none"> • 16-bit decimal <p><1900> (Band indicator for the GSM ARFCN, only valid if arfcn is in the overlapping region)</p> <ul style="list-style-type: none"> • boolean <p><valid> (Flag indicating whether the BSIC ID is valid)</p> <ul style="list-style-type: none"> • boolean <p><bsic> (BSIC ID)</p> <ul style="list-style-type: none"> • 8-bit decimal <p><uarfcn> (WCDMA layer frequency)</p> <ul style="list-style-type: none"> • 16-bit decimal <p><psc> (Scrambling code)</p> <ul style="list-style-type: none"> • 16-bit decimal <p><rscp> (Absolute power level of the CPICH as received by the UE in dBm x10)</p> <ul style="list-style-type: none"> • 16-bit decimal <p><ecn0> (Ratio of received energy per PN chip for the CPICH to the total received power spectral density at the UE antenna connector)</p> <ul style="list-style-type: none"> • 16-bit decimal <p><chan> (Channel number)</p> <ul style="list-style-type: none"> • 16-bit decimal <p><bc> (Band class)</p> <ul style="list-style-type: none"> • 16-bit decimal <p>(Continued on next page)</p>

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
	<p><offsey> (The neighbor cell Pilot PN offset)</p> <ul style="list-style-type: none"> • 16-bit decimal <p><phase> (The neighbor cell Pilot PN phase)</p> <ul style="list-style-type: none"> • 16-bit decimal <p><str> (The neighbor cell Pilot EC/IO)</p> <ul style="list-style-type: none"> • 16-bit decimal
!NVPLMN	<p>Provision/display PLMN list for Network Personalization locking</p> <p>Provision or display the list of PLMN (MCC/MNC pairs) used for Network Personalization locking.</p> <p>Use the execution format to provision the list ONE TIME ONLY. After the list is provisioned, it can only be displayed, not updated.</p> <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Query: AT!NVPLMN? Response: <MCC> <MNC> ... OK ▪ Execution: AT!NVPLMN=<MCC1>, <MNC1>, ..., <MCCn>, <MNCn> Response: OK Purpose: Add up to six MCC/MNC pairs to the PLMN list Note: Execution can be performed one time only (all MCC/MNC pairs must be set at the same time). <p>Parameters:</p> <p><MCC> (Mobile Country Code)</p> <ul style="list-style-type: none"> • 3 digits <p><MNC> (Mobile Network Code)</p> <ul style="list-style-type: none"> • 2 digits

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
!PCINFO	<p>Return power control status information</p> <p>Return the modem's power control status information.</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Query: AT!PCINFO? Response: State: <state> LPM voters - Temp:<vote>, Volt:<vote>, User:<vote>, W_DISABLE: <vote>, IMSWITCH:<vote>, BIOS:<vote>, LWM2M:<vote>, OMADM:<vote>, FOTA:<vote>, RFCAL:<vote> <p style="padding-left: 40px;">LPM persistence - <userlpm></p> <p style="padding-left: 40px;">OK</p> <p>Purpose: Return power control information.</p> <p>Parameters:</p> <p><state> (The modem's power mode)</p> <ul style="list-style-type: none"> ▪ "Low Power Mode" ▪ "Online" ▪ "Offline" <p><vote> (LPM requested flag)</p> <ul style="list-style-type: none"> ▪ 0—LPM requested ▪ 1—LPM not requested <p><userlpm> (Current state of user-initiated Low Power Mode)</p> <ul style="list-style-type: none"> ▪ 0—Host GUI has not requested LPM ▪ 1—Host GUI has requested LPM

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
!PCOFFEN	<p>Set/return Power Off Enable state</p> <p>The modem can be configured to enter low power mode or power off when W_DISABLE is asserted. (This is called the Power Off Enable feature.) Use this command to indicate or set the Power Off Enable feature state.</p> <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: ATPCOFFEN=<state> Response: OK Purpose: Set the current state. ▪ Query: ATPCOFFEN? Response: <state> OK Purpose: Report the current <state>. <p>Parameters:</p> <p><state> (Current state of Power Off Enable)</p> <ul style="list-style-type: none"> • 0—Modem will enter LPM (low power mode) when W_DISABLE is asserted. • 1—Power off modem • 2—Ignore changes on W_DISABLE.
!PCTEMP	<p>Return current temperature information</p> <p>Return the module’s temperature state and actual temperature.</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Query: ATPCTEMP? Response: Temp state: <state> Temperature: <temperature> C OK Purpose: Return the module’s temperature information. <p>Parameters:</p> <p><state> (Temperature state):</p> <ul style="list-style-type: none"> ▪ Valid values: <ul style="list-style-type: none"> • “High Critical” • “High Warning” • “Normal” • “Low Warning” • “Low Critical” <p><temperature> (Current temperature):</p> <ul style="list-style-type: none"> ▪ Current temperature in degrees Celsius. This is the temperature reported by a thermistor positioned near the power amplifiers. ▪ Decimal ASCII

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
!PCTEMPLIMITS	<p>Set/report temperature state limit values</p> <p>Certain modem functionality is affected by the modem's temperature state. The possible temperature states are high critical, high warning, high normal, low normal, and low critical. Use this command to report or set the limits that correspond to these temperature states. To display the current temperature and temperature state, see !PCTEMP on page 42.</p> <hr/> <p><i>Note: All temperatures are in Celsius.</i></p> <hr/> <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!PCTEMPLIMITS=<hc>,<hw>,<hn>,<ln>,<lc> Response: OK Purpose: Set the temperature limits for each state (all five values must be specified). ▪ Query: AT!PCTEMPLIMITS? Response: HI CRIT: <hc> HI WARN: <hw> HI NORM: <hn> LO NORM: <ln> LO CRIT: <lc> Purpose: Return the temperature limits for each state. <p>Parameters:</p> <p><hc> (High Critical, in °C)</p> <ul style="list-style-type: none"> • Integer • Default temperature limit varies by device (see device Product Specification Document or Product Technical Specification). <p><hw> (High Warning, in °C)</p> <ul style="list-style-type: none"> • Integer • Default temperature limit varies by device (see device Product Specification Document or Product Technical Specification). <p><hn>(High Normal, in °C)</p> <ul style="list-style-type: none"> • Integer • Default temperature limit varies by device (see device Product Specification Document or Product Technical Specification). <p><ln> (Low Normal, in °C)</p> <ul style="list-style-type: none"> • Integer • Default temperature limit varies by device (see device Product Specification Document or Product Technical Specification). <p><lc> (Low Critical, in °C)</p> <ul style="list-style-type: none"> • Integer • Default temperature limit varies by device (see device Product Specification Document or Product Technical Specification).

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
!PCVOLT	<p>Return current power supply voltage information</p> <p>Return the module’s power control supply state and actual voltage.</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Query: AT!PCVOLT? Response: Volt state: Normal Power supply voltage: <voltage> mV (ADC: <raw>) OK Purpose: Return the module’s voltage information. <p>Parameters:</p> <p><state> (Power supply state):</p> <ul style="list-style-type: none"> ▪ Valid values: <ul style="list-style-type: none"> • “High Critical” • “High Warning” • “Normal” • “Low Warning” • “Low Critical” <p><voltage>:</p> <ul style="list-style-type: none"> ▪ Current voltage reading in mV. ▪ Decimal ASCII <p><raw>:</p> <ul style="list-style-type: none"> ▪ ADC (Analog/digital convertor) reading ▪ Decimal ASCII

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
!PCVOLTLIMITS	<p>Set/report power supply voltage state limit values</p> <p>Certain modem functionality is affected by the modem's power supply voltage state. The possible voltage states are high critical, high warning, high normal, low normal, and low critical.</p> <p>Use this command to report or set the limits that correspond to these voltage states.</p> <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!PCVOLTLIMITS=<hc>,<hw>,<hn>,<ln>,<lc> Response: OK Purpose: Set the voltage limits for each state (all five values must be specified). ▪ Query: AT!PCVOLTLIMITS? Response: HI CRIT: <hc> HI WARN: <hw> HI NORM: <hn> LO NORM: <ln> LO CRIT: <lc> Purpose: Return the voltage limits for each state. <p>Parameters:</p> <p><hc> (High Critical, in mV)</p> <ul style="list-style-type: none"> • Integer • Default voltage limit varies by device (see device Product Specification Document or Product Technical Specification) <p><hw> (High Warning, in mV)</p> <ul style="list-style-type: none"> • Integer • Default voltage limit varies by device (see device Product Specification Document or Product Technical Specification) <p><hn> (High Normal, in mV)</p> <ul style="list-style-type: none"> • Integer • Default voltage limit varies by device (see device Product Specification Document or Product Technical Specification) <p><ln> (Low Normal, in mV)</p> <ul style="list-style-type: none"> • Integer • Default voltage limit varies by device (see device Product Specification Document or Product Technical Specification) <p><lc> (Low Critical, in mV)</p> <ul style="list-style-type: none"> • Integer • Default voltage limit varies by device (see device Product Specification Document or Product Technical Specification)

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
<p>!PRIID</p>	<p>Set/report module PRI part number and revision</p> <p>Report or set the module’s customer and carrier PRI part numbers and revisions.</p> <p>Password required: Yes—Execution format only</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!PRIID=<priPN>,<priRev>,<pri_cust> Response: OK Purpose: Set the module’s PRI part number (<priPn>), revision (<priRev>), and customer name (<pri_cust>). ▪ Query: AT!PRIID? Response: PRI Part Number: <priPn> Revision: <priRevDisplay> Customer: <pri_cust> <p style="padding-left: 40px;">Carrier PRI: <bcVersion> OK</p> <p>Purpose: Return the module’s PRI information.</p> <p>Parameters:</p> <p><priPn> (PRI part number)</p> <ul style="list-style-type: none"> • 7-digit ASCII number • Example: 9991234 <p><priRev> (PRI revision number being written to the module)</p> <ul style="list-style-type: none"> • 4-digit ASCII: XXYY (implied “.” between XX and YY) • Example: 0100 <p><priRevDisplay> (PRI revision number being read from the module)</p> <ul style="list-style-type: none"> • 4-digit ASCII: XX.YY • Example: 01.00 <p><pri_cust> (PRI customer name)</p> <ul style="list-style-type: none"> • ASCII string • Example: “Generic Operator” <p><bcVersion> (BC version)</p> <ul style="list-style-type: none"> • ASCII string
<p>!RESET</p>	<p>Reset modem</p> <p>Perform a modem reset.</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!RESET Response: OK Purpose: Reset the modem.

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
!SCACT	<p>Activate/deactivate data connection</p> <p>Activate or deactivate a specific data connection between the host and network.</p> <hr/> <p><i>Note: This command does not work on Windows 8 or Windows 7 systems operating in MBIM mode. For those systems, use Microsoft APIs to initiate/end a data connection.</i></p> <hr/> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Query: AT!SCACT? [<pid>] Response: !SCACT: <pid>, <state> ... (additional <pid>/<state> combinations) OK ▪ Purpose: Display a list of all defined connections and their current state, or display a specified connection and its state. ▪ Execution: AT!SCACT=<state>, <pid> Response: OK Purpose: Activate or deactivate a specific data connection. <p>Parameters:</p> <p><pid> (PDN connection ID)</p> <ul style="list-style-type: none"> • Valid values: <ul style="list-style-type: none"> ▪ UMTS: <ul style="list-style-type: none"> ▪ 1–16 ▪ Default: 1 (all networks except Verizon), 3 (Verizon) ▪ CDMA: <ul style="list-style-type: none"> ▪ 101–107 ▪ Default: 101 (all networks except Verizon), 3 (Verizon) <p><state> (Current state of specified <pid>)</p> <ul style="list-style-type: none"> • 0—Deactivated • 1—Activated • Any other value causes command execution to return ERROR.

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description														
!TMSTATUS	<p>Report Thermal Mitigation Status</p> <p>Report the thermal mitigation status of all available Thermal Mitigation Devices (TMD) in the module.</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Query: AT!TMSTATUS? Response: <table border="0" style="margin-left: 20px;"> <tr> <td style="padding-right: 10px;">Device</td> <td style="padding-right: 20px;">Level</td> </tr> <tr> <td>pa</td> <td><status></td> </tr> <tr> <td>modem</td> <td><status></td> </tr> <tr> <td>cpuv_restriction_cold</td> <td><status></td> </tr> <tr> <td>modem_current</td> <td><status></td> </tr> <tr> <td>cpr_cold</td> <td><status></td> </tr> <tr> <td>vbatt_low</td> <td><status></td> </tr> </table> <p style="margin-left: 40px;">OK</p> <p>Purpose: Display the thermal mitigation status of the module's TMDs.</p> <ul style="list-style-type: none"> ▪ Query List: AT!TMSTATUS=? Purpose: Display valid execution format and parameter values. <p>Parameters:</p> <p><status> (Mitigation level)</p> <ul style="list-style-type: none"> • Valid range: 0–3 <ul style="list-style-type: none"> ▪ 'modem' mitigation levels: <ul style="list-style-type: none"> ▪ 0—No mitigation ▪ 1—DL data rate throttling ▪ 3—No data calls ▪ 'pa' mitigation levels: <ul style="list-style-type: none"> ▪ 0—No mitigation ▪ 1—UL data rate throttling ▪ 2—UL rate throttling and Tx power limiting ▪ 3—No data calls 	Device	Level	pa	<status>	modem	<status>	cpuv_restriction_cold	<status>	modem_current	<status>	cpr_cold	<status>	vbatt_low	<status>
Device	Level														
pa	<status>														
modem	<status>														
cpuv_restriction_cold	<status>														
modem_current	<status>														
cpr_cold	<status>														
vbatt_low	<status>														

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
!USBCOMP	<p>Set/report USB interface configuration</p> <p>Set or display the device's USB interface configuration.</p> <p>By default, devices are typically configured to use a USB composition that presents a minimal set of interfaces from a list of available interfaces. This command is used to add or remove interfaces from the configuration.</p> <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: ATIUSBCOMP=<Config Index>,<Config Type>,<Interface bitmask> Response: OK Purpose: Set the current composition. For the change to take effect, you must reset the modem. ▪ Query: ATIUSBCOMP? Response: Config Index: <Config Index> Config Type: <Config Type> <Config Type Desc> Interface bitmask: <Interface bitmask> <Bitmask Desc> OK Purpose: Report the current interface composition. ▪ Query List: ATIUSBCOMP=? Purpose: Display valid execution format and parameter values, and examples. <p>Parameters:</p> <p><Config Index> (USB composition)</p> <ul style="list-style-type: none"> • Valid value: 1 • Use ATIUSBCOMP=? to view the configurations available for the device. Available configurations are identified as "SUPPORTED". <p><Config Type> (USB composition)</p> <ul style="list-style-type: none"> • 1 — USBIF-MBIM. This option is used only for Sierra PIDs 68B1 and 9068. • 2 — PCIE USBIF • 3 — Legacy-Generic • 4 — RNDIS. This option is used only for Sierra PIDs 68B1 and 9068. <p><Config Type Desc> (Configuration description)</p> <ul style="list-style-type: none"> • "(USBIF-MBIM)" — Description of <Config Type> = 1 • "(PCIE USBIF)" — Description of <Config Type> = 2 • "(Legacy-Generic)" — Description of <Config Type> = 3 • "(RNDIS)" — Description of <Config Type> = 4. <p><Interface bitmask> (USB composition)</p> <ul style="list-style-type: none"> • Bitmask representing all enabled interfaces • Format: 32-bit bitmask • Valid values (available interfaces are device-dependent): <ul style="list-style-type: none"> ▪ 0x00000001 — DIAG ▪ 0x00000004 — NMEA ▪ 0x00000008 — MODEM ▪ 0x00000100 — RMNET0 ▪ 0x00001000 — MBIM <p>(Continued on next page)</p>

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
!USBCOMP (continued)	<p>Set/report USB interface configuration (continued)</p> <p><Bitmask Desc> (Interface bitmask description)</p> <ul style="list-style-type: none"> • List of interface descriptions corresponding to <Interface bitmask> components • Example: "(diag, nmea, modem, mbim)"
!USBINFO	<p>Return information from active USB descriptor</p> <p>Return information from the active USB descriptor.</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Query: ATIUSBINFO? Response: VID: <vendor_id> APP PID: <app_product_id> BOOT PID: <boot_product_id> Manufacturer: <product_manufacturer> Product: <product_name> Purpose: Display USB descriptor information. <p>Parameters:</p> <p><vendor_id> (Vendor ID):</p> <ul style="list-style-type: none"> ▪ Valid range: 0000–FFFF <p><app_product_id> (Product ID used when modem is in application mode):</p> <ul style="list-style-type: none"> ▪ Valid range: 0000–FFFF <p><boot_product_id> (Product ID used when modem is in boot loader mode):</p> <ul style="list-style-type: none"> ▪ Valid range: 0000–FFFF <p><product_manufacturer> (Manufacturer string):</p> <ul style="list-style-type: none"> ▪ ASCII string (32 characters maximum) ▪ Example: "Sierra Wireless, Incorporated" <p><product_name> (Product string):</p> <ul style="list-style-type: none"> ▪ ASCII string (64 characters maximum) ▪ Example: "EM7565"

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
!USBPID	<p>Set/report product ID in USB descriptor</p> <p>Use this command to set the device’s product ID in the USB descriptor. (Some devices may support more than one product ID.)</p> <hr/> <p><i>Note: If a custom PID is used for <app product_id>, then the <boot product_id> must be set at the same time.</i></p> <hr/> <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: ATIUSBPID=<app product_id> [<boot product_id>] Response: OK Purpose: Set the application and boot product IDs in the USB descriptor. ▪ Query: ATIUSBPID? Response: !USBPID: <app product_id>, <boot product_id> OK Purpose: Report the product ID that is stored in the USB descriptor. ▪ Query List: ATIUSBPID=? Purpose: Display a list of default (non-custom) product IDs for the device. <p>Parameters:</p> <p><app product_id></p> <ul style="list-style-type: none"> • Hexadecimal ASCII value. • Valid range: 0000–FFFF <p><boot product_id></p> <ul style="list-style-type: none"> • Hexadecimal ASCII value. • Valid range: 0000–FFFF • In the Execution command format, if the <app product_id> is a custom PID, then the <boot product_id> must be set at the same time. (To check if the <app product_id> is a custom PID, use AT!USBPID=? to see a list of all available non-custom PIDs.)

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
!USBSPEED	<p>Set/report USB speed</p> <p>Use this command to set the device’s maximum supported USB speed, and to display the maximum supported speed and current speed.</p> <p>Password required: Yes Reset required to apply changes: Yes Persistent across power cycles: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: ATIUSBSPEED=<max_supported_speed> Response: OK Purpose: Set the device’s maximum supported USB speed. ▪ Query: ATIUSBSPEED? Response: SUPPORTED: <max_supported_speed> CURRENT : <current_usb_speed> OK Purpose: Report the device’s maximum and current speeds. ▪ Query List: ATIUSBSPEED=? Purpose: Display valid execution format and parameter values. <p>Parameters:</p> <p><max_supported_speed></p> <ul style="list-style-type: none"> • 0 — High Speed (USB 2.0) • 1 — Super Speed (USB 3.0) <p><current_usb_speed></p> <ul style="list-style-type: none"> • ASCII string (quotation marks not included) • Valid values: <ul style="list-style-type: none"> ▪ “Super-Speed” ▪ “High-Speed”

Table 3-2: Modem status, customization, and reset commands (Continued)

Command	Description
&V	<p>Return operating mode AT configuration parameters</p> <p>Return the status of all AT command parameters that apply to the current operating mode.</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT&V <p>Response: &C: 2; &D: 2; &F: 0; E: 1; L: 0; M: 0; Q: 0; V: 1; X: 0; Z: 0; S0: 0; S2: 43; S3: 13; S4: 10; S5: 8; S6: 2; S7: 50; S8: 2; S9: 6; S10: 14; S11: 95; +FCLASS: 0; +ICF: 3,3; +IFC: 2,2; +IPR: 115200; +DR: 0; +DS: 0,0,2048,6;+WS46: 12; +CBST: 0,0,1;+CRLP: (61,61,48,6,0),(61,61,48,6,1),(240,240,52,6,2);+CV120: 1,1,1,0,0,0; +CHSN: 0,0,0,0; +CSSN: 0,0; +CREG: 0; +CGREG: 0;+CFUN:;; +CSCS: "IRA"; +CSTA: 129; +CR: 0; +CRC: 0; +CMEE: 2; +CGDCONT: (1,"IP","", "",0,0); +CGDSCONT: ; +CGTFT: ; +CGEQREQ: ; +CGEQMIN: ; +CGQREQ: ; +CGQMIN: ;+CGEREP: 0,0; +CGDATA: "PPP"; +CGCLASS: "A"; +CGSMS: 3; +CSMS: 0;+CMGF: 0; +CSCA: "" ; +CSMP: ,,0,0; +CSDH: 0; +CSCB: 0,"", ""; +FDD: 0;+FAR: 0; +FCL: 0; +FIT: 0,0; +ES: ;; +ESA: 0,,,,0,0,255;; +CMOD: 0;+CVHU: 0; +CPIN: ; +CMEC: 0,0,0; +CKPD: 1,1; +CGATT: 0; +CGACT: 0;+CPBS: "SM"; +CPMS: "SM","SM","SM"; +CNMI: 0,0,0,0,0; +CMMS: 0; +FTS: 0;+FRS: 0; +FTH: 3; +FRH: 3; +FTM: 96; +FRM: 96; +CCUG: 0,0,0;+COPS: 0,0,""; +CUSD: 0; +CAOC: 1; +CCWA: 0; +CPOL: 0,2,""; +CTZR: 0;+CLIP: 0; +COLP: 0; +CMUX: 0,0,5,31,10,3,30,10,2;+CMUX: 0,0,5,31,10,3,30,10,2</p> <p>OK</p> <p><i>Note: this is an example only. The supported commands may vary by device/SKU.</i></p> <p>Purpose: Display command parameters.</p>

4: Diagnostic Commands

4.1 Introduction

This chapter describes commands used to diagnose modem problems.

4.2 Command Summary

The table below lists the commands described in this chapter.

Table 4-1: Diagnostic commands

Command	Description	Page
!BCFWUPDATESTATUS	Report status of most recent firmware update attempt	55
!ERR	Display diagnostic information	56
!GCCLR	Clear crash dump data	56
!GCDUMP	Display crash dump data	57
!LTERXCONTROL	Enable/disable LTE receive (Rx) diversity during Carrier Aggregation	58
!RXDEN	Enable/disable WCDMA/LTE/TD-SCDMA receive (Rx) diversity	59

4.3 Command Reference

Table 4-2: Diagnostic command details

Command	Description
!BCFWUPDATESTATUS	<p>Report status of most recent firmware update attempt</p> <p>Return the status of the most recent firmware update attempt made since the last cold restart.</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!BCFWUPDATESTATUS Response: !BCFWUPDATESTATUS: <result> <i>or</i> !BCFWUPDATESTATUS: <result> Failed IMG TYPE <type>, DATA <data>, PART <part> OK Purpose: Return the status of the most recent firmware update attempt. The second response format appears only if <result> = "FAILED". <p>Parameters:</p> <p><result> (Status of last firmware update attempt)</p> <ul style="list-style-type: none"> • ASCII string: <ul style="list-style-type: none"> ▪ "UNKNOWN"—Status of last attempt is unknown. ▪ "SUCCESS"—Last update was successful. ▪ "FAILED"—Last update failed. <p><type> (Firmware image type that failed to update)</p> <ul style="list-style-type: none"> • ASCII string • Note: Parameter appears only if <result> is FAILED <p><data> (Reference data for failed image)</p> <ul style="list-style-type: none"> • Location of the reference data as an offset in the CWE image • Valid range: 0–(2³²–1) • Note: Parameter appears only if <result> is FAILED <p><part> (Partition associated with the failed image)</p> <ul style="list-style-type: none"> • ASCII string • Applies only to configuration updates • Note: Parameter appears only if <result> is FAILED

Table 4-2: Diagnostic command details (Continued)

Command	Description
<p>!ERR</p>	<p>Display diagnostic information</p> <p>This command is used to display diagnostic information (logged error conditions) that Sierra Wireless uses to assist in resolving technical issues.</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: ATIERR=0 Response: OK Purpose: Clear the logged error conditions. Use this command before running tests to make sure that details displayed using AT!ERR are relevant to the tests being performed. ▪ Query: ATIERR Response: 00 [F] <count> <file> <line> ... nn [F] <count> <file> <line> OK Purpose: Return all logged error conditions that are stored in NVRAM. <p>Parameters:</p> <p><count> (Number of occurrences) <ul style="list-style-type: none"> ▪ Valid range: 0x00–0xFF </p> <p><file> (Log file name) <ul style="list-style-type: none"> ▪ Name of log file using ASCII characters </p> <p><line> (Line number in log file) <ul style="list-style-type: none"> ▪ Valid range: 1–99999 </p>
<p>!GCCLR</p>	<p>Clear crash dump data</p> <p>Clear crash dump data.</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: ATIGCCLR Response: Crash data cleared OK Purpose: Clear crash dump data. <p>Parameters:</p> <p>None</p>

Table 4-2: Diagnostic command details (Continued)

Command	Description
!GCDUMP	Display crash dump data Display crash dump data. Password required: No Usage: <ul style="list-style-type: none">▪ Execution: ATIGCDUMP Response: <crash dump data> OK or No crash data available OK Purpose: Display crash dump data.

Table 4-2: Diagnostic command details (Continued)

Command	Description
<p>LTERXCONTROL</p>	<p>Enable/disable LTE receive (Rx) diversity during Carrier Aggregation</p> <p>Enable or disable LTE receive diversity for individual component carriers (PCC or SCC) during Carrier Aggregation (CA). The new state takes effect immediately, and reverts to the default state when the modem is reset.</p> <hr/> <p><i>Note: !LTERXCONTROL should be issued during an active CA call.</i></p> <hr/> <p><i>Note: When using !LTERXCONTROL to disable any chain, make sure !RXDEN is set to enable all chains.</i></p> <hr/> <p><i>Note: Due to firmware design, LTE open-loop Tx power should be set to 20 dBm when measuring SISO sensitivity with Rx diversity as the primary path.</i></p> <hr/> <p>Password required: Yes Reset required to apply changes: No Persistent across power cycles: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: ATLTERXCONTROL=<cc_id>,<selection> Response: OK Purpose: Configure the component carrier as primary Rx, diversity Rx, or both. ▪ Query List: ATLTERXCONTROL=? Purpose: Returns the command format and valid parameter values. <p>Parameters:</p> <p><cc_id> (Component carrier ID)</p> <ul style="list-style-type: none"> ▪ 0—PCC (Primary cell) ▪ 1—SCC1 (Secondary cell) ▪ 2—SCC2 (Secondary cell) ▪ 3—SCC3 (Secondary cell) <p><selection> (Rx chain to enable)</p> <ul style="list-style-type: none"> ▪ 1—Primary Rx only ▪ 2—Diversity Rx only ▪ 3—Primary Rx and Diversity Rx

Table 4-2: Diagnostic command details (Continued)

Command	Description
!RXDEN	<p>Enable/disable WCDMA/LTE/TD-SCDMA receive (Rx) diversity</p> <p>Enable or disable WCDMA/LTE/TD-SCDMA receive diversity, or establish receive diversity as the primary path. The new state takes effect the next time the modem is reset.</p> <hr/> <p><i>Note: During LTE Carrier Aggregation (CA), this command works only on the Primary Component Carrier (PCC). To control Secondary Component Carrier (SCC) chains, use !LTERXCONTROL. If !LTERXCONTROL is used to also control the PCC, !RXDEN must not be used.</i></p> <hr/> <p><i>Note: When using !LTERXCONTROL to disable any chain, make sure !RXDEN is set to enable all chains.</i></p> <hr/> <p><i>Note: Due to firmware design, LTE open-loop Tx power should be set to 20 dBm when measuring SISO sensitivity with Rx diversity as the primary path.</i></p> <hr/> <p>Password required: Yes—Execution format only</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!RXDEN=<state> Response: OK Purpose: Set the current receive diversity state. ▪ Query: AT!RXDEN? Response: !RXDEN: <state> OK Purpose: Return the current receive diversity <state>. ▪ Query List: AT!RXDEN=? Purpose: Return a list of available <state> values to use in this command. <p>Parameters:</p> <p><state> (Current/ requested receive diversity state)</p> <ul style="list-style-type: none"> • 0 — Rx diversity disabled • 1 — Rx diversity enabled • 2 — Rx diversity is primary path (See note above for measuring SISO sensitivity.)

5: Test Commands

5.1 Introduction

Note: Full test commands support is pending future firmware upgrade.

To obtain regulatory approval and carrier approvals for your product, you may be required to perform tests on the radio component of the embedded modem. This chapter describes AT commands used to perform those tests.

5.2 Command Summary

The table below lists the commands described in this chapter.

Table 5-1: Test commands

Command	Description	Page
!DACGPSCTON	Return GPS CtoN and frequency measurement	61
!DACGPSMASKON	Set CGPS IQ log mask	61
!DACGPSSTANDALONE	Enter /exit StandAlone (SA) RF mode	62
!DACGPSTESTMODE	Start/stop CGPS diagnostic task	62
!DAFTMACT	Put modem into Factory Test Mode	63
!DAFTMDEACT	Put modem into online mode from Factory Test Mode	63
!DAGFTMRXAGC	Get FTM Rx AGC (Primary or Diversity)	64
!DALGRXAGC	Return Rx AGC value (LTE only)	65
!DALGTXAGC	Return Tx AGC value and transmitter parameters (LTE only)	66
!DALTXCONTROL	Configure LTE Tx parameters (LTE only)	68
!DAOFFLINE	Place modem offline	69
!DARCONFIG	Set Band and Channel	70
!DARCONFIGDROP	Drop Radio Configurations	71
!DAWTXCONTROL	Configure WCDMA Tx Power (WCDMA only)	71

Table 5-2: Test command details (Continued)

Command	Description
<p>!DACGPSSTANDALONE</p>	<p>Enter/exit StandAlone (SA) RF mode</p> <p>Enter/exit SA RF mode.</p> <p>Requirements:</p> <ol style="list-style-type: none"> 1. AT!DACGPSTESTMODE=1 (to start CGPS diagnostic task) <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Query: AT!DACGPSSTANDALONE=<state> Response: 4B0D65001400 OK or Error <p>Purpose: Enter/exit SA RF mode</p> <p>Parameters:</p> <p><state> (SA RF mode state)</p> <ul style="list-style-type: none"> • 0 — Enter SA RF mode • 1 — Exit SA RF mode
<p>!DACGPSTESTMODE</p>	<p>Start/stop CGPS diagnostic task</p> <p>Start/stop the CGPS diagnostic task.</p> <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!DACGPSTESTMODE=<mode> Response: (for start): 4B0D0800 OK (for stop): 4B0D0C00 OK or Error <p>Purpose: Start or stop the CGPS diagnostic test.</p> <p>Parameters:</p> <p><mode> (CGPS diagnostic task mode)</p> <ul style="list-style-type: none"> • 0 — Stop • 1 — Start

Table 5-2: Test command details (Continued)

Command	Description
!DAFTMACT	<p>Put modem into Factory Test Mode</p> <p>Place the modem in FTM (Factory Test Mode). FTM is a non-signaling mode that allows the radio component to be manually configured to conduct certain types of tests.</p> <hr/> <p><i>Note: When this command executes successfully, the modem responds with the value 290300. Any other response indicates an error.</i></p> <hr/> <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Query: ATIDAFTMACT Response: 290300 (Success. Any other response indicates an error.) OK Purpose: Place modem in FTM mode.
!DAFTMDEACT	<p>Put modem into online mode from Factory Test Mode</p> <p>This command takes the modem out of FTM and puts the modem back into online mode. (The command !DAFTMACT puts the modem into FTM.)</p> <hr/> <p><i>Note: When this command executes successfully, the modem responds with the value 290400. Any other response indicates an error.</i></p> <hr/> <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Query: ATIDAFTMDEACT Response: 290400 (Success. Any other response indicates an error.) OK Purpose: Place modem in online mode (from FTM mode).

Table 5-2: Test command details (Continued)

Command	Description
!DAGFTMRXAGC	<p>Get FTM Rx AGC (Primary or Diversity)</p> <p>Get the FTM Rx AGC on the primary or diversity path.</p> <p>Requirements: Before using this command:</p> <ul style="list-style-type: none"> • !DAFTMACT must be issued to put the modem into FTM. • !DARCONFIG must be issued to set the technology, band, and channel. <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: ATIDAGFTMRXAGC=<carrier>, <technology>, <LNA Index>, <path> Response: <rsi> OK Purpose: Return the FTM Rx AGC value. <p>Parameters:</p> <p><carrier> (Carrier ID)</p> <ul style="list-style-type: none"> • 0—PCC <p><technology> (Radio access technology (RAT))</p> <ul style="list-style-type: none"> • RAT support is device-dependent. • 0—CDMA • 1—WCDMA • 2—GSM • 3—LTE <p><LNA Index> (LNA offset index)</p> <ul style="list-style-type: none"> • 0 — R0 (Highest gain) • 1 — R1 • 2 — R2 • 3 — R3 (Lowest gain) <p><path> (Rx path)</p> <ul style="list-style-type: none"> • 0—Primary Rx • 1—Diversity Rx <p><rsi> (RSSI, in dBm)</p> <ul style="list-style-type: none"> • Dynamic Rx AGC

Table 5-2: Test command details (Continued)

Command	Description
!DALGRXAGC	<p>Return Rx AGC value (LTE only)</p> <p>Return the Rx AGC (Automatic Gain Control) value and LNA gain states for each RF path (e.g. main and diversity).</p> <p>The AGC value can be converted to RSSI (Received Signal Strength Indicator) in dBm:</p> <pre> if (<AGC_value> < 511) <RX_dBm> = -106 + ((<AGC_value> + 512) / 12) else <RX_dBm> = -106 + (((<AGC_value>-1024) + 512) / 12) </pre> <p>Requirements:</p> <ul style="list-style-type: none"> The modem must be in LTE mode. <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> Execution: ATIDALGRXAGC or ATIDALGRXAGC? Response: Paths: <paths> Rx<n>: AGC: <agc> dBm LNA: <lina> Chain: <chain> Rx<n>: AGC: <agc> dBm LNA: <lina> Chain: <chain> OK Purpose: Return the <AGC value> and LNA gain states for each RF path. <p>Parameters:</p> <p><paths> (Number of receive paths)</p> <ul style="list-style-type: none"> 2 <p><agc> (AGC value in dBm)</p> <ul style="list-style-type: none"> Valid values: Dynamic Rx range <p><LNA Index> (LNA offset index)</p> <ul style="list-style-type: none"> 0 — R0 (Highest gain) 1 — R1 2 — R2 3 — R3 (Lowest gain) <p><chain> (Receive paths)</p> <ul style="list-style-type: none"> 0 — Rx Main 1 — Rx Diversity

Table 5-2: Test command details (Continued)

Command	Description
!DALGTXAGC	<p>Return Tx AGC value and transmitter parameters (LTE only)</p> <p>Return the Tx AGC (Automatic Gain Control) value and other transmitter parameters.</p> <p>Requirements:</p> <ul style="list-style-type: none"> • The modem must be in LTE mode. • Must be in an active call (for example, when connected to a call box or live network) <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!DALGTXAGC or AT!DALGTXAGC? <p>Response: Paths: <paths> Tx<n>:AGC: <agc> dBm RBi: <rbi> RB: <rbn> PA: <pa> TxGainIdx: <txgi> MTPL: <mtpl> dBm IQgain: <iq> MPR: <mpr> AMPR: <ampr> NS: <ns> SARmpr: <sarmpr> PDet Mode: <mode> PDetAGC: <pagc> PDet: <pdbm> Traw: <traw> Tscaled: <tscald> Tidx: <tidx> Trem: <trem> OK</p> <p>Purpose: Return transmitter parameters and the transmit <AGC value>.</p> <p>Parameters:</p> <p><paths> (Number of transmit paths)</p> <ul style="list-style-type: none"> • 1 (Tx) <p><agc> (Tx AGC value in dBm)</p> <ul style="list-style-type: none"> • Valid range: -70 to +23 <p><rbi></p> <ul style="list-style-type: none"> • Start resource block index <p><rbn> (Number of resource blocks)</p> <ul style="list-style-type: none"> • Valid range: 0–50 <p><pa> (PA gain state)</p> <ul style="list-style-type: none"> • Valid range: 0–3 <p><txgi></p> <ul style="list-style-type: none"> • Tx gain index <p><mtpl> (Max Tx power limit)</p> <ul style="list-style-type: none"> • Max value: +23 <p><iq></p> <ul style="list-style-type: none"> • Digital IQ gain scaling <p><mpr> (Maximum power reduction)</p> <ul style="list-style-type: none"> • See 3GPP 36.101 for details <p><ampr> (Additional Max power reduction)</p> <ul style="list-style-type: none"> • See 3GPP 36.101 for details <p><ns> (Network Signaled (NS) value)</p> <ul style="list-style-type: none"> • See 3GPP 36.101 for details <p>(Continued on next page)</p>

Table 5-2: Test command details (Continued)

Command	Description
!DALGTXAGC (continued)	<p>Return Tx AGC value and transmitter parameters (LTE only) (continued)</p> <p><mode> (HDET (power detector) mode)</p> <ul style="list-style-type: none"> • Valid values: <ul style="list-style-type: none"> ▪ L (Lower power) ▪ H (Higher power) <p><padc></p> <ul style="list-style-type: none"> • HDET ADC <p><pdbm></p> <ul style="list-style-type: none"> • HDET dBm <p><traw> (Raw thermistor ADC value)</p> <ul style="list-style-type: none"> • Valid range: 0–4095 <p><tscald> (Scaled thermistor value)</p> <ul style="list-style-type: none"> • Valid range: 0–255 • Value is scaled from <traw> based on calibrated min/max <traw> values for the supported temperature range. <p><tidx> (Temperature compensation bin)</p> <ul style="list-style-type: none"> • Valid range: 0–7 <p><trem></p> <ul style="list-style-type: none"> • Temperature compensation remainder bin

Table 5-2: Test command details (Continued)

Command	Description
!DALTXCONTROL	<p>Configure LTE Tx parameters (LTE only)</p> <p>Configure LTE Tx parameters, including Tx power, waveform, modulation, net signal values, number of resource blocks, and start resource block.</p> <p>Requirements: Before using this command:</p> <ul style="list-style-type: none"> • !DAFTMACT must be issued to put the modem into FTM. • !DARCONFIG must be issued to set the technology, band, and channel. <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!DALTXCONTROL=<carrier><enable>,<tx_pwr>,<waveform>,<mod>,<ns_val>,<start_RB>,<num_RB> <p>Response: OK Purpose: Set the LTE Tx parameters.</p> <p>Parameters:</p> <p><carrier> (Carrier ID)</p> <ul style="list-style-type: none"> • 0—PCC <p><enable> (Enable/disable Tx power output)</p> <ul style="list-style-type: none"> • 0—Disable • 1—Enable <p><tx_pwr> (Desired Tx power in dBm)</p> <ul style="list-style-type: none"> • Valid range: -57 to 23 • Value is ignored if <enable>=0. <p><waveform> (Tx waveform)</p> <ul style="list-style-type: none"> • 1—LTE PUSCH (Physical Uplink Shared Channel) • 2—LTE PUCCH (Physical Uplink Control Channel) Note: LTE PUCCH is not supported by EM75xx modules. • 3—LTE PRACH (Physical Random Access Channel) • 4—LTE SRS (Sounding Reference Signal) • 5—UpPTS (Uplink Pilot Time Slot) <p><mod> (Tx modulation)</p> <ul style="list-style-type: none"> • 0—QPSK • 1—16 QAM • 2—64 QAM <p><ns_val> (LTE NS (Net Sig))</p> <ul style="list-style-type: none"> • Valid range: 1–32 • This value affects maximum output power. <p><num_RB> (Number of resource blocks)</p> <ul style="list-style-type: none"> • Valid range: 0–100 <p><start_RB> (PUSCH starting resource block index)</p> <ul style="list-style-type: none"> • Valid range: 0–255

Table 5-2: Test command details (Continued)

Command	Description
!DAOFFLINE	Place modem offline Put the modem offline. Password required: Yes Usage: <ul style="list-style-type: none">▪ Execution: AT!DAOFFLINEResponse: OKPurpose: Put the modem offline. Parameters: None

Table 5-2: Test command details (Continued)

Command	Description
!DARCONFIG	<p>Set Band and Channel</p> <p>Configure and tune the module’s radio to a specific RAT, band, and channel.</p> <p>Requirements: Before using this command:</p> <ul style="list-style-type: none"> • !DAFTMACT must be issued to put the modem into FTM. <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!DARCONFIG=<carrier>,<technology>,<band>,<channel>[,<lte_bw>] Response: OK Purpose: Set the selected RAT’s band and channel (and bandwidth, for LTE). <p>Parameters:</p> <p><carrier> (Carrier ID)</p> <ul style="list-style-type: none"> • 0—PCC <p><technology> (Radio access technology (RAT))</p> <ul style="list-style-type: none"> • RAT support is device-dependent • 0—CDMA • 1—WCDMA • 2—GSM • 3—LTE <p><band> (Band number)</p> <ul style="list-style-type: none"> • Valid range: 1–71 • e.g. ‘1’ is LTE B1 or WCDMA B1 <p><channel> (Uplink channel number for selected <band>)</p> <ul style="list-style-type: none"> • Integer value • <band>-dependent <p><lte_bw> (LTE bandwidth)</p> <ul style="list-style-type: none"> • 0—1.4 MHz • 1—3 MHz • 2—5 MHz • 3—10 MHz • 4—15 MHz • 5—20 MHz

Table 5-2: Test command details (Continued)

Command	Description
!DARCONFIGDROP	<p>Drop Radio Configurations</p> <p>Drop the radio configurations that were previously set using !DARCONFIG. This command must be used when switching between technologies (RATs).</p> <p>Requirements: Before using this command:</p> <ul style="list-style-type: none"> • !DAFTMACT must be issued to put the modem into FTM. <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: ATIDARCONFIGDROP=<technology> Response: OK Purpose: Drop the current configurations for the selected RAT (<technology>). <p>Parameters: <technology> (Radio access technology (RAT))</p> <ul style="list-style-type: none"> • RAT support is device-dependent • 0—CDMA • 1—WCDMA • 2—GSM • 3—LTE
!DAWTXCONTROL	<p>Configure WCDMA Tx Power (WCDMA only)</p> <p>Configure the Tx power for WCDMA.</p> <p>Requirements: Before using this command:</p> <ul style="list-style-type: none"> • The modem must be in WCDMA mode. • !DAFTMACT must be issued to put the modem into FTM. • !DARCONFIG must be issued to set the technology, band, and channel. <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: ATIDAWTXCONTROL=<enable>,<power_dBm> Response: OK Purpose: Set the WCDMA Tx parameters. <p>Parameters: <enable> (Enable/disable Tx power output)</p> <ul style="list-style-type: none"> • 0—Disable • 1—Enable <p><power_dBm> (Desired Tx power in dBm)</p> <ul style="list-style-type: none"> • Valid range: -57 to 23 • Value is ignored if <enable>=0.

6: Memory Management Commands

6.1 Introduction

The modem uses non-volatile memory to store:

- Factory calibration data
- Settings made in a host application such as Skylight.

The commands in this chapter allow you to back up and restore the data in non-volatile memory.

6.2 Command Summary

The table below lists the commands described in this chapter:

Table 6-1: Memory management commands

Command	Description	Page
!NVBACKUP	Back up device configuration	73
!RMARESET	Restore device to saved restore point	75

6.3 Command Reference

Table 6-2: Memory management command details

Command	Description
!INVBKUP	<p>Back up device configuration</p> <p>Save the device's current configuration as a 'restore point'. The restore point can then be restored at a later time if necessary, using !RMARESET on page 75.</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: ATINVBKUP=<restore point>[,<name>] Response: !INVBKUP: Items Saved: <saved> Items Skipped: <skipped> OK Purpose: Save the current device configuration to the indicated <restore point>. Note: The restore point replaces the existing same-numbered restore point (if present), and deletes higher-numbered restore points. ▪ Query: ATINVBKUP? Response: !INVBKUP: <restore point> <name> ... OK Purpose: Display all available restore points. <p>Usage notes:</p> <ul style="list-style-type: none"> ▪ When saving a restore point: <ul style="list-style-type: none"> • The existing <restore point> is replaced (if present). • Higher-numbered restore points are deleted. ▪ If a <name> is not specified, the file is saved as "unnamed" or "Latest", depending on the <restore point>. <p>Parameters:</p> <p><restore point> (Type of saved restore point)</p> <ul style="list-style-type: none"> • Valid range: 0–3 • 0 — Factory-calibrated configuration (Cannot be replaced) • 1 — Sierra-provided SKU configuration (Cannot be replaced) • 2 — Save the current configuration using a specified file <name>. If no <name> is specified, save as "unnamed". • 3 — Save the current configuration as the 'Latest' restore point. Note: The category 3 restore point is also generated automatically after a successful reconfiguration (e.g. after an image switch or firmware update). <p>(Continued on next page)</p>

Table 6-2: Memory management command details (Continued)

Command	Description
!NVBACKUP	<p>Back up device configuration (continued)</p> <p><name> (Name used to store the restore point)</p> <ul style="list-style-type: none"> • 0–32 ASCII characters <ul style="list-style-type: none"> ▪ <restore point> = 0—“Factory” (Factory-calibrated configuration, pre-SKU) ▪ <restore point> = 1—“Provision” (Sierra-provisioned SKU configuration) ▪ <restore point> = 2—User-defined name provided when restore point was saved, or “unnamed” if no name was provided ▪ <restore point> = 3—“Latest” (Latest saved configuration) <p><saved> (Number of saved items)</p> <ul style="list-style-type: none"> • 0–(2³² - 1) <p><skipped> (Number of skipped items)</p> <ul style="list-style-type: none"> • 0–(2³² - 1) • Note: Does not display if 0

Table 6-2: Memory management command details (Continued)

Command	Description
!IRMARESET	<p>Restore device to saved restore point</p> <p>Restore the device to a previously saved restore point. (To save a restore point, see !NVBACKUP on page 73.)</p> <p>Password required: Yes Reset required to apply changes: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: ATIRMARESET=<restore point> Response: IRMARESET: DEVICE REBOOT REQUIRED Items Restored: <restored count> Items Deleted: <deleted count> Items Defaulted: <defaulted count> Items Skipped: <skipped count> OK ▪ Purpose: Restore device to the specified <restore point> (configuration). A reboot is required to take effect. ▪ Query: ATIRMARESET? Response: IRMARESET: <restore point> <name> ... OK ▪ Purpose: Display all available restore points. <p>Parameters:</p> <p><restore_point> (Saved restore point)</p> <ul style="list-style-type: none"> • 0 — Factory-calibrated configuration (Note: For information only, cannot be restored.) • 1 — Sierra-provided SKU configuration • 2 — Restore to the restore point that was saved earlier using !NVBACKUP on page 73. • 3 — Restore to the latest saved restore point (saved earlier using !NVBACKUP or automatically when the device was successfully reconfigured, e.g. after an image switch or firmware update) <p><name> (Descriptive name of <restore_point>)</p> <ul style="list-style-type: none"> • ASCII string, varies by <restore point>: <ul style="list-style-type: none"> ▪ <restore point> = 0—“Factory” (Factory-calibrated configuration, pre-SKU) ▪ <restore point> = 1—“Provision” (Sierra-provisioned SKU configuration) ▪ <restore point> = 2—User-defined name provided when using !NVBACKUP to save a configuration, or “unnamed” if no name was provided ▪ <restore point> = 3—User-defined name provided when using !NVBACKUP to save a configuration, or “Latest” (Latest saved configuration)

7: GNSS Commands

7.1 Introduction

This chapter describes commands used to access GNSS functionality in supporting modules.

When using these commands, the following considerations apply:

- GNSS is typically enabled by default; however, it may be disabled by default for some SKUs. If so, enable GNSS using **ATICUSTOM="GPSENABLE"**
- If supported by the modem, gpsOneXTRA is enabled (over the NDIS interface) by default when GNSS is enabled, and it generates data traffic.

7.2 Command Summary

The table below lists the commands described in this chapter.

Table 7-1: GNSS commands

Command	Description	Page
!GPSAUTOSTART	Configure GPS auto-start features	77
!GPSCLRASSIST	Clear specific GPS assistance data	79
!GPSOLDSTART	Clear all GNSS assistance data	80
!GPSEND	End an active session	80
!GPSFIX	Initiate GPS position fix	81
!GPSLBSAPN	Set GPS LBS APNs	82
!GPSLOC	Return last known location of the modem	84
!GPSMOMETHOD	Set/report GPS MO method	85
!GPSNMEACONFIG	Enable and set NMEA data output rate	86
!GPSNMEASENTECE	Set/report NMEA sentence type	87
!GPSPORTID	Set/report port ID to use over TCP/IP	88
!GPSSATINFO	Request satellite information	89
!GPSSTATUS	Request current status of a position fix session	90
!GPSSUPLURL	Set/report SUPL server URL	91
!GPSSUPLVER	Set/report SUPL server version	92
!GPSTRACK	Initiate local tracking (multiple fix) session	93
+WANT	Enable/disable GNSS antenna power	94

7.3 Command Reference

Table 7-2: GNSS command details

Command	Description
!GPSAUTOSTART	<p>Configure GPS auto-start features</p> <p>Configure the GPS auto-start features. Any changes take effect the next time the modem is reset.</p> <hr/> <p><i>Note: If auto-start is enabled, another GPS session cannot be started.</i></p> <hr/> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!GPSAUTOSTART=<function>[, <fixtype>, <maxtime>, <maxdist>, <fixrate>] Response: OK or ERROR Purpose: Assign start values for various GPS settings ▪ Query: AT!GPSAUTOSTART? Response: !GPSAUTOSTART function: <function> fixtype: <fixtype> maxtime: <maxtime> seconds maxdist: <maxdist> meters fixrate: <fixrate> seconds OK Purpose: Display the current values for auto-start features ▪ Query List: AT!GPSAUTOSTART=? Purpose: Return the expected command format. <p>(Continued on next page)</p>

Table 7-2: GNSS command details (Continued)

Command	Description
!GPSAUTOSTART	<p>Configure GPS auto-start features (continued)</p> <p>Parameters:</p> <p><function> (Enable/disable the feature)</p> <ul style="list-style-type: none"> • 0 — Disabled • 1 — Enabled at boot (GPS tracking session starts automatically when modem is reset) • 2 — Enabled when NMEA port is opened <p><fixtype> (Type of fix to establish)</p> <ul style="list-style-type: none"> • 1 — Standalone (not supported by a mobile station) • 2 — MS-based only • 3 — MS-assisted only <p><maxtime> (Maximum time to wait for a position fix)</p> <ul style="list-style-type: none"> • Valid range: 0–255 — Number of seconds to wait <p><maxdist> (Requested accuracy of fix)</p> <ul style="list-style-type: none"> • Entered in decimal format • Valid range: <ul style="list-style-type: none"> ▪ 0–4294967279 meters ▪ 4294967280 — No preference <p><fixrate> (Time to wait between fixes)</p> <ul style="list-style-type: none"> • Valid range: 1–65535 seconds

Table 7-2: GNSS command details (Continued)

Command	Description
!GPSCLRASSIST	<p>Clear specific GPS assistance data</p> <p>Clear one or more types of assistance data from the modem. This forces a cold start for GPS acquisition the next time a session starts.</p> <p>The command is only available when there is no active GPS session — the GPS receiver is off and no position fix is being calculated.</p> <p>This command is equivalent to !GPSOLDSTART when all parameters (except <alm>) are set to '1'.</p> <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: !GPSCLRASSIST=<eph>, <alm>, <pos>, <time>, <iono> Response: OK or Command ignored OK Purpose: Clear each assistance data type that is flagged as '1'. ▪ Query List: !GPSCLRASSIST=? Purpose: Return the expected command format and supported values. <p>Parameters:</p> <p><eph> (Ephemeris assistance data)</p> <ul style="list-style-type: none"> • 0 — Ignore (Do not clear the ephemeris assistance data) • 1 — Clear this assistance data type — Clears GPS, GLONASS, and SBAS ephemeris assistance data. <p><alm> (Almanac assistance data)</p> <ul style="list-style-type: none"> • 0 — Ignore (Do not clear the almanac assistance data) • 1 — Clear this assistance data type — Clears GPS, GLONASS, and SBAS almanac assistance data. <p><pos> (Position assistance data)</p> <ul style="list-style-type: none"> • 0 — Ignore (Do not clear the position assistance data) • 1 — Clear this assistance data type <p><time> (Time reference)</p> <ul style="list-style-type: none"> • 0 — Ignore (Do not clear the time reference) • 1 — Clear the time reference <p><iono> (Ionosphere assistance data)</p> <ul style="list-style-type: none"> • 0 — Ignore (Do not clear the ionosphere assistance data) • 1 — Clear this assistance data type

Table 7-2: GNSS command details (Continued)

Command	Description
!GPSCOLDSTART	<p>Clear all GNSS assistance data</p> <p>Clear GNSS assistance details from the modem and put the modem into a coldstart state. Data cleared includes Ephemeris, Previous Position, Ionosphere, and GPS time — almanac data is not cleared. This forces a cold start for GPS acquisition the next time a session starts.</p> <p>The command is only available when there is no active GPS session — the GPS receiver is off and no position fix is being calculated.</p> <p>Requirements:</p> <ul style="list-style-type: none"> Before using this command, end all active GNSS sessions using AT!GPSEND=0,255 <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> Execution: AT!GPSCOLDSTART Response: OK Purpose: Clear the modem’s GPS details <p>Parameters:</p> <p>None</p>
!GPSEND	<p>End an active session</p> <p>End an active position fix session.</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> Execution: AT!GPSEND=<sessType>[, <sessionID>] Response: ERRCODE = <value> OK <i>or</i> OK Purpose: End the current session. <p>Parameters:</p> <p><sessType> (Type of session to end)</p> <ul style="list-style-type: none"> 0 — Position fix session <p><sessionID> (ID of the session to end)</p> <ul style="list-style-type: none"> 255 — End all sessions 0–254 — Reserved <p><value> (Error code returned when command fails for any reason)</p> <ul style="list-style-type: none"> See Table 7-3 on page 94 for a list of possible error codes. N/A — Not available

Table 7-2: GNSS command details (Continued)

Command	Description
!GPSFIX	<p>Initiate GPS position fix</p> <p>Initiate a GPS position fix.</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!GPSFIX=<fixType>, <maxTime>, <maxDist> Response: Fix initiated OK <li style="padding-left: 20px;"><i>or</i> ERROR CODE = <value> OK Purpose: Initiate a time-limited position fix with a specified accuracy. ▪ Query List: AT!GPSFIX=? Purpose: Return supported <fixType>, <maxTime>, and <maxDist> values. <p>Parameters:</p> <p><fixType> (Type of fix to establish)</p> <ul style="list-style-type: none"> • 1 — Standalone (not supported by a mobile station) • 2 — MS-based only • 3 — MS-assisted only <p><maxTime> (Maximum time to wait for a position fix)</p> <ul style="list-style-type: none"> • Valid range: 0–255 seconds <p><maxDist> (Requested accuracy of fix)</p> <ul style="list-style-type: none"> • Entered in decimal format • Valid range: <ul style="list-style-type: none"> ▪ 0–4294967279 meters ▪ 4294967280 — No preference <p><value> (Error code returned when command fails for any reason)</p> <ul style="list-style-type: none"> • See Table 7-3 on page 94 for a list of possible error codes. • N/A — Not available <p>Example(s):</p> <p>AT!GPSFIX=1, 15, 10 requests a standalone position fix to 10 meters accuracy. The request will fail (timeout) if the modem cannot determine a position fix within 15 seconds.</p> <p>Related commands:</p> <ul style="list-style-type: none"> ▪ !GPSSTATUS (page 90)—Use this command while the tracking session is in progress. ▪ !GPSLOC (page 84)—Use this command after the session completes to obtain the result.

Table 7-2: GNSS command details (Continued)

Command	Description
!GPSLBSAPN	<p>Set GPS LBS APNs</p> <p>Set the GPS LBS APNs to be used for various RATs (Radio Access Technologies).</p> <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution (Add): AT!GPSLBSAPN=<operation>,<ratmask>,<IType>,<APN> Execution (Delete one): AT!GPSLBSAPN=<operation>,<ratmask> Execution (Delete all): AT!GPSLBSAPN=<operation> Response: OK or ERROR Purpose: Set the APN to be used for the specified <ratmask>, or delete the APN for a single <ratmask> or all RATs. ▪ Query: AT!GPSLBSAPN? Response: <ratmask>, <IType>, <APN> <ratmask>, <IType>, <APN> ... OK or OK (if no ID has been set) Purpose: Display the APNs currently assigned for each RAT. ▪ Query List: AT!GPSLBSAPN=? Purpose: Display valid parameter options. <p>Parameters:</p> <p><operation> (Add or delete APNs)</p> <ul style="list-style-type: none"> • 1 — Add an APN for a specific <ratmask> and <IType>. Note: All parameters are required. <hr/> <p><i>Note: To change an APN that has been set for a RAT, you must first delete the current APN, then add the new APN.</i></p> <hr/> <ul style="list-style-type: none"> • 2 — Delete the APN for a specific <ratmask> Note: Only <ratmask> is required. • 3 — Delete all APNs Note: No other parameters are required. <p><ratmask> (Radio access technology)</p> <ul style="list-style-type: none"> • Valid values (values shown are in hexadecimal format): <ul style="list-style-type: none"> ▪ 01 — CDMA ▪ 02 — HDR ▪ 04 — GSM ▪ 08 — WCDMA ▪ 10 — LTE <p>(Continued on next page)</p>

Table 7-2: GNSS command details (Continued)

Command	Description
!GPSLBSAPN (continued)	<p>Set GPS LBS APNs (continued)</p> <p><IPtype> (Internet Protocol version)</p> <ul style="list-style-type: none"> • Character string, entered without quotation marks • Valid values: <ul style="list-style-type: none"> ▪ IPV4 ▪ IPV6 ▪ IPV4V6 <p><APN> (Access Point Name)</p> <ul style="list-style-type: none"> • Character string, entered with quotation marks • Examples: "mycompany.mnc987.mcc123.gprs", "ourinternet"

Table 7-2: GNSS command details (Continued)

Command	Description
!GPSLOC	<p>Return last known location of the modem</p> <p>Return the details obtained during the most recent position location session, if available.</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Query: AT!GPSLOC? Response: Unknown (<i>No information is available</i>) OK <li style="padding-left: 20px;"><i>or</i> Not Available (<i>No information is available</i>) OK <li style="padding-left: 20px;"><i>or</i> Lat: <latitude> Lon: <longitude> Time: <time> LocUncAngle: <luAngle> LocUncA: <luA> LocUncP: <luP> HEPE: <hepe> <fixType> Altitude: <altitude> LocUncVe: <luV> Heading: <heading> VelHoriz: <vH> VelVert: <vV> OK (<i>Altitude and heading only appear if data was collected as part of the most recent fix.</i>) <p>Purpose: Return last position location details.</p> <p>Parameters:</p> <p><latitude> (Latitude at last position fix)</p> <ul style="list-style-type: none"> ▪ Example: "49 Deg 10 Min 21.49 Sec N (0x008BDE6C)" <p><longitude> (Longitude at last position fix)</p> <ul style="list-style-type: none"> ▪ Example: "123 Deg 4 Min 14.76 Sec W (0xFEA1EE9A)" <p><time> (Time at which last position fix was taken)</p> <ul style="list-style-type: none"> ▪ Example: "2009 01 30 4 20:27:18 (GPS)" <p><luAngle> (Location uncertainty angle of returned position)</p> <ul style="list-style-type: none"> ▪ Example: "11.2 deg" <p><luA> (Standard deviation of axis along <luAngle>)</p> <ul style="list-style-type: none"> ▪ Example: "6.0 m" <p><luP> (Standard deviation of axis perpendicular to <luAngle>)</p> <ul style="list-style-type: none"> ▪ Example: "6.0 m" <p><hepe> (Horizontal Estimated Positional Error)</p> <ul style="list-style-type: none"> ▪ Example: "8.485 m" <p><fixType> (2D or 3D fix)</p> <ul style="list-style-type: none"> ▪ Example: "2D Fix" or "3D Fix" <p><altitude> (Altitude in meters at which last position fix was taken)</p> <ul style="list-style-type: none"> ▪ Only present if <fixType> is 3D ▪ Example: "-1 m" <p><luV> (Vertical uncertainty in meters)</p> <ul style="list-style-type: none"> ▪ Only present if <fixType> is 3D ▪ Example: "3.0 m" <p>(Continued on next page)</p>

Table 7-2: GNSS command details (Continued)

Command	Description
!GPSLOC (continued)	<p>Return last known location of the modem (continued)</p> <p><heading> (Direction of MS)</p> <ul style="list-style-type: none"> • Example: "0.0 deg" <p><vH> (Horizontal velocity)</p> <ul style="list-style-type: none"> • Example: "0.0 m/s" <p><vV> (Vertical velocity)</p> <ul style="list-style-type: none"> • Example: "0.0 m/s"
!GPSMOMETHOD	<p>Set/report GPS MO method</p> <p>Set or report the GPS MO method (session type) that a mobile-originated GPS session should use (Control plane or User plane).</p> <p>Password required: Yes Reset required to apply changes: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!GPSMOMETHOD=<MO_method> Response: OK or ERROR Purpose: Indicate the MO method to use. ▪ Query: AT!GPSMOMETHOD? Response: <MO_method> OK Purpose: Return the current <MO_method> setting. <p>Parameters:</p> <p><MO_method> (MO method)</p> <ul style="list-style-type: none"> • 0 — CP (Control Plane) • 1 — UP (User Plane)

Table 7-2: GNSS command details (Continued)

Command	Description
!GPSNMEACONFIG	<p>Enable and set NMEA data output rate</p> <p>Enable or disable NMEA data output, and set the output rate for use with !GPSTRACK.</p> <p>Requirements:</p> <ul style="list-style-type: none"> NMEA streaming must be enabled using !GPSNMEA before this command will work. <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> Execution: !GPSNMEACONFIG=<enable>[,<outputRate>] Response: OK or ERROR Purpose: Enable or disable NMEA output and set rate. Query: !GPSNMEACONFIG? Response: Enabled: <enable> Output Rate: <outputRate> OK Purpose: Return the current <timeout> period. Query List: !GPSNMEACONFIG=? Purpose: Return valid parameter values. <p>Parameters:</p> <p><enable> (Enable/disable NMEA data output)</p> <ul style="list-style-type: none"> 0 — Disable. (Note: <outputRate> is ignored) 1 — Enable. (Note: <outputRate> is required) <p><outputRate> (NMEA data output rate—time between outputs)</p> <ul style="list-style-type: none"> Valid range: 1–255 seconds

Table 7-2: GNSS command details (Continued)

Command	Description
!GPSNMEASENTENCE	<p>Set/report NMEA sentence type</p> <p>Set or report the current GPS NMEA sentence types.</p> <p>Requirements:</p> <ul style="list-style-type: none"> NMEA streaming must be enabled using !GPSNMEA before this command will work. <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> Execution: !GPSNMEASENTENCE=<nmea type> Response: OK or ERROR Purpose: Enable or disable NMEA sentence types. Query: !GPSNMEASENTENCE? Response: !GPSNMEASENTENCE: <nmea type> OK Purpose: Indicate the currently enabled GPS NMEA sentence types. Query List: !GPSNMEASENTENCE=? Response: !GPSNMEASENTENCE: (00-1FFFFFF) OK Purpose: Indicates Execution format. See parameter description below for details of supported values. <p>Parameters:</p> <p><nmea type> (NMEA sentence types)</p> <ul style="list-style-type: none"> 2-byte hex format mask (Note: In the execution format, do not include '0x' before the mask value) Each bit: 0 — Disabled; 1 — Enabled Bit 0: GPGGGA (GPS fix data) Bit 1: GPRMC (GPS recommended minimum data) Bit 2: GPGLSV (GPS satellites in view) Bit 3: GPGLSA (GPS overall satellite data) Bit 4: GPVTG (GPS vector track and speed over the ground) Bit 5: Reserved Bit 6: GLGLSV (GLONASS satellites in view) Bit 7: GLGLSA (GLONASS overall satellite data) Bit 8: GNGNS (Time, position, and fix related data for GLONASS receiver) Bit 9: GARMC (Galileo recommended minimum data) Bit 10: GAGSV (Galileo satellites in view) Bit 11: GAGSA (Galileo overall satellite data) Bit 12: GAVTG (Galileo Vector track and speed over the ground) Bit 13: PSTIS (GPS session start indication) <p>(Continued on next page)</p>

Table 7-2: GNSS command details (Continued)

Command	Description
<p>!GPSNMEASENTENCE (continued)</p>	<p>Set/report NMEA sentence type (continued)</p> <ul style="list-style-type: none"> • Bit 14: ExGSV (Extended GSV). This option modifies the output format of the GPGSV sentence to display azimuth and elevation as float values. If this bit is not set, the values appear in decimal format. • Bit 15: GAGGA (Galileo time, position, and fix related data) • Bit 16: PQGSA (QZSS GSA) • Bit 17: PQGSV (QZSS GSV) • Bit 18: GAGNS (Galileo fix data) • Bit 19: GPDTM (GPS datum reference information) • Bit 20: Proprietary sentences for debugging
<p>!GPSPORTID</p>	<p>Set/report port ID to use over TCP/IP</p> <p>Set or report the port ID of the SUPL server to use when using TCP/IP as the transport mechanism for SUPL. The command can also be used when the FQDN is auto-generated from the IMSI.</p> <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: !GPSPORTID=<portid> Response: OK or ERROR Purpose: Queue the request to set the port ID. ▪ Query: !GPSPORTID? Response: <portid> OK Purpose: Return the port ID currently being used <p>Parameters:</p> <p><port ID> (Port ID to use over TCP/IP)</p> <ul style="list-style-type: none"> • Valid range: 0–65535 <p>Related commands</p> <ul style="list-style-type: none"> • !GPSSUPLURL (p.91)—Set/return SUPL server URL used for TCP/IP

Table 7-2: GNSS command details (Continued)

Command	Description
!GPSSATINFO	<p>Request satellite information</p> <p>Return the following information for up to twelve satellites in view (including those used in the latest position fix): satellite vehicle number (SV), elevation (ELEV), azimuth (AZI), and signal to noise ratio (SNR).</p> <p>The information returned is valid regardless of the current fix mode or whether the PDE or the modem performs the fix calculations.</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Query: AT!GPSSATINFO? Response: NO SAT INFO OK or Satellites in view: <numSats> (Timestamp of sat. info) * SV: <SV 1> ELEV:<ELEV 1> AZI:<AZI 1> SNR:<SNR 1> ... * SV: <SV n> ELEV:<ELEV n> AZI:<AZI n> SNR:<SNR n> OK <p>Purpose: Return the number of satellites in view (including those used in the latest position fix) and details for each satellite (or return an error message).</p> <hr/> <p><i>Note: An asterisk (*) at the beginning of a line indicates the satellite was used in the fix location calculation.</i></p> <hr/> <p>Parameters:</p> <p><numSats> (Number of satellites in view)</p> <ul style="list-style-type: none"> • Valid range: 1–12 <p><SV n> (Satellite vehicle number for the nth satellite in the list)</p> <ul style="list-style-type: none"> • Valid ranges: <ul style="list-style-type: none"> ▪ 1–32 (GPS) ▪ 65–96 (GLONASS) ▪ 193–197 (QZS) ▪ 201–237 (Beidou) ▪ 301–336 (Galileo) <p><ELEV n> (Satellite elevation relative to modem location, in degrees)</p> <ul style="list-style-type: none"> • Valid range: 0–90 <p><AZI n> (Satellite azimuth relative to modem location, in degrees)</p> <ul style="list-style-type: none"> • Valid range: 0–360 <p><SNR n> (Signal to noise ratio, in dB)</p> <ul style="list-style-type: none"> • Valid range: 0–99

Table 7-2: GNSS command details (Continued)

Command	Description
!GPSSTATUS	<p>Request current status of a position fix session</p> <p>Return the current status of a position fix session.</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Query: AT!GPSSTATUS? Response: <year> <month> <day> <day of week> <time of day> Last Fix Status = <status> <year> <month> <day> <day of week> <time of day> Fix Session Status = <status> Purpose: Return timestamps and status of a position fix session. <p>Parameters (Timestamp):</p> <p><year></p> <ul style="list-style-type: none"> • Example: "2007" <p><month></p> <ul style="list-style-type: none"> • 01–12 (Jan–Dec) <p><day></p> <ul style="list-style-type: none"> • 01–31 <p><day of week></p> <ul style="list-style-type: none"> • 0–6 (0=Monday) <p><time of day></p> <ul style="list-style-type: none"> • 24-hour clock format • Example: "13:25:48" <p>Parameters (Status):</p> <p><status> (Session status)</p> <ul style="list-style-type: none"> • "NONE": No session of this type has occurred since the modem powered up. <ul style="list-style-type: none"> ▪ The timestamp is the current time. • "ACTIVE": A session of this type is currently active. <ul style="list-style-type: none"> ▪ The timestamp is the time when the session entered this state. • "SUCCESS": The most recent session of this type succeeded. <ul style="list-style-type: none"> ▪ The timestamp is the time when the previous session completed successfully. • "FAIL": The most recent session of this type failed. <ul style="list-style-type: none"> ▪ The timestamp is the time when the previous session failed. ▪ An error code is displayed with the "FAIL" string. See Table 7-3 on page 94 for a list of error codes. <p>Example(s):</p> <p>AT!GPSSTATUS? returns:</p> <pre>2007 01 06 6 00:25:01 Last Fix Status = SUCCESS 2007 01 06 6 00:25:02 Fix Session Status = ACTIVE</pre>

Table 7-2: GNSS command details (Continued)

Command	Description
!GPSSUPLURL	<p>Set/report SUPL server URL</p> <p>Set or return the URL of the SUPL server to be used when TCP/IP is used as the transport mechanism for location processing. Use !GPSPORTID to set the port ID.</p> <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!GPSSUPLURL="<suplURL>" Response: OK or ERROR Purpose: Identify the SUPL server URL. ▪ Query: AT!GPSSUPLURL? Response: <suplURL> OK Purpose: Return the SUPL server's URL.. ▪ Query List: AT!GPSSUPLURL=? Purpose: Return the execution command format. <p>Parameters:</p> <p><suplURL> (SUPL server URL)</p> <ul style="list-style-type: none"> • Must be a fully qualified domain name (FQDN) or address • Examples: "supl.url.net", "123.123.123.123" • The <suplURL> is not checked for correctness—if the string is invalid, the modem will not be able to perform MS-assisted GPS fixes. <p>Example(s):</p> <p>AT!GPSSUPLURL="supl.url.net" AT!GPSSUPLURL="123.123.123.123"</p>

Table 7-2: GNSS command details (Continued)

Command	Description
!GPSSUPLVER	<p>Set/report SUPL server version</p> <p>Set or return the version of the SUPL server.</p> <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!GPSSUPLURL=<supl ver>" Response: OK or ERROR Purpose: Identify the SUPL server version. ▪ Query: AT!GPSSUPLVER? Response: <supl ver> OK Purpose: Return the SUPL server's version. ▪ Query List: AT!GPSSUPLVER=? Purpose: Return the execution command format. <p>Parameters:</p> <p><supl ver> (SUPL server version)</p> <ul style="list-style-type: none"> • 1—SUPL version 1 • 2—SUPL version 2

Table 7-2: GNSS command details (Continued)

Command	Description
!GPSTRACK	<p>Initiate local tracking (multiple fix) session</p> <p>Initiate a local tracking session comprising a specific number of position fixes taken at regular time intervals.</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!GPSTRACK = <fixType>, <maxTime>, <maxDist>, <fixCount>, <fixRate> Response: Fix initiated OK or ERROR CODE = <value> OK Purpose: Initiate a series of time-limited position fixes. ▪ Query List: AT!GPSTRACK=? Purpose: Return supported <fixType>, <maxTime>, <maxDist>, <fixCount>, and <fixRate> values. <p>Parameters:</p> <p><fixType> (Type of fix to establish)</p> <ul style="list-style-type: none"> • 1 — Standalone (not supported by a mobile station) • 2 — MS-based only • 3 — MS-assisted only <p><maxTime> (Maximum time to wait for satellite information)</p> <ul style="list-style-type: none"> • Valid range: 0–255 seconds <p><maxDist> (Requested accuracy of fix)</p> <ul style="list-style-type: none"> • Entered in decimal format • Valid range: <ul style="list-style-type: none"> ▪ 0–4294967279 meters ▪ 4294967280 — No preference <p><fixCount> (Number of position fixes requested)</p> <ul style="list-style-type: none"> • Valid range: 1–1000 (1000 — Take a continuous series of position fixes) <p><fixrate> (Amount of time to wait between fix attempts)</p> <ul style="list-style-type: none"> • Valid range: 0–1799999 seconds <p>Failure conditions:</p> <p>The request fails if the tracking session fails to initiate.</p> <p>If the request fails, the message ERROR CODE = <value> is returned. See Table 7-3 on page 94 for a list of error codes.</p> <hr/> <p><i>Note: The 'time to first fix' may require more time than subsequent fixes, if almanac, ephemeris, or location data needs to be updated. (Almanac data is valid for 3–4 days, ephemeris for 30–120 minutes, and location data for 4 minutes). To avoid a timeout error (time spent > <maxtime>), your application could precede the !GPSTRACK call with a single position fix (AGPSFIX) with a greater <maxTime> value.</i></p> <hr/> <p>(Continued on next page)</p>

Table 7-2: GNSS command details (Continued)

Command	Description
!GPSTRACK (continued)	<p>Initiate local tracking (multiple fix) session (continued)</p> <p>Example(s): AT!GPSTRACK=1, 15, 10, 20, 60 requests a series of 20 standalone position fixes to 10 meters accuracy—fixes are taken every 60 seconds. One of the following responses will be received:</p> <ul style="list-style-type: none"> • “OK” if the request is successful, or • “ERROR CODE = <value>” if the request fails for any reason. See Table 7-3 on page 94 for a list of error codes. <p>Related commands:</p> <ul style="list-style-type: none"> ▪ !GPSSTATUS—Use this command while the tracking session is in progress. ▪ !GPSLOC—Use this command after the session completes to obtain the result.
+WANT	<p>Enable/disable GNSS antenna power</p> <p>Enable or disable GNSS antenna power (3.3V).</p> <p>Password required: No Persistent across power cycles: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT+WANT=<enable> Response: OK Purpose: Enable or disable the GNSS antenna power (3.3V). ▪ Query List: AT+WANT=? Purpose: Display valid execution format and parameter values. <p>Parameters: <enable> (Enable/disable GNSS antenna power)</p> <ul style="list-style-type: none"> • 0 — Disable • 1 — Enable

7.3.1 Error Codes

[Table 7-3](#) describes error codes that can be returned by **!GPSEND** ([page 80](#)), **!GPSSTATUS** ([page 90](#)), and **!GPSTRACK** ([page 93](#)).

[Table 7-4](#) on page 96 describes error codes that can be returned by **!GPSFIX** ([page 81](#))

Table 7-3: AT command error codes (!GPSEND, !GPSSTATUS, !GPSTRACK)

Error code	Description
0	Phone is offline
1	No service
2	No connection with PDE (Position Determining Entity)
3	No data available

Table 7-3: AT command error codes (!GPSEND, !GPSSTATUS, !GPSTRACK) (Continued)

Error code	Description
4	Session Manager is busy
5	Reserved
6	Phone is GPS-locked
7	Connection failure with PDE
8	Session ended because of error condition
9	User ended the session
10	End key pressed from UI
11	Network session was ended
12	Timeout (for GPS search)
13	Conflicting request for session and level of privacy
14	Could not connect to the network
15	Error in fix
16	Reject from PDE
17	GPS is disabled
18	Ending session due to E911 call
19	Server error
20	Reserved
21	Reserved
22	Unknown system error
23	Unsupported service
24	Subscription violation
25	Desired fix method failed
26	Reserved
27	No fix reported because no Tx confirmation was received
28	Network indicated normal end of session
29	No error specified by the network
30	No resources left on the network
31	Position server not available
32	Network reported an unsupported version of protocol

Table 7-4: AT command error codes (!GPSFIX)

Error code	Description
0	No error
1	Invalid client ID
2	Bad service parameter
3	Bad session type parameter
4	Incorrect privacy parameter
5	Incorrect download parameter
6	Incorrect network access parameter
7	Incorrect operation parameter
8	Incorrect number of fixes parameter
9	Incorrect server information parameter
10	Error in timeout parameter
11	Error in QOS accuracy threshold parameter
12	No active session to terminate
13	Session is active
14	Session is busy
15	Phone is offline
16	Phone is CDMA locked
17	GPS is locked
18	Command is invalid in current state
19	Connection failure with PDE
20	PDSM command buffer unavailable to queue command
21	Search communication problem
22	Temporary problem reporting position determination results
23	Error mode not supported
24	Periodic NI in progress
25	Unknown error
26	Unknown error

8: SIM Commands

- [Introduction](#)
- [Command Summary](#)
- [Command Reference](#)

8.1 Introduction

This chapter describes commands used to communicate with an installed (U)SIM.

8.2 Command Summary

Table 8-1 lists the commands described in this chapter:

Table 8-1: SIM command passwords

Command	Description	Page
!UIMS	Select active SIM interface	97

8.3 Command Reference

Table 8-2: SIM command details

Command	Description
!UIMS	<p>Select active SIM interface</p> <p>On a module that supports multiple SIM interfaces, select the active SIM interface. To enable/disable UIM2 slot support, use AT!CUSTOM="UIM2ENABLE". See page 29 for option values.</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!UIMS=<uim_slot> Response: OK Purpose: Configure the module to use the selected SIM interface. ▪ Query: AT!UIMS? Response: !UIMS: <uim_slot> OK Purpose: Display the currently selected interface. ▪ Query List: AT!UIMS=? Purpose: Return the command format and the supported parameter values. <p>Parameters:</p> <p><uim> (SIM interface):</p> <ul style="list-style-type: none"> ▪ 0 — UICC1 — External UIM interface #1 ▪ 1 — UICC2 — External UIM interface #2

9: OMA-DM Commands

9.1 Introduction

This chapter describes commands used to configure DM (Device Management) accounts, sessions, and host–device–server interactions.

9.2 Command Summary

The table below lists the commands described in this chapter.

Table 9-1: OMA-DM commands

Command	Description	Page
!HOSTDEVINFO	Configure host device details	99
!IMSTESTMODE	Enable/disable IMS test mode	100
!OSINFO	Configure host device operating system information	101

9.3 Command Reference

Table 9-2: OMA-DM command details

Command	Description
!HOSTDEVINFO	<p>Configure host device details</p> <p>Configure the host device details that will be reported by OMA DM for AT&T devices, to comply with AT&T <CDR-DVM-4532> requirement. To configure host device operating system information, see !OSINFO on page 101.</p> <hr/> <p><i>Note: In the Execution format, if a parameter is not entered then the value on the device does not change.</i></p> <hr/> <p>Password required: Yes—Execution formation only</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: ATIHOSTDEVINFO="<hostman>","<hostmod>","<hostswv>","<hostplasmaid>"]] Response: OK or ERROR Purpose: Set some or all host device detail parameters. ▪ Query: ATIHOSTDEVINFO? Response: HostMan: <hostman> HostMod: <hostmod> HostSwV: <hostswv> HostPlasmaID: <hostplasmaid> OK Purpose: Display current host device details. ▪ Query List: ATIHOSTDEVINFO=? Purpose: Display the execution command format and parameter values. <p>Parameters:</p> <p><hostman> (Host device manufacturer's name)</p> <ul style="list-style-type: none"> ▪ 256 characters maximum <p><hostmod> (Host device model name)</p> <ul style="list-style-type: none"> ▪ 256 characters maximum <p><hostswv> (Host software version)</p> <ul style="list-style-type: none"> ▪ 256 characters maximum <p><hostplasmaid> (Host Plasma ID)</p> <ul style="list-style-type: none"> ▪ 256 characters maximum <p>Example(s):</p> <ul style="list-style-type: none"> ▪ ATIHOSTDEVINFO="Manufacturer","1.0" This sets the <hostman> and <hostswv> values. The values for <hostmod> and <hostplasmaid> do not change. ▪ ATIHOSTDEVINFO="Manufacturer" This sets the <hostman> value. The values for all other parameters do not change.

Table 9-2: OMA-DM command details (Continued)

Command	Description
!IMSTESTMODE	<p>Enable/disable IMS test mode</p> <p>Enable/disable IMS (IP Multimedia Subsystem) test mode.</p> <p>If IMS test mode is enabled:</p> <ul style="list-style-type: none"> ▪ IMS registration attempts will not occur ▪ SMS over IMS is not supported <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: ATIIMSTESTMODE=<mode> Response: OK Purpose: Enable/disable IMS test mode. ▪ Query: ATIIMSTESTMODE? Response: IMS Test Mode Enabled or IMS Test Mode Disabled Purpose: Return the current state of IMS Test Mode. <p>Parameters:</p> <p><mode> (IMS Test Mode state)</p> <ul style="list-style-type: none"> • 0 — Disable • 1 — Enable

Table 9-2: OMA-DM command details (Continued)

Command	Description
!OSINFO	<p>Configure host device operating system information</p> <p>Configure the host device operating system name and version that will be reported by OMA DM for AT&T devices, to comply with AT&T <CDR-DVM-4533> requirement. To configure host device details, see !HOSTDEVINFO on page 99.</p> <hr/> <p><i>Note: In the Execution format, if a parameter is not entered then the value on the device does not change.</i></p> <hr/> <p>Password required: Yes—Execution format only</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!OSINFO=<osname>[, <osversion>] Response: OK or ERROR Purpose: Set host device operating system information parameters. ▪ Query: AT!OSINFO? Response: OSName: <osname> OSVersion: <osversion> OK Purpose: Display current host device operating system information. ▪ Query List: AT!OSINFO=? Purpose: Display the execution command format and parameter values. <p>Parameters:</p> <p><osname> (Host device operating system name)</p> <ul style="list-style-type: none"> • 256 characters maximum <p><osversion> (Host device operating system version)</p> <ul style="list-style-type: none"> • 256 characters maximum <p>Example(s):</p> <ul style="list-style-type: none"> ▪ AT!OSINFO="An OS Name",1.0" This sets both parameters. ▪ AT!OSINFO="1.0" This sets the <osversion> value. The value for the <osname> does not change.

10: SAR Backoff and Thermal Control Commands

10.1 Introduction

This chapter describes:

- SAR-related commands (Specific Absorption Rate)— SAR commands are used to meet regulatory requirements for the OEM host device by managing the modem's SAR backoff state. OEMs should carefully evaluate their use of these commands and their impact on device operation.

Note: Operators may require OEMs to disclose SAR settings and theory of operation for applicable certifications.

- Thermal mitigation-related commands— These commands may affect the host device's performance. OEMs should carefully evaluate their use of these commands to ensure that the device meets performance expectations.

10.2 Command Summary

The table below lists the commands described in this chapter.

Table 10-1: SAR backoff and thermal control commands

Command	Description	Page
!MAXPWR	Set/report maximum Tx power	103
!SARBACKOFF	Set/report offset from maximum Tx power	104
!SARINTGPIOMODE	Set/report default pull mode for SAR interrupt GPIOs	105
!SARSTATE	Set/report SAR backoff state	105
!SARSTATEDFLT	Set/report default SAR backoff state	106

10.3 Command Reference

Table 10-2: Thermal mitigation command details

Command	Description
!MAXPWR	<p>Set/report maximum Tx power</p> <p>Set or report the maximum Tx power for a specific band.</p> <hr/> <p>Caution: <i>Any adjustments of Tx power may impact regulatory certification of the module in the host platform. The OEM is responsible for ensuring that the final module configuration in the host platform meets all regulatory requirements.</i></p> <hr/> <p><i>Note: Increasing the Tx power affects the module's current consumption and thermal performance.</i></p> <hr/> <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution (WCDMA/LTE): ATIMAXPWR=<band>,<tech>,<max_tx_pwr> Response: OK Purpose: Set the maximum Tx power for the specified band/technology combination. ▪ Query: ATIMAXPWR?<band>,<tech> Response: <maxpwr> dBm OK Purpose: Indicate the maximum Tx power for the specified band/technology combination. ▪ Query list: ATIMAXPWR=? Purpose: Display valid execution format and parameter values. <p>Parameters:</p> <p><band> (RF band)</p> <ul style="list-style-type: none"> • 3GPP band number. For a full listing of 3GPP band numbers, see Table 14-2 on page 130. • Band support is product specific—see the device's Product Specification or Product Technical Specification document for details. • Valid range: 0–93 <p><tech> (Network technology)</p> <ul style="list-style-type: none"> • 0 — WCDMA • 2 — LTE <p><maxpwr> (Maximum Tx power in dB)</p> <ul style="list-style-type: none"> • Valid range: 20.0–24.5

Table 10-2: Thermal mitigation command details (Continued)

Command	Description
!SARBACKOFF	<p>Set/report offset from maximum Tx power</p> <p>Set or report the offset from maximum Tx power limit for a specific band/technology/backoff state combination. Changes take place after the next modem reset.</p> <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: ATISARBACKOFF=<Technology>,<Band>,<State>,<Backoff offset> Response: OK Purpose: Set the maximum Tx power for the tech/band/state combination. ▪ Query: ATISARBACKOFF?<Technology>,<Band>,<State> Response: SAR Backoff: <Backoff offset> dB SAR Limit: <sarlimit> dBm <p style="margin-left: 40px;">OK</p> <ul style="list-style-type: none"> ▪ Purpose: Display the offset from maximum Tx power for the tech/band/state combination. ▪ Query list: ATISARBACKOFF=?<Technology> Purpose: Display valid execution and query formats, and parameter values. <p>Parameters:</p> <p><Technology> (Network technology)</p> <ul style="list-style-type: none"> • 0—WCDMA • 2—LTE <p><Band> (RF band)</p> <ul style="list-style-type: none"> • 1–71 • Band support is device-dependent. See the device’s Product Technical Specification for details. <p><State> (SAR backoff state)</p> <ul style="list-style-type: none"> • 0—No backoff • 1–8—Backoff state 1 to 8 <p><Backoff offset> (Offset from max Tx power, in dBm)</p> <ul style="list-style-type: none"> • Valid values: use the Query List command to display valid values. • Value may be integer or decimal. (For example, 4 or 6.8) <p><sarlimit> (Absolute SAR limit, in dBm)</p> <ul style="list-style-type: none"> • 10–29

Table 10-2: Thermal mitigation command details (Continued)

Command	Description
!SARINTGPIOMODE	<p>Set/report default pull mode for SAR interrupt GPIOs</p> <p>Set or report the default pull mode (high/low) for SAR interrupt GPIOs. This setting applies to all SAR interrupt GPIOs.</p> <p>Password required: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!SARINTGPIOMODE=<mode> Response: OK Purpose: Set the default pull mode for all SAR interrupt GPIOs. ▪ Query: AT!SARINTGPIOMODE? Response: <mode> OK Purpose: Indicate the default pull mode. ▪ Query list: AT!SARINTGPIOMODE=? Purpose: Display valid execution format and parameter values. <p>Parameters:</p> <p><mode> (SAR GPIO interrupt pull mode default setting)</p> <ul style="list-style-type: none"> • 0 — Standard mode — Default pull is HIGH/DAL_GPIO_PULL_UP • 1 — Inverse mode — Default pull is LOW/DAL_GPIO_PULL_DOWN
!SARSTATE	<p>Set/report SAR backoff state</p> <p>Set or report the current SAR (Specific Absorption Rate) backoff state.</p> <hr/> <p><i>Note: This setting is not persistent. To change the default backoff state (persistent), use !SARSTATEDFLT.</i></p> <hr/> <p>Password required: No Persistent across power cycles: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!SARSTATE=<state> Response: OK Purpose: Temporarily set the SAR backoff state. ▪ Query: AT!SARSTATE? Response: !SARSTATE: <state> OK Purpose: Indicate the current SAR backoff state. ▪ Query list: AT!SARSTATE=? Purpose: Display valid execution format and parameter values. <p>Parameters:</p> <p><state> (SAR backoff state)</p> <ul style="list-style-type: none"> • 0 — No backoff • 1–8 — Backoff state 1 to 8

Table 10-2: Thermal mitigation command details (Continued)

Command	Description
<p>!SARSTATEDFLT</p>	<p>Set/report default SAR backoff state</p> <p>Set or report the default (persistent) SAR (Specific Absorption Rate) backoff state.</p> <hr/> <p><i>Note: This setting is persistent. To temporarily change the backoff state, use !SARSTATE.</i></p> <hr/> <p>Password required: No Persistent across power cycles: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!SARSTATEDFLT=<state> Response: OK Purpose: Set the default SAR backoff state. ▪ Query: AT!SARSTATEDFLT? Response: !SARSTATEDFLT: <state> OK Purpose: Indicate the default SAR backoff state. ▪ Query list: AT!SARSTATEDFLT=? Purpose: Display valid execution format and parameter values. <p>Parameters:</p> <p><state> (SAR backoff state)</p> <ul style="list-style-type: none"> • 0 — No backoff • 1–8 — Backoff state 1 to 8

11: AirVantage Commands

11.1 Introduction

This chapter describes AirVantage (AV) related commands.

11.2 Command Summary

Table 11-1 lists the commands described in this chapter.

Table 11-1: AirVantage commands

Command	Description	Page
+WDSC	Configure AirVantage Management Services	108
+WDSE	Display most recent AirVantage Management Services error	110
+WDSG	Display AirVantage Management Services status information	111
+WDSI	Activate / deactivate AirVantage Management Services unsolicited notifications	112
+WDSI (notification)	AirVantage Management Services events — Unsolicited notification	113
+WDSR	Reply to AirVantage server request	116
+WDSS	Configure / connect AirVantage Management Services session	117

11.3 Command Reference

Table 11-2: AirVantage Device Services command details

Command	Description
+WDSC	<p>Configure AirVantage Management Services</p> <p>Configure the following AirVantage Management Services parameters:</p> <ul style="list-style-type: none"> ▪ User agreement for connection, package download and package install ▪ Polling mode to make a connection to the AirVantage server ▪ Retry mode to attempt a new connection to the AirVantage server when the WWAN DATA service is temporarily out of order or when an http/coap error occurs <p>SIM card requirement: Not required Password required: No Persistent across power cycles: Yes (<State>, <Timer_1>, <Timer_n>)</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution (<Mode> = 0, 1, 2, 3, 5): AT+WDSC=<Mode>,<State> Response: OK Purpose: Enable or disable the selected <Mode>. ▪ Execution (<Mode> = 4): AT+WDSC=<Mode>,<Timer_1>[[,<Timer_2>]...[,<Timer_n>]] Response: OK Purpose: Set interval timers for successive connection attempts. ▪ Query: ATIWDSC? Response: +WDSC: 0,<State> +WDSC: 1,<State> +WDSC: 2,<State> +WDSC: 3,<State> +WDSC: 4,<Timer_1>[[,<Timer_2>]...[,<Timer_n>]] +WDSC: 5,<State> OK Purpose: Show the current <Mode> configurations. ▪ Query List: ATIWDSC=? Purpose: Display valid execution format and parameter values. <p>(Continued on next page)</p>

Table 11-2: AirVantage Device Services command details (Continued)

Command	Description
+WDSC	<p>Configure AirVantage Management Services (continued)</p> <p>Parameters:</p> <p><Mode> (Mode being configured)</p> <ul style="list-style-type: none"> • 0 — Reserved for future use • 1 — User agreement for package download. When enabled, the module returns an unsolicited notification to request an agreement before downloading any package. See +WDSI on page 112 for details. • 2 — User agreement for package install. When enabled, the module returns an unsolicited notification to request an agreement before installing any package. See +WDSI on page 112 for details. • 3 — Polling mode. When enabled (<State> > 0), the module waits for the number of minutes specified in <State>, then will initiate a connection to the AirVantage server based if the device is registered on the network. • 4 — Retry mode. If an error occurs during a connection to the AirVantage server (e.g. WWAN DATA establishment failed, http error code received), the module will initiate a new connection according to the defined timers. (Note: This is a persistent setting.) • 5 — User agreement for device reboot. When enabled, the module returns an unsolicited notification to request an agreement before rebooting the device. <p><State> (For <Mode> = 0, 1, 2, 5: Activation state of <Mode>)</p> <ul style="list-style-type: none"> • 0 — Disabled (Default value) • 1 — Enabled <p><State> (For <Mode> = 3: Activation state/timer of <Mode>)</p> <ul style="list-style-type: none"> • 0 — Disabled (Default value) • 1–525600 — Polling timer (in minutes) <p><Timer_1>..<Timer_n> (Connection attempt interval timers)</p> <ul style="list-style-type: none"> • The number of minutes to wait after connection attempt (n-1) before making connection attempt (n). (Note: There is a maximum of 8 connection attempts.) • <Timer_1>—Timer between the first failed connection and the next attempt. <ul style="list-style-type: none"> ▪ Valid range: 0–20160 (0—Retry mode is deactivated) ▪ Default value: 15 • <Timer_n>—Timer between the nth failed connection attempt and the (n+1)th connection (n≤8). <ul style="list-style-type: none"> ▪ Valid range: 1–20160 ▪ Default value: 15 <ul style="list-style-type: none"> ▪ <Timer_2> — 60 (Time to wait after second failed connection attempt.) ▪ <Timer_3> — 240 (Time to wait after third failed connection attempt.) ▪ <Timer_4> — 960 (Time to wait after fourth failed connection attempt.) ▪ <Timer_5> — 2880 (Time to wait after fifth failed connection attempt.) ▪ <Timer_6> — 10080 (Time to wait after sixth failed connection attempt.) ▪ <Timer_7> — 10080 (Time to wait after seventh failed connection attempt.) ▪ <Timer_8> not used <hr/> <p><i>Note: The <State>, <Timer_1>, and <Timer_n> parameters are stored in NV without sending the &W command. The &F command does not affect these values.</i></p>

Table 11-2: AirVantage Device Services command details (Continued)

Command	Description
<p>+WDSE</p>	<p>Display most recent AirVantage Management Services error</p> <p>Display the most recent HTTP(S) response received by the device for the package download.</p> <p>Requirements:</p> <ul style="list-style-type: none"> • AirVantage Management Services must be activated (See +WDSG on page 111 for details). • Session must be initiated using <code>AT+WDSS=1,1</code>. (See +WDSS on page 117 for details). <p>SIM card requirement: Not required</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT+WDSE Response: <code>[+WDSE: <HTTP_Status>]</code> OK <p style="text-align: center;"><i>or</i></p> <ul style="list-style-type: none"> ▪ <code>+CME ERROR: 3</code> <i>(If AirVantage Management services are not in the Activated state.)</i> <p>Purpose: Display most recent response. (If HTTP/HTTPS is not yet used, return only OK.)</p> <p>Parameters:</p> <p><HTTP_Status> (Standard HTTP status code)</p> <ul style="list-style-type: none"> • none — No response shown if HTTP/HTTPS has not yet been used. • Supported statuses: <ul style="list-style-type: none"> ▪ 1xx Informational: 100 (Continue)101 (Switching protocols) ▪ 2xx Success: 200 (OK)201 (Created) 202 (Accepted)203 (Non-authoritative information) 204 (No content)205 (Reset content) 206 (Partial content) ▪ 3xx Redirection: 300 (Multiple choices)301 (Moved permanently) 302 (Found)303 (See other) 304 (Not modified)305 (Use proxy) 307 (Temporary redirect) ▪ 4xx Client Error: 400 (Bad request)401 (Unauthorized) 402 (Payment required)403 (Forbidden) 404 (Not found)405 (Method not allowed) 406 (Not acceptable)407 (Proxy authentication required) 408 (Request time-out)409 (Conflict) 410 (Gone)411 (Length required) 412 (Precondition failed)413 (Request entity too large) 414 (Request URI too large)415 (Unsupported media type) 416 (Requested range not satisfiable)417 (Expectation failed) ▪ 5xx Server Error: 500 (Internal server error)501 (Not implemented) 502 (Bad gateway)503 (Service unavailable) 504 (Gateway time-out)505 (HTTP version not supported)

Table 11-2: AirVantage Device Services command details (Continued)

Command	Description
+WDSG	<p>Display AirVantage Management Services status information</p> <p>Display general AirVantage Management Services status details.</p> <p>SIM card requirement: Not required</p> <p>Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT+WDSG Response: +WDSG: <Status>, <Value> +WDSG: <Status>, <Value> OK Purpose: Returns the current <Value>s for <Status>=1 and <Status>=2. <p>Parameters:</p> <p><Status> (Information type to display)</p> <ul style="list-style-type: none"> • 0—AirVantage Management Services activation state <ul style="list-style-type: none"> ▪ For <Value>=2 and <Value>=3, connection parameters are automatically provisioned and no actions are required by the user. ▪ Device is activated (<Value>=3) when a dedicated APN (Access Point Name) is set manually or automatically in the first session. See +WDSS on page 117 for details. • 1—Session and package indication <p><Value> (Detail for the <Status>)</p> <ul style="list-style-type: none"> • For <Status>=0: <ul style="list-style-type: none"> ▪ 0—AirVantage Management Services prohibited. Management Services will never be activated. ▪ 1—AirVantage Management Services deactivated. Connection parameters to an AirVantage server must be provisioned. This is the default state when a device has never been activated (first use of device services on this device). ▪ 2—AirVantage Management Services must be provisioned. A bootstrap session is required. ▪ 3—AirVantage Management Services are activated. • For <Status>=1: <ul style="list-style-type: none"> ▪ 0—No session or package. ▪ 1—A session is under treatment. ▪ 2—A package is available on the server. ▪ 3—A package was downloaded and ready to install. ▪ Note: If a package is downloaded unsuccessfully, the <Value> is set to 0. If it downloads successfully, the <Value> is set to 3.

Table 11-2: AirVantage Device Services command details (Continued)

Command	Description
<p>+WDSI</p>	<p>Activate/deactivate AirVantage Management Services unsolicited notifications</p> <p>Activate/deactivate specific AirVantage Management Services unsolicited notifications.</p> <p>Requirements:</p> <ul style="list-style-type: none"> To receive unsolicited notifications, AirVantage Management Services must be activated (see +WDSG on page 111 for details). <p>SIM card requirement: Not required</p> <p>Password required: No</p> <p>Reset required to apply changes: No</p> <p>Persistent across power cycles: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> Execution: AT+WDSI=<Level> Response: OK Purpose: Activate/deactivate identifications as specified by <Level>. Query: AT+WDSI? Response: +WDSI: <Level>] OK Purpose: Indicate current state (activated/deactivated) of indications using the <Level> bitmask parameter. Query List: AT+WDSI=? Purpose: Display valid execution format and parameter values. <p>Parameters:</p> <p><Level> (Unsolicited AirVantage Management Services notifications bit mask)</p> <ul style="list-style-type: none"> Bit mask indicating which notifications to enable/disable entered as integer value Default: 0= No indications activated Bit value: <ul style="list-style-type: none"> 0 — Indication deactivated 1 — Indication activated Range: 0–8191. Add the values of each bit listed below. (See +WDSI on page 113 for <Event> details.) <ul style="list-style-type: none"> 1 (Bit 0)—Initialization end indication (<Event> = 0) 2 (Bit 1)—Server request for user agreement indication (<Event> = 1, 2, 3, 24) 4 (Bit 2)—Authentication indications (<Event> = 4, 5) 8 (Bit 3)—Session indication (<Event> = 6, 7, 8) 16 (Bit 4)—Package download indications (<Event> = 9, 10, 11) 32 (Bit 5)—Certified downloaded package indication (<Event> = 12, 13) 64 (Bit 6)—Update indications (<Event> = 14, 15, 16) 128 (Bit 7)—Fallback indication (<Event> = 17) 256 (Bit 8)—Download progress indication (<Event> = 18) 512 (Bit 9)—Memory preemption indication (<Event> = 19) 1024 (Bit 10)—User PIN request indication for bootstrap (<Event> = 20) 2048 (Bit 11)—Reserved 4096 (Bit 12)—Bootstrap event indication (<Event> = 23) <hr/> <p><i>Note: <Level> is stored in NV without sending the &W command. Default value can be restored using &F.</i></p>

Table 11-2: AirVantage Device Services command details (Continued)

Command	Description
+WDSI (notification)	<p>AirVantage Management Services events—Unsolicited notification</p> <p>Unsolicited notification received for various AirVantage Management Services events.</p> <p>Requirements:</p> <ul style="list-style-type: none"> To receive unsolicited notifications, AirVantage Management Services must be activated (see +WDSG on page 111 for details). <p>Notification format: +WDSI: <Event>[,<Data>]</p> <hr/> <p><i>Note: <Event> parameter descriptions below indicate when a <Data> parameter is included in the response.</i></p> <hr/> <p>Examples:</p> <ul style="list-style-type: none"> +WDSI: 9,1000 <i>Package will be downloaded, size is 1000 bytes</i> +WDSI: 18,1 <i>1% of package has been downloaded</i> +WDSI: 18, 100 <i>Entire package (100%) has been downloaded</i> +WDSI: 11,2 <i>Package download failue due to HTTP(S) error (see +WDSE on page 110 for error values)</i> <p>Parameters:</p> <p><Event> (AirVantage Management Services event)</p> <ul style="list-style-type: none"> 0—AirVantage Management Services are initialized and can be used. (Note: Management Services are initialized when the SIM PIN code is entered and a dedicated NAP is configured. See +WDSS on page 117 for details.) 1—AirVantage server requests that the device make a connection. The device requests a user agreement to allow the module to make the connection. The response can be sent using +WDSR (see +WDSR on page 116) and this indication can be returned by the device if the user has activated the user agreement for connection (see +WDSC on page 109 for details). 2—AirVantage server requests that the device make a package download. The device requests a user agreement to allow the module to make the download. The response can be sent using +WDSR (see +WDSR on page 116) and this indication can be returned by the device if the user has activated the user agreement for download (see +WDSC on page 109 for details). 3—Device has downloaded a package. The device requests a user agreement to install the downloaded package. The response can be sent using +WDSR (see +WDSR on page 116) and this indication can be returned by the device if the user has activated the user agreement for install (see +WDSC on page 109 for details). 4—Module starts authentication with the server. 5—Authentication with the server failed. 6—Authentication has succeeded and session with the server has started. 7—Session with the server failed. <p>(Continued on next page)</p>

Table 11-2: AirVantage Device Services command details (Continued)

Command	Description
+WDSI (notification)	<p>AirVantage Management Services events—Unsolicited notification (continued)</p> <ul style="list-style-type: none"> • 8—Session with the server is finished. • 9—Package is available on the server and can be downloaded by the module. A <Data> parameter is returned indicating the package size in kB. • 10—Package was successfully downloaded and stored in flash. • 11—One of the following issues happened during the package download: <ul style="list-style-type: none"> ▪ If the download did not start (a +WDSI <Event>=9 indication has not been received), there is not enough space in the device to download the package. ▪ If the download started (a +WDSI <Event>=9 indication has been received), a flash problem implies that the package has not been saved in the device. • 12—Downloaded package is certified to be sent by the AirVantage server. • 13—Downloaded package is not certified to be sent by the AirVantage server. • 14—Update will be launched. • 15—OTA update client has finished unsuccessfully. • 16—OTA update client has finished successfully. • 17—Reserved • 18—Download progress: <ul style="list-style-type: none"> ▪ No <Data> parameter—Download start ▪ <Data> parameter—Percentage progress • 19–22—Reserved • 23—Session type (only in LWM2M protocol) • 24—AirVantage server requests that the device make a reboot. The device requests a user agreement to allow the module to reboot. The response can be sent using +WDSR (see +WDSR on page 116) and this indication can be returned by the device if the user has activated the user agreement for connection (see +WDSC on page 109 for details). <p>(Continue on next page)</p>

Table 11-2: AirVantage Device Services command details (Continued)

Command	Description
	<p data-bbox="440 310 927 342"><Data> (Additional data for specific <Event>s)</p> <ul style="list-style-type: none"> <li data-bbox="483 344 802 375">• (<Event>=5) To be defined <li data-bbox="483 378 1422 562">• (<Event>=9) Package size: <ul style="list-style-type: none"> <li data-bbox="511 411 1062 443">▪ Package size in bytes, which will be downloaded <li data-bbox="511 445 1268 476">▪ Preempted DOTA area size needed to download an update package <li data-bbox="511 478 1289 510">▪ If preemption is not made, this parameter is not returned for this event. <li data-bbox="511 512 1377 562">▪ If a reverse package is not downloaded and stored, the preempted area will be released after the installation. <li data-bbox="483 575 1422 814">• (<Event>=11) Download failure reason: <ul style="list-style-type: none"> <li data-bbox="511 609 1422 659">▪ 0 — Insufficient memory in device to save firmware update package. Package was not downloaded. <li data-bbox="511 661 1370 722">▪ 1 — HTTP/HTTPS error occurred. See +WDSE on page 110 for possible error values. <li data-bbox="511 724 1422 814">▪ 2 — Corrupted firmware update package, did not store correctly. Reasons include (or example), mismatched CRCs between actual and expected, or signature check error. <li data-bbox="483 827 883 858">• (<Event>=18) Download progress: <ul style="list-style-type: none"> <li data-bbox="511 861 834 892">▪ Integer value (% complete) <li data-bbox="483 894 883 926">• (<Event>=23) Session event type: <ul style="list-style-type: none"> <li data-bbox="511 928 786 959">▪ 0 — Bootstrap session <li data-bbox="511 961 906 993">▪ 1 — Device management session

Table 11-2: AirVantage Device Services command details (Continued)

Command	Description
+WDSR	<p>Reply to AirVantage server request</p> <p>Reply to a user agreement request (see +WDSI on page 113 for details) from the module. SIM card requirement: Required, and PIN 1/CHV 1 code must be entered. Password required: No</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT+WDSR=<Reply>[,<Timer>] Response: OK Purpose: Send <Reply> to a user agreement request from the module. For specific <Reply> types, include a <Timer> to have the module send a new user agreement request after the specified delay. ▪ Query List: AT+WDSR=? Purpose: Display valid execution format and parameter values. <p>Parameters:</p> <p><Reply> (Reply type)</p> <ul style="list-style-type: none"> • 0—Reserved for future use • 1—Reserved for future use • 2—Delay or refuse to download. New user agreement request to be sent by module after <Timer> minutes: <ul style="list-style-type: none"> ▪ Delay—<Timer> must be > 0, or blank (Default 30). New user agreement request to be sent by module after <Timer> minutes. ▪ Refuse—<Timer>=0. Usage restrictions include: <ul style="list-style-type: none"> ▪ Option available only if OMA DM protocol is used. ▪ Not supported for install request (AT+WDSR=5,0). Returns +CME ERROR: 3 ▪ Not supported for device reboot request (AT+WDSR=7,0). Returns +CME_ERROR: 3 • 3—Accept the download (download it now) • 4—Accept the install (install it now) • 5—Delay the install. New user agreement request to be sent by module after <Timer> minutes. • 6—Accept the device reboot (reboot now) • 7—Delay the device reboot. New user agreement request to be sent by module after <Timer> minutes. • Note: If the module is powered down before a delay (install, download, or reboot) finishes, the new user agreement request will be returned during the next start up. <p><Timer> (Interval before new user agreement request to be sent by module)</p> <ul style="list-style-type: none"> • Applies to <Reply> types 2, 5, 7 • Valid values: <ul style="list-style-type: none"> ▪ Valid range: 0–1440 (minutes) ▪ 0—If <Reply>=2 and OMA DM protocol is used, refuse the user agreement request. ▪ Default (if not specified): 30 (minutes)

Table 11-2: AirVantage Device Services command details (Continued)

Command	Description
+WDSS	<p>Configure/connect AirVantage Management Services session</p> <p>Configure a dedicated access point name (APN), and initiate a connection to the AirVantage server. Also used to activate an automatic registration to the AirVantage server.</p> <p>Activating dedicated PDP context:</p> <ul style="list-style-type: none"> ▪ If a dedicated NAP has not been defined using this command, and a session is requested (via AT command, or via an SMS notification (SMS only in the OMA DM protocol use case), the module uses an APN that has been defined using AT+CGDCONT to activate the dedicated PDP context. This APN will be recorded to configure the AirVantage server's APN and it will be used to activate the dedicated PDP context for the next sessions. ▪ If the PDP context cannot be activated because the AirVantage server's APN is misconfigured, the module uses an APN defined using AT+CGDCONT command to activate the dedicated PDP context. However, the initial APN configuration is not erased. <p>SIM card requirement: Required, and PIN 1/CHV 1 code must be entered.</p> <p>Password required: No</p> <p>Persistent across power cycles: Yes (<Apn> only)</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution (<Mode> = 0): <ul style="list-style-type: none"> AT+WDSS=<Mode>,<Apn>[,<User>[,<Pwd>]] Response: OK Purpose: Configure the AirVantage server connection. ▪ Execution (<Mode> = 1): <ul style="list-style-type: none"> AT+WDSS=<Mode>,<Action> Response: OK Purpose: Connect to/disconnect from the AirVantage server ▪ Query: <ul style="list-style-type: none"> AT+WDSS? Response: [+WDSS: 0,<Apn>[,<User>] +WDSS: 1,<Action>] OK Purpose: Return the current AirVantage server configuration details. If no APN has been defined, return only OK. ▪ Query List: <ul style="list-style-type: none"> AT+WDSS=? Purpose: Display valid execution format and parameter values. <p>Parameters:</p> <p><Mode> (Connection method)</p> <ul style="list-style-type: none"> • 0—PDP context configuration for AirVantage server • 1—User-initiated connection to the AirVantage server <p><Apn> (AirVantage server access point name)</p> <ul style="list-style-type: none"> • ASCII string • Max length: 50 characters • Note: Stored in NV. <p>(Continued on next page)</p>

Table 11-2: AirVantage Device Services command details (Continued)

Command	Description
<p>+WDSS (continued)</p>	<p>Configure/connect AirVantage Management Services session (continued)</p> <p><User> (AirVantage server APN login)</p> <ul style="list-style-type: none"> • ASCII string • Max length: 30 characters • Note: Stored in flash without using &W. &F does not affect this parameter. <p><Pwd> (AirVantage server APN password)</p> <ul style="list-style-type: none"> • ASCII string • Max length: 30 characters • Note: Stored in flash without using &W. &F does not affect this parameter. <p><Action> (Connect to/disconnect from AirVantage server)</p> <ul style="list-style-type: none"> • 0—Release connection (Default) • 1—Establish connection <hr/> <p><i>Note: <User> and <Pwd> are stored in flash without sending the &W command. &F does not affect these values. <Apn> is stored in NV.</i></p>

12: SMS Wake Commands

12.1 Introduction

This chapter describes commands used for the SMS host wake-up feature.

12.2 Command Summary

Table 12-1 lists the commands described in this chapter.

Table 12-1: SMS Wake commands

Command	Description	Page
!SMSWAKE	Enable / disable SMS host wake-up feature	120
!SMSWAKEWIDTH	Set / read SMS Wake signal width	121

12.3 Command Reference

Table 12-2: SMS Wake commands

Command	Description
<p>!SMSWAKE</p>	<p>Enable/disable SMS host wake-up feature</p> <p>Enable/disable the SMS host wake-up feature. Using this feature, an SMS message containing a defined 'wake mask' can be used to wake a tethered host processor (e.g. a laptop).</p> <p>Password required: Yes Reset required to apply changes: No Persistent across power cycles: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!SMSWAKE=<bEnabled>[,<wakeMask>] Response: OK or ERROR ▪ Purpose: Disable the SMS host wake up feature, or enable the SMS host wake up feature and define the <wakeMask> that can be used to wake the tethered host. ▪ Query: AT!SMSWAKE? Response: !SMSWAKE: Enabled <wakeMask>> OK or !SMSWAKE: Disabled OK ▪ Purpose: Report the current state of the SMS host wake-up feature. ▪ Query List: AT!SMSWAKE=? Purpose: Return the esupported parameter values. <p>Parameters:</p> <p><bEnabled> (SMS wake-up feature state)</p> <ul style="list-style-type: none"> • 0— Disabled • 1— Enabled <p><wakeMask> (Bitmask)</p> <ul style="list-style-type: none"> • 32-bit bitmask, in Hex format • Parameter is not used when command is used to disable the feature. • Example: F27A4BB6

Table 12-2: SMS Wake commands (Continued)

Command	Description
!SMSWAKEWIDTH	<p>Set/read SMS Wake signal width Set/read the SMS Wake signal width. Password required: Yes Reset required to apply changes: No Persistent across power cycles: Yes</p> <p>Usage:</p> <ul style="list-style-type: none"> ▪ Execution: AT!SMSWAKEWIDTH=<width> Response: OK or ERROR ▪ Purpose: Set the wake signal width. ▪ Query: AT!SMSWAKEWIDTH? Response: !SMSWAKEWIDTH: <width> OK ▪ Purpose: Report the configured wake signal width. ▪ Query List: AT!SMSWAKEWIDTH=? Purpose: Return the execution command format and the supported parameter values. <p>Parameters: <width> (SMS Wake signal width, in milliseconds)</p> <ul style="list-style-type: none"> • Integer • Valid range: 1–65535

13: Supported GSM / WCDMA AT Commands

This chapter identifies standard AT commands that are supported by most Sierra Wireless AirPrime devices. These commands:

- Control serial communications over an asynchronous interface (*ITU-T Serial Asynchronous Dialling and Control Recommendation V.250*), available on the International Telecommunication Union web site, www.itu.int. See [Table 13-1](#) below.
- Control SMS functions for devices on GSM / WCDMA networks (*3GPP TS 27.005*, available on the 3GPP web site, www.3gpp.org) See [Table 13-2](#) on page 124.
- Control devices operating on GSM / WCDMA networks (*3GPP TS 27.007*, available on the 3GPP web site, www.3gpp.org) See [Table 13-3](#) on page 125.

The tables below identify whether each command is supported on Sierra Wireless UMTS devices. An “N/A” in the Supported column of the table indicates that the command is related to a feature (such as voice) that is not available on the modems.

Commands that are partially supported include descriptions identifying any limitations on command usage. Also, some commands are described in more detail in other chapters — the descriptions for these commands link to those detailed entries (for example, [&V](#) in [Table 13-1](#) on page 122).

Table 13-1: Supported ITU-T Recommendation V.250 AT commands

Command	Description	Supported 4=Yes; 8=No
&C	Set Data Carrier Detected (Received line signal detector) function mode	8
&D	Set Data Terminal Ready function mode	4
&F	Set all current parameters to manufacturer’s defaults	4
&S	Set DSR signal	4
&T	Auto tests	8
&V	Return operating mode AT configuration parameters	4
&W	Store current parameter to user-defined profile	4
+DR	V42bis data compression report	4
+DS	V42bis data compression	4
+GCAP	Request complete TA capabilities list	4
+GMI	Request manufacturer identification	4
+GMM	Request TA model identification	4
+GMR	Request TA revision identification	4
+GOI	Request global object identification	8
+GSN	Request TA serial number identification	4
+ICF	Set TE-TA control character framing	4

Table 13-1: Supported ITU-T Recommendation V.250 AT commands (Continued)

Command	Description	Supported 4=Yes; 8=No
+IFC	Set TE-TA local data flow control	4
+ILRR	Set TE-TA local rate reporting mode	8
+IPR	Set fixed local rate	4
A	Answer incoming call	4
A/	Re-issues last AT command given	4
D	Dial	4
D><MEM><N>	Originate call to phone number in memory <MEM>	8
D><N>	Originate call to phone number in current memory	4
D><STR>	Originate call to phone number in memory which corresponds to alphanumeric field <STR>	8
DL	Redial last telephone number used	8
E	Set command echo mode	4
H	Disconnect existing connections	4
I	Display product identification information	4
L	Set monitor speaker loudness	8
M	Set monitor speaker mode	8
O	Switch from command mode to data mode	4
P	Select pulse dialing	8
Q	Set Result code presentation mode	4
S0	Set number of rings before automatically answering the call	4
S10	Set disconnect delay after indicating the absence of data carrier	4
S3	Set command line termination character	4
S4	Set response formatting character	4
S5	Set command line editing character	4
S6	Set pause before blind dialing	4
S7	Set number of seconds to wait for connection completion	4
S8	Set number of seconds to wait when comma dial modifier used	4
T	Select tone dialing	4
V	Set result code format mode	4
X	Set connect result code format and call monitoring	4
Z	Set all current parameters to user-defined profile	4

Table 13-2: Supported 27.005 AT commands

Command	Description	Supported 4=Yes; 8=No
+CBM	Cell broadcast message directly displayed	4
+CBMI	Cell broadcast message stored in memory at specified <index> location	8
+CDS	SMS status report after sending a SMS	4
+CDSI	Incoming SMS status report	4
+CMGC	Send command	4
+CMGD	Delete message	4
+CMGF	Message format	4
+CMGL	List messages	4
+CMGR	Read message	4
+CMGS	Send message	4
+CMGW	Write message to memory	4
+CMMS	More messages to send	4
+CMNA	New message acknowledgement to ME/TA	4
+CMS ERROR: <err>	SMS error (mobile or network error)	4
+CMSS	Send message from storage	4
+CMT	Incoming message directly displayed	4
+CMTI	Incoming message stored in <mem> ("SM" - (U)SIM message storage) at location <index>	4
+CNMA	New message acknowledgement to mobile equipment	4
+CNMI	New message indications to TE	4
+CPMS	Preferred message storage	4
+CRES	Restore settings	8
+CSAS	Save settings	8
+CSCA	Service center address	4
+CSCB	Select cell broadcast message types	4
+CSDH	Show text mode parameters	4
+CSMP	Set text mode parameters	4
+CSMS	Select message service	4

Table 13-3: Supported 27.007 AT commands

Command	Description	Supported 4=Yes; 8=No
C	ITU T V.24 circuit 109 carrier detect signal behavior command Format <ul style="list-style-type: none"> C<value> Limitations <ul style="list-style-type: none"> Default <value> = 2 <value> = 2 causes the AT/Data carrier detect pin to 'wink' (briefly switch off and on) when data calls end. <value> = 0 or 1 performs as defined in the standard 	Partial
+CACM	Accumulated call meter	8
+CACSP	Voice Group or Voice Broadcast Call State Attribute Presentation	N/A
+CAEMLPP	eMLPP Priority Registration and Interrogation	8
+CAHLD	Leave an ongoing Voice Group or Voice Broadcast Call	N/A
+CAJOIN	Accept an incoming Voice Group or Voice Broadcast Call	N/A
+CALA	Alarm	N/A
+CALCC	List current Voice Group and Voice Broadcast Calls	N/A
+CALD	Delete alarm	N/A
+CALM	Alert sound mode	8
+CAMP	Accumulated call meter maximum	8
+CANCHEV	NCH Support Indication	8
+CAOC	Advice of Charge	8
+CAPD	Postpone or dismiss an alarm	N/A
+CAPTT	Talker Access for Voice Group Call	N/A
+CAREJ	Reject an incoming Voice Group or Voice Broadcast Call	N/A
+CAULEV	Voice Group Call Uplink Status Presentation	N/A
+CBC	Battery charge	4
+CBST	Select bearer service type	4
+CCCM	Current call meter value	8
+CCFC	Call forwarding number and conditions	4
+CCHC	Close logical channel	4
+CCHO	Open logical channel	4
+CCLK	Clock	N/A
+CCUG	Closed user group	4
+CCWA	Call waiting	4

Table 13-3: Supported 27.007 AT commands (Continued)

Command	Description	Supported 4=Yes; 8=No
+CCWE	Call Meter maximum event	8
+CDIP	Called line identification presentation	8
+CDIS	Display control	8
+CEER	Extended error report	8
+CFUN	Set phone functionality Format <ul style="list-style-type: none"> ▪ +CFUN = [<fun> [, <rst>]] Limitations <ul style="list-style-type: none"> ▪ Valid <fun> values: <ul style="list-style-type: none"> · 0 (minimum functionality, low power draw) · 1 (full functionality, high power draw) 	Partial
+CGACT	PDP context activate or deactivate	4
+CGANS	Manual response to a network request for PDP context activation	8
+CGATT	PS attach or detach	4
+CGAUTO	Automatic response to a network request for PDP context activation	8
+CGCLASS	GPRS mobile station class	4
+CGCLOSP	Configure local octet stream PAD parameters	8
+CGCMOD	PDP Context Modify	8
+CGDATA	Enter data state	4
+CGDCONT	Define PDP Context	4
+CGDSCONT	Define Secondary PDP Context	4
+CGEQMIN	3G Quality of Service Profile (Minimum acceptable)	4
+CGEQNEG	3G Quality of Service Profile (Negotiated)	4
+CGEQREQ	3G Quality of Service Profile (Requested)	4
+CGEREP	Packet Domain event reporting	4
+CGEV	GPRS network event indication	4
+CGLA	Generic UICC logical channel access	4
+CGMI	Request manufacturer identification	4
+CGMM	Request model identification	4
+CGMR	Request revision identification	4
+CGPADDR	Show PDP address	4
+CGQMIN	Quality of Service Profile (Minimum acceptable)	4

Table 13-3: Supported 27.007 AT commands (Continued)

Command	Description	Supported 4=Yes; 8=No
+CGQREQ	Quality of Service Profile (Requested)	4
+CGREG	GPRS network registration status	4
+CGSMS	Select service for MO SMS messages	4
+CGSN	Request product serial number identification	4
+CGTFT	Traffic Flow Template	4
+CHLD	Call related supplementary services	4
+CHSA	HSCSD non-transparent asymmetry configuration	N/A
+CHSC	HSCSD current call parameters	N/A
+CHSD	HSCSD device parameters	N/A
+CHSR	HSCSD parameters report	N/A
+CHST	HSCSD transparent call configuration	N/A
+CHSU	HSCSD automatic user initiated upgrading	N/A
+CHUP	Hangup call	4
+CIEV	Indicator event	4
+CIMI	Request international mobile subscriber identity	4
+CIND	Indicator control	4
+CKEV	Key press or release event	8
+CKPD	Keypad control	8
+CLAC	List all available AT commands	8
+CLAE	Language Event	8
+CLAN	Set Language	8
+CLCC	List current calls	4
+CLCK	Facility lock	4
+CLIP	Calling line identification presentation	4
+CLIR	Calling line identification restriction	4
+CLVL	Set/return internal loudspeaker volume	4
+CMAR	Master Reset	8
+CME ERROR: <err>	Mobile Termination error result code	4
+CMEC	Mobile Termination control mode	8
+CMEE	Report Mobile Termination error	4

Table 13-3: Supported 27.007 AT commands (Continued)

Command	Description	Supported 4=Yes; 8=No
+CMER	Mobile Termination event reporting	4
+CMOD	Call mode	4
+CMUT	Enable/disable uplink voice muting	4
+CMUX	Multiplexing mode	4 (When MUX mode configured on USB interface.)
+CNUM	Subscriber number	4
+COLP	Connected line identification presentation	4
+COPN	Read operator names	4
+COPS	Operator selection	4
+CPAS	Phone activity status	4
+CPBF	Find phonebook entries	4
+CPBR	Read phonebook entries	4
+CPBS	Select phonebook memory storage	4
+CPBW	Write phonebook entry	4
+CPIN	Enter PIN	4
+CPINR	Remaining PIN retries	4
+CPLS	Preferred PLMN list selection	4
+CPOL	Preferred operator list	4
+CPROT	Enter protocol mode	8
+CPUC	Price per unit and currency table	4
+CPWC	Power class	8
+CPWD	Change password	4
+CR	Service reporting control	4
+CRC	Cellular result codes	4
+CREG	Network registration	4
+CRING	Incoming call type	4
+CRLP	Radio link protocol	4
+CRMP	Ring Melody Playback	N/A
+CRSL	Ringer sound level	N/A
+CRSM	Restricted SIM access	4

Table 13-3: Supported 27.007 AT commands (Continued)

Command	Description	Supported 4=Yes; 8=No
+CSCC	Secure control command	8
+CSCS	Select TE character set	4
+CSDF	Settings date format	N/A
+CSGT	Set Greeting Text	N/A
+CSIL	Silence Command	N/A
+CSIM	Generic SIM access	4
+CSNS	Single numbering scheme	8
+CSQ	Signal quality	4
+CSSN	Supplementary service notifications	4
+CSTA	Select type of address	4
+CSTF	Settings time format	4
+CSVM	Set Voice Mail Number	8
+CTFR	Call deflection	4
+CTZR	Time Zone Reporting	N/A
+CTZU	Automatic Time Zone Update	8
+CUSD	Unstructured supplementary service data	4
+CV120	V.120 rate adaptation protocol	8
+CVHU	Voice Hangup Control	8
+CVIB	Vibrator mode	N/A
D	ITU T V.25ter [14] dial command	4
D*99#	Sets up a packet data call (PDP context) based on profile ID #1	4
D*99**<n>#	Sets up a packet data call (PDP context) based on profile ID #<n> (<n> is the <cid> in the +CGDCONT command)	4
+VTD	Tone duration	4
+VTS	DTMF and arbitrary tone generation	4
+WS46	PCCA STD 101 [17] select wireless network	8

14: Band Definitions

Some commands described in this document include input and/or output 'band' parameters, where the band value is one of the following:

- An enumerated value representing a network technology and band (Table 14-1)
- A 3GPP band number (Table 14-2 on page 130)

Note: Band support is product-specific — see the device's Product Specification Document or Product Technical Specification for details.

Table 14-1: Band / technology enumerations^a

<band>	Description	<band>	Description	<band>	Description	<band>	Description
0	CDMA	22	WCDMA 800	42	LTE B4	60	LTE B24
2	Sleep	25	WCDMA BC3	43	LTE B2	61	LTE B25
5	CDMA 800	26	CDMA BC14	44	LTE B3	62	LTE B26
6	CDMA 1900	27	CDMA BC11	45	LTE B5	63	LTE B27
7	HDR	28	WCDMA BC4	46	LTE B6	64	LTE B28
8	CDMA 1800	29	WCDMA BC8	47	LTE B8	65	LTE B29
9	WCDMA IMT	30	MF 700	48	LTE B9	66	LTE B30
10	GSM 900	31	WCDMA BC9	49	LTE B10	67	LTE B31
11	GSM 1800	32	CDMA BC15	50	LTE B12	68	LTE B32
12	GSM 1900	33	CDMA BC10	51	LTE B14	69	LTE B33
14	JCDMA	34	LTE B1	52	LTE B15	70	LTE B34
15	WCDMA 1900A	35	LTE B7	53	LTE B16	71	LTE B35
16	WCDMA 1900B	36	LTE B13	54	LTE B18	72	LTE B36
17	CDMA 450	37	LTE B17	55	LTE B19	73	LTE B37
18	GSM 850	38	LTE B38	56	LTE B20	74	LTE B39
19	IMT	39	LTE B40	57	LTE B21	75	WCDMA BC19
20	HDR 800	40	WCDMA BC11	58	LTE B22	76	LTE B41
21	HDR 1900	41	LTE B11	59	LTE B23		

a. Band values not listed (e.g. 1, 3, 4) are reserved.

Table 14-2: 3GPP bands

Band	Type	Frequency bands (MHz)		Band	Type	Frequency bands (MHz)		Band	Type	Frequency bands (MHz)	
		Rx	Tx			Rx	Tx			Rx	Tx
1	Mid	1920–1980	2110–2170	25	Mid	1850–1915	1930–1995	49	High	3550–3700	
2	Mid	1850–1910	1930–1990	26	Low	814–849	859–894	50	Mid	1432–1517	

Table 14-2: 3GPP bands (Continued)

Band	Type	Frequency bands (MHz)		Band	Type	Frequency bands (MHz)		Band	Type	Frequency bands (MHz)	
		Rx	Tx			Rx	Tx			Rx	Tx
3	Mid	1710–1785	1805–1880	27	-	Reserved	Reserved	51	Mid	1427–1432	
4	Mid	1710–1755	2110–2155	28	Low	703–748	758–803	52	High	3300–3400	
5	Low	824–849	869–894	29	Low	N/A	717–728	53	High	2483.5–2495	
6	Low	830–840	875–885	30	High	2305–2315	2350–2360	54–64	-	Reserved	Reserved
7	High	2500–2570	2620–2690	31	Low	452.5–457.5	462.5–467.5	65	Mid	1920–2010	2110–2200
8	Low	880–915	925–960	32	Mid	N/A	1452–1496	66	Mid	1710–1780	2110–2200
9	Mid	1749.9–1784.9	1844.9–1879.9	33	-	Reserved	Reserved	67	Low	N/A	738–758
10	Mid	1710–1770	2110–2170	34	Mid	2010–2025		68	Low	698–728	753–783
11	Mid	1427.9–1447.9	1475.9–1495.9	35	-	Reserved	Reserved	69	High	N/A	2570–2620
12	Low	699–716	729–746	36	-	Reserved	Reserved	70	Mid	1695–1710	1995–2020
13	Low	777–787	746–756	37	Mid	1910–1930		71	Low	663–698	617–652
14	Low	788–798	758–768	38	High	2570–2620		72	Low	451–456	461–466
15	-	Reserved	Reserved	39	Mid	1880–1920		73	Low	450–455	460–465
16	-	Reserved	Reserved	40	High	2300–2400		74	Mid	1427–1470	1475–1518
17	Low	704–716	734–746	41	High	2496–2690		75	Mid	N/A	1432–1517
18	Low	815–830	860–875	42	High	3400–3600		76	Mid	N/A	1427–1432
19	Low	830–845	875–890	43	High	3600–3800		77–84	-	Reserved	Reserved
20	Low	832–862	791–821	44	Low	703–803		85	Low	698–716	728–746
21	Mid	1447.9–1462.9	1495.9–1510.9	45	-	Reserved	Reserved	86	-	Reserved	Reserved
22	-	Reserved	Reserved	46	High	5150–5925		87	Low	410–415	420–425
23	Mid	2000–2020	2180–2200	47	High	5855–5925		88	Low	412–417	422–427
24	Mid	1626.5–1660.5	1525–1559	48	High	3550–3700		89–93	-	Reserved	Reserved

15: ASCII Table

Table 15-1: ASCII values

Char	Dec	Hex	Char	Dec	Hex	Char	Dec	Hex	Char	Dec	Hex
NUL	0	00	SP	32	20	@	64	40	'	96	60
SOH	1	01	!	33	21	A	65	41	a	97	61
STX	2	02	"	34	22	B	66	42	b	98	62
ETX	3	03	#	35	23	C	67	43	c	99	63
EOT	4	04	\$	36	24	D	68	44	d	100	94
ENQ	5	05	%	37	25	E	69	45	e	101	95
ACK	6	06	&	38	26	F	70	46	f	102	96
BEL	7	07	'	39	27	G	71	47	g	103	97
BS	8	08	(40	28	H	72	48	h	104	98
HT	9	09)	41	29	I	73	49	i	105	99
LF	10	0A	*	42	2A	J	74	4A	j	106	6A
VT	11	0B	+	43	2B	K	75	4B	k	107	6B
FF	12	0C	,	44	2C	L	76	4C	l	108	6C
CR	13	0D	-	45	2D	M	77	4D	m	109	6D
SO	14	0E	.	46	2E	N	78	4E	n	110	6E
SI	15	0F	/	47	2F	O	79	4F	o	111	6F
DLE	16	10	0	48	30	P	80	50	p	112	70
XON	17	11	1	49	31	Q	81	51	q	113	71
DC2	18	12	2	50	32	R	82	52	r	114	72
XOFF	19	13	3	51	33	S	83	53	s	115	73
DC4	20	14	4	52	34	T	84	54	t	116	74
NAK	21	15	5	53	35	U	85	55	u	117	75
SYN	22	16	6	54	36	V	86	56	v	118	76
ETB	23	17	7	55	37	W	87	57	w	119	77
CAN	24	18	8	56	38	X	88	58	x	120	78
EM	25	19	9	57	39	Y	89	59	y	121	79
SUB	26	1A	:	58	3A	Z	90	5A	z	122	7A
ESC	27	1B	;	59	3B	[91	5B	{	123	7B
FS	28	1C	<	60	3C	\	92	5C		124	7C
GS	29	1D	=	61	3D]	93	5D	}	125	7D
RS	30	1E	>	62	3E	^	94	5E	~	126	7E
US	31	1F	?	63	3F	_	95	5F	DEL	127	7F