

**Certification
Issued Under the Authority of the
Federal Communications Commission
By:**

**Compliance Certification Services
47173 Benicia Street
Fremont, CA 94538**

**Date of Grant: 05/14/2008
Application Dated: 05/14/2008**

**Sierra Wireless Inc.
13811 Wireless Way
Richmond, BC, V6V 3A4
Canada**

Attention: Ying Wang , Senior RF Engineer

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: N7NMC8790
Name of Grantee: Sierra Wireless Inc.
Equipment Class: PCS Licensed Transmitter
Notes: 850/900/1800/1900/2100 MHz Multi-band Module
Modular Type: Single Modular

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
BC	22H	824.2 - 848.8	1.524	2.5 PM	245KGXW
BC	22H	824.2 - 848.8	0.514	2.5 PM	240KG7W
BC	22H	826.4 - 846.6	0.203	2.5 PM	4M17F9W
BC	24E	1850.2 - 1909.8	0.743	2.5 PM	247KGXW
BC	24E	1850.2 - 1909.8	0.386	2.5 PM	243KG7W
BC	24E	1852.4 - 1907.6	0.455	2.5 PM	4M18F9W

Output power listed is conducted. Modular Approval for use as a module in mobile-only exposure conditions, antenna gain including cable loss must not exceed 5 dBi in Cellular Band and 4 dBi in PCS band, for purposes of 2.1043 and 2.1091. This device is allowed only for OEM integration into host products; consumer or end-user installation is not allowed. The antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons. The antenna(s) used for this transmitter must not be co-located or operating in conjunction with any other antenna or transmitter. End-users must be provided with specific information required to satisfy RF exposure compliance for final host devices and installations. This device contains functions that are not operational in U.S Territories. This filing is only applicable for US operations.

BC: The output power is continuously variable from the value listed in this entry to 5%-10% of the value listed.