



Customer Process Guidelines - Handling of Sampling Parts

AirPrime Modules



SIERRA
WIRELESS®

4115345 (FileHold), 2102904 (Arena)

5.0

June 07, 2017

Important Notice

Due to the nature of wireless communications, transmission and reception of data can never be guaranteed. Data may be delayed, corrupted (i.e., have errors) or be totally lost. Although significant delays or losses of data are rare when wireless devices such as the Sierra Wireless modem are used in a normal manner with a well-constructed network, the Sierra Wireless modem should not be used in situations where failure to transmit or receive data could result in damage of any kind to the user or any other party, including but not limited to personal injury, death, or loss of property. Sierra Wireless accepts no responsibility for damages of any kind resulting from delays or errors in data transmitted or received using the Sierra Wireless modem, or for failure of the Sierra Wireless modem to transmit or receive such data.

Safety and Hazards

Do not operate the Sierra Wireless modem in areas where cellular modems are not advised without proper device certifications. These areas include environments where cellular radio can interfere such as explosive atmospheres, medical equipment, or any other equipment which may be susceptible to any form of radio interference. The Sierra Wireless modem can transmit signals that could interfere with this equipment. Do not operate the Sierra Wireless modem in any aircraft, whether the aircraft is on the ground or in flight. In aircraft, the Sierra Wireless modem **MUST BE POWERED OFF**. When operating, the Sierra Wireless modem can transmit signals that could interfere with various onboard systems.

Note: Some airlines may permit the use of cellular phones while the aircraft is on the ground and the door is open. Sierra Wireless modems may be used at this time.

The driver or operator of any vehicle should not operate the Sierra Wireless modem while in control of a vehicle. Doing so will detract from the driver or operator's control and operation of that vehicle. In some states and provinces, operating such communications devices while in control of a vehicle is an offence.

Limitations of Liability

This manual is provided "as is". Sierra Wireless makes no warranties of any kind, either expressed or implied, including any implied warranties of merchantability, fitness for a particular purpose, or noninfringement. The recipient of the manual shall endorse all risks arising from its use.

The information in this manual is subject to change without notice and does not represent a commitment on the part of Sierra Wireless. SIERRA WIRELESS AND ITS AFFILIATES SPECIFICALLY DISCLAIM LIABILITY FOR ANY AND ALL DIRECT, INDIRECT, SPECIAL, GENERAL, INCIDENTAL, CONSEQUENTIAL, PUNITIVE OR EXEMPLARY DAMAGES INCLUDING, BUT NOT LIMITED TO, LOSS OF PROFITS OR REVENUE OR ANTICIPATED PROFITS OR REVENUE ARISING OUT OF THE USE OR INABILITY TO USE ANY SIERRA WIRELESS PRODUCT, EVEN IF SIERRA WIRELESS AND/OR ITS AFFILIATES HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES OR THEY ARE FORESEEABLE OR FOR CLAIMS BY ANY THIRD PARTY.

Notwithstanding the foregoing, in no event shall Sierra Wireless and/or its affiliates aggregate liability arising under or in connection with the Sierra Wireless product, regardless of the number of events, occurrences, or claims giving rise to liability, be in excess of the price paid by the purchaser for the Sierra Wireless product.

Patents

This product may contain technology developed by or for Sierra Wireless Inc.

This product includes technology licensed from QUALCOMM®.

This product is manufactured or sold by Sierra Wireless Inc. or its affiliates under one or more patents licensed from MMP Portfolio Licensing.

Copyright

© 2017 Sierra Wireless. All rights reserved.

Trademarks

Sierra Wireless®, AirPrime®, AirLink®, AirVantage®, WISMO®, ALEOS® and the Sierra Wireless and Open AT logos are registered trademarks of Sierra Wireless, Inc. or one of its subsidiaries.

Watcher® is a registered trademark of NETGEAR, Inc., used under license.

Windows® and Windows Vista® are registered trademarks of Microsoft Corporation.

Macintosh® and Mac OS X® are registered trademarks of Apple Inc., registered in the U.S. and other countries.

QUALCOMM® is a registered trademark of QUALCOMM Incorporated. Used under license.

Other trademarks are the property of their respective owners.

Contact Information

Sales information and technical support, including warranty and returns	Web: sierrawireless.com/company/contact-us/ Global toll-free number: 1-877-687-7795 6:00 am to 6:00 pm PST
Corporate and product information	Web: sierrawireless.com

Document History

Version	Date	Updates
1.0	February 14, 2014	Creation
2.0	May 15, 2014	Updated for sampling modules shipped in dry bag
	August 13, 2014	Updated Table 1 Baking Conditions of AirPrime Modules
3.0	January 02, 2015	Clarified shielded and molded HL series modules; added Arena reference number
4.0	January 11, 2016	Updated the module list in Table 1 Baking Conditions of AirPrime Modules
5.0	June 07, 2017	Updated the module list in Table 1 Baking Conditions of AirPrime Modules



1. Introduction

This document presents guidelines for the handling of solderable AirPrime products as they are moisture/reflow sensitive surface mount devices.

2. Specificity of Device Samples

As AirPrime solderable modules are MSL3, the components should be delivered in dry-pack. But for small sampling quantities requested for prototype use, Sierra Wireless may not be able to supply the components in dry-pack packaging.

Therefore, when receiving the components, the customer should consider that the components have exceeded their floor life.

To not damage the AirPrime modules when soldering it in the customer board, the modules need to be baked prior to any reflow.

Modules should be in a tray and baked as per Table 1 Baking Conditions of AirPrime Modules before any module reflow on the customer's PCB.

As the MSL level is only assumed during the sampling stage, units have to be placed inside a dry cabinet (<10%RH) once baked.

Some sampling modules may also be delivered in dry bag. In the same way, units delivered in dry bag have to be placed inside a dry cabinet (<10%RH) once the vacuum bag is opened.

Table 1. Baking Conditions of AirPrime Modules

AirPrime Modules	Baking Conditions
Shielded modules (AR series, SL series, some HL variants such as the HL6528x, WP series)	24 hours minimum at 85°C
Molded modules (WS6318, some HL8 variants such as the HL8548x)	48 hours minimum at 125°C




Figure 1. Different Assembly Technologies on AirPrime HL Series Modules

It is recommended to follow the standard MSL procedure, as described in the following norm:

- IPC/JEDEC J-STD-033A - Handling, Packing, Shipping and Use of Moisture / Reflow Sensitive Surface Mount Devices.



SIERRA
WIRELESS®