



TECHNICAL DATA SHEET - CAST STONE BAT BOX

Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: Facing and rendered masonry, load bearing or non-load bearing masonry structures. For use in unprotected Masonry.

Declared Performance	Performance		Harmonised Technical Specification		
	440 x 100 x 215		This product, although manufactured all or in part from individual components covered in the scope of a harmonised		
Dimensions and tolerance - mm	Tolerance	NA	European or UK standard, is not currently covered in its current assembly and therefore must not carry the CE or UKCA		
	Range	NA	marking. For further technical advice please contact the		
Configuration	Cast stone with high grade plywood resinbonded backing panel.		Design and Technical team at technical@ibstock.co.uk		
Group	N/A				
Flatness of bed faces	N/A				
			215mm Bot entrance.		
Compressive Strength - N/mm2	Mean Normalised Category	NPD NPD N/A			
Active Soluble Salts	N/A		440mm		
Colour	Variety available		100mm		
Dry Unit Weight	Approx.10 kg				
Reaction to Fire	NPD		Although cast stone is classified A1 non-combustible, this product utilises epoxy resin for bonding high grade plywood backing panel and consequently is not classed as non-combustible and must not be used in buildings over 11m in the UK.		
Water absorption %	NPD				
Water vapour permeability	NPD		Details on installation can be found via IG 7.1 https://www.ibstock.co.uk/design-and-technical-services/technical-		
Direct airborne sound insulation	NPD				
Thermal conductivity W/mk	NPD		information#37KwVClgr0eNXBGtnkJs6d		
Durability against freeze thaw	PASS				
Dangerous substances	N	lil			

• NPD – No Product Data (Available)





Item Code	Item Name	Item Description	LxWxD	Aperture
CEB/7996/BBOX/BT	Bat Box	MTO Bat Box Bath	440 x 100 x 215	60 x 55

For further help and advice contact Technical on 01909 775000 or email technical@forticrete.com