

TEXTURED RANGE OF LINTELS LOAD/SPAN TABLE – Uniformly distributed service loads (kN/m)  
The self weight of the lintel must be subtracted from the load given



Manufacture size to order	Section	P100	P150	P220	P255	S10	R15	R15A	S15	R21	R21A	R22	R22A	R23
	Profile*	100 X 65	140 X 65	215 X 65	255 X 65	100 X 100	140 X 100	100 X 140	140 X 150	215 X 140	140 X 215	215 X 100	100 X 215	215 X 215
	CLEAR SPAN	Maximum service load in kN/m (in addition to self weight)												
600	300	39.56	48.19	77.46	89.09	53.11	80.70	83.25	112.95	164.05	171.86	123.23	134.04	219.01
750	450	25.56	29.22	56.24	64.68	38.56	58.60	60.46	82.01	119.12	124.80	89.49	97.34	158.98
900	600	15.06	17.96	43.63	46.53	28.93	39.87	47.43	64.33	93.44	97.90	62.09	76.38	124.68
1050	750	9.89	12.11	29.48	31.43	19.54	26.93	37.50	52.89	76.83	80.50	41.95	62.81	102.49
1200	900	6.97	8.69	21.21	22.60	14.05	19.37	27.00	44.88	58.98	68.32	30.17	53.31	86.95
1350	1050	5.16	6.52	15.96	16.99	10.57	14.56	20.34	38.96	44.42	59.32	22.69	46.29	75.47
1500	1200	3.96	5.05	12.42	13.21	8.22	11.33	15.84	34.41	34.61	52.39	17.64	37.70	66.63
1650	1350	3.13	4.02	9.91	10.54	6.56	9.04	12.67	30.52	27.68	42.00	14.08	30.20	59.63
1800	1500	2.52	3.26	8.08	8.59	5.35	7.36	10.35	24.98	22.61	34.37	11.48	24.71	50.62
2100	1800	1.73	2.25	5.64	5.98	3.72	5.13	7.24	17.57	15.82	24.17	7.99	17.38	35.58
2400	2100	1.24	1.63	4.12	4.36	2.72	3.74	5.32	12.98	11.62	17.84	5.83	12.83	26.26
2700	2400	0.92	1.21	2.85	3.29	2.05	2.82	4.04	9.94	8.84	13.66	4.40	9.82	20.09
3000	2700	0.70	0.92	2.03	2.41	1.59	2.18	3.16	7.82	6.90	10.75	3.41	7.73	15.80
3300	3000	0.54	0.71	1.50	1.78	1.25	1.72	2.51	6.29	5.50	8.64	2.69	6.21	12.69
3600	3300	0.42	0.56	1.13	1.35	1.00	1.37	2.03	5.15	4.45	7.06	2.15	5.08	10.36
4200*	3900	—	—	—	—	—	—	1.38	3.58	3.02	4.90	1.41	3.53	7.19

Please Note! Safe working loads indicated are based on the clear span plus 150mm of bearing each end.

Our lintels are supplied in a standard range of lengths and can be cut to length as required.

The safe working load per metre is the least of the flexural strength, the shear strength or the load that gives a deflection limit of L/325.

Deflection information is available for our full range of lintels, please see Supreme DoP or contact our technical department.

\* Lengths indicated are not available in all section sizes

The safe working loads indicated in the grey band on the longer spans are not great relative to the span, these lintels should be used with caution