

Tile Specifications

	Pitch	Batten Spacing	Headlap	Tiles Per m ²	Batten Per m ²	Mass Per m ²	Mass Per Tile	Overall Length	Hanging Length	Overall Width	Cover Width	Nail Size
SL8	17.5°-22.5°	330mm max	90mm min	8.37/m ²	3.03lm	45.20kg	5.4kg	420mm	396mm	390mm	362mm	45mm x 3.35mm
		320mm min	100mm max	8.63/m ²	3.13lm	46.62kg						
PAN8	22.5°-75°	345mm max	75mm min	8.01/m ²	2.90lm	43.24kg	4.9kg	420mm	398mm	390mm	367mm	40mm x 3.35mm
		320mm min	100mm min	8.63/m ²	3.13lm	46.62kg						
Gemini	25°-75°	345mm max	75mm min	7.90/m ²	2.9lm	38.70kg	2.85kg	270mm	243mm	337mm	316mm	45mm x 3.35mm
		320mm min	100mm max	8.51/m ²	3.13lm	41.72kg						
Minislate	22.5°-29.5°	190mm max	80mm min	16.66/m ²	5.26lm	47.47kg	2.85kg	270mm	243mm	337mm	316mm	45mm x 3.35mm
		175mm min	95mm max	18.08/m ²	5.71lm	51.54kg						
Centurion	30°-70°	195mm max	75mm min	16.23/m ²	5.13lm	46.25kg	2.9kg	385mm	368mm	230mm	200mm	Tile clip 50mm x 3.35mm
		175mm min	95mm max	18.08/m ²	5.71lm	51.54kg						
Senator	22.5°-70°	190mm max	80mm min	16.66/m ²	5.26lm	47.47kg	2.9kg	385mm	368mm	230mm	200mm	40mm x 3.35mm
		175mm min	95mm max	18.08/m ²	5.71lm	51.54kg						
V2	17.5°-70°	310mm max	75mm min	16.13/m ²	3.23lm	46.77kg	2.95kg	385mm	360mm	230mm	200mm	50mm x 3.35mm
		285mm min	100mm max	17.54/m ²	3.51lm	51.75kg						