

APOLLO TIRES (US) INC. 1175 Peachtree Street NE Atlanta, GA 30361, USA +1 (770) 302-2163, contact.us@apollotyres.com www.apollotrucktires.com





ENDU®COMBI RA

THE ENDU®COMBI RA REGIONAL ALL POSITION TIRE OFFERS EXCEPTIONAL PERFORMANCE & CASING DURABILITY.



M + S





PRODUCT CODE	TIRE SIZE	PLY Rating	LOAD Range	LOAD Index	SPEED Symbol	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	ORIGINAL Tread Depth (1/32")	STATIC Loaded Radius (Inch)	RECOM- MENDED RIM WIDTH (INCH)	ALTERNATE RIM WIDTH (INCH)	TIRE WEIGHT		LOAD DETAILS (LBS)	
												LBS	KG	SINGLE	DUAL
2021106	11R22.5	14	G	144/142	L	41.2	11.1	20	19.3	8.25	7.50	129.0	58.5	6175 lbs @ 105 psi	5840 lbs @ 105 psi
2021105	11R22.5	16	Н	146/143	L	41.2	11.1	20	19.3	8.25	7.50	129.0	58.5	6610 lbs @ 120 psi	6005 lbs @ 120 psi
2021110	295/75R22.5	14	G	144/141	L	40.2	11.5	20	18.7	9.00	8.25	127.4	57.8	6175 lbs @ 110 psi	5675 lbs @ 110 psi
2021109	295/75R22.5	16	Н	149/146	L	40.2	11.5	20	18.7	9.00	8.25	127.4	57.8	7160 lbs @ 125 psi	6610 lbs @ 125 psi

1 ENHANCED STABILITY



Tapered sinusoidal grooves facilitate additional reinforcement on continuous channelized ribs therefore enhancing vehicle stability.

3 EVEN WEAR



Deep stress relieving sipes assists in maintaining even wear and higher removal mileages.



2 IMPROVED TRACTION



- Deep 3D sipes provide excellent traction throughout the tread life.
- Zig-Zag grooved walls help provide optimized biting edges for excellent traction in all seasonal conditions.

4 MULTIPLE RETREADS



Robust construction with optimized belt package.