

F-500



ECO vessel



Tier III compliant



IMO Cargo 1-9



Heavy lift



Strengthened deck



ICE class

BASICS

| | |
|--------------|-------------------------|
| TYPE | Premium Project Carrier |
| YARD | Taizhou Sanfu, China |
| DELIVERY | Q4 2025 & Q2 2026 |
| FLAG | To be announced |
| CLASS | DNV |
| IMO NO | To be announced |
| HULL NUMBERS | SF230204 & SF230204 |

TONNAGE AND CAPACITY

| | |
|--------------|---------------------|
| DWT | abt. 12.500 mts |
| GT / NT | abt. 11.500 / 4.500 |
| GRAIN | 17.654 cbm |
| TEU CAPACITY | 842 TEU, 50 Reefer |

DIMENSIONS

| | |
|-----------|---------------------|
| LOA / LPP | 147,00 m / 140,00 m |
| BREADTH | 22,80 m |
| DRAFT | max. 8,18 m |

CRANES

| | |
|----------|---|
| TYPE | MacGregor electrical, port-side mounted |
| CAPACITY | 2 x 250 mts, combinable 500 mts |
| OUTREACH | at 120mts up to 33,00 m |

MAIN ENGINE

| | |
|------|-----------------------------------|
| TYPE | MAN 5G45ME-C9.7 with HPSCR (TIII) |
| MCR | 4.800 kW |

SPEED / CONSUMPTION

| | |
|-------|-----------------------------------|
| LADEN | 15,00 kts on abt. 15,50 mts VLSFO |
|-------|-----------------------------------|

CARGO HOLDS AND HATCHES

| | |
|--------------|--------------------------------------|
| HATCH COVERS | automatic folding-type |
| TWEENDECKS | multilevel, can be used as bulkheads |
| HOLDS | box-shaped |

| | |
|-----------|-----------------------------|
| HOLD NO 1 | 12,75 m x 12,56 m x 11,40 m |
| TANK TOP | abt. 158 sqm |
| TWEENDECK | abt. 158 sqm |
| TOTAL | abt. 316 sqm |

| | |
|-----------|-----------------------------|
| HOLD NO 2 | 76,50 m x 17,60 m x 12,00 m |
| TANK TOP | abt. 1.321 sqm |
| TWEENDECK | abt. 1.321 sqm |
| TOTAL | abt. 2.642 sqm |

| | |
|-------------------|----------------------|
| AREA HATCH COVERS | total abt. 1.372 sqm |
|-------------------|----------------------|

DECK STRENGTH

| | |
|--------------|----------------|
| TANK TOP | 20,00 mt / sqm |
| HATCH COVERS | 4,00 mt / sqm |

ADDITIONAL FEATURES

ECO vessel – most efficient vessel in its class
Tier III compliant on NO_x emissions
Methanol ready
Open hatch notation
Vessel is Great Lakes fitted, Australia fitted, grain fitted Equipped for carriage of IMO cargo 1-9
Ice-class 1A
Mechanical hold ventilation
Ballast Water Treatment
Bow thruster

F-600 XL



ECO vessel



Tier III compliant



IMO Cargo 1-9



Heavy lift



Strengthened deck



ICE class

BASICS

| | |
|--------------|-------------------------|
| TYPE | Premium Project Carrier |
| YARD | Taizhou Sanfu, China |
| DELIVERY | Q3 2026 & Q4 2026 |
| FLAG | To be announced |
| CLASS | DNV |
| IMO NO | To be announced |
| HULL NUMBERS | SF230205 & SF230207 |

TONNAGE AND CAPACITY

| | |
|--------------|---------------------|
| DWT | abt. 14.000 mts |
| GT / NT | abt. 14.042 / 5.344 |
| GRAIN | 20.100 cbm |
| TEU CAPACITY | 953 TEU, 50 Reefer |

DIMENSIONS

| | |
|-----------|---------------------|
| LOA / LPP | 159,75 m / 152,75 m |
| BREADTH | 22,80 m |
| DRAFT | max. 8,30 m |

CRANES

| | |
|----------|---|
| TYPE | MacGregor electrical, port-side mounted |
| CAPACITY | 2 x 350 mts, combinable 600 mts |
| OUTREACH | at 130mts up to 35,00 m |

MAIN ENGINE

| | |
|------|-----------------------------------|
| TYPE | MAN 5G45ME-C9.7 with HPSCR (TIII) |
| MCR | 5.200 kW |

SPEED / CONSUMPTION

| | |
|-------|-----------------------------------|
| LADEN | 15,00 kts on abt. 15,80 mts VLSFO |
|-------|-----------------------------------|

CARGO HOLDS AND HATCHES

| | |
|--------------|--------------------------------------|
| HATCH COVERS | automatic folding-type |
| TWEENDECKS | multilevel, can be used as bulkheads |
| HOLDS | box-shaped |

| | |
|-----------|-----------------------------|
| HOLD NO 1 | 12,75 m x 12,56 m x 11,10 m |
| TANK TOP | abt. 158 sqm |
| TWEENDECK | abt. 158 sqm |
| TOTAL | abt. 316 sqm |

| | |
|-----------|-----------------------------|
| HOLD NO 2 | 89,25 m x 17,60 m x 11,70 m |
| TANK TOP | abt. 1.545 sqm |
| TWEENDECK | abt. 1.545 sqm |
| TOTAL | abt. 3.090 sqm |

| | |
|-------------------|----------------------|
| AREA HATCH COVERS | total abt. 1.731 sqm |
|-------------------|----------------------|

DECK STRENGTH

| | |
|--------------|----------------|
| TANK TOP | 20,00 mt / sqm |
| HATCH COVERS | 5,00 mt / sqm |

ADDITIONAL FEATURES

ECO vessel – most efficient vessel in its class
Tier III compliant on NO_x emissions
Methanol ready
Open hatch notation
Vessel is Great Lakes fitted, Australia fitted, grain fitted Equipped for carriage of IMO cargo 1-9
Ice-class 1A
Mechanical hold ventilation
Ballast Water Treatment
Bow thruster

All details are given in good faith, but not guaranteed. Values in charter party agreements always prevail.