VS SERIES
SURFACE MOUNT

VSR

Code 3's VS Series is a high-intensity directional LED warning light specifically designed for vehicle headlight and taillight applications. In addition, the VS Series can be surface mounted to the vehicle's exterior using the included mounting bezel. It features six LEDs that provide exceptional warning with the electronics being embedded in the lighthead, eliminating the need for an in-line driver module. All 29 (single-color) and 69 (dual-color) flash patterns are synchronizable with other Hide-A-Blast™ and the CD3511. Additional benefits of LED technology include low current draw and a long maintenance-free service life.

VOLTS | AMPS	12-24V | 0.67A Single, 0.46A Dual
DIMS	1.1" H x 1.5" Diameter | 28mm H x 33mm Diameter
FLASH PATTERNS	29 Single, 69 Dual
CERTS	CE, R10, IP67, IP69K, ROHS, REACH
DETAILS	▪ All electronics embedded in lighthead ▪ 29 flash patterns (single-color), 69 flash patterns (dual-color) ▪ VS Series replaces the VX Series ▪ 1" headlight/taillight mount or surface mount using included bezel ▪ Six LEDs per lighthead ▪ Multiple heads are synchronizable (simultaneous or alternating operation ▪ Polycarbonate lens and 12" cable ▪ Temperature Range: -40°F to +149°F (-40°C to +65°C)
REPLACE	"_" with A = Amber, B = Blue, G = Green, R = Red, W = White

MODEL	TYPE	ILLUMINATION COLORS
VS_	Single, 6 LED, 1" hole or surface/2 bolt	A, B, R, W
VS_ _	Dual, 6 LED, 1" hole or surface/2 bolt	AB, AG, AR, AW, BW, RB, RW

2.3[57]
Ø1.5[38]
Ø0.15[4]
MOUNTING HOLES
Ø0.15[4]
MOUNTING HOLES
1.80[46]
1.28[33]

1.2[30]
1.1[29]

12.5±0.5[318±13]

4-20 AWG WIRES
RED - POWER (+)
BLACK - GROUND (-)
BLUE - PATTERN SELECT (-)/ DIM (+)
YELLOW - SYNCH

⚠ **WARNING:** Cancer and Reproductive Harm – www.P65 Warnings.ca.gov