

# X86 340R

The Normet Xrock X86-340R breaker boom combines robust, heavy-duty performance with a compact design. Tailored for low-profile breaking in grizzlies, the X86-340R boasts a minimal footprint, making it ideal for narrow workspaces, particularly in underground applications.

**Perfect balance**

between a low-profile design for reduced excavation and a wide operating area for efficient mining.

**Small footprint**

with a slew ring allows for controlled, safer rotation and movement.

**Standardized wear parts**

and high-capacity, maintenance free cylinder eye bearings enhance serviceability while reducing the need for extensive spare part inventory.

**Internal hydraulic lines**

and cylinder and motor protections for extended uptime even in harsh environment



**SPECIFICATION**

	X86-340R
Maximum reach (incl. nominal breaker), m (ft)	4.4 (14.4)
Horizontal reach, max (breaker vertical), m (ft)	3.2 (10.5)
Vertical reach, max (incl. nominal breaker), m (ft)	1.6 (5.2)
Recommended breaker weight, kg (lb)	280 - 610 (617 - 1 344)
Operating mass, without breaker, kg (lb)	1 400 (3 086)

**ROBUST,  
HEAVY-DUTY  
PERFORMANCE**

## POWER UNITS

Normet Xrock power units offer streamlined power to maximize boom and breaker performance. Our power units are delivered fully assembled and rigorously tested, ensuring immediate readiness for deployment. The power unit system is ready for use by simply connecting it to the boom and providing the necessary power supply. Integrated drip tray is always included in our power units and their accessible service points allow effortless maintenance.



### SPECIFICATION

	PU18-43
Weight without oil, kg (lb)	800 (1 764)
Oil tank volume, l (gal)	250 (66)
Oil flow, l/min (gal/min) 1500 rpm (50 Hz)	65 (17)
Oil flow, l/min (gal/min) 1800 rpm (60 Hz)	78 (20)

## ACCESSORIES

### Wireless Remote Control

The wireless and lightweight, our handheld remote control enables flexible operations from a secure and remote location.

### Automatic lubrication system

The automatic lubrication system improves uptime and safety by reducing the necessity for potentially hazardous boom maintenance procedures.

### Automatic breaker lubrication system

The automatic breaker lubrication system enhances the operational lifespan of breakers and ensures peak equipment performance over an extended period.

## COMPATIBLE BREAKERS

To optimize productivity, extend equipment lifespan, and maximize usability, complement your Normet Xrock booms with perfectly compatible Normet Xrock hydraulic breakers. The thoughtfully curated features of Normet Xrock breakers, paired with our agile and maneuverable booms, guarantee efficient task completion while maintaining cost-effectiveness in your operations.



### SPECIFICATION

	XB5	XB6
Operating weight, kg (lb)	335 (738)	450 (992)
Oil flow, l/min (gal/min)	25 - 60 (6.6 - 15.8)	45 - 100 (11.8 - 26.4)
Impact rate (bpm)	450 - 1 000	500 - 1 050
Operating pressure, bar (psi)	110 - 120 (1 595 - 1 740)	110 - 120 (1 595 - 1 740)
Tool diameter, mm (in)	70 (2.7)	75 (2.9)
Noise level (dB)	125	127
Excavator weight, t (lb)	4 - 8 (1 7636 - 3 0864)	5 - 10 (11 023 - 22 046)