

Protective Agent for Machinery and Equipment

DESCRIPTION



TamCrete EasyClean is an odourless, non-toxic, skin-friendly, environmentally-friendly and biodegradable protective agent for mechanical equipment being used for sprayed and in-situ concrete and grouting applications. TamCrete EasyClean prevents the build-up of cement laitance and rebound from bonding to steel and rubber surfaces, ensuring that equipment remains in an as-new condition when jet-washed.

KEY BENEFITS

- > Simple and easy to apply
- > Non-toxic and environmentally-friendly
- > Non-flammable
- > Protects machinery and equipment from hardened concrete build up
- > Suitable with all types of concrete pumping and spraying machines
- > Does not damage materials like steel, aluminum, glass, rubber or paint
- > Prevents moving parts from seizing
- > Anti-corrosion effect on metal surfaces
- > Makes cleaning easier

TYPICAL APPLICATIONS

- > Concrete pumps
- > Sprayed concrete equipment
- > Grouting equipment
- > Batching plants and transport / mixer trucks

TECHNICAL DATA

TamCrete EasyClean	
Form	Liquid
Colour	Clear
Density (g/cm ³)	0.84 ± 0.02
Solubility in Water	Insoluble
All at 20°C	

All technical data stated herein is based on tests carried out under laboratory conditions.

APPLICATION GUIDELINES

Using an airless sprayer, spray a thin coating to all moving parts and areas of equipment exposed to possible cement laitance, spillage and sprayed concrete rebound. After concreting has finished, jet-wash down the machine in order to keep it in an as new condition.

For equipment already having hardened deposits of concrete and cement laitance, remove these using TamCrete CR prior to application.

PACKAGING

TamCrete EasyClean is supplied in drum, barrel, and IBC. Packaging size may vary subject to local regulations and requirements, please contact your local Normet representative for more details.

STORAGE

TamCrete EasyClean should be stored at room temperature, kept dry and out of direct sunlight. If these conditions are maintained and the product packaging is unopened, then a shelf life of one year can be expected.

HEALTH & SAFETY

TamCrete EasyClean should only be used as directed. We always recommend that the Safety Data Sheet (SDS) is carefully read prior to application of the material. Our recommendations for protective equipment should be strictly adhered to for your personal protection. The Safety Data Sheet is available upon request from your local Normet representative.