

XQUICK

QUICK COUPLERS FOR AUTOMATIC TOOL CHANGES

High-grade steel
with adjustable mounting
for most excavators.

Swift, secure attachment
with a single cylinder movement;
no messy hose couplings.

Hardened pins
and precision-fit design
minimize wear.

**Locking bolts and
H-cylinder**

with double hose break valves
ensure secure attachment
even at full pressure.

**OQLS operator
support system**
for safe and efficient tool
changes.

**Distributes hydraulic oil,
grease, water, and electricity.**



In cooperation with



Xquick couplers streamline attachment connections to booms, optimizing fleet costs while boosting productivity. Automatic hose closure and dust-protected oil connections promote cleanliness and safety, ensuring smoother operations.

SPECIFICATIONS

Quick coupler with 2 parallel hydraulic cylinders

Max. working pressure 350 Bar/ 5,080 Psi

Load-bearing hose break valves Yes

Pressure control valves Yes

Leak-free quick couplers made of steel

Coupling sizes	1/2"	3/4"	1"
Oil flow at 30 Bar pressure loss (l/min)	70	140	250
Oil flow at 30 Bar pressure loss (gal/min)	18	37	66
Max. continuous working pressure (Bar)	350	350	350
Max. continuous working pressure (Psi)	5,080	5,080	5,080
No. of couplings	2	2	2



Normet Breaker Boom model	Lifting force with XG 15D Grapple, kg	Largest hammer
X46-480	2316 (5106 lb)	XB27
X46-590	1398 (3082 lb)	XB27
X46-670	685 (1510 lb)	XB23
X86-550	2374 (5234 lb)	XB32
X86-640	845 (1863 lb)	XB23
X86-790	845 (1863 lb)	XB23
X66-980	2788 (6146 lb)	XB45
X66-1050	2075 (4575 lb)	XB45
X66-1220	953 (2101 lb)	XB32
X66-1410	699 (1541 lb)	XB27
X68-900R	4626 (10199 lb)	XB45
X68-1050R	2995 (6603 lb)	XB45
X68-1150R	2995 (6603 lb)	XB45
X68-1250R	2282 (5031 lb)	XB45
X68-1450R	1160 (2557 lb)	XB32
X68-1550R	508 (1120 lb)	XB23
X88-540R	743 (1638 lb)	XB23
X88-650R	743 (1638 lb)	XB23