

Dulux®

AcraTex®

AcraGuard

Masonry coatings have never been easier




Self Priming



AcraGuard is self priming on new masonry surfaces such as new fibre cement cladding, and Tilt-Up / Pre-Cast Concrete when used with Dulux® Acratex® BondFree Concentrate to prepare the surface.

10m²/L Coverage



AcraGuard is designed to cover large areas of new masonry surfaces, while delivering the protection of a high film build coating.

Higher Film Build Protection



	Wet Film Thickness Per Coat	Dry Film Thickness Per Coat
AcraGuard	100 Micron	41 Micron
	+42% Thicker	+70% Thicker
Standard Exterior Paint	70 Micron	24 Micron

Extended wet edge increases open time for reduced roller lap marks and picture framing

Accommodates small crack movement of **0.28mm** (3.5 x Dry Film Thickness (DFT))



Tilt & Pre-Cast Concrete

Pairing with **Acratex® BondFree Concentrate** allows fast & easy protection of new concrete walls. BondFree Concentrate is a water dilutable cleansing solution designed to remove barrier-type form release agents (bond breakers) from concrete panels prior to coating.



AcraGuard Application

AcraGuard has been formulated to ensure fast and easy application.

- **Self priming** on clean new masonry surfaces
- **Extended wet edge** - more time to apply
- **Ease of application** - reduced roller marks and picture framing



41 Micron Dry Film Thickness per coat



Tintable to thousands of Dulux colours



10 year warranty*



3 hour re-coat

*A 10 year material warranty is issued on product performance when Dulux Acratex AcraGuard has been applied according to the product specification, spreading rates and surface preparation details outlined in the Dulux Acratex Specification Manual or relevant DuSpec+ specification. Dulux Acratex warrants that the coating system will retain its film integrity and not peel or crack as a result of faulty manufacture or formulation.

Fibre Cement Cladding

AcraGuard is the perfect solution for protecting new **express jointed or lap jointed fibre cement cladding**. It is self priming so there's no need for an additional primer. And with a 10sqm per Litre coverage, you can cover large areas of fibre cement cladding with two fast & easy coats.



Dulux®**Acratex®**

AcraGuard Topcoat Product Range

Product Name	Base	Gloss	Size	Coats	Recoat Time	Coverage m ² Per Pail	Wet Film Build Using Nap Roller (Microns Per Coat)	Dry
Acratex AcraGuard VW	Vivid White							
Acratex AcraGuard DTB	Deep							
Acratex AcraGuard UDTB	Ultra Deep	Matt	15L	2	3hrs	150	100	41
Acratex AcraGuard EBTB	Extra Bright							

AcraGuard Coating Systems

System Description	Substrate	Process			DuSpec+ Specification Number
		Surface Prep	Base Coat	Topcoat	
Self Priming Systems	Express Jointed / Lap Jointed Fibre Cement Cladding	Direct to Substrate on clean, new fibre cement cladding	AcraGuard	AcraGuard	AUAC02694 AUAC02688
	New Off Form, Pre-Cast, Tilt-Up Concrete	Dulux Acratex BondFree Concentrate	AcraGuard	AcraGuard	AUAC02427
Texture Systems	Fibre Cement Cladding where a texture effect is desired	Prime Joints, fill & seal with paintable polyurethane joint sealant	Acratex Sedona	AcraGuard x 2 coats	AUAC01425



Learn more at **acratex.com.au**

Customer Service **13 23 77**

Dulux Acratex is a division of DuluxGroup (Australia) Pty Ltd. ABN 67 000 049 427.

Dulux, Acratex are registered trade marks of DuluxGroup (Australia) Pty Ltd