

System Overview

Application

Found on both new and old buildings this substrate is constructed with many types of bricks and blocks. All, with the exception of hard fired glazed bricks, provide good adhesion for Dulux AcraTex coating systems. Brick and block work is laid in cement mortar joints that can be finished with a rolled joint (curved shallow recess), a raked joint (square recess) or a flush joint (flush to surface).

Description

Rendered brick and block has been the cornerstone of the Australian building industry. Since the inception of Dulux Acratex we have been offering texture coating systems designed specifically for the long term protection of brick and block building substrates.

Dulux Acratex has the performance coating soutions to deliver long term protection of facades.

When specifying your next project it makes sense to protect it against the harsh elements. That's why Dulux promotes the Acratex systems, designed to give you maximum design flexibility and maintain the coating's good looks now and for years to come.

Dulux Acratex Coating Systems

When you specify a Dulux Acratex Coating System, you immediately get the peace of mind that comes from using a proven system from a company with the reputation of Dulux.

Benefits of the Acratex Coating System



Resistant to mould and dirt pick up



Resistant to atmospheric pollution and protects from UV radiation, moisture and salt air



Available in a wide range of Australia's most popular Dulux colours



Easy to clean and maintain



Weather resistant

CLAY BRICKS, CEMENT BRICK & BLOCK



BASECOAT

Dulux Acratex RenderWall AcraBuild Coarse

Acrabuild Coarse is a pre-packaged, dry mix cement render used as a low/medium build levelling coat over brick and block in a single pass application.



Trowel



Thickness

Min DFT DFT 4000 6000 microns microns

For more product details, scan or click the QRcode



SEALER COAT

Dulux Acratex Green Render Sealer

Green Render Sealer is a water-based primer/sealer for preparation of fresh masonry surfaces to minimise efflorescence migrating through the coating system.



Nap roller with yoke frame



Thickness Recomm WFT 125 microns



product details scan or click the QR code



TEXTURE COATING

Dulux Acratex Texture coating selected to desired aesthetic requirements

Example shown here: **COVENTRY COARSE**



Trowel



Thickness Min

DET

1000

Min WFT 1333 microns microns



product details, scan or click the QRcode



PROTECTIVE COATING

Dulux Acratex AcraShield 2 COATS

The AcraShield system is a multilayered protective, high build elastomeric membrane coating, which protects against all climatic conditions and environmental pollutants.



Naproller with yoke frame



Min Min WFT 167



product details, scan or click the QR code





Refer to DuSpec+ AUAC02656 for full coating system specification Click here to access

For further information visit <u>acratex.com.au</u> or call **13 23 77**

Disclaimer: Any advice, recommendation, information, assistance or service provided by Dulux Acratex in relation to goods manufactured by it or their use and application is given in good faith and is believed by Dulux Acratex to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Dulux Acratex is provided without liability or responsibility.

Dulux Acratex is a division of DuluxGroup (Australia) Pty Ltd. ABN 67 000 049 427. Dulux, Acratex, AcraBuild, AcraShield, Coventry RenderWall, AcraBuild and DuSpecPlus are registered trade marks of DuluxGroup (Australia) Pty Ltd.

