# **Dulux**<sup>®</sup>



# CABINET DOORS EASY HOW-TO PROJECT GUIDE

# Dulux Mt Aspiring Half Dulux NOVATION

# **CABINET DOORS**

Dulux<sup>®</sup> Renovation Range Cabinet Doors provides the smart way to rejuvenate your kitchen cabinet doors and can be applied to laminate, melamine and wooden doors.



#### EXPERT TIP

When painting over dark colours or timber with white or a light colour, you may require more than 2 coats, so make sure you calculate how much paint you need before you start your project.

# Preparation

Dulux Renovation Range Cabinet Doors requires a clean surface to adhere. All grease and dirt contamination MUST be removed, or the paint will not adhere and will peel or flake off.

## **Previously Painted Surfaces:**

On ALL surfaces cleaning is the most important step.

- Scrub down all areas with Selleys® Sugar Soap and rinse with clean water to remove any dirt, oil or grease. Use a plastic scouring pad on heavily contaminated surfaces.
- Repeat this process using clean water, at least twice.

IMPORTANT: Do not use abrasive cleaning detergents.

- Mask as required using a good quality painters tape.
- Completely remove any loose and flaking paint. Fill any cracks or holes with a suitable acrylic water based filler such as Selleys<sup>®</sup> Spakfilla<sup>®</sup> Rapid<sup>™</sup>.
- Sand glossy and semi gloss finishes to a dull flat finish using p400 paper before coating.
- Use a clean damp cloth to remove any dust.

## Kitchen, Bathroom & Laundry Cabinets

Including laminate and varnished timber.

Remove doors for easy coating of edges and door surrounds.

Follow preparation as per Previously Painted Surfaces above.

## Wooden Cabinet Doors & Kick Boards

Follow preparation as per Previously Painted Surfaces above.

If there are any breaks or scratches in the coating, apply *Dulux* PRECISION® Stain, Smoke & Odour Blocker spraypack before topcoat.

#### Vinyl and Plastic Wrapped Cabinet Doors & Panels

Follow preparation as per Previously Painted Surfaces above.

# Mixing

For both primer and topcoat, add all of the additive found under each blue lid to each of the cans. Stir well for approximately 2-5 minutes with a broad flat paddle, using an up and down scooping action until the additive is completely mixed into the paint.

Once mixed the product is suitable to use for up to 10 days.



Clean



Stir well before use

# Application

#### Primer

Apply 1 coat of *Dulux* Renovation Range Primer to the surface following the instructions on pack, and allow to fully dry for 8 hours before applying your topcoat.

#### Topcoat

- Cut in as necessary using a 38–50mm high quality angled sash cutter brush and 4mm nap 100mm wide microfibre roller.
- 2. Coat surface using a 4mm nap 100mm wide microfibre roller.
- Lay off. Once each section is coated, gently go over the surface in the same direction with an unloaded roller using minimal pressure. This will give a smooth consistent finish.

#### Clear Coat

For best finish on cabinet door areas apply Dulux Renovation Range Clear Coat as the final coating. This will add a layer of protection to the Dulux Renovation Range topcoat.







Roll on primer, topcoat and then clear coat

# Check out the video at dulux.co.nz/paint/renovation-range

# THE PERFECT RENOVATION SYSTEM

This revolutionary range works as a three step system. For the best possible result, ensure you always follow all three steps.\*

**3. FINAL TOUCHES** 1. CLEAN & PREP 2. TOPCOAT Dulux RENOVATION SELLEYS Dulux RENOVATION Dulux RENOVATION Cleaning & Prep Topcoat Clear Coat<sup>+</sup> Clean with Sellevs® Sugar Cabinet Doors. Available in satin and Soap and prep with gloss clear coat.

# NEED HELP & ADVICE?

CALL: NZ 0800 800 424

Renovation Range Primer.

ONLINE & LIVE CHAT: dulux.co.nz



For 'How To' videos, helpful tips and more, scan here!

#### FRONT COVER: Tiles: Dulux Renovation Range Cabinet Doors in Dulux Mt Aspiring Half.

Disclaimers: Colours shown are as close as possible to actual paint colours. Please note, due to limitations of the printing process, photographic and printed images may not represent the true colour. Always confirm your choice with a *Dulux* Sample Pot.

"For full use instructions please see the *Dulux* website and review the Data Sheet, Application and FAO information. "The *Dulux* Renovation Range Floor product does not require a clear coat as it will reduce the non-slip performance.

Registered trade mark information: Dulux, Worth doing, worth Dulux, PRECISION, Selleys and Spakfilla are registered trade marks. Rapid and Natural White are trade marks of DuluxGroup (Australia) Pty Ltd. DX3201