

Worth doing, worth Dulux.

LOVE YOUR BATHROOM WITH DULUX® RENOVATION RANGE

Project Guide

A step-by-step guide on how to refresh your bathroom shower base

Dulux Diplomatic

Dulux

RENOVATION

Dulux Vivid White™

Dulux

RENOVATION

Dulux RENOVATION **Dulux** Vivid White™

REIMAGINE Your space

Dulux Diplomatic



Dulux

Everything you need to get the job done!



SHOPPING LIST Cleaning cloth Scouring Pad Selleys" sugar soap Selleys" Silicone Remover Painters' tape 38-50mm angled sash cutter 4mm nap, 100mm wide microfibre roller & tray Paint stirrer Dulux" Renovation Range Primer Dulux" Renovation Range Floors, in your chosen colour and sheen





Choose Dulux[®] Renovation Range FLOORS to transform your shower base in 3 steps.



STEP 1: PREP

- Remove all silicone with Selleys Silicone Remover. Post clean with a scouring pad.
- Remove all grease and dirt with Selleys sugar soap.
- Mask any edges and surfaces you don't want painted.



STEP 2: PRIME

- Ensure surface is dry.
- Cut-in using a sash brush around edges.
- Apply one coat of Dulux* Renovation Range Primer with a microfibre roller
 4mm nap, 100mm wide.
- Allow to dry for at least eight hours.



STEP 3: TOPCOAT

- Add all of the additive, found underneath the lid, to the Dulux[®] Renovation Range Floors topcoat.
- Stir well using a lifting motion for 2–5 minutes.
- Cut-in using a sash brush around edges.
- Coat surface using a 4mm nap, 100mm wide microfibre roller.
- Apply at least two coats, allowing at least eight hours before re-coating.

NOTE: Ensure safety and application directions are followed as per product labels.

RETURN TO USE: Light use after 2 days (including running water and foot traffic). General use after 7 days (with normal exposure to water, soap and foot traffic).

Popular colour schemes

Dulux	Dulux [.]
Vivid White™	Diplomatic
Dulux	Dulux [.]
White Polar Quarter	Mornington Half
Dulux	Dulux
Snowy Mountains Half	Grass Sands



How-to make the most out of your paint and accessories

If you're completing your painting project over a few days:

To keep your paint fresh simply put the lid back on your tin and store in a cool, dry area.

To get the most out of your accessories including brush and roller, cover with foil or plastic wrap to avoid washing and wasting paint. Note: if using water based paint you can wash your accessories in a bucket with water. If solvent based, mineral turpentine is required.

If you've completed your painting project:

You've got a little bit of paint left in the tin? There's a few options:



Paintback takes unwanted paint and packaging and responsibly disposes of it, diverting it from landfill and vital waterways.





Scan me to find a local Paintback location



Step 1

Simply scoop the desired amount of waste hardener into the paint tin and stir until paint solidifies.

For easy disposal of water based paint, Dulux Envirosolutions Waste Paint Hardener is a great option. This handy product turns unwanted water based paint back into

Step 2

Leave for 2 hours with the lid off.

Step 3

Wrap hardened paint in newspaper and dispose of as hard waste. The clean, paint free tin can also be disposed of in recycled waste, providing a sustainable option to minimise the environmental impacts of paint products.



Save your accessories for next time! Simply give them a good clean. If you've used water-based paint you can clean your brushes in a bucket of water to remove most of the paint, ready for use next time.

Note: for solvent based paint, mineral turpentine is required.

solid waste for easy and safe household disposal in 3 steps:

Need a hand? Dulux[®] is here to help



Scan me for LiveChat

Ask an expert. Speak to one of our consultants for help about colour, products, projects and more.