

DULUX ACRATEX COATING SYSTEM FOR

FIBRE CEMENT WITH EXPRESS JOINT

PROTECTIVE COATING: ACRAGUARD



System Overview

Application

Fibre Cement (FC) façade panels are versatile for all segments of the construction industry. They are suitable for new housing, alterations and additions, high & low-rise multi-residential dwellings, and freeway noise barriers. FC panels are non-load bearing external wall solutions, providing durability, fire resistance, and sound insulation.

Description

Fibre cement sheet is manufactured from Portland cement, ground sand, cellulose fibre, water and additives.

Compressed fibre cement is manufactured under high pressure to increase density and strength and are used on commercial facades.

Dulux Acratex has the performance coating solutions to deliver long term protection of facades.

When specifying your next project it makes sense to protect it against the harsh elements. That's why Dulux promotes the Acratex systems, designed to give you maximum design flexibility and maintain the coating's good looks now and for years to come.

Dulux Acratex Coating Systems

When you specify a Dulux Acratex Coating System, you immediately get the peace of mind that comes from using a proven system from a company with the reputation of Dulux.

Benefits of the Acratex Coating System



Resistant to mould and dirt pick up



Protects from UV radiation



Available in a wide range of Australia's most popular Dulux colours



Easy to clean and maintain



Weather resistant

FIBRE CEMENT WITH EXPRESS JOINT

PROTECTIVE COATING


PROTECTIVE COATING

Dulux Acratex AcraGuard
2 COATS

AcraGuard is a pigmented, water based 100% acrylic coating that is designed as a self priming top coat to overcoat masonry substrates.



Nap roller
with yoke frame



Thickness

Min WFT 100 microns	Min DFT 41 microns
------------------------------	-----------------------------



For more
product details,
scan or click the
QR code



Colour shown: New Fawn
Light Reflection Value: 60

When using dark colours, thermal stresses will increase on the coated substrate and additional control joints should be considered



Refer to DuSpec+ [AUAC02431](#)
for full coating system specification
[Click here to access](#)

For further information visit acratex.com.au or call **13 23 77**

Disclaimer: Any advice, recommendation, information, assistance or service provided by Dulux Acratex in relation to goods manufactured by it or their use and application is given in good faith and is believed by Dulux Acratex to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Dulux Acratex is provided without liability or responsibility.

Dulux Acratex is a division of DuluxGroup (Australia) Pty Ltd. ABN 67 000 049 427. Dulux, Acratex and DuSpecPlus are registered trade marks of DuluxGroup (Australia) Pty Ltd.

