


DECORATIVE FINISHES

A contemporary range of decorative effects to transform and personalise your space











Understated Charm



Tranquil Haze













SHOPPING LIST Dulux Concrete Finish 4L Drop sheet Selleys Sugar Soap 100mm synthetic brush for cutting in Long nap synthetic roller Roller tray Paint stirrer Painter's tape Steel trowel 600 grit sandpaper	Everything you need to get the job done!	
Drop sheet Selleys Sugar Soap 100mm synthetic brush for cutting in Long nap synthetic roller Roller tray Paint stirrer Painter's tape Steel trowel	SHOPPING LIST	
Selleys Sugar Soap 100mm synthetic brush for cutting in Long nap synthetic roller Roller tray Paint stirrer Painter's tape Steel trowel	Dulux Concrete Finish 4L	
100mm synthetic brush for cutting in Long nap synthetic roller Roller tray Paint stirrer Painter's tape Steel trowel	Drop sheet	
cutting in Long nap synthetic roller Roller tray Paint stirrer Painter's tape Steel trowel	Selleys Sugar Soap	
Roller tray Paint stirrer Painter's tape Steel trowel	-	
Paint stirrer Painter's tape Steel trowel	Long nap synthetic roller	
Painter's tape Steel trowel	Roller tray	
Steel trowel	Paint stirrer	
	Painter's tape	
600 grit sandpaper	Steel trowel	
	600 grit sandpaper	

Step 1: Choose your colour

 Choose from our curated range of colours or LiveChat for free personalised colour advice.

Step 2: Prep

- · Clean your walls.
- If you have any cracks or holes, fill them with the appropriate filler.
- Sand them back, wipe them down and spot prime where needed.
- · Mask around the edges.

Step 3: Topcoat

- Stir Dulux Concrete Effect thoroughly prior to use.
- Work in small sections. Use a long nap roller to apply to the wall.
- Smooth the surface with a steel trowel with broad, sweeping strokes.
- Apply 3 coats using the same process. The final coat should dry for at least 2 hours, but no longer than 24 hours, before polishing. To polish, use 600 grit sandpaper in a circular motion.





WATCH THE CONCRETE HOW-TO VIDEO



TIP:

Apply enough pressure to keep the trowel edge flat against the surface. Be careful not to gouge the surface with the edge of the trowel.



How to re-use and reduce wastage while painting

Responsibly dispose of your paint



1. PaintBack

Take your paint tin with leftover paint to your local Paintback collection site – there are over 160 nationally!

Paintback takes unwanted paint and packaging and recycles or otherwise responsibly disposes of it, diverting it from landfill and vital waterways.





Scan me to find a local Paintback location



2. Recycle your tin with waste paint hardener

Easy disposal of paint

Dulux Envirosolutions Waste Paint Hardener is a great option. This handy product turns unwanted water-based paint back into solid waste for easy and safe household disposal in 3 steps:

Step 1

Simply scoop the desired amount of waste hardener into the paint tin and stir until paint solidifies.

Step 2

Leave for 2 hours with the lid off.

Step 3

Wrap hardened paint in newspaper and dispose of as hard waste. The clean, paint free tin can also be disposed of in recycled waste, providing a sustainable option to minimise the environmental impacts of paint products.



Re-use accessories



Save your accessories for next time! Simply give them a good clean. If you've used water-based paint you can clean your brushes in a bucket of water to remove most of the paint, ready for use next time.

Note: for solvent-based paint, mineral turpentine is required.

Need a hand? Dulux is here to help



Scan me for LiveChat

Ask an expert. Speak to one of our consultants for help with colour, products, projects and more.



Scan me for all the project advice you need, including:

- Shopping list
- Colour schemes
- How-to guide

