

Dulux®

RENOVATION RANGE

TRANSFORMATION MADE EASY

BENCHTOPS

EASY HOW-TO PROJECT GUIDE



Dulux
Maraetai



BENCHTOPS

Dulux® Renovation Range Tiles & Benchtops is a revolutionary, water based interior coating perfect for transforming your benchtop.

Shopping List

- ✓ Dulux® Renovation Range Tiles & Benchtops in your chosen colour
- ✓ Dulux® Renovation Range Clear Coat
- ✓ Dulux® Renovation Range Primer
- ✓ 38–50mm high quality angled sash cutter
- ✓ 4mm nap 100mm wide microfibre roller
- ✓ Paint stirrer and drop sheet
- ✓ Painters tape
- ✓ P400 sanding paper
- ✓ Selleys® Sugar Soap
- ✓ Selleys® Silicone Remover
- ✓ Selleys® Rapid Mould Killer™

EXPERT TIP

For best results, use Renovation Range Primer before the topcoat. Remember, using poor quality or worn rollers can affect the final finish achieved. Make sure you use a 4mm nap roller to get the best finish.

Preparation

Dulux Renovation Range Tiles & Benchtops requires a clean surface to adhere. All grease and dirt contamination **MUST** be removed, or the paint will not adhere and will peel or flake off.

Previously Painted Surfaces:

On ALL surfaces cleaning is the most important step.

- Scrub down all areas with Selleys® Sugar Soap and rinse with clean water to remove any dirt, oil or grease. Use a plastic scouring pad on heavily contaminated surfaces.
- Repeat this process using clean water, at least twice.

IMPORTANT: Do not use abrasive cleaning detergents.

- Completely remove any loose and flaking paint. Fill any cracks or holes with a suitable hard epoxy based filler such as Selleys® Knead-IT® Aqua.
- Sand glossy and semi gloss finishes to a dull flat finish using p400 paper before coating.
- Use a clean damp cloth to remove any dust.

Laminate & Melamine Benchtops:

- Clean using Selleys® Rapid Mould Killer™.
- Remove all silicone sealant from joints on all surfaces using Selleys® Silicone Remover.
- Wash down well with water.
- Sand with p400 paper in all areas where silicone has been removed.

- Wash with Selleys® Sugar Soap.
- Rinse with clean water and dry with a clean cloth.
- Use a stainless steel wool pad to lightly abrade laminate surfaces.
- Use a clean damp cloth to remove any sanding dust. Mask using a good quality painters tape.

Vinyl & Plastic Surfaces

Follow preparation of laminate benchtops.

Mixing

For both primer and topcoat, add all of the additive found under each blue lid to each of the cans. Stir well for approximately 2-5 minutes with a broad flat paddle, using an up and down scooping action until the additive is completely mixed into the paint.

Once mixed the product is suitable to use for up to 10 days.



Sand surface



Add the additive and stir well

Application

Primer

Apply 1 coat of *Dulux* Renovation Range Primer to the surface following the instructions on pack, and allow to fully dry for 8 hours before applying your topcoat.

Topcoat

After the additive has been added and stirred, apply at least two coats of *Dulux* Renovation Range Tiles & Benchtops ensuring that the previous coat is left for a minimum of 8 hours before recoating.

1. Cut in as necessary using a 38–50mm high quality angled sash cutter brush.
2. Coat surface using a 4mm nap 100mm wide microfibre roller.
3. Lay off. Once each section is coated, gently go over the surface in the same direction with an unloaded roller using minimal pressure. This will give a smooth consistent finish.

Clear Coat

On Benchtop and Splashback areas apply *Dulux* Renovation Range Clear Coat as the final coating. This will add a layer of protection to the *Dulux* Renovation Range topcoat.



Clean with a damp cloth



Roll on primer, topcoat and then clear coat

Check out the video at dulux.co.nz/paint/renovation-range

THE PERFECT RENOVATION SYSTEM

This revolutionary range works as a three step system. For the best possible result, ensure you always follow all three steps.*

1. CLEAN & PREP



Cleaning & Prep

Clean with Selleys® Sugar Soap and prep with Renovation Range Primer.

2. TOPCOAT



Topcoat

Tiles & Benchtops.

3. FINAL TOUCHES



Clear Coat†

Available in satin and gloss clear coat.

NEED HELP & ADVICE?



CALL:
NZ 0800 800 424



ONLINE & LIVE CHAT:
dulux.co.nz



For 'How To' videos,
helpful tips and more,
scan here!

FRONT COVER: Benchtop: **Dulux Renovation Range Tiles & Benchtops** in *Dulux Maraetai*.

Disclaimers: Colours shown are as close as possible to actual paint colours. Please note, due to limitations of the printing process, photographic and printed images may not represent the true colour. Always confirm your choice with a *Dulux* Sample Pot.

*For full use instructions please see the *Dulux* website and review the Data Sheet, Application and FAQ information. †The *Dulux* Renovation Range Floor product does not require a clear coat as it will reduce the non-slip performance.

Registered trade mark information: Dulux, Worth doing, worth Dulux, Selleys and Knead-IT are registered trade marks and Rapid Mould Killer is a trade mark of DuluxGroup (Australia) Pty Ltd.

DX3200