

# Smart office assistant

Harnessing the power of the cloud, these smart multifunction printers automate everyday document processes, leaving you free to focus on your core business activities.

## Intelligent workflow tools:

- Intuitive user interface
- Ricoh Smart apps
- Cloud-share services
- Smartphone connection

Ricoh's super-sized 10.1 inch Smart Operation Panel is host to a suite of intelligent workflow tools. Pre-installed Smart apps, such as ID Card Copy, automate time-consuming processes. More applications can be installed on demand. It is easy to print from and scan to smartphones and tablets, and critical documents can be scanned in color directly to DropBox™ or Sharepoint™.

### Simply more productive:

- 37 & 45 ppm print speeds (letter)
- 14 68 lb. Bond (52 256 gsm)
- Large paper capacity
- Offline stapler option



To save time, double-sided originals are scanned in a single pass. The first immaculate 1200 dpi print is ready in under 6 seconds. Multipage documents are produced at speeds of 37 or 45 pages per minute and can be quickly collated using the Offline Stapler option. The optional High Capacity Paper Trays further enhance productivity. It is easy to print onto envelopes and labels. And, with the printer switching from one tray to another, you need never run out of paper.

Despite their advanced functionality, Ricoh's new multifunction printers are surprisingly easy to set up and support. With their compact design and quiet operation, they are a perfect fit for every office. Ricoh's installation wizard simplifies setup. To safeguard information, they support tap and go authentication and confidential documents can be securely locked, pending release. Clever energy saving features reduce power consumption and contribute to a low total cost of ownership.

#### A friendly and affordable solution:

- Space saving design
- Secure authentication
- Confidential printing



# **RICOH IM 350F/IM 430F/IM 430Fb**

MAIN SPECIFICATIONS

	RICOH IM 350F	RICOH IM 430F	RICOH IM 430Fb
GENERAL			
Warm-up time	Quick Mode: 23 seconds Without Quick Mode: Less than 47.4 seconds	Quick Mode: 24 seconds Without Quick Mode: Less than 49.3 seconds	Quick Mode: 24 seconds Without Ouick Mode: Less than 49.3 seconds
First output speed: B/W	5.4 seconds (A4 / LT SEF)	4.5 seconds (A4 / LT SEF)	4.5 seconds (A4 / LT SEF)
Continuous output speed	37 ppm	45 ppm	45 ppm
1emory: standard	2 GB		
lemory: maximum	2 GB		
IDD: standard	320 GB		
IDD: maximum	320 GB		
PDF capacity	50 sheets		
Veight	67.24 lbs. (30.5 kg)		
Dimensions: W x D x H	18.7" x 17.4" x 20.1" (476 x 442 x 510 mm)		
ower source	120-127V/12A 60Hz		
OPIER (STANDARD)			
fultiple copying	Up to 999 copies		
Copy resolution: maximum	600 x 600 dpi		
oom	From 25% to 400% in 1% steps		
RINTER (STANDARD)			
PU	Intel Atom Processor Bay Trail 1.46GHz		
rinter language: standard	PCL5e, PCL6, PostScript 3 (emulation), PDF direct (emulation	n)	
rinter language: option	Genuine Adobe® PostScript® 3™, IPDS, PDF Direct from Adol	be <sup>®</sup>	
rint resolution: maximum	1,200 x 1,200 dpi		
letwork interface: standard	Ethernet 10 base-T/100 base-TX/1000 base-T, USB Host 2.0		
etwork interface: option	Wireless LAN (IEEE 802.11a/b/g/n), Additional NIC (2nd port)	), Extended USB Board, File Format Converter	
Nobile printing capability	Apple AirPrint™, Mopria, Google Cloud Print, NFC, Ricoh Sr	mart Device Connector	
letwork protocol	TCP/IP (IP v4, IP v6)		
Vindows <sup>®</sup> environments	Windows® 7, Windows® 8.1, Windows® 10, Windows® Sen	ver 2008, Windows® Server 2008R2, Windows® Server 2012,	Windows® Server 2012R2, Windows® Server 2016
Aac OS environments	Macintosh OS X v10.10 or later		
JNIX environments	UNIX Sun <sup>®</sup> Solaris, HP-UX, SCO OpenServer, RedHat <sup>®</sup> Linux,	IBM® AIX, Citrix XenApp	
AP® environments	SAP® R/3®, SAP® S/4®		
Other supported environments	NDPS Gateway, AS/400® using OS/400 Host Print Transform	, IBM iSeries	
CANNER (STANDARD)			
canning: B/W	45.7 ipm		
canning: full color	45.7 ipm		
lesolution: maximum	600 dpi		
Compression method	TIFF (MH, MR, MMR, JBIG2), Grayscale		
ile formats	Single Page TIFF, Single page JPEG, Single page PDF, Single p page PDF/A	age High compression PDF, Single page PDF/A, Multi page TIF	F, Multi page PDF, Multi page High compression PDF, Mul
can modes	E-mail, Folder, USB, SD Card		
AX (STANDARD)			
ircuit	PSTN, PBX		
ransmission speed	2 seconds (200x100 dpi, JBIG, ITUT #1 chart TTI off, memory	y transmission)	
Nodem speed: maximum	33.6 Kbps		
esolution: standard	8x7.7 line per mm, 200x200 dpi		
ompression method	MH, MR, MMR, JBIG		
canning speed	28 spm		
Nemory: standard	4 MB (Approx. 320 pages)		
Memory: maximum	4 MB (Approx. 320 pages)		
APER HANDLING			
Recommended paper size	Standard paper tray(s): 5.5" x 8.5" - 8.5" x 14" (A6-A4, B6- Optional paper tray(s): 5.5" x 8.5" - 8.5" x 14" (A6-A4, B6- Bypass tray: 5.5" x 8.5" - 8.5" x 14" (A6-A4, B6-B5) Custon		i.43" (127 - 900 mm)
Paper input: standard	500 sheets		
aper input: maximum	2,100 sheets		
Paper output: standard	250 sheets		

Trays: 14 - 58 lb. Bond (52 - 220 g/m²) Bypass: 14 - 68 lb. Bond (52 - 256 g/m²) Duplex: 14 - 43 lb. Bond (52 - 162 g/m²)

Plain, Recycled, Special, Colored, Letterhead, Cardstock, Pre-printed, Bond, Coated, Envelope, Label, OHP

Paper weight

Paper types

# RICOH IM 350F/IM 430F/IM 430Fb

MAIN SPECIFICATIONS

	RICOH IM 350F	RICOH IM 430F	RICOH IM 430Fb		
ECOLOGY					
Power consumption: Maximum (kW)	Less than 1,380 W				
Power consumption: operation	566 W	628 W	628 W		
Power consumption: ready	91 W				
Power consumption: sleep	0.7 W	0.74 W	0.74 W		
TEC1	0.46 kWh	0.57 kWh	0.57 kWh		
ENERGY STAR <sup>®</sup>	Certified				
EPEAT®	Gold Rated*				
	* EPEAT Gold rating is applicable only in the USA.				
OUTPUT TRAYS					
1 x 250-sheet Paper Tray (PB 1110)	Paper size: 5.5" x 8.5" - 8.5" x 14" (A6-A4, B6); Paper weight: 14-58 lb. Bond (52-220 g/m²)				
1 x 500-sheet Paper Tray (PB 1120)	Paper size: 5.5" x 8.5" - 8.5" x 14" (A6-A4, B6-B5); Paper weight: 14-58 lb. Bond (52-220 g/m²)				

#### OTHER OPTIONS

IPDS Unit Type M34, Offline Stapler Type M34, PostScript 3 Unit Type M34, IEEE 802.11 Interface Unit Type M24, USB Device Server Option Type M19A, File Format Converter Type M19, OCR Unit Type M13, Page Keeper Type M28, Extended USB Board Type M19, Medium Cabinet Type P, Tall Cabinet Type Q, Caster Table Type M34, Optional Counter Interface Unit Type M12, NFC Card Reader Type M27

## CONSUMABLE

	Starter Supplies	Yield (CTN)
RICOH IM 350F		
Print Cartridge IM 350	14,000	14,000
Refill Staple Type M34		5,000
RICOH IM 430F		
Print Cartridge IM 430	17,400	17,400
Refill Staple Type M34		5,000
RICOH IM 430Fb		
Print Cartridge P 501H		14,000
Print Cartridge P 501L	6,000	3,000
Refill Staple Type M34		5,000
Drum Unit P 501		40,000
Maintenance Kit P 501		120,000

<sup>&</sup>lt;sup>1</sup> TEC value is measured based on the ENERGY STAR Ver. 3.0 test method.

Some options may not be available at the time of market release.

Specifications are subject to change without notice.

For maximum performance and yield, we recommend using genuine Ricoh parts and supplies.

Some features may require additional options and/or charges.

# Ricoh USA, Inc.

300 Eagleview Boulevard Exton, PA 19341



1-800-63-RICOH



www.ricoh-usa.com

