

AUFW00095 Feast Watson Wet Look Deck

Introduction

Part A
563W0093

Description and Image

Feast Watson Wet Look Deck is a timber finish that provides a freshly coated 'wet look' for decking, fences, steps, walkways, pergolas, furniture and all other exterior timber. Wet Look Deck is convenient to apply as it is fast drying, has low odour and all application equipment can be cleaned up with water. The unique formula of Wet Look Deck penetrates to nourish timber more effectively than standard acrylic water based timber coatings. The gloss finish weathers naturally over time, and the freshly coated wet timber look can be restored easily with a single maintenance coat of Wet Look Deck.



Features and Benefits

- Gloss finish.
- Unique penetrating formula.
- Fast drying.
- Freshly coated, wet timber look.
- Nourishes and penetrates into the timber more effectively than standard acrylic products.
- 4 Hour Recoat.

Uses




Decking, fences, steps, walkways, pergolas, furniture and all other exterior timber.

Precautions and Limitations

Do not apply in temperatures under 10°C or above 35°C or when rain or heavy dew is expected within the coating dry time.

Performance Guide

Weather Exterior durable.	Heat Resistance Up to 70 degrees Celsius.
Water Excellent.	Abrasion Good.

Typical Properties			
Gloss Level Gloss	Heat Thinner WET LOOK DECK does NOT require thinning.		
Colour Lightly tinted.			
Number of Coats 2-3			
V.O.C. Level < 25g/L			
Meets GBCA V.O.C. Requirements? Yes Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.			
Touch Dry 2 hours			
Clean Up  Water			
Application Methods  Brush  Pad			
Application Conditions	Solids by Volume		
	<input type="text" value="17"/>		
	Min	Max	Recommended
Recoat Time (min/hours)	<input type="text" value="4 hours"/>	<input type="text"/>	<input type="text"/>
Theoretical Spread Rate (m ² /L)	<input type="text"/>	<input type="text" value="12"/>	<input type="text"/>
Typical Property Notes Drying time Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Touch Dry: 2 hours. Recoat: Allow a minimum of 4 hours drying between coats. Decking can be walked on with care after 12 hours. Full curing 7 days. Coverage Softwood: 8-10m ² per litre. Hardwood: 10-12m ² per litre.			

Application Guide

Surface Preparation

New, Pre-Oiled Timber

Timber that is factory pre-oiled with Feast Watson Industrial Timber Oil or Intergrain Universal Timber Oil does not require exterior weathering or treatment to remove tannin or oils. This pre-oiled timber can be directly over coated with any Feast Watson water based or oil-based topcoat.

All timber should be clean and free from dust, dirt, debris, and mortar prior to coating.

Light surface soiling: A light wipe down with a clean damp cloth will be Suitable.

Heavy surface soiling: Clean the surface with Cabot's Deck Clean as per the instructions.

IMPORTANT

Prior to topcoat purchase and application, it is important to identify the type of oil the supplier or timber merchant has used, to ensure it is compatible with water-based oil application. If unsure, follow the recommendations below for new raw timber timber.

New, Raw Timber

Allow new Treated Pine to weather for 2 weeks prior to application or follow timber manufacturer's recommendation.

Allow other timbers to weather for approximately 4-6 weeks.

We recommend that tannin rich timbers are regularly hosed with water to assist leaching during this time.

Weathering periods are provided as a guide only, consult your timber supplier to ensure you correctly prepare your timber for your particular requirements.

For immediate application, clean timber with Intergrain UltraDeck Tannin and Oil Remover, followed by WOODCLEAN. Follow directions of both products as outlined.

Weathered Timber

Prepare weathered or grey timber by cleaning thoroughly with WOODCLEAN™ as per the instructions.

Sanding may be required to remove stains and restore deteriorated surfaces. Remove all sanding dust before coating.

Previously Coated Timber

Timber coated with stain or oil can be coated with Feast Watson Wet Look Deck after the surface has weathered. Test if the surface is ready by sprinkling water onto the timber: if the water absorbs into the timber, it is suitable for coating. If the water beads, further weathering, sanding or stripping is required.

Painted or varnished surfaces need to be taken back to bare timber by stripping or sanding.

Prepare timber for coating with WOODCLEAN as per the instructions.

Application Procedure and Equipment

Allow the timber to dry completely before applying Wet Look Deck.

Wet Look Deck should be stirred thoroughly before and during application with a flat blade stirrer taking care not to introduce bubbles.

If the job requires more than one can of oil, mix all together in one large container prior to commencing.

Do not apply with a roller.

Apply one coat of Wet Look Deck using a quality synthetic or pure bristle brush or Feast Watson Floor Applicator.

Work along 3 - 4 planks at a time, in the direction of the grain. Ensure edges and end grain are fully coated. Maintain a wet edge at all times.

Do not over brush or apply thinly, as insufficient film thickness will compromise performance and durability.

Allow to dry for 4 hours.

Apply a second coat as above.

A third coat of Wet Look Deck may be required in extreme conditions such as full sun exposure, around pools and in humid areas, and may be required on porous timbers. A third coat will increase the gloss level.

Allow to dry for 12 hours before light foot traffic.

Do not apply in temperatures under 10°C or above 35°C or when rain or heavy dew is expected within the coating dry time.

Maintenance

Regularly monitor coated timber for signs of colour loss, dryness and weathering. Recoat the timber when it begins to show signs of dryness to help maintain its natural beauty and protection.

If sheen level shows signs of decreasing, the wet look can be restored by applying a maintenance coat of Wet Look Deck.

When required, clean the surface using WOODCLEAN, allow the surface to dry and recoat with one coat of Wet Look Deck.

Health and Safety	
SDS Number 23196	SDS Link View SDS Link
Using Safety Precautions Keep out of reach of children. Avoid contact with skin and eyes. Provide adequate ventilation.	
Please refer to SDS Link. In case of emergency, please call 1800 220 770.	

Transport and Storage	
Pack A 563W0093	
Size: 4L 100ml	Weight: 4.5 kg 0.24Kg
Please refer to the Safety Data Sheet for full safety, health and transportation information.	

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.