



[Safety Data Sheets](#) for all available Feast Watson Prooftint™ variants below:

[331-LINE FEAST WATSON PROOFTINT STAIN BLACK](#)

[331-LINE FEAST WATSON PROOFTINT STAIN BLACK JAPAN](#)

[331-LINE FEAST WATSON PROOFTINT STAIN BROWN JAPAN](#)

[331-LINE FEAST WATSON PROOFTINT STAIN CEDAR](#)

[331-LINE FEAST WATSON PROOFTINT STAIN ELM](#)

[331-LINE FEAST WATSON PROOFTINT STAIN GOLDEN TEAK](#)

[331-LINE FEAST WATSON PROOFTINT STAIN MAHOGANY](#)

[331-LINE FEAST WATSON PROOFTINT STAIN MAPLE](#)

[331-LINE FEAST WATSON PROOFTINT STAIN OAK](#)

[331-LINE FEAST WATSON PROOFTINT STAIN OLD BALTIC](#)

[331-LINE FEAST WATSON PROOFTINT STAIN TEAK BROWN](#)

[331-LINE FEAST WATSON PROOFTINT STAIN WALNUT](#)

<https://www.lupinsys.com/search/feastwatson/>

## Product specs

[↓ Product data sheet](#)

### Where to use

All interior timber including floors, furniture, trim, paneling, window frames, skirting boards, doors, Plywood and MDF.

### Finish

Stain

### Coverage rate

10m<sup>2</sup> per litre

### Number of coats

Bare timber: Continue to coat until desired colour has been achieved

### Recoat time

Recoat after 30 minutes if product is applied straight  
Recoat after 1 hour if product is diluted

### Dry time

30 minutes if product is applied straight  
12 hour if product is diluted

### Clean up

Methylated Spirits. Soak application cloths in water prior to disposal.

### Sizes

50ml, 250ml, 1L