

## Feast Watson Surface Restore

**AU\_DW02749**

<b>Part A</b>	91AW0339
---------------	----------

### Description

FEAST WATSON SURFACE RESTORE IS MADE FROM A BLEND OF PENETRATING TUNG OIL WITH HARD-DRYING BEESWAX AND CARNAUBA WAX. IT REJUVENATES TIRED AND WORN COATED INTERIOR TIMBER SURFACES WITHOUT HAVING TO SAND THE ORIGINAL COATING. STIR GENTLY BEFORE USE. APPLY WITH A NYLON SCOURING PAD OR FINE STEEL WOOL (000), THEN BUFF WITH A SOFT CLOTH TO THE REQUIRED SHEEN. CAN BE BUFFED TO A HIGH SHEEN. A SECOND COAT CAN BE APPLIED FOR ADDITIONAL SHINE AND PROTECTION. ALLOW 12 HOURS TO DRY AND BEFORE RE-COATING. 250mL PROVIDES UP TO 5m<sup>2</sup> COVERAGE. WASH UP USING MINERAL TURPENTINE. SOAK APPLICATION CLOTHS IN WATER BEFORE DISPOSAL.

### Features

- COMBINATION OF WAXES AND OILS
- RESTORE TIMBER FINISHES
- NO NEED TO SAND OR STRIP

### Uses

COATED INTERIOR TIMBER SURFACES

### Performance Guide

<b>Weather</b>	Interior only	<b>Heat Resistance</b>	Up to 100C. Premature yellowing and embrittlement will occur if subjected to continuous heat
<b>Water</b>	Good water resistance		

### Typical Properties

<b>V.O.C. Level</b>	<630g/L	<b>Meets GBCA VOC Requirement?</b>	No																								
<b>Touch Dry</b>	6 hours																										
<b>Clean Up Description</b>	Mineral turpentine To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.																										
<b>Application Method</b>	<b>Other:</b> Nylon scouring pad, Fine steel wool (000)																										
<b>Application Conditions</b>	<table> <tr> <td><b>Solids By Volume</b></td><td>24</td><td></td><td></td></tr> <tr> <td></td><td><b>Min</b></td><td><b>Max</b></td><td><b>Recommended</b></td></tr> <tr> <td><b>Wet Film Per Coat (microns)</b></td><td></td><td></td><td></td></tr> <tr> <td><b>Dry Film Per Coat (microns)</b></td><td></td><td></td><td></td></tr> <tr> <td><b>Recoat Time (min)</b></td><td>12 hours</td><td></td><td></td></tr> <tr> <td><b>Theoretical Spread Rate (m<sup>2</sup>/L)</b></td><td></td><td></td><td></td></tr> </table>			<b>Solids By Volume</b>	24				<b>Min</b>	<b>Max</b>	<b>Recommended</b>	<b>Wet Film Per Coat (microns)</b>				<b>Dry Film Per Coat (microns)</b>				<b>Recoat Time (min)</b>	12 hours			<b>Theoretical Spread Rate (m<sup>2</sup>/L)</b>			
<b>Solids By Volume</b>	24																										
	<b>Min</b>	<b>Max</b>	<b>Recommended</b>																								
<b>Wet Film Per Coat (microns)</b>																											
<b>Dry Film Per Coat (microns)</b>																											
<b>Recoat Time (min)</b>	12 hours																										
<b>Theoretical Spread Rate (m<sup>2</sup>/L)</b>																											
<b>Typical Properties Notes</b>	COVERAGE Up to 20m <sup>2</sup> per litre  DRYING TIME Recoat: 12 hours minimum Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times.																										

### Application Guide

<b>Surface Preparation</b>	<ul style="list-style-type: none"> <li>▪ Surfaces to be coated must be clean and dry.</li> <li>Clean with Feast Watson Floorclean if required, and allow surface to dry completely.</li> </ul>
<b>Application Procedure And Equipment</b>	<ul style="list-style-type: none"> <li>▪ Stir gently and thoroughly before use.</li> <li>Apply with a nylon scouring pad or with fine steel wool (000). Apply in the direction of the grain.</li> <li>Leave for 10-20 minutes, then wipe with a clean cloth.</li> <li>Leave for at least 6 hours then buff surface with a soft clean cloth.</li> <li>A second coat can be applied for additional shine and protection.</li> </ul>

## Health And Safety

<b>MSDS Number</b>	DLXGHCEN003409	<b>Using Safety Precautions</b>	Flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Harmful if inhaled. Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and all other equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust, fume, gas, mist, vapours or spray.. Wash hands, face and all exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective clothing, gloves, eye/face protection and suitable respirator.
<b>Health Effects</b>	<p><b>FIRST AID:</b> If poisoning occurs, contact a Doctor or Poisons Information Centre (Phone Australia 131 126; New Zealand 0800 764 766). If medical advice is needed, have product container or label at hand.</p> <p><b>SWALLOWED:</b> If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical assistance.</p> <p><b>EYE:</b> If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.</p> <p><b>SKIN:</b> If skin contact occurs, remove contaminated clothing and wash skin thoroughly. If irritation occurs seek medical advice.</p> <p><b>INHALED:</b> Remove from contaminated area. Apply artificial respiration if not breathing. Seek medical advice.</p>	<b>Flammability</b>	Flammable liquid and vapour
<b>Fire Suppression</b>	If material is involved in a fire use alcohol resistant foam, standard foam or dry agent (carbon dioxide, dry chemical powder)	<b>Protective Equipment</b>	Wear protective clothing, gloves, eye/face protection and suitable respirator
<b>Storage</b>	Keep out of reach of children	<b>Disposal</b>	Do not pour leftover paint down the drain. Unwanted paint should be brushed out on newspaper (note spontaneous combustion warning), allowed to dry and then disposed of via domestic waste collections. Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.
In the case of emergency, please call 1800 033 111			

## Transport And Storage

<b>Pack A</b>	91AW0339	<b>Shipment Name</b>	PAINT
<b>Size</b> 500ml	<b>Weight</b> 0.54kg		
<b>Flash Point</b>	>23C	<b>UN Number</b>	1263
<b>Dangerous Goods Class</b>	3	<b>Package Group</b>	III

**Disclaimer**

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427