

AUFW00110 Feast Watson Surface Restore

Introduction

Part A
91AW0339

Description and Image

Feast Watson Surface Restore is made from a blend of penetrating tung oil with hard-drying beeswax and carnauba wax. It rejuvenates tired and worn coated interior timber surfaces without having to sand the original coating. Stir gently before use. Apply with a nylon scouring pad or fine steel wool (000), then buff with a soft cloth to the required sheen. Can be buffed to a high sheen. A second coat can be applied for additional shine and protection. Allow 12 hours to dry and before re-coating. 250mL provides up to 5m2 coverage. Wash up using mineral turpentine. Soak application clothes in water before disposal.



Features and Benefits

- Combination of waxes and oils
- Restore timber finishes
- No need to sand or strip

Uses

Coated interior timber surfaces

Precautions and Limitations

Use on previously coated timber only. Do not use on bare timber.

Performance Guide

Weather
Interior only

Heat Resistance
Up to 100C. Premature yellowing and embrittlement will occur if subjected to continuous heat

Water
Good water resistance

Typical Properties			
V.O.C. Level <595g/L			
Meets GBCA V.O.C. Requirements? No			
Touch Dry 6 hours			
Clean Up Description Mineral turpentine To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.			
Application Methods Nylon scouring pad, Fine steel wool (000)			
Application Conditions	Solids by Volume		
	<input type="text" value="26"/>		
	Min	Max	Recommended
Recoat Time (min/hours)	<input type="text" value="12 hours"/>	<input type="text"/>	<input type="text"/>
Typical Property Notes Coverage Up to 20m ² per litre Drying time Recoat: 12 hours minimum Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times.			

Application Guide
Surface Preparation Surfaces to be coated must be clean and dry. Clean with Feast Watson Floorclean if required, and allow surface to dry completely.
Application Procedure and Equipment Stir gently and thoroughly before use. Apply with a nylon scouring pad or with fine steel wool (000). Apply in the direction of the grain. Leave for 10-20 minutes, then buff with a clean soft cloth. A second coat can be applied for additional shine and protection. The coating can be buffed again after 6 hours if a higher sheen is desired.

Health and Safety	
SDS Number DLXGHSEN003409	SDS Link View SDS Link
<p>Using Safety Precautions</p> <p>Flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Harmful if inhaled. Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and all other equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust, fume, gas, mist, vapours or spray.. Wash hands, face and all exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective clothing, gloves, eye/face protection and suitable respirator.</p>	
<p>Please refer to SDS Link. In case of emergency, please call 1800 220 770.</p>	

Transport and Storage	
Pack A 91AW0339	
Size: <input type="text" value="500ml"/>	Weight: <input type="text" value="0.54kg"/>
<p>Please refer to the Safety Data Sheet for full safety, health and transportation information.</p>	

Further Information
Product page

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.