

AUFW00107 Feast Watson Soft Wax

Introduction

Part A
91AW0343

Description and Image

Feast Watson Soft Wax is made from a blend of refined oil and waxes that rejuvenates and protects coated interior timber furniture. Apply with a soft cloth. Allow 5-15 minutes to dry then lightly buff with a clean cloth to achieve the desired lustre. Contains beeswax.



Features and Benefits

- Blend of refined oils and waxes
- Rejuvenates and protects
- Easy to use

Uses

Interior timber furniture

Performance Guide

Weather
Interior use only

Typical Properties

Colour Colourless
Number of Coats 1+
V.O.C. Level <5g/L
Meets GBCA V.O.C. Requirements? Yes Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.
Clean Up Description Mineral turpentine
Application Methods Soft cloth

Application Guide

Surface Preparation Ensure surface is clean and dry.
Application Procedure and Equipment Apply with a soft cloth. Allow 5-15 minutes to dry, then lightly buff with a clean cloth to achieve the desired lustre.

Health and Safety

SDS Number DLXGHSEN003410	SDS Link View SDS Link
Using Safety Precautions Avoid contact with skin and eyes. Avoid breathing dust, fume, gas, mist, vapour or spray. Wear overalls, safety shoes, impervious gloves and safety glasses. Use only in well ventilated areas. Wash hands after use. Keep containers closed when not in use.	
Please refer to SDS Link. In case of emergency, please call 1800 220 770.	

Transport and Storage

Pack A 91AW0343
Size: <input type="text" value="125g"/> Weight: <input type="text" value="125g"/>
Please refer to the Safety Data Sheet for full safety, health and transportation information.

Further Information

Product page

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.