

Datasheet



AUFW00011 Feast Watson Floorclean

Introduction

Part A

872 94646

Description and Image

Feast Watson Floorclean is an all purpose, neutral cleaner for use over all hard floor finishes: timber, terrazzo and ceramic tiles, slate, linoleum and laminate floors. Floorclean has been specially formulated to work on hardwood floor coatings including both polyurethane and tung oil based coatings such as Feast Watson Floorproof Pro, Floorclear, Floorseal Oil and Traditional Timber Oil.



Features and Benefits

- Water-based
- Concentrate
- Dries streak free and residue free
- Easy to use
- 1L makes approximately 60L cleaning solution

Uses

Use Feast Watson Floorclean to clean coated timber floors, terrazzo and ceramic floor tiles, vinyl and lino floors.

Typical Properties
Heat Thinner
Water
Colour
Blue liquid
Components
1
Clean Up
₹ Water
Application Methods
Мор
Typical Property Notes



Datasheet



Coverage

1 litre will make approx. 60 litres.

Application Guide

Surface Preparation

Sweep or vacuum floor to remove surface dirt prior to cleaning with Feast Watson Floorclean.

Application Procedure and Equipment

Shake thoroughly prior to use. Add approximately 50mls of Floorclean concentrate, (2 capfuls) to 4 litres of water (1/2 a bucket). Apply liberally to floor with mop to loosen grime and dirt. Return excess solution to a bucket and allow to dry. For extra dirty floors, increase amount of Floorclean concentrate, 100ml (4 caps) to 4 litres of water.

Maintenance

Use for general cleaning or at regular intervals when necessary.

Health and Safety			
SDS Number 1152	SDS Link https://go.lupinsys.com/duluxgroup/harms/public/materials/3c8bb9f 28239cf735c4e49d35e5c7878- published/attachments api/95246ff9c28759901d320a6405be5974/se arch api/872-94646 FEAST WATSON FLOORCLEAN-AUS GHS.pdf		
Using Safety Precautions Avoid breathing vapour and spray mist.			
Please refer to <u>SDS Link</u> . In case of emergency, please call 1800 220 770.			

Transport and Storage			
Pack A			
872-94646			
Size:	Weight:		
4L 1L	4.1Kg 1Kg		
Please refer to the Safe	ety Data Sheet for full safety, health	and transportation information.	

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.