

AUFW00072 Feast Watson Woodclean

Introduction

Part A
917 W0505

Description and Image

Feast Watson Woodclean is a preparatory treatment for all exterior timber. Using Woodclean leads to a long lasting, evenly applied top-coat, as it helps to remove the surface contaminants such as oils and dirt which may otherwise affect how the final coating performs. On new timber, Woodclean helps to remove the tannins and oils. On weathered grey timber, Woodclean breaks down dead wood fibre and dirt, restoring the natural colour of the timber. Woodclean is suitable for wooden decks, outdoor furniture, weatherboards, windows, doors and fences.



Features and Benefits

- Supplied as concentrate
- Contains cleaning agents
- Contains Oxalic acid
- Dilute to suit timber condition
- Cleans slippery, unsafe walkways
- Removes water or metal-stains

Uses

Use on exterior wooden decks, outdoor furniture, weatherboards, windows, doors and fences.

Precautions and Limitations

Woodclean may cause erosion of some sealants and patching products. Test surface prior to application. Protect paintwork, plants and other surfaces with plastic sheeting or wet first and rinse off immediately after.

Typical Properties

Heat Thinner
Water


Colour
Green

Components
1

Number of Coats
1 or 2

Toxicity
POISON

V.O.C. Level
< 5g/L

<p>Meets GBCA V.O.C. Requirements?</p> <p>Yes</p> <p>Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.</p>
<p>Clean Up</p> <p> Water</p>
<p>Application Methods</p> <p>Stiff bristle broom or brush</p>
<p>Typical Property Notes</p> <p>Coverage</p> <p>One litre of Woodclean when diluted with 4 litres of water will treat approximately 20m2, subject to timber porosity, species and condition.</p>

Application Guide	
<p>Surface Preparation</p> <p>Sweep surface clean and thoroughly wash down with water.</p> <p>Woodclean may cause erosion of some sealants and patching products. Test surface prior to application. Protect paintwork, plants and other surfaces with plastic sheeting or wet first and rinse off immediately after.</p>	
<p>Application Procedure and Equipment</p> <p>Dilute Woodclean in water by mixing one (1) part Woodclean to four (4) parts water. Stir diluted mixture thoroughly. Apply Woodclean by scrubbing into timber surface with a stiff bristle brush. Leave formula for approximately 20 minutes to penetrate the timber surface. Do not allow surface to dry. Prevent drying by wetting timber with a very light mist spray. After 20 minutes rinse thoroughly with a high-pressure water cleaner. For more stubborn or badly weathered areas, use a higher concentration of Woodclean. Allow surface to dry completely before applying top coats.</p>	

Health and Safety	
<p>SDS Number</p> <p>DLXGHSEN004027</p>	<p>SDS Link</p> <p>https://go.lupinsys.com/duluxgroup/harms/public/materials/3c8bb9f28239cf735c4e49d35e5c77f4-published/attachments_api/a38f490ccbd98571bb133f8746e708a7/se arch_api/917-94684_FEAST_WATSON_WOODCLEAN-AUS_GHS.pdf</p>
<p>Using Safety Precautions</p> <p>Causes skin irritation. Causes serious eye damage.</p> <p>Keep out of reach of children. Read carefully and follow all instructions. Wash hands, face and all exposed skin thoroughly after handling. Wear protective gloves/protective clothing including eye/face protection and suitable respirator.</p>	
<p>Please refer to SDS Link. In case of emergency, please call 1800 220 770.</p>	

Transport and Storage	
<p>Pack A</p> <p>91794684</p>	
<p>Size:</p> <p><input type="text" value="1L 4L"/></p>	<p>Weight:</p> <p><input type="text" value="1.13Kg 4.33Kg"/></p>
<p>Please refer to the Safety Data Sheet for full safety, health and transportation information.</p>	

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.