

AUFW00020 Feast Watson Kitchen Timber Oil

Introduction

Part A

870 W0040

Description and Image

Feast Watson Kitchen Timber Oil is a traditional oil that contains genuine tung oil, a natural wood oil. Kitchen Timber Oil is formulated to penetrate deeply into timber, resulting in a natural matt finish that can be buffed or waxed if desired. Kitchen Timber Oil is quick and easy to apply, resistant to water and spills, and easily maintained. It is suitable for all interior timber including benchtops, cutting boards, furniture, cabinetry and timber trim. Feast Watson Proofint can be added to Kitchen Timber Oil for a one step stain and oil application.

Features and Benefits

- Contains genuine tung oil.
- Penetrates deeply into timber.
- Quick and easy to apply.
- Natural wood oil.
- Natural matt finish.
- Convenient.

Uses

All interior timber including benchtops, cutting boards, furniture, cabinetry and timber trim.

Precautions and Limitations

Note Feast Watson Kitchen Timber Oil contains pure tung oil, which is obtained from the pressed seeds and nuts of the tung tree. As the source of tung oil is nut, we recommend that individuals with known nut allergies avoid use and/or contact with this product, as they would other products derived from nut oils. Interior use only. Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Do not apply in temperatures under 10°C. Spreading rate will be dependent on the porosity and age of the timber.

Performance Guide

Weather

Interior only product.

Heat Resistance

Up to 120C.

Water

Resistant to water.

Typical Properties

Gloss Level

Matt

Colour

Clear

Components

1

Number of Coats

2

Toxicity

Lead free

V.O.C. Level

< 455g/L

Touch Dry

2 hours

Clean Up

Clean Up Description

Mineral turpentine. To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.

Application Methods



Application Conditions

Solids by Volume

41

Min

Max

Recommended

Wet Film Per Coat (microns)

83

Dry Film Per Coat (microns)

34

Recoat Time (min/hours)

24 hours

Theoretical Spread Rate (m²/L)

12

12

Typical Property Notes

Coverage

10 to 12 square metres per litre. The first coat may require more depending on the porosity and age of the timber.

Drying Time

Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times.

Application Guide

Surface Preparation

The surface must be clean, dry and free from dirt, grease, oil, wax and mould. Sand to a smooth surface and clean to remove dust. If the timber has been previously coated, ensure the surface is thoroughly stripped and sanded back to bare timber.

Application Procedure and Equipment

Stir gently prior to use with a flat blade stirrer. Apply a liberal coat of Kitchen Timber Oil to the timber with a brush, roller or clean cloth. Ensure the surface is evenly covered. Leave the Kitchen Timber Oil to soak into timber for approximately 45 to 60 minutes and then wipe off any excess product with a clean cloth. Allow approximately 24 hours to dry between coats. Apply a second coat of Kitchen Timber Oil following the application process outlined above. Allow a minimum of 24 hours to dry. For a wax finish use Feast Watson Mastertouch Carnauba Wax. Allow 7 days before waxing.

Staining

Seal soft porous timbers with one coat of Kitchen Timber Oil first for even adsorption rate of stain. Add up to a maximum of 10% Feast Watson Proofint to Kitchen Timber Oil and follow directions for use outlined above.

Maintenance

Clean using Feast Watson Floorclean. To rejuvenate, ensure that the surface to be treated is dry and free from dirt, oil, wax and grease. Apply one light coat of Kitchen Timber Oil and buff.

Food safety

Ensure surfaces have thoroughly dried before exposing to food. Kitchen Timber Oil contains oil from tree nuts.

Health and Safety

SDS Number 22555	SDS Link https://go.lupinsys.com/duluxgroup/harms/public/materials/fee62a9c4b8013f1e9ea398e9cbdf68e-published/attachments_api/19801663d98fc2b9f6c9a12910509f22/se-arch_api/872-W0040_FEAST_WATSON_KITCHEN_TIMBER_OIL-AUS_GHS.pdf
Using Safety Precautions Avoid skin and eye contact and breathing in vapour. Provide adequate ventilation. Keep windows and doors open during use and while drying. This product is flammable, so eliminate any sources of ignition. Do not smoke.	
Please refer to SDS Link. In case of emergency, please call 1800 220 770.	

Transport and Storage	
Pack A 870 W0040	
Size: <div>250ml 1L</div>	Weight: <div>0.3Kg 1.0Kg</div>
Please refer to the Safety Data Sheet for full safety, health and transportation information.	

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.