

Feast Watson Timber Floor Varnish Gloss

AU_DW02888

| | |
|--------|----------|
| Part A | 87294797 |
|--------|----------|

Description

FEAST WATSON TIMBER FLOOR VARNISH IS A CLEAR, OIL BASED POLYURETHANE FINISH THAT PRODUCES A TOUGH, ABRASION RESISTANT FINISH THAT ENHANCES THE NATURAL BEAUTY OF THE TIMBER. SUITABLE FOR NEW AND EXISTING INTERIOR TIMBER AND CORK FLOORS, PARQUETRY AND OTHER INTERIOR TIMBER SUBJECT TO HIGHWEAR, SUCH AS BENCHTOPS. TIMBER FLOOR VARNISH HAS BEEN FORMULATED USING LOW ODOUR SOLVENTS FOR A MORE PLEASANT APPLICATION EXPERIENCE.

Features

- TOUGH, ABRASION RESISTANT FINISH
- SUITABLE FOR ALL NEW AND EXISTING INTERIOR TIMBER SUBJECT TO HIGHWEAR
- FORMULATED USING LOW ODOUR SOLVENTS FOR A MORE PLEASANT APPLICATION EXPERIENCE

Uses




SUITABLE FOR NEW AND EXISTING INTERIOR TIMBER AND CORK FLOORS, PARQUETRY AND OTHER INTERIOR TIMBER SUBJECT TO HIGHWEAR, SUCH AS BENCHTOPS.

Precautions And Limitations

Do NOT apply this product at temperatures below 10°C or above 35°C.

Performance Guide

| | | | |
|----------------|---------------|-----------------|------|
| Weather | Interior only | Abrasion | Good |
|----------------|---------------|-----------------|------|

| Typical Properties | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|--------------------|-------------------------|----|--|--|--|------------|------------|--------------------|------------------------------------|--|--|--|------------------------------------|--|--|--|--------------------------|----------|--|--|--------------------------------------------------|--|--|--|
| Gloss Level | >80% measured at 85 degrees | Colour | Clear | | | | | | | | | | | | | | | | | | | | | | | | |
| Number Of Coats | 2-3 | V.O.C. Level | <470g/L | | | | | | | | | | | | | | | | | | | | | | | | |
| Meets GBCA VOC Requirement? | No | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Clean Up Description | Clean brushes and other equipment with mineral turpentine. To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other. | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Application Method |  Brush  Roller  Pad | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Application Conditions | <table> <tr> <td>Solids By Volume</td><td>42</td><td></td><td></td></tr> <tr> <td></td><td>Min</td><td>Max</td><td>Recommended</td></tr> <tr> <td>Wet Film Per Coat (microns)</td><td></td><td></td><td></td></tr> <tr> <td>Dry Film Per Coat (microns)</td><td></td><td></td><td></td></tr> <tr> <td>Recoat Time (min)</td><td>12 hours</td><td></td><td></td></tr> <tr> <td>Theoretical Spread Rate (m²/L)</td><td></td><td></td><td></td></tr> </table> | | | Solids By Volume | 42 | | | | Min | Max | Recommended | Wet Film Per Coat (microns) | | | | Dry Film Per Coat (microns) | | | | Recoat Time (min) | 12 hours | | | Theoretical Spread Rate (m²/L) | | | |
| Solids By Volume | 42 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | Min | Max | Recommended | | | | | | | | | | | | | | | | | | | | | | | | |
| Wet Film Per Coat (microns) | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Dry Film Per Coat (microns) | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Recoat Time (min) | 12 hours | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Theoretical Spread Rate (m²/L) | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Typical Properties Notes | <p>COVERAGE Softwood: 12 - 13m² per litre. Hardwood: 13 - 14m² per litre. Cork: 10 - 12m² per litre.</p> <p>DRYING TIME Drying times are given at 25°C and 50% relative humidity. Lower temperatures and higher humidity can lead to extended drying times. Touch Dry: 8 hours. Recoat: 12 hours. Allow 24 hours before light foot traffic and 72 hours for normal foot traffic. Full curing after 7 days. Wait until fully cured to replace furniture and rugs. All furniture should have protective felt pads on floor contact points. Do not use furnishing with rubber pads or backing.</p> | | | | | | | | | | | | | | | | | | | | | | | | | | |

Application Guide

| | |
|--------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Surface Preparation | <ul style="list-style-type: none"> NEW OR BASE TIMBER/CORK Punch exposed nails below the surface. Note that holes and imperfections should be filled with timber putty after the first coat of TIMBER FLOOR VARNISH to match the putty colour with the coated timber colour. Sand timber to an even, smooth surface. Vacuum and wipe to remove dust. Prepare uncoated cork tiles in accordance with the supplier's recommendation. For porous timbers such as pine, apply one coat of Feast Watson® TIMBER PRIMER after sanding to ensure the top coats will absorb evenly. For oily timbers such as tallowwood, brush box and cypress pine, apply one coat of Feast Watson® PROOFSEAL after sanding to prevent the timber oils from discolouring the coating. <p>PREVIOUSLY COATED SURFACES Clean surface with Feast Watson® FLOORCLEAN™ and allow to dry. Sand surface thoroughly until a uniform matt appearance is achieved. Vacuum and wipe to remove dust. Check adhesion by applying TIMBER FLOOR VARNISH to a small test area. Allow to dry for 24hrs then firmly press a strip of sticky tape over the test area and rip off quickly. If coating is removed, it will not adhere to the surface so the surface needs to be sanded back to bare timber. If coating is not removed, sand the test area back to a uniform matt surface, remove all sanding dust, and apply TIMBER FLOOR VARNISH as per instructions below. If previous coating has worn back to expose bare timber it must be completely removed.</p> <p>STAINING If staining timber is desired complete these steps after the timber has been prepared and before applying TIMBER FLOOR VARNISH. If no staining is required the staining instructions can be disregarded. Stain bare timber after sanding using Feast Watson® PROOFTINT or Feast Watson® LIMING WHITE STAIN as per the application instructions. Seal porous timber such as pine with one coat of Feast Watson® TIMBER PRIMER prior to staining to ensure the stain absorbs evenly. To stain flooring, mix PROOFTINT with Feast Watson® PROOFTINT COLOUR REDUCER to allow time to evenly work the stain across the floor. Test the colour mix on off-cuts of flooring to confirm the colour before staining the whole area. Apply stain to the floor with a FLOOR FINISH APPLICATOR as per PROOFTINT instructions. Allow 12 hours to dry before applying TIMBER FLOOR VARNISH.</p> |
| Application Procedure And Equipment | <ul style="list-style-type: none"> Surfaces to be coated must be dry and free from all dirt, dust, grease, wax, polish and oil. TIMBER FLOOR VARNISH should be stirred thoroughly before and during application with a flat blade stirrer taking care not to introduce bubbles. Apply with a Feast Watson® FLOOR FINISH APPLICATOR, brush or short nap roller. Work along the whole length of 3 to 4 floorboards at a time, maintaining a wet edge to prevent lap marks. Ensure final brush strokes are in the direction of the grain. Take care to not introduce bubbles. When the first coat is thoroughly dry, lightly sand and vacuum to remove dust. Apply second coat as outlined above. A third coat may be required on porous timber or cork to achieve desired gloss level. <p>Do NOT apply this product at temperatures below 10°C or above 35°C.</p> <p>MAINTENANCE Allow TIMBER FLOOR VARNISH to cure for a minimum of 4 weeks before polishing. Regularly clean using FLOORCLEAN. Rejuvenate floors with Feast Watson® FLOOR POLISH. When floor requires an additional coat of TIMBER FLOOR VARNISH, apply as per the instructions for Previously Coated Surfaces.</p> |

Health And Safety

| | | | |
|----------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MSDS Number | DLXGHCEN001030 | Using Safety Precautions | Flammable liquid and vapour. May be harmful if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and all other equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust, fume, gas, mist, vapours or spray. Wash hands, face and all exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective clothing, gloves, eye/face protection and suitable respirator. |
| Health Effects | FIRST AID: If poisoning occurs, contact a Doctor or Poisons Information Centre (Phone Australia 131 126; New Zealand 0800 764 766). If medical advice is needed, have product container or label at hand. SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical assistance. EYE: If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor. SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly. If irritation occurs seek medical advice. INHALED: Remove from contaminated area. Apply artificial respiration if not breathing. Seek medical advice. | Flammability | Flammable liquid and vapour. |
| Fire Suppression | If material is involved in a fire use alcohol resistant foam, standard foam or dry agent (carbon dioxide, dry chemical powder). | Protective Equipment | Wear protective clothing, gloves, eye/face protection and suitable respirator. |
| Storage | Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. | Other | CONTAINS: 30 - 60% HYDROCARBON SOLVENT, <1% METHYL ETHYL KETOXIME For further information or a copy of the Safety Data Sheet call Feast Watson® Customer Service Department on AUST 1800 252 502, NZ 0800 222 687. EMERGENCY INFORMATION: AUST – 1800 220 770; NZ – 0800 220 770 (ALL HOURS). |
| In the case of emergency, please call 1800 033 111 | | | |

Transport And Storage

| | | | |
|------------------------------|---------------|----------------------|-------|
| Pack A | 87294797 | Shipment Name | PAINT |
| Size | Weight | | |
| 1L | 1.053kg | | |
| 4L | 4.017kg | | |
| 10L | 9.925kg | | |
| Flash Point | >23C | UN Number | 1263 |
| Dangerous Goods Class | 3 | Package Group | III |

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427