

AUFW00102 Feast Watson Water Repellent Timber & Deck Oil

Introduction

Part A
840W0211

Description and Image

Feast Watson Water Repellent Timber & Deck Oil is a clear penetrating oil which allows exterior timber to naturally grey over time whilst repelling water. Water Repellent Timber & Deck Oil can be used for exterior cladding, weatherboards, decking, fences, gates, windows, doors, boardwalks and walkways. Regular maintenance every 3-6 months is required. Note: timber may not grey evenly, the grey appearance will depend on the timber species and degree of exposure to the weather.



Features and Benefits

- Clear water repellent
- Matt finish
- Allows exterior timber to naturally grey over time whilst repelling water
- Natural look

Uses

For use on exterior cladding and weatherboards, decking, fences, gates, windows, doors, boardwalks and walkways.

Precautions and Limitations

Do not apply in temperatures under 10°C or above 35°C or when rain or heavy dew is expected within the coating dry time.
Maintenance required every 3-6 months to maintain water repellency.

Performance Guide

Weather
Exterior use

Water
Excellent

Typical Properties

Colour
Clear

Number of Coats
2 minimum

V.O.C. Level
725g/L

Meets GBCA V.O.C. Requirements?
No

Clean Up Description
Mineral turpentine

To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.

Application Methods



Brush



Roller



Spray

Application Conditions

Solids by Volume

10

Min

Max

Recommended

Recoat Time (min/hours)

2 hours min.

Theoretical Spread Rate (m²/L)

6

10

Typical Property Notes

Drying time

Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times.

Recoat: Allow at least 2 hours to penetrate.

Coating does not need to fully dry before applying subsequent coats.

Coverage

Softwood: 6 - 8m² per litre

Hardwood: 8 - 10m² per litre

Application Guide

Surface Preparation

New, Pre-Oiled Timber

Timber that is factory pre-oiled with Feast Watson Industrial Timber Oil or Intergrain Universal Timber Oil does not require exterior weathering or treatment to remove tannin or oils. This pre-oiled timber can be directly over coated with Feast Watson Water Repellent Timber & Deck Oil. All timber should be clean and free from dust, dirt, debris, and mortar prior to coating.

Light surface soiling: A light wipe down with a clean damp cloth will be suitable.

Heavy surface soiling: Clean the surface with WOODCLEAN as per the instructions.

New, Raw Timber

Allow new Treated Pine to weather for 2 weeks prior to application or follow timber manufacturer's recommendation.

Allow other timbers to weather for approximately 4-6 weeks.

We recommend that tannin rich timbers are regularly hosed with water to assist leaching during this time.

Weathering periods are provided as a guide only, consult your timber supplier to ensure you correctly prepare your timber for your particular requirements.

Weathered Timber

Prepare weathered or grey timber by cleaning thoroughly with WOODCLEAN™ as per the instructions.

Sanding may be required to remove stains and restore deteriorated surfaces. Remove all sanding dust before coating.

Previously Coated Timber

Timber coated with stain or oil can be coated with TRADITIONAL TIMBER OIL after the surface has weathered. Test if the surface is ready by sprinkling water onto the timber: if the water absorbs into the timber, it is suitable for coating. If the water beads, further weathering, sanding or stripping is required.

Painted or varnished surfaces need to be taken back to bare timber by stripping or sanding.

Prepare timber for coating with WOODCLEAN as per the instructions.

Application Procedure and Equipment

Allow the timber to dry completely before applying Water Repellent Timber & Deck Oil.

Water Repellent Timber & Deck Oil should be stirred thoroughly before and during application with a flat blade stirrer taking care not to introduce bubbles.

Apply one coat of Water Repellent Timber & Deck Oil using a brush, roller or spray. If applying with a roller or spray, back brush the coating to ensure even penetration. Work along 3 - 4 planks at a time, in the direction of coated.

Allow coating to fully soak into timber before applying additional coats. Allow at least 2 hours to penetrate. Coating does not need to fully dry before applying subsequent coats.

A minimum of two coats is required.

Maintenance

Regularly monitor coated timber for signs of loss of water repellency.

Maintenance required every 3-6 months to maintain water repellency.

When required, clean the surface using a high pressure water hose and a stiff bristled brush or broom, allow the surface to dry and recoat with two coats of Water Repellent Timber & Deck Oil.

Health and Safety

SDS Number
DLXGHSEN001298

SDS Link
[View SDS Link](#)

Using Safety Precautions

Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause drowsiness and dizziness.

Keep out of reach of children. Read the label before opening or using. Keep away from all sources of ignition – No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and all other equipment.

Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist, vapours or spray. Use only outdoors or in a well ventilated area. Wear protective clothing, gloves, eye/face protection and a suitable respirator as required. Wash contaminated clothing before re-use. Store locked up. Store in a well ventilated place, away from oxidising agents and foodstuffs. Keep cool. Avoid release to the environment.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A

840W0211

Size:

Weight:

4L

3.67Kg

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Further Information

Product page

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.