

Feast Watson Mastertouch French Polish

AUDW0746

Part A	917 94665
---------------	-----------

Description

Feast Watson FRENCH POLISH is a shellac based spirit varnish for use on furniture where a deep patina is desired. It is ideal for enthusiasts and professionals who want to achieve a warm, high gloss French polished finish for fine timber furniture. It is an authentic finish for the restoration of antique furniture and French polished surfaces. FRENCH POLISH is not suitable on table tops subject to high wear or liquid spills.

Features

- Traditional finish
- Fast drying
- May be tinted with a spirit stain

Benefits

- Perfect for restoring fine furniture
- 1 hour re-coat
- makes colour matching easier

Uses



Use FEAST WATSON French Polish on furniture and other timber articles where a deep patina polish is desired.
Not suitable for table tops subject to high use, and wet areas

Precautions And Limitations

Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times.
Do not apply in temperatures under 10°C or above 35°C.

Performance Guide

Weather	For interior use only	Salt	Unaffected by splash or spillage
Heat Resistance	Up to 120C. Premature yellowing and embrittlement will occur if subjected to continuous heat.	Water	Poor.
Solvent	Resists mineral turpentine and similar solvents.	Abrasion	Moderate resistance to abrasion.

Typical Properties																											
Gloss Level	Gloss	Thinner	Methylated spirits																								
Colour	Amber tone	Components	1																								
Number Of Coats	4 +	Toxicity	Lead free. Dry film is non-toxic and conforms to AS1647, Part 3.																								
V.O.C. Level	< 550g/L	Touch Dry	30 minutes																								
Clean Up	 Thinner																										
Clean Up Description	Methylated spirits To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.																										
Application Method	 Brush Other: French polish mop, rubber or a clean cloth pad																										
Application Conditions	<table> <tr> <td>Solids By Volume</td><td>24</td><td></td><td></td></tr> <tr> <td></td><td>Min</td><td>Max</td><td>Recommended</td></tr> <tr> <td>Wet Film Per Coat (microns)</td><td></td><td></td><td></td></tr> <tr> <td>Dry Film Per Coat (microns)</td><td></td><td></td><td></td></tr> <tr> <td>Recoat Time (min)</td><td>1 hour</td><td></td><td></td></tr> <tr> <td>Theoretical Spread Rate (m²/L)</td><td></td><td></td><td></td></tr> </table>			Solids By Volume	24				Min	Max	Recommended	Wet Film Per Coat (microns)				Dry Film Per Coat (microns)				Recoat Time (min)	1 hour			Theoretical Spread Rate (m²/L)			
Solids By Volume	24																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)																											
Dry Film Per Coat (microns)																											
Recoat Time (min)	1 hour																										
Theoretical Spread Rate (m²/L)																											
Typical Properties Notes	DRYING TIME Drying times are given at 25oC and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Sanding: 24 hours. Full curing after 7 days.																										

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> New Timber Sand to a smooth surface and remove all sanding dust before coating. To achieve a super-smooth finish or if the timber grain is open or coarse, seal with Feast Watson SANDING SEALER and sand back as per the directions. Previously Coated Timber Previously varnished surfaces need to be sanded to a dull finish. Remove all sanding dust before coating. Previously French polished surfaces should be cleaned thoroughly with warm soapy water or wood turpentine. Antique Restoration Seek professional advice before commencing work on antiques.
Application Procedure And Equipment	<ul style="list-style-type: none"> Surfaces to be coated must be dry and free from all dirt, dust, grease, polish, wax and oil. Apply in dry conditions between 15-30C. Apply FRENCH POLISH with a good quality soft bristled brush, French polish mop, rubber or a clean cloth pad. Apply three coats of FRENCH POLISH allowing one hour dry time between coats. After the third coat allow 24 hours to dry. If a more durable and higher gloss coating is desired, further coats can be applied. Rub down the surface with very fine sand paper or 000 steel wool, then clean the surface and apply more coats as above. After every third coat allow 24 hours to dry and rub back before applying subsequent coats. When the desired finish is achieved, set aside for a week to allow the finish to develop hardness. After 7 days, the gloss can be reduced by cutting and polishing the finish with fine 0000 steel wool lubricated with Feast Watson MASTERTOUC WAX, then buffing with a clean cloth. Staining Apply Feast Watson PROOFTINT following label directions prior to the application of FRENCH POLISH. Alternatively, add 10% PROOFTINT to tint FRENCH POLISH. MAINTENANCE Maintain the surface finish by regularly applying Feast Watson MASTERTOUC POLISH or Feast Watson MASTERTOUC WAX. Avoid placing hot items on surfaces coated with FRENCH POLISH Quickly clean and dry liquid spills

Health And Safety

MSDS Number	14606801	Using Safety Precautions	Avoid contact with eyes. Provide adequate ventilation. If using indoors keep windows and doors open during use and while drying. All potential sources of ignition (open flames, pilot lights etc) must be eliminated both in or near the work area. Do not smoke.
Health Effects	<p>FIRST AID: For advice, contact a Poisons Information Centre (Phone Australia 131126; New Zealand 0800 764 766) or a doctor.</p> <p>Swallowed: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.</p> <p>Eye: Irrigate with copious quantities of water. Seek medical assistance if effects persist.</p> <p>Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.</p>	Flammability	This product is flammable
Storage	Keep out of reach of children.	Disposal	Do not pour leftover product down the drain. Keep unwanted product in sealed containers for disposal via special chemical waste collections. Disposal of empty containers via domestic kerbside recycling programs may differ between local authorities. Check with your local council first.

In the case of emergency, please call 1800 033 111

Transport And Storage

Pack A	917-94665	Shipment Name	PAINTS
Size 4 Litre 1 Litre 500ml 250ml	Weight 3.2 Kg 800g 400g 200g		
Flash Point	13C	UN Number	1263
Dangerous Goods Class	3	Package Group	I

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427