

Feast Watson Stain & Varnish Satin

AUDW1295

Part A	917-Line
---------------	----------

Description

Feast Watson STAIN & VARNISH is a traditional timber stain combined with a professional clear polyurethane. STAIN & VARNISH adds rich colour to timber and simultaneously preserves the stain by protecting it with a durable clear finish. With superior clarity, STAIN & VARNISH imparts colour without obscuring the natural characteristics of the timber grain. It is ideal for use on all interior furniture and woodwork and is available in Gloss and Satin sheen levels.

Note: This datasheet does not cover Feast Watson Stain & Varnish LIMING WHITE.

Features

- Stain and Varnish.
- Polyurethane varnish.
- Semi transparent.

Benefits

- Easy one-step process.
- Durable finish.
- Imparts colour without obscuring timber grain.

Uses


Use on all interior furniture and woodwork.

Precautions And Limitations

Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Do not apply in temperatures under 10°C or above 35°C.

Performance Guide

Weather	Interior use only.	Salt	Good.
Heat Resistance	Up to 120C.	Water	Good.
Solvent	Good.	Abrasion	Good.
Acid	Fair.	Alkali	Fair.

Typical Properties																											
Gloss Level	Satin	Components	1																								
Number Of Coats	1-3	Toxicity	Lead free.																								
V.O.C. Level	< 485g/L	Touch Dry	8 hours																								
Clean Up Description	Mineral turpentine To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.																										
Application Method	 Brush																										
Application Conditions	<table> <tr> <td>Solids By Volume</td><td>43</td><td></td><td></td></tr> <tr> <td></td><td>Min</td><td>Max</td><td>Recommended</td></tr> <tr> <td>Wet Film Per Coat (microns)</td><td></td><td></td><td>83</td></tr> <tr> <td>Dry Film Per Coat (microns)</td><td></td><td></td><td>36</td></tr> <tr> <td>Recoat Time (min)</td><td>12 hours</td><td></td><td></td></tr> <tr> <td>Theoretical Spread Rate (m²/L)</td><td></td><td>12</td><td>12</td></tr> </table>			Solids By Volume	43				Min	Max	Recommended	Wet Film Per Coat (microns)			83	Dry Film Per Coat (microns)			36	Recoat Time (min)	12 hours			Theoretical Spread Rate (m²/L)		12	12
Solids By Volume	43																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)			83																								
Dry Film Per Coat (microns)			36																								
Recoat Time (min)	12 hours																										
Theoretical Spread Rate (m²/L)		12	12																								
Typical Properties Notes	<p>COVERAGE 10 to 12m² per litre</p> <p>DRYING TIME Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times.</p>																										

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> New Timber Sand to a smooth surface and remove all sanding dust before coating. To achieve a super-smooth finish or if the timber grain is open or coarse, apply a coat of Feast Watson SANDING SEALER and sand back as per the directions. For naturally oily timbers, seal the timber with Feast Watson PROOFSEAL as per the directions prior to application. Previously Coated Timber Previously varnished surfaces need to be sanded to a dull finish. Remove all sanding dust before coating.
Application Procedure And Equipment	<ul style="list-style-type: none"> Test colour on an off-cut or inconspicuous area prior to staining the whole job to ensure satisfaction with colour choice. STAIN & VARNISH should be stirred thoroughly before and during application with a flat blade stirrer taking care not to introduce bubbles. Apply STAIN & VARNISH using a brush, roller or spray. If spraying STAIN & VARNISH may be thinned by using 10% mineral turpentine. If applying by roller, use a short nap (5mm) mohair roller. Ensure edges and end grain are fully coated. Three coats of varnish are required. If the desired colour is achieved with the first coat, complete the following coats with Feast Watson CLEAR VARNISH as additional coats of STAIN & VARNISH will intensify the colour. Allow 12 hours drying between coats. Sand lightly between coats with a fine sandpaper. If applying over a previous varnish coating, two coats will be sufficient. For new timber, and if applying by spray, apply a minimum of three coats. More coats may be applied for extra durability. MAINTENANCE Regularly monitor the surface for signs of colour loss or surface defects. When required, lightly sand the surface and remove dust. Recoat with additional coats of CLEAR VARNISH as per application instructions.

Health And Safety

MSDS Number	21103	Using Safety Precautions	Avoid contact with skin and eyes. Provide adequate ventilation. If using indoors keep windows and doors open during use and while drying. If painting large areas wear an organic vapour respirator. This paint is flammable, so eliminate any sources of ignition. Do not smoke.
Health Effects	<p>FIRST AID: For advice, contact a Poisons Information Centre (Phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor.</p> <p>SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical assistance.</p> <p>EYE: Rinse with plenty of running water. Seek medical help if irritation occurs.</p> <p>SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water.</p>	Flammability	This product is flammable.
Protective Equipment	Wear eye protection, protective clothing and gloves.	Disposal	Do not pour leftover paint down the drain. Unwanted paint should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collections. Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.

In the case of emergency, please call 1800 033 111

Transport And Storage

Pack A	917-Line	Shipment Name	PAINT
Size 250ml 500ml 1L	Weight 0.31Kg 0.58Kg 1.1Kg		
Flash Point	>23C	UN Number	1263
Dangerous Goods Class	3	Package Group	III

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427