

# **Datasheet**



## **AUFW00109 Feast Watson Kitchen Timber Wax**

Introduction

Part A

91AW0344

#### **Description and Image**

**Feast Watson Kitchen Timber Wax** is made from a blend of waxes and food grade mineral oil that nourishes and protects timber chopping boards, utensils and bowls. Apply with a soft cloth for a natural, soft lustre.

Contains Australian beeswax. Fragrance free.



## Features and Benefits

- Blend of waxes and food grade mineral oil
- Nourishes and protects
- Contains Australian beeswax
- Fragrance free

#### Uses

Kitchen timber utensils, chopping boards and bowls.

### Performance Guide

Weather

Interior use only



# **Datasheet**



Typical Properties	
Colour Colourless	
Number of Coats 1+	
V.O.C. Level <5g/L	
Meets GBCA V.O.C. Requirements? Yes	
Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.	
Clean Up Description Mineral turpentine	
Application Methods	
Soft cloth	
Application Guide	
Surface Preparation	
Ensure surface is clean and dry.	
Application Procedure and Equipment	
Apply with a soft cloth for a natural, soft lustre.	
Health and Safety	
SDS Number DLXGHSEN003411	SDS Link View SDS Link
Using Safety Precautions Avoid contact with skin and eyes. Avoid breathing dust, fume, gas, mist, vapour or spray. Wear overalls, safety shoes, impervious gloves and safety glasses. Use only in well ventilated areas. Wash hands after use. Keep containers closed when not in use.	
Please refer to SDS Link. In case of emergency, please call 1800 220 770.	
Transport and Storage	
Pack A 91AW0344	
Size:	Weight:
125g	125g

Please refer to the Safety Data Sheet for full safety, health and transportation information.



## **Datasheet**



#### **Further Information**

**Product page** 

#### Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from <a href="https://www.duspecplus.com.au">www.duspecplus.com.au</a>. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.