

## AUFW00088 Feast Watson Stain & Varnish Liming White Gloss

### Description and Image

Feast Watson STAIN & VARNISH LIMING WHITE is a water based timber stain combined with a professional clear polyurethane. STAIN & VARNISH LIMING WHITE gives a soft, milky white effect to timber and simultaneously preserves the stain by protecting it with a durable clear finish. The water based formula is non-yellowing, and imparts colour without obscuring the natural characteristics of the timber grain. One coat gives a subtle, pale colour; multiple coats will build the opacity and whiteness. STAIN & VARNISH LIMING WHITE is convenient to apply as it is fast drying, low odour and all application equipment can be cleaned up with water. It is ideal for use on all interior furniture and woodwork

### Features and Benefits





- Lime stain combined with a professional clear polyurethane
- water based
- One step stain and varnish
- Non yellowing
- No clear top coat required
- low odour, fast drying and easy water clean up

### Uses

On all interior furniture and woodwork

### Performance Guide

Weather <b>Interior Only</b>	Heat Resistance <b>Softens at temperatures above 70C</b>
Water <b>Good water resistance, unaffected by splash or spillage</b>	Abrasion <b>Good Resistance to Abrasion</b>

Typical Properties			
Gloss Level <b>Gloss</b>	Heat Thinner <b>Water</b>		
Colour <b>Liming White</b>			
Components <b>1</b>	Number of Coats <b>1+</b>		
Toxicity <b>Lead Free</b>	V.O.C. Level <b>&lt;65 g/L</b>		
Meets GBCA V.O.C. Requirements? <b>Yes</b> Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.			
Touch Dry <b>30 minutes</b>			
Clean Up  <b>Water</b>			
Application Methods  <b>Brush</b>  <b>Roller</b>  <b>Pad</b>			
Application Conditions	Solids by Volume		
	<input type="text" value="25"/>		
	Min	Max	Recommended
Wet Film Per Coat (microns)	<input type="text" value="83"/>	<input type="text" value="100"/>	<input type="text" value="91"/>
Dry Film Per Coat (microns)	<input type="text" value="21"/>	<input type="text" value="25"/>	<input type="text" value="23"/>
Recoat Time (min/hours)	<input type="text" value="2 Hours"/>	<input type="text" value="Indefinite"/>	<input type="text" value="2 hours +"/>
Theoretical Spread Rate (m <sup>2</sup> /L)	<input type="text" value="10"/>	<input type="text" value="12"/>	<input type="text" value="11"/>
Typical Property Notes DRYING TIME Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times. Touch Dry: 30 minutes. Recoat: 2 hours. Allow 24 hours before light foot traffic and 72 hours for normal traffic. Full curing after 7 days. COVERAGE Softwood: 8 - 10m <sup>2</sup> per litre. Hardwood: 10 - 12m <sup>2</sup> per litre. Cork: 8 - 10m <sup>2</sup> per litre.			

Application Guide
<p><b>Surface Preparation</b></p> <p>New or bare timber/cork Sand to a smooth surface and remove all sanding dust before coating. To achieve a super-smooth finish or if the timber grain is open or coarse, apply a coat of Feast Watson SANDING SEALER and sand back as per the directions. Previously Coated Timber Previously coated surfaces need to be sanded back to bare timber. Remove all sanding dust before coating.</p>
<p><b>Application Procedure and Equipment</b></p> <p>Test colour on an off-cut or inconspicuous area prior to staining the whole job to ensure satisfaction with colour choice. LIMING WHITE STAIN &amp; VARNISH should be stirred thoroughly before and during application with a flat blade stirrer taking care not to introduce bubbles. Apply LIMING WHITE STAIN &amp; VARNISH using a brush, roller or spray. If spraying LIMING WHITE STAIN &amp; VARNISH may be thinned by using 10% water. If applying by roller, use a short nap (5mm) mohair roller. Ensure edges and end grain are fully coated. Three coats of varnish are required. If the desired colour is achieved with the first coat, complete the following coats with a suitable water based clear coating, such as Cabot's CARBOTHANE clear water based or Intergrain ULTRACLEAR INTERIOR as additional coats of LIMING WHITE STAIN &amp; VARNISH will intensify the colour. Allow 2 hours drying between coats. Sand lightly between coats with a fine sandpaper. If applying over a previous varnish coating, two coats will be sufficient. For new timber, and if applying by spray, apply a minimum of three coats. More coats may be applied for extra durability. Do not apply in temperatures under 10°C or above 35°C.</p>

Health and Safety	
<p>SDS Number <b>22937</b></p>	<p>SDS Link</p>
<p><b>Using Safety Precautions</b></p> <p>Keep out of reach of children. Avoid contact with skin and eyes. Provide adequate ventilation. If using indoors keep windows and doors open during use and while drying.</p>	
<p><b>Please refer to SDS Link. In case of emergency, please call 1800 220 770.</b></p>	

Transport and Storage	
<p>Pack A <b>917W0054</b></p>	
<p>Size: <b>1L, 250mL</b></p>	<p>Weight: <b>1L = 1.2kg, 250ml = 0.33 kg</b></p>
<p><b>Please refer to the Safety Data Sheet for full safety, health and transportation information.</b></p>	

**Disclaimer**

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from [www.duspecplus.com.au](http://www.duspecplus.com.au). Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.